


Bits, Bytes, and Integers – Ch2

- ❑ **Representing information as bits**
- ❑ Bit-level manipulations
- ❑ **Integers**
 - ❑ Representation: unsigned and signed
 - ❑ Conversion, casting
 - ❑ Expanding, truncating
 - ❑ Addition, negation, multiplication, shifting
 - ❑ Summary
- ❑ **Representations in memory, pointers, strings**

Everything is bits

- ❑ Each bit is 0 or 1
- ❑ **Why bits? Electronic Implementation**
 - Easy to store with bistable elements
 - Reliably transmitted on noisy and inaccurate wires




Representing decimal numbers in binary number system

❑ Base 2 Number Representation

- ❑ Represent 15213_{10} as 11101101101101_2
- ❑ Represent 1.20_{10} as $1.0011001100110011[0011]..._2$
- ❑ Represent 1.5213×10^4 as $1.1101101101101_2 \times 2^{13}$

Decimal to Binary conversion by hand



29 decimal = 11101 binary

Converting decimal to binary Source: © Eugene Brennan

Decimal to Binary conversion for fractions by hand

□ 0.35_{10}



$$0.35 \times 2 = 0.70$$

$$0.70 \times 2 = 0.40$$

$$0.40 \times 2 = 0.80$$

$$0.80 \times 2 = 0.60$$

$$0.60 \times 2 = 0.20$$


with a carry of

with a carry of

with a carry of

with a carry of

with a carry of



Circuit Globe

□ $0.010110101101011\dots_{10}$

□ 0.01011_{10}

Binary to Decimal conversion by hand

Convert 10110111 to Decimal

10110111_2



1	0	1	1	0	1	1	1
128	64	32	16	8	4	2	1

$1 \times 1 = 1$
 $1 \times 2 = 2$
 $1 \times 4 = 4$
 $0 \times 8 = 0$
 $1 \times 16 = 16$
 $1 \times 32 = 32$
 $0 \times 64 = 0$
 $1 \times 128 = 128$

 $\text{Add } 183$



183_{10}

$10110111 = 183$ decimal

Encoding Byte Values

- ❑ **Byte = 8 bits**
 - ❑ **Binary** 00000000_2 to 11111111_2
 - ❑ **Decimal**: 0_{10} to 255_{10}
 - ❑ **Hexadecimal** 00_{16} to FF_{16}
 - ❑ Base 16 number representation
 - ❑ Use characters '0' to '9' and 'A' to 'F'
 - ❑ Write $FA1D37B_{16}$ in C as
 - ❑ `0xFA1D37B`
 - ❑ `0xfa1d37b`

Hex	Decimal	Binary
0	0	0000
1	1	0001
2	2	0010
3	3	0011
4	4	0100
5	5	0101
6	6	0110
7	7	0111
8	8	1000
9	9	1001
A	10	1010
B	11	1011
C	12	1100
D	13	1101
E	14	1110
F	15	1111

Example use in C: https://onlinegdb.com/OldKx_gJ7

Practice

❑ Perform number conversions:

❑ Binary 1001101110011110110101 to hexadecimal

❑ 0xD5E4C to binary

Hex	Decimal	Binary
0	0	0000
1	1	0001
2	2	0010
3	3	0011
4	4	0100
5	5	0101
6	6	0110
7	7	0111
8	8	1000
9	9	1001
A	10	1010
B	11	1011
C	12	1100
D	13	1101
E	14	1110
F	15	1111

Practice

- ❑ Perform number conversions:
 - ❑ Binary 1001101110011110110101 to hexadecimal
 - ❑ 0xD5E4C to binary

Binary 1001101110011110110101 to hexadecimal:

Binary	10	0110	1110	0111	1011	0101
Hexadecimal	2	6	E	7	B	5
Hexadecimal	D	5	E	4	C	
Binary	1101	0101	1110	0100	1100	

Hex	Decimal	Binary
0	0	0000
1	1	0001
2	2	0010
3	3	0011
4	4	0100
5	5	0101
6	6	0110
7	7	0111
8	8	1000
9	9	1001
A	10	1010
B	11	1011
C	12	1100
D	13	1101
E	14	1110
F	15	1111

Practice

❑ Perform the following addition and subtractions in Hex

❑ $0x503c + 0x8 =$

❑ $0x503c - 0x40 =$

Hex	Decimal	Binary
0	0	0000
1	1	0001
2	2	0010
3	3	0011
4	4	0100
5	5	0101
6	6	0110
7	7	0111
8	8	1000
9	9	1001
A	10	1010
B	11	1011
C	12	1100
D	13	1101
E	14	1110
F	15	1111

Practice

❑ Perform the following addition and subtractions in Hex

❑ $0x503c + 0x8 =$

❑ $0x503c - 0x40 =$

❑ $0x503c + 0x8 = 0x5044$. Adding 8 to hex c gives 4 with a carry of 1.

❑ $0x503c - 0x40 = 0x4ffc$. Subtracting 4 from 3 in the second digit position requires a borrow from the third. Since this digit is 0, we must also borrow from the fourth position.

Today: Bits, Bytes, and Integers

- ❑ Representing information as bits
- ❑ **Bit-level manipulations**
- ❑ **Integers**
 - ❑ Representation: unsigned and signed
 - ❑ Conversion, casting
 - ❑ Expanding, truncating
 - ❑ Addition, negation, multiplication, shifting
 - ❑ Summary
- ❑ Representations in memory, pointers, strings

Boolean Algebra

■ Developed by George Boole in 19th Century

- Algebraic representation of logic
 - Encode “True” as 1 and “False” as 0

And

- $A \& B = 1$ when both $A=1$ and $B=1$

$\&$	0	1
0	0	0
1	0	1

Not

- $\sim A = 1$ when $A=0$

\sim	
0	1
1	0

Or

- $A | B = 1$ when either $A=1$ or $B=1$

$ $	0	1
0	0	1
1	1	1

Exclusive-Or (Xor)


- $A \wedge B = 1$ when either $A=1$ or $B=1$, but not both

\wedge	0	1
0	0	1
1	1	0


Guess the operation




Original



Original
OR
random
stream



Original
AND
Random
stream



Original
XOR
random
stream

Resource: [khanacademy.org](https://www.khanacademy.org)

Bitwise Operations

❑ Operate on Bit Vectors

❑ Operations applied bitwise

01101001	01101001	01101001	
& 01010101	01010101	^ 01010101	~ 01010101
01000001	01111101	00111100	10101010

❑ All of the Properties of Boolean Algebra Apply

Boolean Laws

T1 : Commutative Law

(a) $A + B = B + A$

(b) $A \& B = B \& A$

T2 : Associative Law

(a) $(A + B) + C = A + (B + C)$

(b) $(A \& B) \& C = A \& (B \& C)$

T3 : Distributive Law

(a) $A \& (B + C) = A \& B + A \& C$

(b) $A + (B \& C) = (A + B) \& (A + C)$

T4 : Identity Law

(a) $A + A = A$


(b) $A \& A = A$

Practice


■ We can create eight different colors based on the absence (0) or presence (1) of light sources R , G , and B :

■ Describe the effect of applying Boolean operations on the following colors:

- Blue | Green =
 - Cyan (011)
- Yellow & Cyan =
 - Green (010)
- Red ^ Magenta =
 - Blue (001)



RGB color model



R	G	B	Color
0	0	0	Black
0	0	1	Blue
0	1	0	Green
0	1	1	Cyan
1	0	0	Red
1	0	1	Magenta
1	1	0	Yellow
1	1	1	White

Bit-Level Operations in C

■ Operations &, |, ~, ^ Available in C

- Apply to any “integral” data type
 - long, int, short, char, unsigned
- View arguments as bit vectors
- Arguments applied bit-wise

■ Examples (Char data type)

- $\sim 0x41 \rightarrow 0xBE$
 - $\sim 01000001_2 \rightarrow 10111110_2$
- $\sim 0x00 \rightarrow 0xFF$
 - $\sim 00000000_2 \rightarrow 11111111_2$
- $0x69 \& 0x55 \rightarrow 0x41$
 - $01101001_2 \& 01010101_2 \rightarrow 01000001_2$
- $0x69 | 0x55 \rightarrow 0x7D$
 - $01101001_2 | 01010101_2 \rightarrow 01111101_2$

```
#include <stdio.h>
```

```
void main()  
{
```

```
    unsigned char A = 'A';  
    unsigned char Anot = ~A;  
    printf("0x%x\n",A);  
    printf("0x%x\n",Anot);
```

```
}
```

```
0x41  
0xbe
```

x represents unsigned
hex integer

Hex	Decimal	Binary
0	0	0000
1	1	0001
2	2	0010
3	3	0011
4	4	0100
5	5	0101
6	6	0110
7	7	0111
8	8	1000
9	9	1001
A	10	1010
B	11	1011
C	12	1100
D	13	1101
E	14	1110
F	15	1111

Contrast: Logic Operations in C

■ Contrast to Logical Operators

- `&&`, `||`, `!`
 - View 0 as “False”
 - Anything nonzero as “True”
 - Always return 0 or 1
 - **Early termination**

■ Examples (char data type)

- `!0x41 -> 0x00`
- `!0x00 -> 0x01`
- `!!0x41 -> 0x01`

- `0x69 && 0x55 -> 0x01`
- `0x69 || 0x55 -> 0x01`

Contrast: Logic Operations in C

■ Contrast to Logical Operators

- &&, ||, !
 - View 0 as “False”
 - Anything nonzero as “True”
 - Always return 0 or 1
 - **Early termination**

■ Examples (char data)

- !0x41 -> 0x00
- !0x00 -> 0x01
- !!0x41 -> 0x01

- 0x69 && 0x55 -> 0x01
- 0x69 || 0x55 -> 0x01

Watch out for && vs. & (and || vs. |)...
one of the common oopsies in
C programming

Practice 2.14

■ Suppose that x and y have byte values 0x66 and 0x39, respectively. Fill in the following table indicating the byte values of the different C expressions:

Expression	Value	Expression	Value
x & y	_____	x && y	_____
x y	_____	x y	_____
~x ~y	_____	!x !y	_____
x & !y	_____	x && ~y	_____

Hex	Decimal	Binary
0	0	0000
1	1	0001
2	2	0010
3	3	0011
4	4	0100
5	5	0101
6	6	0110
7	7	0111
8	8	1000
9	9	1001
A	10	1010
B	11	1011
C	12	1100
D	13	1101
E	14	1110
F	15	1111

Practice 2.14

■ Suppose that x and y have byte values 0x66 and 0x39, respectively. Fill in the following table indicating the byte values of the different C expressions:

Expression	Value	Expression	Value
x & y	0x20	x && y	0x01
x y	0x7F	x y	0x01
~x ~y	0xDF	!x !y	0x00
x & !y	0x00	x && ~y	0x01

x = 0110 0110

Y = 0011 1001

0110 0110

& 0011 1001

0110 0110

| 0011 1001

~X = 1001 1001

~Y = 1100 0110

1001 1001

| 1100 0110

Shift Operations

■ Left Shift: $x \ll y$

- Shift bit-vector x left y positions
 - Throw away extra bits on the left
- Fill with 0's on the right

Argument x	01100010
$\ll 3$	00010 000
Log. $\gg 2$	000 11000
Arith. $\gg 2$	000 11000

■ Right Shift: $x \gg y$

- Shift bit-vector x right y positions
 - Throw away extra bits on the right
- Logical shift
 - Fill with 0's on the left
- Arithmetic shift
 - Replicate most significant bit on the left

Argument x	10100010
$\ll 3$	00010 000
Log. $\gg 2$	00 101000
Arith. $\gg 2$	11 101000

■ Undefined Behavior

- Shift amount < 0 or \geq word size

In C:

\gg unsigned is logical
 \gg signed is Arithmetic

Shift Operations

```
unsigned int num1 = 64;
int num2 = -64;

printf("0x%08x  %d\n", num1, num1);
printf("0x%08x  %d\n", num1>>4, num1>>4);
printf("0x%08x  %d\n", num1<<4, num1<<4);
printf("\n");
printf("0x%x  %d\n", num2, num2);
printf("0x%x  %d\n", num2>>4, num2>>4);
printf("0x%x  %d\n", num2<<4, num2<<4);
```

- Left shift is always equivalent to multiplication by 2
- Right shift is always equivalent to division by 2 **for even numbers**.

0x00000040	64
0x00000004	4
0x00000400	1024
0xffffffffc0	-64
0xfffffffffc	-4
0xffffffffc00	-1024

Today: Bits, Bytes, and Integers

- Representing information as bits

- Bit-level manipulations

- **Integers**

- **Representation: unsigned and signed**
- Conversion, casting
- Expanding, truncating
- Addition, negation, multiplication, shifting
- Summary

- Representations in memory, pointers, strings

- Summary