

**UNIVERSITY OF LONDON**

**BSc EXAMINATION 2022**

For Internal Students of  
Royal Holloway

**DO NOT TURN OVER UNTIL TOLD TO BEGIN**

**CS2900: Multi-dimensional Data Processing**  
**CS2900R: Multi-dimensional Data Processing – for**  
**FIRSTSIT/RESIT CANDIDATES**

Time Allowed: **TWO hours**

Answer ALL questions  
Calculators are NOT permitted

**Important Copyright Notice**

This exam paper has been made available in electronic form  
strictly for the educational benefit of current Royal Holloway students  
on the course of study in question.

No further copying, distribution or publication of this exam paper is permitted.  
By printing or downloading this exam paper, you are consenting to these restrictions.

©Royal Holloway, University of London 2022

1. The following questions require short definitions of technical terms in the context of vectors and matrices. Component-wise definitions are sufficient. You may assume that  $\underline{u}$  is a real valued vector in  $N$ -dimensions ( $N$  is finite) and that  $\mathbf{M}$ ,  $\mathbf{A}$  and  $\mathbf{B}$  are real valued  $N \times N$  matrices.
- (a) List three properties of the dot product of two vectors that are true in any finite number of dimensions. [9 marks]
  - (b) If  $\mathbf{M} = \mathbf{AB}$  then what is  $M_{ij}$  in terms of  $\mathbf{A}$  and  $\mathbf{B}$ ? [3 marks]
  - (c) Define the following.
    - i. The scalar product operation for a vector. [3 marks]
    - ii. Diagonal matrix. [3 marks]
    - iii. Symmetric matrix. [3 marks]
    - iv. Upper diagonal matrix. [3 marks]

2. (a) The real-valued vectors  $\underline{u}$  and  $\underline{v}$  have the same number of dimensions.
- i. What are the necessary steps to compute  $\underline{y}$ , the projection of  $\underline{u}$  onto  $\underline{v}$ ? [9 marks]
  - ii. How do you compute the vector  $\underline{w}$  that is orthogonal to  $\underline{y}$  and whose sum with  $\underline{y}$  is  $\underline{u}$ ? [3 marks]
- (b) The following questions regard algorithms for ranking the importance of web pages.
- i. Explain the necessary steps in the PageRank algorithm. A pseudo-code description is sufficient. [8 marks]
  - ii. Give two reasons why one cannot use the simple diffusion-based algorithm rather than the PageRank algorithm. [6 marks]
- (c) Do all matrices have an inverse? Explain your reasoning with a specific example. [6 marks]
- (d) Given two rectangular matrices  $C$  and  $D$  what one must check to determine if  $CD$  exists? If  $CD$  exists, what does it corresponds to in terms of linear transformations? [4 marks]

3. (a) Compute the projection of the vector  $(1 \ 0 \ 0 \ 1)^T$  onto the 2-dimensional plane that lies in a 4-dimensional space and passes through the origin and the points  $(1, -1, 0, 1)$  and  $(1, 1, 1, 0)$ . Do this using basis vectors for the plane. The projected vector is to be represented in the original 4-dimensional space. Show all the necessary steps to compute this. [8 marks]
- (b) A graph has the following adjacency matrix

$$\mathbf{A} = \begin{pmatrix} 0 & 1 & 1 & 1 \\ 0 & 0 & 1 & 1 \\ 1 & 0 & 0 & 0 \\ 0 & 0 & 1 & 0 \end{pmatrix}$$

- i. Draw the equivalent directed graph, labelling the vertices 1 to 4. [3 marks]
- ii. Using the adjacency matrix list the one ordered pair of nodes that have two paths of length two between them. Show your reasoning. [4 marks]
- iii. Compute the corresponding diffusion matrix for this graph. [3 marks]
- iv. This graph corresponds to set of web pages and their links and one is starting from the page corresponding to vertex 1. Assuming random selection of web links from a page is it more likely that after two iterations one will be at vertex 1 or vertex 3? Explain your reasoning. [6 marks]

4. (a) Using the singular value decomposition of a matrix  $\mathbf{X} = \mathbf{U}\mathbf{D}\mathbf{V}^\top$
- i. derive an expression for  $\mathbf{X}\mathbf{X}^\top$  in terms of the components of the above decomposition. [3 marks]
  - ii. Using the previous derived expression in 4(a)(i) derive an expression for  $(\mathbf{X}\mathbf{X}^\top)^{2n}$ . [3 marks]
- (b) On the next page a Python class `specialMatrix` is defined. This class is used to define a matrix with a specific structure.
- i. What is the structure of the matrix? [2 marks]
  - ii. What does the function `func1` do? [3 marks]
  - iii. What is the advantage of using this object for storing this type of matrix over a standard Numpy matrix? [2 marks]
  - iv. Write a function `trace` that can be added to `specialMatrix` which returns the trace of the matrix. It is not necessary to write down the rest of the `specialMatrix` code. [3 marks]

```
import numpy as np
import sys

class specialMatrix:
    """
    input :-
        M is a Numpy vector
    """
    def __init__(self,M):
        self.MSize = np.size(M)
        self.a = np.copy(M)
    """
    input :- integers i,j
    output (i,j) entry of matrix
    """
    def getEntry(self,i,j):
        if i<0 or j<0 or i>=self.MSize or j>=self.MSize:
            sys.exit("getEntry_ _indices_out_of_range")
        if i==j:
            return(self.a[i])
        else:
            return(0)
    """
    input :- Numpy array A
    """
    def func1(self,A):
        s = np.shape(A)
        if s[0] != self.MSize or s[1] != self.MSize:
            sys.exit("specialMatrix_ _matrix_is_not_correct_ _
dimensions!")
        X = np.zeros_like(A)
        for i in range(self.MSize):
            for j in range(self.MSize):
                X[i,j] = self.a[i] * A[i,j]
        return(X)
```

**END**