

UNIVERSITY OF LONDON

BSc EXAMINATION 2022

For Internal Students of
Royal Holloway

DO NOT TURN OVER UNTIL TOLD TO BEGIN

CS2860: Algorithms and Complexity
CS2860R: Algorithms and Complexity – FOR FIRST
SITS/RESIT CANDIDATES

Time Allowed: **TWO hours**

Please answer **ALL** questions.

Important Copyright Notice

This exam paper has been made available in electronic form
strictly for the educational benefit of current Royal Holloway students
on the course of study in question.

No further copying, distribution or publication of this exam paper is permitted.
By printing or downloading this exam paper, you are consenting to these restrictions.

©Royal Holloway, University of London 2022

1. (a) Describe the order of growth of the following functions in standard Θ notation as simply as possible. Sort the resulting Θ expressions by increasing speed of growth. [10 marks]
 - i. $f(n) = 5(\log n)^3 + 3n^2 + 5$
 - ii. $f(n) = 3n + 4n \log n + 42$
 - iii. $f(n) = 15n^2 \log n - 3 \log n + \frac{7n-2}{\log n}$
 - iv. $f(n) = 47 \log n - 25$
- (b) Explain what is the meaning of c and n_0 in the definition of Big-Oh notation. Given $4n^2 - 2n = O(n^4)$, find the minimum possible value of c for $n_0 = 1$ and for $n_0 = 10$. [6 marks]
2. Write a recursive function to compute the heights of all nodes in a given binary tree. The height of a leaf node is 1, and the height of the root is the number of nodes in the longest path from the root to a leaf.

The tree nodes have the structure:

```

1    class Node {
2        int height;
3        Node left;
4        Node right;
5    }
```

Your function should correctly fill in the `height` field for every node in the tree. [10 marks]

3. Both parts of the question relate to the tree in Figure 1 below.
 - (a) Perform the following operations on the binary search tree (BST) in the given order, and show the shape of the tree after each one: Delete 20. Delete 43. Insert 26. Delete 32. Show the ordinary binary search tree operations; do not rebalance the tree after insertions or deletions. [4 marks]
 - (b) Consider the tree in Figure 1 again. The tree can also be seen as an AVL tree into which we just inserted 43. Describe the rotation(s) that need to be performed to rebalance the tree. [8 marks]




FIGURE 1: BST FOR QUESTION 3.

4. (a) State the heap property for binary min-heaps. [2 marks]
- (b) Which of the following two arrays is a binary min-heap?
- i. $A = [1, 3, 18, 25, 4, 48, 27, 41, 31, 49]$
 - ii. $B = [4, 23, 28, 32, 92, 27, 96, 97, 67, 53]$ [2 marks]
- (c) Consider the following array $C = [10, 19, 24, 43, 41, 31, 92, 75, 47, 62]$ representing a binary min-heap.
- i. Draw the tree representation of the binary min-heap. [2 marks]
 - ii. Describe the algorithm from lectures for deleting the minimum from binary min-heap and illustrate it on the heap C . [3 marks]
 - iii. Describe the algorithm from lectures for inserting a new element to a binary min-heap and illustrate it by inserting the number 25 in the heap C (i.e., the original min-heap C , not the outcome of 4(c)ii). [3 marks]
5. What is the difference between the `HashMap` and `TreeMap` implementations of the `Map` abstract data type? Give an advantage and a disadvantage of each. [8 marks]




FIGURE 2: DIRECTED GRAPH FOR QUESTION 6.

6. (a) Illustrate Kruskal's algorithm on the graph in Figure 2. In addition show how the Union-Find data structure changes throughout the computation. [5 marks]
- (b) Draw the minimum spanning tree found in the part (a). [2 marks]
- (c) By examining the choices made in your computation, determine how many minimum spanning trees (MSTs) the graph in Figure 2 has. [4 marks]

7. Consider the following function fn .

```
1  int fn(n) {  
2      if (n == 0) {  
3          return 1;  
4      }  
5      int sum = 0;  
6      for (int i=0; i<n; i++) {  
7          sum += fn(i);  
8      }  
9      return sum;  
10 }
```

- (a) Compute the value $fn(5)$. [4 marks]
 - (b) Illustrate all recursive calls made by the algorithm on input $n = 4$, i.e., when calling $fn(4)$, by drawing the recursion tree. [4 marks]
 - (c) What does $fn(n)$ compute for $n \geq 1$. You do not need to justify your answer. [3 marks]
 - (d) Compute an estimate of the execution time as a function of n . Give your answer in Big-Oh notation and justify your answer. [3 marks]
 - (e) Describe how you can use the Memoisation technique to improve the running time of the function. [2 marks]
 - (f) Compute an estimate of the execution time as a function of n after using Memoisation. Give your answer in Big-Oh notation and justify your answer. [4 marks]
8. Suggest an algorithm that helps you select all possible holiday destinations within a given budget. Its input is a list of possible connections between cities, where each connection is given as a combination of a starting location, a destination location, and a cost of a ticket (For example, one such connection could be “a train from London to Manchester, £30”). Propose an algorithm that, given a starting location and overall budget, finds all destinations that you can reach with given budget. [11 marks]

END