

Machine-Level Programming II: Control



Today

- 🌀 **Control: Condition codes**
- 🌀 Conditional branches
- 🌀 Loops
- 🌀 Switch Statements



Processor State (x86-64, Partial)

Information about currently executing program

- Temporary data (**%rax**, ...)
- Location of runtime stack (**%rsp**)
- Location of current code control point (**%rip**, ...)
- Status of recent tests (**CF**, **ZF**, **SF**, **OF**)

Current stack top

Registers

%rax	%r8
%rbx	%r9
%rcx	%r10
%rdx	%r11
%rsi	%r12
%rdi	%r13
%rsp	%r14
%rbp	%r15

%rip

Instruction pointer

CF

ZF

SF

OF

Condition codes



Condition Codes (Implicit Setting)

Single bit registers

CF Carry Flag (for unsigned) **SF** Sign Flag (for signed)
ZF Zero Flag **OF** Overflow Flag (for signed)

Implicitly set (think of it as side effect) by arithmetic operations

Example: `addq Src, Dest` \leftrightarrow `t = a+b`

CF set if carry out from most significant bit (unsigned overflow)

ZF set if `t == 0`

SF set if `t < 0` (as signed)

OF set if two's-complement (signed) overflow

`(a>0 && b>0 && t<0) || (a<0 && b<0 && t>=0)`

Not set by `leaq` instruction



Condition Codes (Explicit Setting: Compare)

🌀 Explicit Setting by Compare Instruction

🌀 `cmpq Src2, Src1`

🌀 `cmpq b, a` like computing `a-b` without setting destination

🌀 **CF set** if carry out from most significant bit (used for unsigned comparisons)

🌀 **ZF set** if `a == b`

🌀 **SF set** if `(a-b) < 0` (as signed)

🌀 **OF set** if two's-complement (signed) overflow

`(a>0 && b<0 && (a-b)<0) || (a<0 && b>0 && (a-b)>0)`



Condition Codes (Explicit Setting: Test)

• Explicit Setting by Test instruction

• `testq Src2, Src1`

• `testq b, a` like computing `a&b` without setting destination

• Sets condition codes based on value of `Src1` & `Src2`

• Useful to have one of the operands be a mask

• **ZF set** when `a&b == 0`

• **SF set** when `a&b < 0`



Reading Condition Codes

🌀 SetX Instructions

- 🌀 Set low-order byte of destination to 0 or 1 based on combinations of condition codes
- 🌀 Does not alter remaining 7 bytes

SetX	Condition	Description
sete	ZF	Equal / Zero
setne	~ZF	Not Equal / Not Zero
sets	SF	Negative
setns	~SF	Nonnegative
setg	~ (SF^OF) & ~ZF	Greater (Signed)
setge	~ (SF^OF)	Greater or Equal (Signed)
setl	(SF^OF)	Less (Signed)
setle	(SF^OF) ZF	Less or Equal (Signed)
seta	~CF & ~ZF	Above (unsigned)
setb	CF	Below (unsigned)



x86-64 Integer Registers

%rax	%al
%rbx	%bl
%rcx	%cl
%rdx	%dl
%rsi	%sil
%rdi	%dil
%rsp	%spl
%rbp	%bpl

%r8	%r8b
%r9	%r9b
%r10	%r10b
%r11	%r11b
%r12	%r12b
%r13	%r13b
%r14	%r14b
%r15	%r15b

 Can reference low-order byte



Reading Condition Codes (Cont.)

• SetX Instructions:

- Set single byte based on combination of condition codes

• One of addressable byte registers

- Does not alter remaining bytes
- Typically use **movzbl** to finish job
- 32-bit instructions also set upper 32 bits to 0

```
int gt (long x, long y)
{
    return x > y;
}
```

Register	Use(s)
%rdi	Argument x
%rsi	Argument y
%rax	Return value

```
cmpq    %rsi, %rdi    # Compare x:y
setg    %al            # Set when >
movzbl  %al, %eax      # Zero rest of %rax
ret
```



Today

- 🔗 Control: Condition codes
- 🔗 **Conditional branches**
- 🔗 Loops
- 🔗 Switch Statements



Jumping

jX Instructions

-  Jump to different part of code depending on condition codes

jX	Condition	Description
jmp	1	Unconditional
je	ZF	Equal / Zero
jne	$\sim ZF$	Not Equal / Not Zero
js	SF	Negative
jns	$\sim SF$	Nonnegative
jg	$\sim (SF \wedge OF) \ \& \ \sim ZF$	Greater (Signed)
jge	$\sim (SF \wedge OF)$	Greater or Equal (Signed)
jl	$(SF \wedge OF)$	Less (Signed)
jle	$(SF \wedge OF) \mid ZF$	Less or Equal (Signed)
ja	$\sim CF \ \& \ \sim ZF$	Above (unsigned)
jb	CF	Below (unsigned)



Conditional Branch Example (Old Style)

Generation

```
shark> gcc -Og -S -fno-if-conversion control.c
```

```
long absdiff
(long x, long y)
{
    long result;
    if (x > y)
        result = x-y;
    else
        result = y-x;
    return result;
}
```

```
absdiff:
    cmpq    %rsi, %rdi    # x:y
    jle     .L4
    movq    %rdi, %rax
    subq    %rsi, %rax
    ret
.L4:       # x <= y
    movq    %rsi, %rax
    subq    %rdi, %rax
    ret
```

Register	Use(s)
%rdi	Argument x
%rsi	Argument y
%rax	Return value



Expressing with Goto Code

- C allows goto statement
- Jump to position designated by label

```
long absdiff
(long x, long y)
{
    long result;
    if (x > y)
        result = x-y;
    else
        result = y-x;
    return result;
}
```

```
long absdiff_j
(long x, long y)
{
    long result;
    int ntest = x <= y;
    if (ntest) goto Else;
    result = x-y;
    goto Done;
Else:
    result = y-x;
Done:
    return result;
}
```



General Conditional Expression Translation (Using Branches)

C Code

```
val = Test ? Then_Expr : Else_Expr;
```

```
val = x > y ? x - y : y - x;
```

Goto Version

```
n_test = !Test;  
if (n_test) goto Else;  
val = Then_Expr;  
goto Done;  
Else:  
    val = Else_Expr;  
Done:  
    . . .
```

- Create separate code regions for then & else expressions
- Execute appropriate one



Using Conditional Moves

Conditional Move Instructions

- Instruction supports:
if (Test) Dest \leftarrow Src
- Supported in post-1995 x86 processors
- GCC tries to use them
 - But, only when known to be safe

Why?

- Branches are very disruptive to instruction flow through pipelines
- Conditional moves do not require control transfer

C Code

```
val = Test  
    ? Then_Expr  
    : Else_Expr;
```

Goto Version

```
result = Then_Expr;  
eval = Else_Expr;  
nt = !Test;  
if (nt) result = eval;  
return result;
```



Conditional Move Example

```
long absdiff
(long x, long y)
{
    long result;
    if (x > y)
        result = x-y;
    else
        result = y-x;
    return result;
}
```

Register	Use(s)
%rdi	Argument x
%rsi	Argument y
%rax	Return value

absdiff:

```
movq    %rdi, %rax    # x
subq    %rsi, %rax    # result = x-y
movq    %rsi, %rdx
subq    %rdi, %rdx    # eval = y-x
cmpq    %rsi, %rdi    # x:y
cmovle  %rdx, %rax    # if <=, result = eval
ret
```



Bad Cases for Conditional Move

Expensive Computations

```
val = Test(x) ? Hard1(x) : Hard2(x);
```

- Both values get computed
- Only makes sense when computations are very simple

Risky Computations

```
val = p ? *p : 0;
```

- Both values get computed
- May have undesirable effects

Computations with side effects

```
val = x > 0 ? x*=7 : x+=3;
```

- Both values get computed
- Must be side-effect free



Today

- 🌀 Control: Condition codes
- 🌀 Conditional branches
- 🌀 **Loops**
- 🌀 Switch Statements



“Do-While” Loop Example

C Code

```
long pcount_do
(unsigned long x) {
    long result = 0;
    do {
        result += x & 0x1;
        x >>= 1;
    } while (x);
    return result;
}
```

Goto Version

```
long pcount_goto
(unsigned long x) {
    long result = 0;
    loop:
        result += x & 0x1;
        x >>= 1;
        if(x) goto loop;
    return result;
}
```

- Count number of 1's in argument **x** (“popcount”)
- Use conditional branch to either continue looping or to exit loop



“Do-While” Loop Compilation

Goto Version

```
long pcount_goto
(unsigned long x) {
    long result = 0;
loop:
    result += x & 0x1;
    x >>= 1;
    if(x) goto loop;
    return result;
}
```

Register	Use(s)
%rdi	Argument x
%rax	result

```
        movl    $0, %eax    # result = 0
.L2:                                # loop:
        movq    %rdi, %rdx
        andl    $1, %edx    # t = x & 0x1
        addq    %rdx, %rax  # result += t
        shrq    %rdi        # x >>= 1
        jne     .L2         # if (x) goto loop
        rep; ret
```



General “Do-While” Translation

C Code

```
do
    Body
while (Test) ;
```

Goto Version

```
loop:
    Body
    if (Test)
        goto loop
```

🌀 **Body:** {
 Statement_1 ;
 Statement_2 ;
 ...
 Statement_n ;
}



General “While” Translation #1

- 🌀 “Jump-to-middle” translation
- 🌀 Used with -Og

While version

```
while (Test)  
    Body
```



Goto Version

```
    goto test;  
loop:  
    Body  
test:  
    if (Test)  
        goto loop;  
done:
```



While Loop Example #1

C Code

```
long pcount_while
(unsigned long x) {
    long result = 0;
    while (x) {
        result += x & 0x1;
        x >>= 1;
    }
    return result;
}
```

Jump to Middle

```
long pcount_goto_jtm
(unsigned long x) {
    long result = 0;
    goto test;
loop:
    result += x & 0x1;
    x >>= 1;
test:
    if(x) goto loop;
    return result;
}
```

- 🔄 Compare to do-while version of function
- 🔄 Initial goto starts loop at test



General “While” Translation #2

While version

```
while (Test)  
    Body
```



Do-While Version

```
if (!Test)  
    goto done;  
do  
    Body  
    while (Test);  
done:
```



Goto Version

```
if (!Test)  
    goto done;  
loop:  
    Body  
    if (Test)  
        goto loop;  
done:
```

- “Do-while” conversion
- Used with -O1



While Loop Example #2

C Code

```
long pcount_while
(unsigned long x) {
    long result = 0;
    while (x) {
        result += x & 0x1;
        x >>= 1;
    }
    return result;
}
```

Do-While Version

```
long pcount_goto_dw
(unsigned long x) {
    long result = 0;
    if (!x) goto done;
loop:
    result += x & 0x1;
    x >>= 1;
    if(x) goto loop;
done:
    return result;
}
```

- 🔄 Compare to do-while version of function
- 🔄 Initial conditional guards entrance to loop



“For” Loop Form

General Form

```
for (Init; Test; Update )  
    Body
```

```
#define WSIZE 8*sizeof(int)  
long pcount_for  
    (unsigned long x)  
{  
    size_t i;  
    long result = 0;  
    for (i = 0; i < WSIZE; i++)  
    {  
        unsigned bit =  
            (x >> i) & 0x1;  
        result += bit;  
    }  
    return result;  
}
```

Init

```
i = 0
```

Test

```
i < WSIZE
```

Update

```
i++
```

Body


```
{  
    unsigned bit =  
        (x >> i) & 0x1;  
    result += bit;  
}
```



“For” Loop → While Loop

For Version

```
for (Init; Test; Update )  
    Body
```



While Version

```
Init;  
while (Test) {  
    Body  
    Update;  
}
```



For-While Conversion

Init

```
i = 0
```

Test

```
i < WSIZE
```

Update

```
i++
```

Body

```
{  
    unsigned bit =  
        (x >> i) & 0x1;  
    result += bit;  
}
```

```
long pcount_for_while  
(unsigned long x)  
{  
    size_t i;  
    long result = 0;  
    i = 0;  
    while (i < WSIZE)  
    {  
        unsigned bit =  
            (x >> i) & 0x1;  
        result += bit;  
        i++;  
    }  
    return result;  
}
```



“For” Loop Do-While Conversion

C Code Goto Version

```
long pcount_for
(unsigned long x)
{
    size_t i;
    long result = 0;
    for (i = 0; i < WSIZE; i++)
    {
        unsigned bit =
            (x >> i) & 0x1;
        result += bit;
    }
    return result;
}
```

 Initial test can be optimized away

```
long pcount_for_goto_dw
(unsigned long x) {
    size_t i;
    long result = 0;
    i = 0; Init
if (!(i < WSIZE)) ! Test
goto done;
loop:
{
    unsigned bit =
        (x >> i) & 0x1; Body
    result += bit;
}
i++; Update
if (i < WSIZE) Test
    goto loop;
done:
    return result;
}
```



Today

- 🔗 Control: Condition codes
- 🔗 Conditional branches
- 🔗 Loops
- 🔗 **Switch Statements**



```

long switch_eg
(long x, long y, long z)
{
    long w = 1;
    switch(x) {
    case 1:
        w = y*z;
        break;
    case 2:
        w = y/z;
        /* Fall Through */
    case 3:
        w += z;
        break;
    case 5:
    case 6:
        w -= z;
        break;
    default:
        w = 2;
    }
    return w;
}

```

Switch Statement Example

Multiple case labels

Here: 5 & 6

Fall through cases

Here: 2

Missing cases

Here: 4



Jump Table Structure

Switch Form

```
switch(x) {  
  case val_0:  
    Block 0  
  case val_1:  
    Block 1  
    . . .  
  case val_n-1:  
    Block n-1  
}
```

Jump Table

jtab:	Targ0
	Targ1
	Targ2
	• • •
	Targn-1

Jump Targets

Targ0:

Code Block
0

Targ1:

Code Block
1

Targ2:

Code Block
2

•
•
•

Targn-1:

Code Block
n-1



Translation (Extended C)


```
goto *JTab[x];
```


Switch Statement Example

```
long switch_eg(long x, long y, long z)
{
    long w = 1;
    switch(x) {
        . . .
    }
    return w;
}
```

Setup:

```
switch_eg:
    movq    %rdx, %rcx
    cmpq    $6, %rdi    # x:6
    ja      .L8
    jmp     *.L4(, %rdi, 8)
```



What range of values
takes default?

Register	Use(s)
%rdi	Argument x
%rsi	Argument y
%rdx	Argument z
%rax	Return value

Note that **w** not
initialized here



Switch Statement Example

```
long switch_eg(long x, long y, long z)
{
    long w = 1;
    switch(x) {
        . . .
    }
    return w;
}
```

Jump table

```
.section      .rodata
    .align 8
.L4:
    .quad     .L8      # x = 0
    .quad     .L3      # x = 1
    .quad     .L5      # x = 2
    .quad     .L9      # x = 3
    .quad     .L8      # x = 4
    .quad     .L7      # x = 5
    .quad     .L7      # x = 6
```

Setup:

```
switch_eg:
    movq      %rdx, %rcx
    cmpq      $6, %rdi      # x:6
    ja        .L8           # Use default
    jmp       *.L4(, %rdi, 8) # goto *JTab[x]
```

*Indirect
jump*



Assembly Setup Explanation

Table Structure

- Each target requires 8 bytes
- Base address at `.L4`

Jumping

- Direct:** `jmp .L8`
- Jump target is denoted by label `.L8`

Indirect: `jmp *.L4(, %rdi, 8)`

- Start of jump table: `.L4`
- Must scale by factor of 8 (addresses are 8 bytes)
- Fetch target from effective Address `.L4 + x*8`
 - Only for $0 \leq x \leq 6$

Jump table

```
.section      .rodata
    .align 8
.L4:
    .quad     .L8    # x = 0
    .quad     .L3    # x = 1
    .quad     .L5    # x = 2
    .quad     .L9    # x = 3
    .quad     .L8    # x = 4
    .quad     .L7    # x = 5
    .quad     .L7    # x = 6
```



Jump Table

Jump table

```
.section .rodata
.align 8
.L4:
.quad .L8 # x = 0
.quad .L3 # x = 1
.quad .L5 # x = 2
.quad .L9 # x = 3
.quad .L8 # x = 4
.quad .L7 # x = 5
.quad .L7 # x = 6
```

```
switch(x) {
case 1:      // .L3
    w = y*z;
    break;
case 2:      // .L5
    w = y/z;
    /* Fall Through */
case 3:      // .L9
    w += z;
    break;
case 5:
case 6:      // .L7
    w -= z;
    break;
default:    // .L8
    w = 2;
}
```



Code Blocks (x == 1)

```
switch(x) {  
  case 1:      // .L3  
    w = y*z;  
    break;  
  . . .  
}
```

```
.L3:  
  movq    %rsi, %rax  # y  
  imulq   %rdx, %rax  # y*z  
  ret
```

Register	Use(s)
%rdi	Argument x
%rsi	Argument y
%rdx	Argument z
%rax	Return value



Handling Fall-Through

```
long w = 1;  
.  
.  
.  
switch(x) {  
.  
.  
.  
case 2:   
    w = y/z;  
    /* Fall Through */  
case 3:   
    w += z;  
    break;  
.  
.  
.  
}
```

```
case 2:  
    w = y/z;  
    goto merge;
```

```
case 3:  
    w = 1;  
  
merge:  
    w += z;
```



Code Blocks (x == 2, x == 3)

```
long w = 1;
. . .
switch(x) {
. . .
case 2:
    w = y/z;
    /* Fall Through */
case 3:
    w += z;
    break;
. . .
}
```

```
.L5:                                # Case 2
    movq    %rsi, %rax
    cqto
    idivq   %rcx                    # y/z
    jmp     .L6                    # goto merge
.L9:                                # Case 3
    movl    $1, %eax               # w = 1
.L6:                                # merge:
    addq    %rcx, %rax             # w += z
    ret
```

Register	Use(s)
%rdi	Argument x
%rsi	Argument y
%rdx	Argument z
%rax	Return value



Code Blocks (x == 5, x == 6, default)

```
switch(x) {  
    . . .  
    case 5:  // .L7  
    case 6:  // .L7  
        w -= z;  
        break;  
    default: // .L8  
        w = 2;  
}
```

```
.L7:                # Case 5,6  
    movl    $1, %eax    # w = 1  
    subq    %rdx, %rax  # w -= z  
    ret  
.L8:                # Default:  
    movl    $2, %eax    # 2  
    ret
```

Register	Use(s)
%rdi	Argument x
%rsi	Argument y
%rdx	Argument z
%rax	Return value



Summarizing

🌀 C Control

- 🌀 if-then-else
- 🌀 do-while
- 🌀 while, for
- 🌀 switch

🌀 Assembler Control

- 🌀 Conditional jump
- 🌀 Conditional move
- 🌀 Indirect jump (via jump tables)
- 🌀 Compiler generates code sequence to implement more complex control

🌀 Standard Techniques

- 🌀 Loops converted to do-while or jump-to-middle form
- 🌀 Large switch statements use jump tables



Summary

🌀 Today

- 🌀 Control: Condition codes
- 🌀 Conditional branches & conditional moves
- 🌀 Loops
- 🌀 Switch statements

🌀 Next Time

- 🌀 Stack
- 🌀 Call / return
- 🌀 Procedure call discipline

