pimpamboing
Data Dictionary

Model: Model - Pimpamboing
Author: Administrator
Date: 2026-04-23 21:42:53
Version: 1.0

Generated with Navicat

Table of Contents

1. Introduction 1
2. Model: Model - Pimpamboing (MySQL) 2
    2.1. Database: pimpamboing 2
        2.1.1. Tables 2
            2.1.1.1. Table: bitacora 2
            2.1.1.2. Table: habilidades 2
            2.1.1.3. Table: licencias 3
            2.1.1.4. Table: metodos_pago 4
            2.1.1.5. Table: niveles 5
            2.1.1.6. Table: perfiles_jugadores 6
            2.1.1.7. Table: persona_fisica 7
            2.1.1.8. Table: persona_moral 7
            2.1.1.9. Table: personas 8
            2.1.1.10. Table: planes_licencia 9
            2.1.1.11. Table: progreso_niveles 9
            2.1.1.12. Table: sesiones_juego 10
            2.1.1.13. Table: transacciones_financieras 11
            2.1.1.14. Table: usuarios 12
        2.1.2. Views 14
            2.1.2.1. View: kpi_10_retencion_usuarios 14
            2.1.2.2. View: kpi_1_conversion_premium 14
            2.1.2.3. View: kpi_2_arpu 14
            2.1.2.4. View: kpi_3_abandono_checkout 14
            2.1.2.5. View: kpi_4_revenue_mix 14
            2.1.2.6. View: kpi_5_dispositivos 14
            2.1.2.7. View: kpi_6_abandono_niveles 14
            2.1.2.8. View: kpi_7_mrr 14
            2.1.2.9. View: kpi_8_crecimiento_usuarios 14
            2.1.2.10. View: kpi_9_rechazo_pagos 14
        2.1.3. Functions 15
            2.1.3.1. Function: fn_dias_restantes_licencia 15
            2.1.3.2. Function: fn_ingresos_persona 15
            2.1.3.3. Function: fn_licencia_vigente 15
            2.1.3.4. Function: fn_nivel_mas_jugado 15
            2.1.3.5. Function: fn_promedio_fallos_nino 16
            2.1.3.6. Function: fn_tasa_abandono_nino 16
            2.1.3.7. Function: fn_total_sesiones_nino 16
            2.1.3.8. Function: sp_simulacion_pinpon_v2 16

1. Introduction

A data dictionary is a collection of metadata such as object name, data type, size, classification, and relationships with other data assets. It is used by data administrators, analysts, and engineers to understand and trust data assets. It helps in the creation of authentic, transparent, and consistent data throughout the organization.

In this data dictionary, following models are chosen for documentation:
Model - Pimpamboing (MySQL)

For each model, definitions of tables (entities/collections), views, functions are listed in order. Detailed properties of data elements (data type, size, nullability, optionality, indexes, foreign keys, constraints) are organized in tabular format.

2. Model: Model - Pimpamboing (MySQL)

Version: 8.0

1 database is listed below.

2.1. Database: pimpamboing

Database objects to be listed: 14 tables, 10 views, 8 functions

2.1.1. Tables

2.1.1.1. Table: bitacora

Fields

Pos	Name	Type	Not Null	Others
1	id 🔑	int Auto Increment	✓	
2	tabla	varchar(100)		Index: idx_bitacora_tabla
3	operacion	enum		Index: idx_bitacora_operacion_fec...
4	usuario	varchar(100)		
5	descripcion	text		
6	fecha_hora	datetime		Default: CURRENT_TIMESTAMP Index: idx_bitacora_operacion_fec...

Indexes

Name	Type	Method	Fields
idx_bitacora_tabla	NORMAL	BTREE	tabla
idx_bitacora_operacion_fecha	NORMAL	BTREE	operacion, fecha_hora

2.1.1.2. Table: habilidades

Fields

Pos	Name	Type	Not Null	Others

1	id 🔑	int Auto Increment	✓	
2	nombre	varchar(100)		
3	descripcion	text		
4	estatus	enum		Default: 'Activo'

Triggers

Name	Time	Insert	Update	Delete
tr_hab_ins	AFTER	✓		
tr_hab_upd	AFTER		✓	
tr_hab_del	AFTER			✓

2.1.1.3. Table: licencias

Fields

Pos	Name	Type	Not Null	Others
1	id 🔑	int Auto Increment	✓	
2	personas_id	int		Index: fk_l_persona
3	plan_id	int		Index: fk_l_plan
4	fecha_inicio	datetime		
5	fecha_fin	datetime		
6	fecha_pago	datetime		
7	estatus	enum		Default: 'En Espera'
8	Temporalidad	enum		

Indexes

Name	Type	Method	Fields
fk_l_persona	NORMAL	BTREE	personas_id
fk_l_plan	NORMAL	BTREE	plan_id

Foreign Keys

Name	Fields	Referenced Table	Referenced Fields	On Delete	On Update
fk_l_persona	personas_id	pimpamboing.personas	id	RESTRICT	RESTRICT
fk_l_plan	plan_id	pimpamboing.planes_licencia	id	RESTRICT	RESTRICT

Triggers

Name	Time	Insert	Update	Delete
tr_lic_ins	AFTER	✓		
tr_licencias_upd	AFTER		✓	
tr_licencias_delete	AFTER			✓

2.1.1.4. Table: metodos_pago

Fields

Pos	Name	Type	Not Null	Others
1	id 🔑	int Auto Increment	✓	
2	personas_id	int		Index: fk_mp_persona
3	numero_tarjeta	char(16)		
4	tipo_red_bancaria	enum		
5	tipo_cuenta	enum		
6	titular	varchar(100)		
7	fecha_expiracion	char(5)		
8	fecha_registro	datetime		Default: CURRENT_TIMESTAMP
9	fecha_actualizacion	datetime		
10	estatus	enum		Default: 'Vigente'

Indexes

Name	Type	Method	Fields
fk_mp_persona	NORMAL	BTREE	personas_id

Foreign Keys

Name	Fields	Referenced Table	Referenced Fields	On Delete	On Update
fk_mp_persona	personas_id	pimpamboing.personas	id	RESTRICT	RESTRICT

Triggers

Name	Time	Insert	Update	Delete
tr_met_ins	AFTER	✓		
tr_met_upd	AFTER		✓	
tr_metodos_pago_del	AFTER			✓

2.1.1.5. Table: niveles

Fields

Pos	Name	Type	Not Null	Others
1	id 🔑	int Auto Increment	✓	
2	habilidad_id	int		Index: fk_n_habilidad
3	nombre_nivel	varchar(100)		
4	orden	int		
5	es_premium	tinyint(1)		
6	estatus	enum		Default: 'Activo'

Indexes

Name	Type	Method	Fields
fk_n_habilidad	NORMAL	BTREE	habilidad_id

Foreign Keys

Name	Fields	Referenced Table	Referenced Fields	On Delete	On Update
fk_n_habilidad	habilidad_id	pimpamboing.habilidades	id	RESTRICT	RESTRICT

Triggers

Name	Time	Insert	Update	Delete

tr_niv_ins	AFTER	✓		
tr_niveles_upd	AFTER		✓	
tr_niv_del	AFTER			✓

2.1.1.6. Table: perfiles_jugadores

Fields

Pos	Name	Type	Not Null	Others
1	id 🔑	int Auto Increment	✓	
2	personas_id	int		Index: fk_pj_persona
3	apodo	varchar(50)		Index: idx_perfil_apodo
4	fecha_nacimiento	date		
5	avatar_url	varchar(255)		
6	fecha_registro	datetime		Default: CURRENT_TIMESTAMP
7	fecha_actualizacion	datetime		
8	estatus	enum		Default: 'Activo'

Indexes

Name	Type	Method	Fields
fk_pj_persona	NORMAL	BTREE	personas_id
idx_perfil_apodo	NORMAL	BTREE	apodo

Foreign Keys

Name	Fields	Referenced Table	Referenced Fields	On Delete	On Update
fk_pj_persona	personas_id	pimpamboing.personas	id	RESTRICT	RESTRICT

Triggers

Name	Time	Insert	Update	Delete
tr_pro_ins	AFTER	✓		
tr_pro_upd	AFTER		✓	
tr_pro_del	AFTER			✓

2.1.1.7. Table: persona_fisica

Fields

Pos	Name	Type	Not Null	Others
1	personas_id 🔑	int	✓	
2	nombre	varchar(60)		
3	primer_apellido	varchar(60)		Index: idx_persona_apellido
4	segundo_apellido	varchar(60)		
5	fecha_nacimiento	date		
6	genero	enum		

Indexes

Name	Type	Method	Fields
idx_persona_apellido	NORMAL	BTREE	primer_apellido

Foreign Keys

Name	Fields	Referenced Table	Referenced Fields	On Delete	On Update
fk_pf_persona	personas_id	pimpamboing.personas	id	RESTRICT	RESTRICT

Triggers

Name	Time	Insert	Update	Delete
tr_pf_ins	AFTER	✓		
tr_pf_upd	AFTER		✓	
tr_pf_del	AFTER			✓

2.1.1.8. Table: persona_moral

Fields

Pos	Name	Type	Not Null	Others
1	personas_id 🔑	int	✓	
2	razon_social	varchar(200)		
3	tipo	varchar(100)		
4	fecha_creacion	date		

5	rfc	varchar(13)		
6	capacidad_juridica	varchar(100)		

Foreign Keys

Name	Fields	Referenced Table	Referenced Fields	On Delete	On Update
fk_pm_persona	personas_id	pimpamboing.personas	id	RESTRICT	RESTRICT

Triggers

Name	Time	Insert	Update	Delete
tr_pm_ins	AFTER	✓		
tr_persona_moral_upd	AFTER		✓	
tr_pm_del	AFTER			✓

2.1.1.9. Table: personas

Fields

Pos	Name	Type	Not Null	Others
1	id 🔑	int Auto Increment	✓	
2	tipo	enum		Default: 'Fisica'
3	fecha_registro	datetime		Default: CURRENT_TIMESTAMP
4	codigo_pais	char(2)		
5	estatus	enum		Default: 'Activo'

Triggers

Name	Time	Insert	Update	Delete
tr_per_ins	AFTER	✓		
tr_per_upd	AFTER		✓	
tr_personas_delete	AFTER			✓

2.1.1.10. Table: planes_licencia

Fields

Pos	Name	Type	Not Null	Others
1	id 🔑	int Auto Increment	✓	
2	nombre_plan	enum		
3	descripcion	text		
4	precio	decimal(10, 2)	✓	
5	duracion_dias	int	✓	
6	estatus	enum		Default: 'Activo'

Triggers

Name	Time	Insert	Update	Delete
tr_plan_ins	AFTER	✓		
tr_planes_upd	AFTER		✓	
tr_plan_del	AFTER			✓

2.1.1.11. Table: progreso_niveles

Fields

Pos	Name	Type	Not Null	Others
1	id 🔑	int Auto Increment	✓	
2	perfil_id	int		Index: fk_pn_perfil
3	nivel_id	int		Index: fk_pn_nivel
4	estatus	enum		Default: 'Bloqueado' Index: idx_progreso_estatus
5	intentos_fallidos	int		Default: 0
6	tiempo_empleado	time		
7	fecha_desbloqueo	datetime		
8	fecha_completado	datetime		

Indexes

Name	Type	Method	Fields
fk_pn_perfil	NORMAL	BTREE	perfil_id
fk_pn_nivel	NORMAL	BTREE	nivel_id
idx_progreso_estatus	NORMAL	BTREE	estatus

Foreign Keys

Name	Fields	Referenced Table	Referenced Fields	On Delete	On Update
fk_pn_nivel	nivel_id	pimpamboing.niveles	id	RESTRICT	RESTRICT
fk_pn_perfil	perfil_id	pimpamboing.perfiles_jugadores	id	RESTRICT	RESTRICT

Triggers

Name	Time	Insert	Update	Delete
tr_pno_ins	AFTER	✓		
tr_pno_upd	AFTER		✓	
tr_progreso_delete	AFTER			✓

2.1.1.12. Table: sesiones_juego

Fields

Pos	Name	Type	Not Null	Others
1	id 🔑	int Auto Increment	✓	
2	perfil_id	int		Index: fk_sj_perfil
3	nivel_id	int		Index: fk_sj_nivel
4	tipo_dispositivo	enum		Index: idx_sesiones_dispositivo
5	fecha_inicio	datetime		Default: CURRENT_TIMESTAMP
6	fecha_fin	datetime		
7	intentos_fallidos	int		
8	estatus	enum		Default: 'En Curso' Index: idx_sesiones_estatus

Indexes

Name	Type	Method	Fields
fk_sj_perfil	NORMAL	BTREE	perfil_id
fk_sj_nivel	NORMAL	BTREE	nivel_id
idx_sesiones_dispositivo	NORMAL	BTREE	tipo_dispositivo
idx_sesiones_estatus	NORMAL	BTREE	estatus

Foreign Keys

Name	Fields	Referenced Table	Referenced Fields	On Delete	On Update
fk_sj_nivel	nivel_id	pimpamboing.niveles	id	RESTRICT	RESTRICT
fk_sj_perfil	perfil_id	pimpamboing.perfiles_jugadores	id	RESTRICT	RESTRICT

Triggers

Name	Time	Insert	Update	Delete
tr_ses_ins	AFTER	✓		
tr_sesiones_upd	AFTER		✓	
tr_ses_del	AFTER			✓

2.1.1.13. Table: transacciones_financieras

Fields

Pos	Name	Type	Not Null	Others
1	id 🔑	int Auto Increment	✓	
2	personas_id	int		Index: fk_tf_persona
3	metodo_pago_id	int		Index: fk_tf_metodo
4	monto	decimal(10, 2)	✓	
5	tipo	enum		
6	fecha_registro	datetime		Default: CURRENT_TIMESTAMP Index: idx_transacciones_fecha

7	fecha_actualizacion	datetime		Default: CURRENT_TIMESTAMP
8	estatus	enum		Index: idx_transacciones_estatus

Indexes

Name	Type	Method	Fields
fk_tf_persona	NORMAL	BTREE	personas_id
fk_tf_metodo	NORMAL	BTREE	metodo_pago_id
idx_transacciones_estatus	NORMAL	BTREE	estatus
idx_transacciones_fecha	NORMAL	BTREE	fecha_registro

Foreign Keys

Name	Fields	Referenced Table	Referenced Fields	On Delete	On Update
fk_tf_metodo	metodo_pago_id	pimpamboing.metodos_pago	id	RESTRICT	RESTRICT
fk_tf_persona	personas_id	pimpamboing.personas	id	RESTRICT	RESTRICT

Triggers

Name	Time	Insert	Update	Delete
tr_trans_ins	AFTER	✓		
tr_tra_upd	AFTER		✓	
tr_tra_del	AFTER			✓

2.1.1.14. Table: usuarios

Fields

Pos	Name	Type	Not Null	Others
1	id 🔑	int Auto Increment	✓	
2	personas_id	int		Index: fk_u_persona
3	email	varchar(150)		Index: email idx_usuarios_email

4	password	varchar(255)		
5	ultimo_acceso	datetime		
6	estatus	enum		Default: 'Activo'

Indexes

Name	Type	Method	Fields
email	UNIQUE	BTREE	email
fk_u_persona	NORMAL	BTREE	personas_id
idx_usuarios_email	NORMAL	BTREE	email

Foreign Keys

Name	Fields	Referenced Table	Referenced Fields	On Delete	On Update
fk_u_persona	personas_id	pimpamboing.personas	id	RESTRICT	RESTRICT

Triggers

Name	Time	Insert	Update	Delete
tr_usu_ins	AFTER	✓		
tr_usu_upd	AFTER		✓	
tr_usuarios_delete	AFTER			✓

2.1.2. Views

2.1.2.1. View: kpi_10_retencion_usuarios

2.1.2.2. View: kpi_1_conversion_premium

2.1.2.3. View: kpi_2_arpu

2.1.2.4. View: kpi_3_abandono_checkout

2.1.2.5. View: kpi_4_revenue_mix

2.1.2.6. View: kpi_5_dispositivos

2.1.2.7. View: kpi_6_abandono_niveles

2.1.2.8. View: kpi_7_mrr

2.1.2.9. View: kpi_8_crecimiento_usuarios

2.1.2.10. View: kpi_9_rechazo_pagos

2.1.3. Functions

2.1.3.1. Function: fn_dias_restantes_licencia

Function Type: Function

Return Type: int

Parameters

Mode	Name	Data Type
IN	p_persona_id	INT

2.1.3.2. Function: fn_ingresos_persona

Function Type: Function

Return Type: decimal(10,2)

Parameters

Mode	Name	Data Type
IN	p_persona_id	INT

2.1.3.3. Function: fn_licencia_vigente

Function Type: Function

Return Type: tinyint

Parameters

Mode	Name	Data Type
IN	p_persona_id	INT

2.1.3.4. Function: fn_nivel_mas_jugado

Function Type: Function

Return Type: varchar(100) CHARSET utf8mb4

Parameters

Mode	Name	Data Type
IN	p_perfil_id	INT

2.1.3.5. Function: fn_promedio_fallos_nino

Function Type: Function

Return Type: decimal(5,2)

Parameters

Mode	Name	Data Type
IN	p_perfil_id	INT

2.1.3.6. Function: fn_tasa_abandono_nino

Function Type: Function

Return Type: decimal(5,2)

Parameters

Mode	Name	Data Type
IN	p_perfil_id	INT

2.1.3.7. Function: fn_total_sesiones_nino

Function Type: Function

Return Type: int

Parameters

Mode	Name	Data Type
IN	p_perfil_id	INT

2.1.3.8. Function: sp_simulacion_pinpon_v2

Function Type: Procedure

Parameters

Mode	Name	Data Type
IN	p_personas	INT
IN	p_max_ninos	INT
IN	p_max_sesiones	INT