

WDL Question Paper – Set 1

HTML Programming – Questions with Output Images & Code Answers

Q1: Write a HTML code to generate the following output

Q] 1. HTML Programming

a) Write a HTML program to design a form which should allow to enter your personal data
(Hint: make use of text field, password field, e-mail, lists, radio buttons, checkboxes, submit button)

b) Write html code to generate following output.

- Coffee
- Tea
 - Black Tea
 - Green Tea
- Milk

Part (a) – Personal Data Form (text, password, email, radio, checkbox, dropdown):

```
<!DOCTYPE html>
<html>
<head><title>Personal Data Form</title></head>
<body>
  <h2>Personal Information Form</h2>
  <form>
    <label>Name: <input type="text" name="name"></label><br><br>
    <label>Password: <input type="password" name="pwd"></label><br><br>
    <label>Email: <input type="email" name="email"></label><br><br>

    Gender:
    <input type="radio" name="gender" value="Male"> Male
    <input type="radio" name="gender" value="Female"> Female <br><br>

    Hobbies:
    <input type="checkbox" name="h1" value="Reading"> Reading
    <input type="checkbox" name="h2" value="Sports"> Sports
    <input type="checkbox" name="h3" value="Music"> Music <br><br>

    Country:
    <select name="country">
      <option value="India">India</option>
      <option value="USA">USA</option>
      <option value="UK">UK</option>
    </select><br><br>

    <input type="submit" value="Submit">
    <input type="reset" value="Reset">
  </form>
</body>
</html>
```

Part (b) – Nested Unordered List (Coffee, Tea → Black/Green, Milk):

```
<!DOCTYPE html>
```

```
<html>
<head><title>Nested Lists</title></head>
<body>
  <ul>
    <li>Coffee</li>
    <li>Tea
      <ul>
        <li>Black Tea</li>
        <li>Green Tea</li>
      </ul>
    </li>
    <li>Milk</li>
  </ul>
</body>
</html>
```

Q2: Write a HTML code to generate the following output

GeeksforGeeks

Table with Rowspan and Colspan

Name		Class	School
Mahima	Gupta	11	MVM School
		A	
Sri	Krishn	3	LMS School
		B	
Shivika	Goyal	5	SCPM School
		A	

Code – GeeksforGeeks Table with Rowspan and Colspan:

```
<!DOCTYPE html>
<html>
<head>
  <title>GeeksforGeeks Table</title>
  <style>
    body { font-family: Arial, sans-serif; }
    h1 { color: green; text-align: center; }
    h3 { color: green; text-align: center; }
    table { border-collapse: collapse; width: 80%; margin: auto; }
    td, th { border: 1px solid black; padding: 8px; }
    th { text-align: center; font-weight: bold; }
    .fname { color: red; }
    .lname { color: orange; }
  </style>
</head>
<body>
  <h1>GeeksforGeeks</h1>
  <h3>Table with Rowspan and Colspan</h3>
  <table>
    <tr>
      <th colspan="2">Name</th>
      <th>Class</th>
      <th>School</th>
    </tr>
    <!-- Mahima row: first name + last name span 2 rows, school spans 2 rows -->
    <tr>
      <td rowspan="2" class="fname">Mahima</td>
      <td rowspan="2" class="lname">Gupta</td>
      <td>11</td>
      <td rowspan="2">MVM School</td>
    </tr>
    <tr><td>A</td></tr>

    <!-- Sri row -->
```

```
<tr>
  <td rowspan="2" class="fname">Sri</td>
  <td rowspan="2" class="lname">Krishn</td>
  <td>3</td>
  <td rowspan="2">LMS School</td>
</tr>
<tr><td>B</td></tr>

<!-- Shivika row -->
<tr>
  <td rowspan="2" class="fname">Shivika</td>
  <td rowspan="2" class="lname">Goyal</td>
  <td>5</td>
  <td rowspan="2">SCPM School</td>
</tr>
<tr><td>A</td></tr>
</table>
</body>
</html>
```

Q3: Write a HTML code to generate the following output

Write a HTML code to generate following output



Code – HTML Frames Layout (Top Frame + Left Frame + Right Frame):

```
<!-- main.html (load this file in your browser) -->
<!DOCTYPE html>
<html>
<head><title>Frames Layout</title></head>
<frameset rows="40%,60%">

    <!-- Top Frame -->
    <frame src="top.html" name="topFrame">

    <!-- Bottom row split into Left and Right -->
    <frameset cols="50%,50%">
        <frame src="left.html" name="leftFrame">
        <frame src="right.html" name="rightFrame">
    </frameset>
</frameset>
</html>

<!-- top.html -->
<!DOCTYPE html>
<html>
<body style="background:darkred; color:white;
            display:flex; align-items:center;
            justify-content:center; height:100%; margin:0;
            font-size:22px; font-weight:bold;">
    Top Frame
</body>
</html>

<!-- left.html -->
<!DOCTYPE html>
<html>
<body style="background:orange; color:white;
            display:flex; align-items:center;
            justify-content:center; height:100%; margin:0;
            font-size:20px; font-weight:bold;">
    Left Frame
</body>
</html>

<!-- right.html -->
<!DOCTYPE html>
```

```
<html>
<body style="background:orange; color:white;
            display:flex; align-items:center;
            justify-content:center; height:100%; margin:0;
            font-size:20px; font-weight:bold;">
    Right Frame
</body>
</html>
```

Q4: Write a HTML code to generate the following output

Write a HTML code to generate following output



Code – Colored Frames (Orange, Blue, Red, Green):

```
<!-- main.html -->
<!DOCTYPE html>
<html>
<head><title>Color Frames</title></head>
<!-- Top row: ORANGE (left big) | right column (RED top + GREEN top + BLUE bottom) -->
<frameset cols="50%,50%">

    <!-- Left column: ORANGE (top half) + BLUE (bottom half) -->
    <frameset rows="50%,50%">
        <frame src="orange.html" name="orange">
        <frame src="blue.html" name="blue">
    </frameset>

    <!-- Right column: RED (spans full) + GREEN (top) stacked, then BLUE handled left -->
    <frameset rows="50%,50%">
        <frameset cols="50%,50%">
            <frame src="red.html" name="red">
            <frame src="green.html" name="green">
        </frameset>
        <!-- Bottom right is empty to match the image layout -->
        <frame src="empty.html" name="empty">
    </frameset>

</frameset>
</html>

<!-- orange.html -->
<!DOCTYPE html>
<html>
<body style="background:orange; display:flex; align-items:center;
            justify-content:center; height:100%; margin:0;">
```



```
    <b style="color:white; font-size:24px; font-family:Impact;">ORANGE</b>
</body>
</html>
```

```
<!-- blue.html -->
<!DOCTYPE html>
<html>
<body style="background:blue; display:flex; align-items:center;
            justify-content:center; height:100%; margin:0;">
    <b style="color:white; font-size:24px; font-family:Impact;">BLUE</b>
</body>
</html>
```

```
<!-- red.html -->
<!DOCTYPE html>
<html>
<body style="background:red; display:flex; align-items:center;
            justify-content:center; height:100%; margin:0;">
    <b style="color:white; font-size:24px; font-family:Impact;">RED</b>
</body>
</html>
```

```
<!-- green.html -->
<!DOCTYPE html>
<html>
<body style="background:darkgreen; display:flex; align-items:center;
            justify-content:center; height:100%; margin:0;">
    <b style="color:white; font-size:24px; font-family:Impact;">GREEN</b>
</body>
</html>
```

```
<!-- empty.html -->
<!DOCTYPE html>
<html>
<body style="background:red; height:100%; margin:0;"></body>
</html>
```

Q5: Write HTML Code to generate the following Output

Time Table						
Hours	Mon	Tue	wed	Thur	Fri	Sat
	DBMS	WT	OOAD	JP	OR	COA
		OR	WT	COA	OOAD	JP
	LUNCH BREAK					
	DBMS	WT	OOAD	JP	OR	COA
	DBMS	OR	WT	COA	OOAD	JP

Code – Time Table using HTML Table with Rowspan and Colspan:

```
<!DOCTYPE html>
<html>
<head>
  <title>Time Table</title>
  <style>
    body { font-family: Arial, sans-serif; }
    table {
      border-collapse: collapse;
      border: 3px solid green;
    }
    td, th {
      border: 2px solid green;
      padding: 6px 10px;
      background-color: yellow;
      text-align: center;
    }
    .header-row td {
      background-color: pink;
      font-weight: bold;
    }
    .hours-cell {
      background-color: green;
      color: white;
      font-weight: bold;
      font-size: 18px;
    }
    .lunch {
      background-color: pink;
    }
  </style>
</head>
<body>
  <table>
    <tr>
      <th data-cs="7" data-kind="parent">Time Table</th>
      <th data-kind="ghost"></th>
      <th data-kind="ghost"></th>
      <th data-kind="ghost"></th>
      <th data-kind="ghost"></th>
      <th data-kind="ghost"></th>
      <th data-kind="ghost"></th>
    </tr>
    <tr>
      <th data-kind="parent" data-rs="6">Hours</th>
      <th>Mon</th>
      <th>Tue</th>
      <th>wed</th>
      <th>Thur</th>
      <th>Fri</th>
      <th>Sat</th>
    </tr>
    <tr>
      <th data-kind="ghost"></th>
      <td data-kind="parent" data-rs="2">DBMS</td>
      <td>WT</td>
      <td>OOAD</td>
      <td>JP</td>
      <td>OR</td>
      <td>COA</td>
    </tr>
    <tr>
      <th data-kind="ghost"></th>
      <td data-kind="ghost"></td>
      <td>OR</td>
      <td>WT</td>
      <td>COA</td>
      <td>OOAD</td>
      <td>JP</td>
    </tr>
    <tr>
      <th data-kind="ghost"></th>
      <td data-cs="6" data-kind="parent">LUNCH BREAK</td>
      <td data-kind="ghost"></td>
      <td data-kind="ghost"></td>
      <td data-kind="ghost"></td>
      <td data-kind="ghost"></td>
      <td data-kind="ghost"></td>
    </tr>
    <tr>
      <th data-kind="ghost"></th>
      <td>DBMS</td>
      <td>WT</td>
      <td>OOAD</td>
      <td>JP</td>
      <td>OR</td>
      <td>COA</td>
    </tr>
    <tr>
      <th data-kind="ghost"></th>
      <td>DBMS</td>
      <td>OR</td>
      <td>WT</td>
      <td>COA</td>
      <td>OOAD</td>
      <td>JP</td>
    </tr>
  </table>
</body>
</html>
```

```

        font-weight: bold;
    }
</style>
</head>
<body>
<table>
    <!-- Title row -->
    <tr>
        <td class="header-row" colspan="7"
            style="background:pink; font-size:18px;">
            Time Table
        </td>
    </tr>
    <!-- Day headings row -->
    <tr class="header-row">
        <td></td>
        <td>Mon</td>
        <td>Tue</td>
        <td>wed</td>
        <td>Thur</td>
        <td>Fri</td>
        <td>Sat</td>
    </tr>
    <!-- Row 1 -->
    <tr>
        <td class="hours-cell" rowspan="5">Hours</td>
        <td rowspan="2">DBMS</td>
        <td>WT</td>
        <td>OOAD</td>
        <td>JP</td>
        <td>OR</td>
        <td>COA</td>
    </tr>
    <!-- Row 2 -->
    <tr>
        <td>OR</td>
        <td>WT</td>
        <td>COA</td>
        <td>OOAD</td>
        <td>JP</td>
    </tr>
    <!-- Lunch Break -->
    <tr>
        <td class="lunch" colspan="6">LUNCH BREAK</td>
    </tr>
    <!-- Row 3 -->
    <tr>
        <td>DBMS</td>
        <td>WT</td>
        <td>OOAD</td>
        <td>JP</td>
        <td>OR</td>
        <td>COA</td>
    </tr>
    <!-- Row 4 -->
    <tr>
        <td>DBMS</td>
        <td>OR</td>

```

```
<td>WT</td>
<td>COA</td>
<td>OOAD</td>
<td>JP</td>
</tr>
</table>
</body>
</html>
```

Q6: Write HTML Code to generate the following Output

First Frame: Name and address		
Second frame	Third frame	
Bulleted list of qualifications	Links to favourite sites	
Fourth frame	Fifth frame	Sixth frame
Scrolling message	Blinking reminders	Image

Code – 6-Frame Layout (Name, Qualifications, Links, Scroll, Blink, Image):

```
<!-- index.html - 6-frame layout -->
<!DOCTYPE html>
<html>
<head><title>6 Frame Layout</title></head>
<frameset rows="20%,40%,40%">

    <!-- Row 1: First Frame (Name and address) -->
    <frame src="frame1.html" name="f1">

    <!-- Row 2: Second + Third frame side by side -->
    <frameset cols="50%,50%">
        <frame src="frame2.html" name="f2">
        <frame src="frame3.html" name="f3">
    </frameset>

    <!-- Row 3: Fourth + Fifth + Sixth frame -->
    <frameset cols="33%,33%,34%">
        <frame src="frame4.html" name="f4">
        <frame src="frame5.html" name="f5">
        <frame src="frame6.html" name="f6">
    </frameset>

</frameset>
</html>

<!-- frame1.html: Name and address -->
<!DOCTYPE html>
<html>
<body style="background:#ff8c00; color:white; padding:10px;
            font-family:Arial; font-size:16px; font-weight:bold;">
    First Frame: Name and address
    <p style="font-weight:normal;">John Doe, 123 Main Street, Mumbai - 400001</p>
</body>
</html>

<!-- frame2.html: Bulleted list of qualifications -->
<!DOCTYPE html>
```

```

<html>
<body style="background:#ffd0b0; font-family:Arial; padding:10px;">
  <b>Second frame: Bulleted list of qualifications</b>
  <ul>
    <li>B.Sc. Computer Science</li>
    <li>M.Sc. Information Technology</li>
    <li>Diploma in Web Design</li>
  </ul>
</body>
</html>

<!-- frame3.html: Links to favourite sites -->
<!DOCTYPE html>
<html>
<body style="background:#ffd0b0; font-family:Arial; padding:10px;">
  <b>Third frame: Links to favourite sites</b>
  <ul>
    <li><a href="https://google.com" target="_blank">Google</a></li>
    <li><a href="https://youtube.com" target="_blank">YouTube</a></li>
    <li><a href="https://github.com" target="_blank">GitHub</a></li>
  </ul>
</body>
</html>

<!-- frame4.html: Scrolling message -->
<!DOCTYPE html>
<html>
<body style="background:#ffd0b0; font-family:Arial; padding:10px;">
  <b>Fourth frame: Scrolling message</b><br><br>
  <marquee behavior="scroll" direction="left" scrollamount="4"
    style="color:darkred; font-weight:bold;">
    Welcome to my personal webpage! Enjoy your visit!
  </marquee>
</body>
</html>

<!-- frame5.html: Blinking reminders -->
<!DOCTYPE html>
<html>
<body style="background:#ffd0b0; font-family:Arial; padding:10px;">
  <b>Fifth frame: Blinking reminders</b><br><br>
  <blink style="color:red; font-weight:bold;">
    *** Meeting at 3 PM today! ***
  </blink>
  <p style="animation: blink 1s step-start infinite; color:red;">
    Don't forget to submit the assignment!
  </p>
  <style>
    @keyframes blink { 50% { opacity: 0; } }
    p { animation: blink 1s step-start infinite; }
  </style>
</body>
</html>

<!-- frame6.html: Image -->
<!DOCTYPE html>
<html>
<body style="background:#ffd0b0; font-family:Arial; padding:10px;"

```

```
        text-align:center;">
<b>Sixth frame: Image</b><br><br>
<!-- Replace photo.jpg with your actual image file -->

</body>
</html>
```

Q7: Write a HTML code to generate the following output

Write a HTML code to generate following output

- **Maharashtra**
 - **Pune**
 - I. Dighi**
 - II. Moshi**
 - III. Shivajinagar**
 - **Mumbai**
 - I. Santakruiz**
 - II. Vikroli**
 - III. Mumbra**

Code – Nested List: Maharashtra → Pune/Mumbai → Roman numbered places:

```
<!DOCTYPE html>
<html>
<head><title>Nested List - Maharashtra</title></head>
<body>
  <!-- Outermost: disc bullet (default) -->
  <ul>
    <li>Maharashtra
      <!-- Second level: circle bullets -->
      <ul style="list-style-type: circle;">
        <li>Pune
          <!-- Third level: upper-roman (I. II. III.) -->
          <ol type="I">
            <li>Dighi</li>
            <li>Moshi</li>
            <li>Shivajinagar</li>
          </ol>
        </li>
        <li>Mumbai
          <ol type="I">
            <li>Santakruiz</li>
            <li>Vikroli</li>
            <li>Mumbra</li>
          </ol>
        </li>
      </ul>
    </li>
  </ul>
</body>
</html>
```


Q8: Write the HTML code to generate the following output

2. Write the HTML code which generates the following output.

Country	Population (In Crores)	
INDIA	1998	85
	1999	90
	2000	100
USA	1998	30
	1999	35
	2000	40
UK	1998	25
	1999	30
	2000	35

Code – Country Population Table with Rowspan and Colspan:

```
<!DOCTYPE html>
<html>
<head>
  <title>Country Population Table</title>
  <style>
    table { border-collapse: collapse; width: 60%; margin: 20px auto; }
    td, th { border: 1px solid black; padding: 6px 12px; text-align: center; }
    th { font-weight: bold; }
  </style>
</head>
<body>
  <table>
    <tr>
      <th>Country</th>
      <th colspan="2">Population (In Crores)</th>
    </tr>
    <!-- INDIA: country cell spans 3 rows -->
    <tr>
      <td rowspan="3">INDIA</td>
      <td>1998</td>
      <td>85</td>
    </tr>
    <tr>
      <td>1999</td>
      <td>90</td>
    </tr>
    <tr>
      <td>2000</td>
      <td>100</td>
    </tr>
    <!-- USA: country cell spans 3 rows -->
    <tr>
      <td rowspan="3">USA</td>
      <td>1998</td>
      <td>30</td>
    </tr>
```

```
<tr>
  <td>1999</td>
  <td>35</td>
</tr>
<tr>
  <td>2000</td>
  <td>40</td>
</tr>
<!-- UK: country cell spans 3 rows -->
<tr>
  <td rowspan="3">UK</td>
  <td>1998</td>
  <td>25</td>
</tr>
<tr>
  <td>1999</td>
  <td>30</td>
</tr>
<tr>
  <td>2000</td>
  <td>35</td>
</tr>
</table>
</body>
</html>
```

Q9: Write a HTML code to generate the following output

Write a HTML code to generate following output.

Enter Name of your friend	
Choose the file you want to post to your friend	
	Browse...
What does the file contain?	
☒ Image	☒ Source code
☐ Binary code	
You have Completed the Form .	Submit Query

Code – File Upload Form with Checkboxes and Submit Button:

```
<!DOCTYPE html>
<html>
<head><title>File Upload Form</title></head>
<body>
  <form>
    <table>
      <tr>
        <td>Enter Name of your friend</td>
        <td><input type="text" name="friendname" size="30"></td>
      </tr>
      <tr>
        <td colspan="2">Choose the file you want to post to your friend</td>
      </tr>
      <tr>
        <td colspan="2">
          <input type="file" name="uploadfile">
        </td>
      </tr>
      <tr>
        <td colspan="2">What does the file contain?</td>
      </tr>
      <tr>
        <td colspan="2">
          <input type="checkbox" name="filetype" value="image" checked> Image
          <input type="checkbox" name="filetype" value="source" checked> Source code
          <input type="checkbox" name="filetype" value="binary"> Binary code
        </td>
      </tr>
      <tr>
        <td>You have Completed the Form .</td>
        <td><input type="submit" value="Submit Query"
          style="font-weight:bold; padding:6px 14px;"></td>
      </tr>
    </table>
  </form>
</body>
</html>
```

```
</form>
</body>
</html>
```

Q10: Write a HTML Code that generates the following output

- **Maharashtra**
 - i. Pune**
 - ii. Dighi**
 - iii. Moshi**
 - iv. Shivajinagar**
- **Mumbai**
 - i. Santakruiz**
 - ii. Vikroli**
 - iii. Mumbra**

Code – Nested List: Maharashtra/Mumbai with lower-roman ordered sub-list:

```
<!DOCTYPE html>
<html>
<head><title>Maharashtra Nested List</title></head>
<body>
  <!-- Outer: circle bullets -->
  <ul style="list-style-type: circle;">
    <li>Maharashtra
      <!-- Inner: lower-roman i. ii. iii. -->
      <ol type="i">
        <li>Pune</li>
        <li>Dighi</li>
        <li>Moshi</li>
        <li>Shivajinagar</li>
      </ol>
    </li>
    <li>Mumbai
      <ol type="i">
        <li>Santakruiz</li>
        <li>Vikroli</li>
        <li>Mumbra</li>
      </ol>
    </li>
  </ul>
</body>
</html>
```

Q11: Write a HTML Code that generates the following output

- 1
- 2
 - 2.1
 - 2.2
- 3

Code – Bullet list 1, 2 (with 2.1, 2.2), 3:

```
<!DOCTYPE html>
<html>
<head><title>Nested List 1 2 2.1 2.2 3</title></head>
<body>
  <ul>
    <li>1</li>
    <li>2
      <ul style="list-style-type: circle;">
        <li>2.1</li>
        <li>2.2</li>
      </ul>
    </li>
    <li>3</li>
  </ul>
</body>
</html>
```

Q12: Write a HTML Code that generates the following output

Create following output.

- **Milk**
 - A. Paneer**
 - B. Ghee**
 - C. Ice Cream**
- **Coffee**
 - a. Hot Coffee**
 - b. Cold Coffee**

Code – Nested List: Milk (A/B/C) and Coffee (a/b):

```
<!DOCTYPE html>
<html>
<head><title>Milk and Coffee List</title></head>
<body>
  <ul>
    <li>Milk
      <!-- Upper-case alphabetic: A. B. C. -->
      <ol type="A">
        <li>Paneer</li>
        <li>Ghee</li>
        <li>Ice Cream</li>
      </ol>
    </li>
    <li>Coffee
      <!-- Lower-case alphabetic: a. b. -->
      <ol type="a">
        <li>Hot Coffee</li>
        <li>Cold Coffee</li>
      </ol>
    </li>
  </ul>
</body>
</html>
```

Q13: Write a HTML Code that generates the following output



Create Tables in HTML

Columu 1	Columu 2	Columu 3
Row 1 Cell 1	Row 1 Cell 2	Row 1 Cell 3
	Row 2 Cell 2	Row 2 Cell 3
Row 3 Cell 1		

Code – HTML Table with Rowspan and Colspan (Column headers + merged cells):

```
<!DOCTYPE html>
<html>
<head>
  <title>Create Tables in HTML</title>
  <style>
    table { border-collapse: collapse; width: 60%; margin: 20px; }
    td, th { border: 1px solid black; padding: 10px 16px; }
    th { text-align: center; }
  </style>
</head>
<body>
  <h2>Create Tables in HTML</h2>
  <table>
    <!-- Header row with 3 columns -->
    <tr>
      <th>Columu 1</th>
      <th>Columu 2</th>
      <th>Columu 3</th>
    </tr>
    <!-- Row 1: Cell 1 spans 2 rows, Cells 2 and 3 are separate -->
    <tr>
      <td rowspan="2">Row 1 Cell 1</td>
      <td>Row 1 Cell 2</td>
      <td>Row 1 Cell 3</td>
    </tr>
    <!-- Row 2: only Cells 2 and 3 (Cell 1 is covered by rowspan) -->
    <tr>
      <td>Row 2 Cell 2</td>
      <td>Row 2 Cell 3</td>
    </tr>
    <!-- Row 3: Cell 1 spans all 3 columns -->
```



```
<tr>
  <td colspan="3">Row 3 Cell 1</td>
</tr>
</table>
</body>
</html>
```

Q14: Write a HTML Code that generates the following output

Complex Table Examl... >

Team	Player	Statistics	
Team A	Player 1	Goals: 4	Assists: 7
	Player 2	Goals: 6	Assists: 5
Team B	Player 3	Goals: 5	Assists: 6
	Player 4	Goals: 3	Assists: 8

Code – Sports Statistics Table (Team A/B with Player stats, Rowspan):

```
<!DOCTYPE html>
<html>
<head>
  <title>Sports Statistics Table</title>
  <style>
    table { border-collapse: collapse; width: 55%; margin: 20px; }
    td, th { border: 1px solid black; padding: 8px 14px; text-align: center; }
    th { font-weight: bold; }
  </style>
</head>
<body>
  <table>
    <!-- Header row -->
    <tr>
      <th>Team</th>
      <th>Player</th>
      <th colspan="2">Statistics</th>
    </tr>
    <!-- Team A: spans 2 rows -->
    <tr>
      <td rowspan="2">Team A</td>
      <td>Player 1</td>
      <td>Goals: 4</td>
      <td>Assists: 7</td>
    </tr>
    <tr>
      <td>Player 2</td>
      <td>Goals: 6</td>
      <td>Assists: 5</td>
    </tr>
    <!-- Team B: spans 2 rows -->
    <tr>
      <td rowspan="2">Team B</td>
```

```
        <td>Player 3</td>
        <td>Goals: 5</td>
        <td>Assists: 6</td>
    </tr>
    <tr>
        <td>Player 4</td>
        <td>Goals: 3</td>
        <td>Assists: 8</td>
    </tr>
</table>
</body>
</html>
```

Q15: Write a HTML Code that generates the following output

A test table with merged cells			
	Average		Red eyes
	height	weight	
Males	1.9	0.003	40%
Females	1.7	0.002	43%

Code – Test Table with Merged Cells (Average height/weight, Red eyes):

```
<!DOCTYPE html>
<html>
<head>
  <title>Merged Cells Test Table</title>
  <style>
    body { font-family: Arial, sans-serif; font-size: 14px; }
    table { border-collapse: collapse; margin: 20px; }
    td, th { border: 1px solid black; padding: 6px 14px; text-align: center; }
    caption { font-style: italic; margin-bottom: 6px; }
  </style>
</head>
<body>
  <table>
    <caption>A test table with merged cells</caption>
    <tr>
      <!-- Top-left corner: empty cell spanning 2 rows and 1 col -->
      <td rowspan="2"></td>
      <!-- "Average" spans 2 columns -->
      <th colspan="2">Average</th>
      <!-- "Red eyes" spans 2 rows -->
      <td rowspan="2">Red<br>eyes</td>
    </tr>
    <tr>
      <!-- Sub-columns under Average -->
      <th>height</th>
      <th>weight</th>
    </tr>
    <tr>
      <th>Males</th>
      <td>1.9</td>
      <td>0.003</td>
      <td>40%</td>
    </tr>
    <tr>
      <th>Females</th>
      <td>1.7</td>
      <td>0.002</td>
      <td>43%</td>
    </tr>
  </table>
</body>
```

</html>