

Indian Airlines Ticket Price Analysis

Samarth Chetan

MS in Data Analytics Engineering

Northeastern University

```
In [3]: # importing necessary libraries for conducting EDA
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
import seaborn as sns
import warnings
warnings.filterwarnings('ignore')
```

```
In [9]: # reading the dataset using built-in functions
df = pd.read_csv("Indian Airlines.csv")
df.head(10)
```

```
Out[9]:
```

	Unnamed: 0	airline	flight	source_city	departure_time	stops	arrival_time	destination_city	class	duration	days_left	price
0	0	SpiceJet	SG-8709	Delhi	Evening	zero	Night	Mumbai	Economy	2.17	1	5953
1	1	SpiceJet	SG-8157	Delhi	Early_Morning	zero	Morning	Mumbai	Economy	2.33	1	5953
2	2	AirAsia	I5-764	Delhi	Early_Morning	zero	Early_Morning	Mumbai	Economy	2.17	1	5956
3	3	Vistara	UK-995	Delhi	Morning	zero	Afternoon	Mumbai	Economy	2.25	1	5955
4	4	Vistara	UK-963	Delhi	Morning	zero	Morning	Mumbai	Economy	2.33	1	5955
5	5	Vistara	UK-945	Delhi	Morning	zero	Afternoon	Mumbai	Economy	2.33	1	5955
6	6	Vistara	UK-927	Delhi	Morning	zero	Morning	Mumbai	Economy	2.08	1	6060
7	7	Vistara	UK-951	Delhi	Afternoon	zero	Evening	Mumbai	Economy	2.17	1	6060
8	8	GO_FIRST	G8-334	Delhi	Early_Morning	zero	Morning	Mumbai	Economy	2.17	1	5954
9	9	GO_FIRST	G8-336	Delhi	Afternoon	zero	Evening	Mumbai	Economy	2.25	1	5954


```
In [10]: df.nunique()
```

```
Out[10]: Unnamed: 0      300153
         airline      6
         flight    1561
         source_city  6
         departure_time  6
         stops      3
         arrival_time  6
         destination_city  6
         class      2
         duration    476
         days_left   49
         price      12157
         dtype: int64
```


```
In [11]: # understanding column information
         for col in df:
             if df[col].dtype == 'object':
                 print(df[col].unique())
```

```
['SpiceJet' 'AirAsia' 'Vistara' 'GO_FIRST' 'Indigo' 'Air_India']
['SG-8709' 'SG-8157' 'I5-764' ... '6E-7127' '6E-7259' 'AI-433']
['Delhi' 'Mumbai' 'Bangalore' 'Kolkata' 'Hyderabad' 'Chennai']
['Evening' 'Early_Morning' 'Morning' 'Afternoon' 'Night' 'Late_Night']
['zero' 'one' 'two_or_more']
['Night' 'Morning' 'Early_Morning' 'Afternoon' 'Evening' 'Late_Night']
['Mumbai' 'Bangalore' 'Kolkata' 'Hyderabad' 'Chennai' 'Delhi']
['Economy' 'Business']
```


```
In [15]: # conducting EDA
         # number of flights operating form each airlines
         from turtle import title
         plt.figure(figsize=(15,5))
         NF = sns.countplot(x='airline', data = df)
         NF.set(xlabel='Airline in India', ylabel='Total number of flights', title='Number of flights by airlines')
         plt.show(NF)
```




```
In [14]: # price range analysis as a factor of class of travel
from turtle import title
plt.figure(figsize=(15,5))
CE = sns.stripplot(x='price', y='class', data = df)
CE.set(xlabel='Ticket cost', ylabel='Travel Class', title='Price Range')
plt.show(CE)
```




```
In [17]: #ticket availability by class of travel
from turtle import title
plt.figure(figsize=(15,5))
TA = sns.countplot(x='class', data = df)
TA.set(xlabel='Travel Class', title='Ticket availability')
plt.show(TA)
```




```
In [20]: #price of tickets based on duration of flight
plt.figure(figsize=(15,5))
PD = sns.scatterplot(df['duration'], df['price'], hue= df['airline'])
PD.set(xlabel='Flight duration', ylabel='Ticket Price', title='Ticket price v/s Flight duration')
plt.show(PD)
```




```
In [21]: # Ticket prices by class and type of airlines
plt.figure(figsize=(15,5))
AS = sns.barplot(x='airline', y='price', hue='class', data = df.sort_values('price'))
AS.set(xlabel='Flights of India', ylabel='Ticket Price', title='Economy Vs Business Ticket Prices by Airlines')
plt.show(AS)
```




```
In [23]: # Variation of ticket prices by date of purchase
df_temp = df.groupby(['days_left'])['price'].mean().reset_index()
plt.figure(figsize=(15,5))
ax = plt.axes()
sns.regplot(x = df_temp.loc[df_temp['days_left'] == 1].days_left, y = df_temp.loc[df_temp['days_left'] == 1].price, data=
sns.regplot(x = df_temp.loc[(df_temp['days_left'] > 1) & (df_temp['days_left'] < 20)].days_left, y = df_temp.loc[(df_temp[
sns.regplot(x = df_temp.loc[df_temp['days_left'] >= 20].days_left, y = df_temp.loc[df_temp['days_left'] >= 20].price, data=
ax.set(xlabel='Tickets booked before X days', ylabel='Ticket price', title='Ticket prices based on when tickets were booked')
plt.show(ax)
```



```
In [24]: # average price based on flight duration
df_temp2 = df.groupby(['duration'])['price'].mean().reset_index()
plt.figure(figsize=(15,5))
PD = sns.scatterplot(x='duration', y='price', data = df_temp2)
PD = sns.regplot(x='duration', y='price', data = df_temp2, order = 2)
PD.set(xlabel='Flight duration', ylabel='Ticket Price', title='Average price based on flight duration')
plt.show(PD)
```





```
In [27]: plt.figure(figsize=(15,5))
plt.subplot(1,2,1)
sns.boxplot(data = df, x = 'departure_time', y = 'price', showfliers = False).set(xlabel = 'Departure Time', ylabel = 'Pri
plt.subplot(1,2,2)
sns.boxplot(data = df, x = 'arrival_time', y = 'price', showfliers = False).set(xlabel = 'Arrival Time', ylabel = 'Price
plt.show()
```



```
In [31]: # price variatoin based on source and destination
ax = sns.relplot(x = 'destination_city', y = 'price', col='source_city', col_wrap= 3, kind= 'line', data = df)
ax.fig.subplots_adjust(top=0.9)
ax.fig.suptitle('Ticket Prices as a variation of source and destination')
plt.show(ax)
```

Ticket Prices as a variation of source and destination



```
In [33]: # Price variation as a factor of number of stops
fig, axs = plt.subplots(1,2, gridspec_kw= {'width_ratios': [3,1]}, figsize = (15,5))
sns.barplot(y = 'price', x = 'airline', hue = 'stops', data = df.loc[df['class'] == 'Economy'].sort_values('price', ascending= True))
axs[0].set(xlabel='Airlines', ylabel='Price of Ticket', title='Economic Class stops vs Ticket Prices')
sns.barplot(y='price', x='airline', hue='stops', data= df.loc[df['class'] == 'Business'].sort_values('price', ascending= True))
axs[1].set(xlabel='Airlines', ylabel='Price of Ticket', title='Business Class Stops vs Ticket Prices')
plt.show(fig, axs)
```

