


# Qubit and Single-qubit Gates

$$|0\rangle = \begin{bmatrix} 1 \\ 0 \end{bmatrix}$$

$$|1\rangle = \begin{bmatrix} 0 \\ 1 \end{bmatrix}$$

Gate	Action on Computational Basis	Matrix Representation
Identity	$I 0\rangle =  0\rangle$ $I 1\rangle =  1\rangle$	$I = \begin{pmatrix} 1 & 0 \\ 0 & 1 \end{pmatrix}$
Pauli X	$X 0\rangle =  1\rangle$ $X 1\rangle =  0\rangle$	$X = \begin{pmatrix} 0 & 1 \\ 1 & 0 \end{pmatrix}$
Pauli Y	$Y 0\rangle = i 1\rangle$ $Y 1\rangle = -i 0\rangle$	$Y = \begin{pmatrix} 0 & -i \\ i & 0 \end{pmatrix}$
Pauli Z	$Z 0\rangle =  0\rangle$ $Z 1\rangle = - 1\rangle$	$Z = \begin{pmatrix} 1 & 0 \\ 0 & -1 \end{pmatrix}$
Phase S	$S 0\rangle =  0\rangle$ $S 1\rangle = i 1\rangle$	$S = \begin{pmatrix} 1 & 0 \\ 0 & i \end{pmatrix}$
T	$T 0\rangle =  0\rangle$ $T 1\rangle = e^{i\pi/4} 1\rangle$	$T = \begin{pmatrix} 1 & 0 \\ 0 & e^{i\pi/4} \end{pmatrix}$
Hadamard H	$H 0\rangle = \frac{1}{\sqrt{2}}( 0\rangle +  1\rangle)$ $H 1\rangle = \frac{1}{\sqrt{2}}( 0\rangle -  1\rangle)$	$H = \frac{1}{\sqrt{2}} \begin{pmatrix} 1 & 1 \\ 1 & -1 \end{pmatrix}$

# Pauli I Gate




Bloch sphere : I gate




Quantum Composer: I gate

## Pauli X Gate




$$|0\rangle = \begin{bmatrix} 1 \\ 0 \end{bmatrix}$$



$$|1\rangle = \begin{bmatrix} 0 \\ 1 \end{bmatrix}$$

# Pauli X Gate




Bloch sphere : X gate




Quantum Composer : X gate

# Pauli Y Gate




Bloch sphere : Y gate



Quantum Composer : Y gate

# Pauli Z Gate




Bloch sphere : Z gate



Quantum Composer : Z gate

# S Gate




Bloch sphere : S gate



Quantum Composer : S gate

# T Gate



Bloch sphere : T gate




Quantum Composer : T gate



# H Gate

H Gate




Bloch sphere : H gate



Quantum Composer : H gate



# Hadamard Gate



$$\begin{aligned} H(|0\rangle) &= \frac{|0\rangle + |1\rangle}{\sqrt{2}} \\ &= \frac{1}{\sqrt{2}}|0\rangle + \frac{1}{\sqrt{2}}|1\rangle \end{aligned}$$


$$\frac{1}{\sqrt{2}} \begin{bmatrix} 1 & 1 \\ 1 & -1 \end{bmatrix} \begin{bmatrix} 1 \\ 0 \end{bmatrix} = \frac{1}{\sqrt{2}} \begin{bmatrix} 1 \\ 1 \end{bmatrix}$$

$$\begin{aligned} &= \frac{1}{\sqrt{2}} \left( \begin{bmatrix} 1 \\ 0 \end{bmatrix} + \begin{bmatrix} 0 \\ 1 \end{bmatrix} \right) \\ &= \frac{1}{\sqrt{2}}|0\rangle + \frac{1}{\sqrt{2}}|1\rangle \end{aligned}$$

$$H|0\rangle = \frac{1}{\sqrt{2}}(|0\rangle + |1\rangle) = |+\rangle$$

$$H|1\rangle = \frac{1}{\sqrt{2}}(|0\rangle - |1\rangle) = |-\rangle$$

## Associative: Hardmard gate




$$H|0\rangle = \frac{1}{\sqrt{2}}(|0\rangle + |1\rangle) = |+\rangle$$

$$H|1\rangle = \frac{1}{\sqrt{2}}(|0\rangle - |1\rangle) = |-\rangle$$

$$\begin{aligned} H(H(|0\rangle)) &= H\left(\frac{1}{\sqrt{2}}|0\rangle + \frac{1}{\sqrt{2}}|1\rangle\right) \\ &= \frac{1}{\sqrt{2}}(H(|0\rangle) + H(|1\rangle)) \\ &= \frac{1}{\sqrt{2}}\left(\frac{1}{\sqrt{2}}|0\rangle + \frac{1}{\sqrt{2}}|1\rangle + \frac{1}{\sqrt{2}}|0\rangle - \frac{1}{\sqrt{2}}|1\rangle\right) \\ &= |0\rangle \end{aligned}$$

$$\begin{aligned} H * H * |0\rangle &= \frac{1}{\sqrt{2}} \begin{bmatrix} 1 & 1 \\ 1 & -1 \end{bmatrix} * \frac{1}{\sqrt{2}} \begin{bmatrix} 1 & 1 \\ 1 & -1 \end{bmatrix} * \begin{bmatrix} 1 \\ 0 \end{bmatrix} \\ &= \frac{1}{2} \begin{bmatrix} 2 & 0 \\ 0 & 2 \end{bmatrix} \\ &= \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix} * \begin{bmatrix} 1 \\ 0 \end{bmatrix} \\ &= \begin{bmatrix} 1 \\ 0 \end{bmatrix} \\ &= |0\rangle \end{aligned}$$

# Noncommutative: $HX \neq XH$

$q[0]$  
 $HX \quad |0\rangle = \frac{1}{\sqrt{2}} \begin{bmatrix} 1 & 1 \\ 1 & -1 \end{bmatrix} \begin{bmatrix} 0 & 1 \\ 1 & 0 \end{bmatrix} \begin{bmatrix} 1 \\ 0 \end{bmatrix} = \frac{1}{\sqrt{2}} \begin{bmatrix} 1 \\ -1 \end{bmatrix} = \frac{1}{\sqrt{2}} |0\rangle - \frac{1}{\sqrt{2}} |1\rangle$


c1

$$XH \quad |0\rangle = \begin{bmatrix} 0 & 1 \\ 1 & 0 \end{bmatrix} * \frac{1}{\sqrt{2}} \begin{bmatrix} 1 & 1 \\ 1 & -1 \end{bmatrix} \begin{bmatrix} 1 \\ 0 \end{bmatrix} = \frac{1}{\sqrt{2}} \begin{bmatrix} 1 & -1 \\ 1 & 1 \end{bmatrix} \begin{bmatrix} 1 \\ 0 \end{bmatrix} = \frac{1}{\sqrt{2}} \begin{bmatrix} 1 \\ 1 \end{bmatrix} = \frac{1}{\sqrt{2}} |0\rangle + \frac{1}{\sqrt{2}} |1\rangle$$

Probabilities ▾

ⓘ


:



Statevector ▾

ⓘ

:



Output state  
[ 0.707+0j, -0.707+0j ]



