MESSAGE PERMISSION MATRIX

Write the rules before messages send

Use a message-permission matrix: automatic sends, human approvals and hard stops. Set those boundaries through policy, not the model's confidence.

Classify by content and stage

Check the application stage and message purpose.

Routine wording can become sensitive during screening; wording alone doesn't determine the permission path.

Tier A: approved factual answers

Use current approved facts for property answers.

Check the right reference and recipient;

block invented terms, negotiation and unsupported availability promises.

Tier A: routine coordination

Tour confirmations, reminders and application links can use the permitted automatic lane.

Check the booking and destination; a scheduled send doesn't prove delivery.

Tier B: screening-stage messages

In this demo, applicant-facing screening messages need individual manager approval, **including document requests and outcome-related wording.**

They aren't routine listing replies.

THE NAMED APPROVER

Approval needs a named person

Record who approved which final draft and when.

Generated text or criteria results don't authorize sending.

Changed wording returns through approval.

— THE FINAL CHECK

Check the final message *again*

Check approved text against current facts and stage before sending.

After edits or record changes, earlier checks don't authorize stale or unsupported wording.

THE FAILURE ROUTE

A blocked send needs a visible route

Log the failure; alert its owner.

In conversation, use a permitted neutral fallback, not silence.

This demo never drafts or sends adverse-action notices.

A REUSABLE MATRIX

Use this permission worksheet

For each message type, record:

Stage.	Allowed facts.
Automatic or approved lane.	Approver.
Send-time check.	Delivery evidence.
Failure owner.	

Review before enabling sends.