

S.N	Sensor / Actuator	Part Nomenclature	Signal Type	Connection Ports	Connections	Electrical Matching Description
1	TDS 1	SUP-TDS210-B	Analog Output	4-Wire	V+, V-, P+, P-	24V DC auxiliary power with independent meter display.
2	TDSC 1		Controller			
3	pH 1	SUP-PH6.5	Analog Output	4-Wire	V+, V-, P+, P-	24V DC auxiliary power with independent meter display.
4	pHC 1		Controller			
5	ORP 1	SUP-pH5013A	Analog Output	4-Wire	V+, V-, P+, P-	24V DC auxiliary power with independent meter display.
6	ORPC 1		Controller			
7	PBV 2	Solenoid Valve	Digital Output	2-Wire	24V PLC, 0V return	Pneumatic valve driven by 24V Solenoid coil interface.
8	PBV 1	Solenoid Valve	Digital Output	2-Wire	24V PLC, 0V return	Pneumatic valve driven by 24V Solenoid coil interface.
9	LPS 1	SUP-Y210	Digital Input	2-Wire	Electrical Meter	
10	HPS 1	SUP-Y210	Digital Input	2-Wire	Electrical meter	
11	TDS 2	SUP-TDS210-B	Analog Output	4-Wire	V+, V-, P+, P-	24V DC auxiliary power with independent meter display.
12	TDSC 2		Controller			
13	PBV 3	Solenoid Valve	Digital Output	2-Wire	24V PLC, 0V return	Pneumatic valve driven by 24V Solenoid coil interface.
14	PBV 4	Solenoid Valve	Digital Output	2-Wire	24V PLC, 0V return	Pneumatic valve driven by 24V Solenoid coil interface.
15	LPS 2	SUP-Y210	Digital Input	2-Wire	Electrical Meter	
16	HPS 2	SUP-Y210	Digital Input	2-Wire	Electrical meter	
17	TDS 3	SUP-TDS210-B	Analog Output	4-Wire	V+, V-, P+, P-	24V DC auxiliary power with independent meter display.
18	TDSC 3		Controller			
19	PBV 5	Solenoid Valve	Digital Output	2-Wire	24V PLC, 0V return	Pneumatic valve driven by 24V Solenoid coil interface.
20	PBV 6	Solenoid Valve	Digital Output	2-Wire	24V PLC, 0V return	Pneumatic valve driven by 24V Solenoid coil interface.
21	PS 1	SUP-Y210	Digital Input	2-Wire		Standard pressure switch contact configuration.
22	FLS 1	SUP-ZPM	Digital Input	2-Wire		Float/Flow switch level contact configuration.
23	EC	SUP-TDS210-B	Analog Output	4-Wire	V+, V-, P+, P-	Conductivity controller using 24V auxiliary power.