



LIST OF COMPONENTS			
LOC.	DESCRIPTION	DRW#	QTY.
A	BUSHING	- - - -	1
B	STOP PIECE	- - - -	2

TOLERANCES FOR ENGLISH DIM. MACHINED PART

UNLESS OTHERWISE SPECIFIED DIM'S ARE IN INCHES AND WHEN DUAL DIMENSIONED ARE INCHES (mm)

GENERAL TOLERANCES FOR DIMENSIONS OF MACHINED SURFACES NOT OTHERWISE SPECIFIED

IN.
.XX ± .005
.XX ± .05
.X ± .1
ANGLE: ± 0.5°

DIMENSION AND TOLERANCE PREPARED IN ACCORDANCE WITH CURRENT VERSIONS OF ASME Y14.5M

GENERAL NOTES FOR ENGLISH DIMENSIONED PART

1) DIMENSIONS RELATED TO MULTIPLE DATUM REFERENCES SHALL FOLLOW A PRIMARY, SECONDARY & TERTIARY ORDER OF PRECEDENCE.

2) ALL DIMENSIONS AND TOLERANCES APPLY IN A FREE STATE CONDITION UNLESS OTHERWISE SPECIFIED

3) BREAK CORNERS .01-.02 X 45°

4) 3/64 R MAX. TOOL RADIUS

5) REMOVE ALL BURRS

6) DIMENSIONS IN () ARE REFERENCE

7) ✓ = 125°

INCHES

EPD APPROVALS		DRAWING APPROVALS		MODEL	
FOUNDry	DATE	DRAWN	DATE	3600	
N.A.		TLD	02-06-96	SIZE CHARTED	
MACH. SHOP	DATE	CHK'D	DATE	MATERIAL STEEL	
N.A.		GLP	03-13-96	PART NAME BUSHING, THROTTLE COATED (MACH.)	
O.A.	DATE	APPR'D	DATE	SIZE PATTERN C N.A.	
N.A.		CWG	03-13-96	DWG. NO. C05158A	
DRAWING REFERENCE C0080H		CONTRACT NO.		REV. 6	

THIRD ANGLE PROJECTION

PRO/E DWG