Repair Station Quality Control Manual

QCM

Revision: Original

Revision date: 01 January 2025

Elevate MRO-BJC

9586 Metro Airport Avenue, Hangar E

Broomfield, CO 80021

Repair Station K4LR032E

Phone: 720-800-1612

https://eag.aero/elevate-mro.com

Table of Contents

REPAIR STATION QUALITY CONTROL MANUAL **1**

TABLE OF CONTENTS **2**

RECORD OF REVISIONS **5**

MANUAL DISTRIBUTION LIST **7**

SECTION A QCM OVERVIEW **8**

A - 1.0 PREFACE 8
A - 2.0 FAA OVERSIGHT 9
A - 3.0 COMPANY SAFETY, QUALITY, AND SECURITY POLICY 9

SECTION B QUALITY CONTROL PROCEDURES AND STANDARDS **11**

B - 1.0 QUALITY CONTROL SYSTEM 11
B - 1.1 Quality Control System Overview *11*
B - 2.0 RULES OF OPERATION 12
B - 2.1 Return to service *12*
B - 2.2 Non-Certificated Employees *12*
B - 2.3 Error correction *13*
B - 2.4 Rules for Checklists and Documentation *13*
B - 3.0 SERVICE DIFFICULTY REPORTS 13
B - 3.1 Service Difficulty Reports (SDR) Process *13*
B - 4.0 PARTS SYSTEM 13
B - 4.1 Incoming Material Inspection System (General) *13*
B - 4.2 Receiving Inspection *13*
B - 4.3 Preservation of Parts *15*
B - 4.4 Shelf Life *15*
B - 4.5 Inventory Storage and Handling *15*
B - 4.6 Segregation of Parts *16*
B - 4.7 Tagging and Identification of Parts *16*
B - 4.8 Procedures for Detecting and Reporting Suspected Unapproved Parts *17*
B - 4.9 Hidden Damage Inspections *17*
B - 4.10 LLPs Life Limited Parts *17*
B - 5.0 WORK ORDER SYSTEM 17
B - 5.1 Work Order System Description *17*
B - 5.2 Electronic and Paper Work Orders *18*
B - 5.3 RESERVED *18*
B - 5.4 Pre-Induction *18*
B - 5.5 Initial Inspection / Preliminary Inspection *19*
B - 5.6 Inspection phase *20*
B - 5.6.1 Maintenance Inspection 20
B - 5.7 Record of Inspection Test Results *21*
B - 5.8 Repair Phase *21*
B - 5.8.1 Major Repair and Alteration: Aircraft and Components 21

B - 5.9 One-time Self Inspection Authority ... 22
B - 5.10 Technician and Inspector Turnover / Continuity of Maintenance Responsibility ... 23
B - 5.11 Final Inspection and Release to Service ... 23
B - 5.11.1 Maintenance Release ... 24
B - 5.11.2 Maintenance Release Statement: Air Carrier "Example" ... 24
B - 5.12 Work order records ... 25
B - 5.12.1 Major alteration or repair records ... 25
B - 5.13 Paper Workorder Process ... 26
B - 6.0 SECURITY ... 29
B - 6.1 Security Policy ... 29
B - 6.2 Authorization Control ... 29
B - 7.0 TECHNICAL DATA ... 29
B - 7.1 Current Technical Data ... 29
B - 7.2 Document Control ... 29
B - 7.3 OEM Manuals and Technical Library Data Control ... 30
B - 8.0 PROFICIENCY OF INSPECTION PERSONNEL ... 31
B - 8.1 Proficiency of Inspection Personnel ... 31
B - 8.2 Inspectors, Technicians, And Supervisors ... 31
B - 8.3 Inspectors, Mechanics, and Supervisors ... 31
B - 8.4 Required Inspection Items (RII) ... 32
B - 9.0 CONTRACTOR AND OUTSIDE VENDORS ... 33
B - 9.1 Quality Control System for Non-Certificated Contract Maintenance Providers ... 33
B - 9.2 Personnel Requirements ... 34
B - 9.3 Communications ... 34
B - 9.4 Ongoing Auditing of Non-Certificated Maintenance Providers ... 34
B - 9.5 Non-certificated Maintenance Contract ... 34
B - 10.0 CALIBRATION ... 35
B - 10.1 Record of Tests and Calibration of Precision Equipment ... 35
B - 10.2 Employee-Owned Inspection and Test Equipment ... 35
B - 10.3 Control of Precision Tools and Test Equipment ... 36
B - 10.4 Use of Calibrated Tooling ... 36
B - 10.5 Errors in Use ... 36

SECTION C MANUAL CONTROL AND REVISIONS ... 37

C - 1.0 MANUAL CONTROL ... 37
C - 1.1 Manual Control ... 37
C - 1.1.1 Manual Markings ... 37
C - 2.0 QUALITY CONTROL AUDIT PROGRAM ... 39
C - 2.1 Overview / Standards ... 39
C - 2.2 Audit Procedures ... 40
C - 2.3 Audit Responsibility ... 41
C - 2.3.1 Employee feedback and reporting. ... 41
C - 2.3.2 Root Cause Analysis Process ... 41
C - 2.4 Voluntary Disclosure Policy ... 42
C - 2.5 Safety Responsibility ... 42
C - 3.0 STANDARD MANUAL OR FORM REVISION PROCESS ... 42
C - 3.1 Temporary revisions ... 43

SECTION D DEFINITIONS AND ABBREVIATIONS ... 45

D - 1.0 LIST OF ABBREVIATIONS ... 45

Record of Revisions

Rev.	Pages	Changes	Date	Authorization
--		Complete rewrite and reissue	1 Jan 2025	J. Slack

Approved By & Date President: Jim Slack **1 JAN 2025**	FAA approval

List of Effective Pages

This Repair Station & Quality Control Manual is a complete redesign and reissue of the entire manual. All pages in the revision have been revised.

Cover	Reissue	01 Oct 2024

This list of effective pages details each page number, its individual page revision level, and the page's corresponding date of the revision. The footer on all pages reflects the overall revision status of the entire publication.

Manual Distribution List

Copy	**Assigned To:** (Name or Location)	**Title/Organization**
Master	Repair Station (Physical Copy)	Chief Inspector
001	FAA Flight Standards District Office (Electronic copy)	Principal Maintenance Inspector
002	Company Server (Electronic Copy)	General Manager (Accountable Manager)

Section A QCM Overview

A - 1.0 Preface

The purpose of this manual is to provide regulatory compliance with Part 145 repair station operations. This manual is the regulatory document governing the repair station and shall be adhered to during all operations of the repair station. This repair station will follow the policies and procedure contained within this manual.

This manual combines the requirements for a repair station manual and quality control manual into a single document. Section B primarily contains the requirements for the repair station manual as required in 14 CFR § 145.207, and Section C Primarily contains the requirements for a quality control system as required by 14 CFR § 145.211. Section D instructs on the audit, revision, and reporting process for the repair station manuals. Section E contains definitions of terms.

The Company, Elevate MRO**,** is the official name of the Repair Station and will be the name used throughout this manual and on all forms used by the Repair Station. Any reference made to a repair station will refer only to this repair station, FAA CRS K4LR032E,

Elevate MRO is located at 9586 Metro Airport Avenue, Hangar E, Broomfield, CO 80021, has the necessary housing, facilities, equipment, materials, data, and qualified personnel to perform maintenance, preventive maintenance and alterations on aircraft and components, as referenced on current Operation Specifications (Ops Specs) Rating or capabilities list. This meets the applicable requirements for the issuance of the certificate and ratings the repair station holds. [FAR § 145.101]

All Aircraft Manufacturer's Maintenance Manuals and Engine Manufacturer's Maintenance Manuals, as revised, all Component Maintenance Manuals referenced therein, as revised, are to be used in conjunction with this manual. Please Reference: OEM Manuals and Technical Library Data Control [FAR § 145.211 (c)2]

Section C of this manual explains the inspection system in detail, including the continuity of inspection responsibility. The manual gives a detailed explanation of the following portions of the inspection system; incoming materials, preliminary inspection, hidden damage, inspection continuity, and final inspection of the article being maintained or altered at this facility. [FAR § 145.211 (c)1(vii)] This quality control system conforms to the requirements of [FAR § 145.211]

The forms that are used in the Repair Stations are found in the company Forms Manual; it gives samples of the forms. The description and use of these forms are found in the text throughout the Repair Station System.

The Accountable Manager is responsible for full compliance with all procedures outlined in this Inspection System as appropriate to any item being inspected, repaired, overhauled or altered by the Repair Station. The airworthiness of those items and compliance with record requirements of the operators of those items and of the Repair Station depends upon conformity to the procedures of this system.

The inspection, repair, overhaul or alteration of products will be performed in accordance with the current Code of Federal Regulations, manufacturer's data, drawings, specifications, bulletins, or other technical data accepted or approved by the Administrator for the particular airframe, engine, radio or appliance that the facility is rated for.

The Repair Station will not inspect, maintain, or alter any item that is not listed on the Ops Specs, or for which it is not rated. The Repair Station will not inspect maintain or alter any item for which it is rated if it requires technical data, equipment, materials, facilities or trained personnel that are not available. [14 CFR 145.201]

The technical library and this *RSQCM*, required for operation of this Repair Station, will be maintained in a current status at all times.

In accordance with 14 CFR Part 145.211(c) all repair station personnel have access to this manual through the Maintenance Shared Drive, where the company's manuals are electronically stored. A current printed copy of the manual will be available in the repair station office. Each inspector and supervisor working for this Repair Station should thoroughly understand its contents. It is expected that this manual will be read carefully by all company maintenance personnel in order that each employee will be familiar with the policies and procedures outlined herein. The material in this manual is directive in nature; however, compliance with the manual is not a substitute for common sense and sound judgment.

Terms used in this manual will have the same meaning as those defined in the Code of Federal Regulations Part 1, entitled "Definitions and Abbreviations." Also, reference Section E "DEFINITIONS AND ABBREVIATIONS" of this manual for additional definitions.

A - 2.0 FAA Oversight

This repair station certificated repair station shall allow the FAA to inspect that repair station at any time to determine compliance with FAR part 145. [Ref FAR § 145.233 (a)]

A - 3.0 Company Safety, Quality, and Security Policy

The company operating policies are based on the concept that safety, quality, and security come first. Management and all employees shall include safety, quality, and security in the basic duties and responsibilities at all levels. Essential elements of safety, quality, and security include condition of equipment, aircraft inspections, training of maintenance and support personnel. It is essential that all personnel are devoted to duty, good judgment, sound operational planning, and efficient use of available resources. All employees have responsibility for safety, quality, and security and shall report any event, job hazard, faulty equipment, accident, or incidents to the accountable manager. All employees are responsible for safety, security, and quality.

Management/Employees Commitment:

All employees are expected to stop or intervene when witnessing a potentially hazardous situation; accept responsibility and accountability for our own behavior; openly communicate information about safety incidents and share the lessons with others. Everyone is concerned for the safety of others in our organization

In this organization we all have important job functions and responsibilities. Regardless of position or title, each of us must incorporate safety, quality, security, and health into our daily routines. When situations are encountered that are hazardous we must do our upmost to ensure we are safe and effectively eliminate the hazard. If hazards are identified that threaten anyone inside or outside of the organization we have a duty to report and mitigate the hazard as a team. We will maintain a culture that elevates our consciousness towards personal and collective safety

Each employee must accept responsibility to communicate any information that may affect the integrity of safety, quality, and security. This communication will never result in reprisal, thus allowing a timely, uninhibited flow of information to occur.

All employees are formally advised that the company will not initiate disciplinary actions against an employee who discloses an incident or occurrence involving safety. This policy cannot apply to criminal or willful infractions or any event where there was intentional disregard for safety, substance abuse, controlled substances, alcohol or intentional falsification, willful misconduct or gross negligence.

Section B Quality Control Procedures and Standards

The Quality Control process has been prepared in accordance with the current and applicable Code of Federal Regulations (CFR's) pertaining to the operation of a domestic Repair Station and the policies of Elevate MRO. Revisions and notification of its responsible Flight Standards office of revisions to its quality control manual will be made pursuant to Section D of this manual. [Ref FAR § 145.211 (d)]

B - 1.0 Quality Control System

B - 1.1 Quality Control System Overview

This certificated repair station has established and maintains a quality control system acceptable to the FAA that ensures the airworthiness of the articles on which the repair station or any of its contractors performs maintenance, preventive maintenance, or alterations.

The accountable manager will continually ensure that Repair station personnel follow the quality control system when performing maintenance, preventive maintenance, or alterations under the repair station certificate and operations specifications.

The following processes are outlined in this section of the *RSQCM*:

1. Inspecting incoming raw materials to ensure acceptable quality (Section C – 4.1)
2. Performing preliminary inspection of all articles that are maintained (Section C – 5.4)
3. Inspecting all articles that have been involved in an accident for hidden damage before maintenance, preventive maintenance, or alteration is performed (Section C – 4.9)
4. Establishing and maintaining proficiency of inspection personnel (Section C – 8)
5. Establishing and maintaining current technical data for maintaining articles (Section C – 7.0)
6. Qualifying and surveilling noncertificated persons who perform maintenance, prevention maintenance, or alterations for the repair station (Section C – 9.1)
7. Performing final inspection and return to service of maintained articles (Section C – 2.1 & 5.5)
8. Calibrating measuring and test equipment used in maintaining articles, including the intervals at which the equipment will be calibrated (Section C – 10)
9. Taking corrective action on deficiencies (Section C – 5.8)
10. Use of to the manufacturer's inspection standards for a particular article, including reference to any data specified by that manufacturer (Section C – 7.0)

11. A sample of the inspection and maintenance forms and instructions for completing such forms or a reference to a separate forms manual (Repair Station Forms Manual
12. Procedures for revising the quality control manual required under this section and notifying the responsible Flight Standards office of the revisions, including how often the responsible Flight Standards office will be notified of revisions.
13. Notifying the responsible Flight Standards office of revisions to its quality control manual.

[Ref FAR § 145.211 (a)(b)]

B - 2.0 Rules of operation

B - 2.1 Return to service

The repair station shall approve for return to service any article for which it is rated after it has performed maintenance, preventive maintenance, or an alteration in accordance with part 43. [Ref FAR § 145.201 (a)3]

The repair station may not maintain or alter any article for which it is not rated, and may not maintain or alter any article for which it is rated if it requires technical data, equipment, or facilities that are not available to it.

The certificated repair station may not approve for return to service

a. Any article unless the maintenance, preventive maintenance, or alteration was performed in accordance with the applicable approved technical data or data acceptable to the FAA.
b. Any article after a major repair or major alteration unless the major repair or major alteration was performed in accordance with applicable approved technical data; and
c. Any experimental aircraft after a major repair or major alteration performed under § 43.1(b) unless the major repair or major alteration was performed in accordance with methods and applicable technical data acceptable to the FAA. [Ref FAR § 145.201 (b-c)]

B - 2.2 Non-Certificated Employees

The repair station may employ non-certificated technicians. These technicians are restricted from signing off inspections or making any airworthiness determinations. Their entire work shall be supervised by an appropriately rated technician, all of their work will be done in accordance with the quality control measures, procedures, and policies found in this quality control manual and repair station manual. All non-certificated employees will be required to go through initial training as outlined in the repair station training manual.

B - 2.3 Error correction

When errors are detected by the quality control system they will be systematically evaluated and corrected using the audit procedures and root cause analysis as prescribed in Section D – 2.0

B - 2.4 Rules for Checklists and Documentation

All technicians and inspectors when using checklists or other documents will indicate when items are not applicable to the particular project by writing "N/A" not applicable or "N/R" not required, and also their initials. The performing mechanic or inspector initials are required to keep record of who made the specific determination that the item in question was not applicable or required for that specific task. If a date of the determination is not included in the checklist format then the technician or inspected shall write in the date of the determination next to their initials.

B - 3.0 Service Difficulty Reports

B - 3.1 Service Difficulty Reports (SDR) Process

This Repair Station will report to the FAA within 96 hours after it discovers any serious defect or other recurring un- airworthy condition of an aircraft, power plant, propeller, or component thereof. The report will be made in a format acceptable to the FAA describing the defect or malfunction completely without withholding any pertinent information and will include the following, i.e.; aircraft registration number, type, make and model of the article, date of the discovery, nature of the failure, malfunction, or defect, time since last overhaul, if applicable, and apparent cause of the failure malfunction, or defect, and any other pertinent information that is necessary for more complete identification, determination of seriousness, or corrective action. [Ref FAR § 145.221 (a,b)]

The Accountable Manager is responsible for reporting, preparing and submitting the Service Difficulty Report. This can be accomplished using FAA form 8070-1, or electronically using the web. The Accountable Manager will also coordinate with the aircraft owner/operator so that this submission is not duplicated. [Ref FAR § 145.221 (e)]

B - 4.0 Parts System

B - 4.1 Incoming Material Inspection System (General)

The Accountable Manager of the Repair Station is responsible for ensuring full compliance with all procedures outlined in this inspection system for all work performed on behalf of the repair station.

B - 4.2 Receiving Inspection

No individual or certified technician is allowed to perform receiving inspections unless they have properly documented training on the policy and procedures found in this manual. The accountable manager will issue receiving inspection authority.

All parts inbound to the repair station will be set into a receiving inspection holding area. Until a receiving inspection has been completed these parts/materials will not leave the designated area. If the area is not appropriate for the parts/materials being received, then the parts/materials will be marked with "receiving inspection not complete," Until the inspection has been accomplished at which time the parts/materials shall be marked receiving inspection compete."

Receiving inspection process: All incoming materials, hardware, parts, components, and raw material procured for the use by the Repair Station shall be inspected for the following:

1. Damage from shipping
2. Suspected unapproved parts
3. Proper quantity
4. Any contamination
5. Matching specifications
6. Shelf life
7. Proper state of preservation
8. Life limit's
9. Visual damage
10. Manufacturing defects
11. Raw materials will be inspected to ensure they are of acceptable quality

If technical data is required to evaluate the part being received then acquisition of that data is required before the inspection is performed and will then be used subsequently to complete the inspection.

If special testing is required to verify a parts condition or acceptability the receiving inspector will make arrangements for this testing and will incorporate them into the receiving inspection determination.

Traceability: All parts/materials will be inspected for proper certificates of conformance, 8130-3 forms, EASA form 1, or other documentation of traceability. All documents will be retained by attaching records or copies of records to the parts as well as retaining records in an electronic inventory system.

If traceability cannot be determined as appropriate for that specific part or material, then the part or material will be quarantined in a designated area until proper documentation can be obtained or verified. All traceability documents will be physically attached to parts/materials and when received lots are split copies of the traceability paperwork will be attached to the new sub lot as issued. A record will be made of the life limit, total time in service, time since overhaul if applicable to parts that undergo the receiving inspection.

When the receiving inspection is completed the part/material's traceability paperwork will be annotated with the Repair Station Incoming Parts Inspection Stamp as "Approved" and initialed by the properly trained Receiving Inspector. All such documentation will

remain with the material until it is required for use and then will be retained as a permanent record in the Work Order file.

Any material inspected and found to be “Unserviceable” or “Rejected” shall be tagged with a rejected part red tag, description of the discrepancy will be recorded, and the part placed into the red tags parts cabinet following procedures in this manual. If lack of traceability is found, then the part will be marked with a purple quarantine tag and placed in the quarantine locker. All parts that do not pass the receiving inspection will be brought to the attention of the Accountable Manager for proper disposition and correction of discrepancies. [Ref FAR § 145.211 (c)1(i-ii)]

All parts and materials which are found acceptable will be labeled with a mark “Receiving inspection is satisfactory” and the receiving inspectors name, Date, and signature. A lot number will be assigned to the item being received using an electronic inventory system.

B - 4.3 Preservation of Parts

Components are preserved in accordance with manufacturer recommendations or other acceptable industry standards. To afford protection against humidity, extreme temperatures, dust, rough handling or other damage, the components will be preserved by wrapping with suitable materials, placement in containers or plastic bags and/or rigid boxes containing effective shock absorption material, suitable for the item being preserved. Preserved items will be stored at the Repair Station in such a manner as to maximize the prevention of contamination or damage.

B - 4.4 Shelf Life

All shelf life limited materials must be clearly marked with the recommended expiration date prior to adding into inventory and/or issue. Stockroom personnel will continually monitor life limited items in inventory and verify expiration dates at the time of issue and will issue the oldest non-expired materials first. Technicians will shall observe the expiration date of all shelf life items before each use and to return out-of-date materials to the stockroom. The Parts Receiving Inspector will, when found, immediately issue a Rejected Tag (red) for any out of date material and the Parts Receiving Inspector will have them segregated in a secure area until they are properly disposed of. All rubber O-rings, rubber hoses, seals and gaskets that are received and remain in the supplier’s sealed packages will carry an indefinite shelf life if stored in a controlled environment, unless otherwise specified by the manufacturer. Preserved components or parts that have exceeded allowable preservation shelf life limits, will be red tagged directed to the Accountable Manager for evaluation to determine proper disposition.

B - 4.5 Inventory Storage and Handling

Flammable, toxic or volatile materials will be appropriately labeled and stored in an appropriately marked approved storage containers for each material type per OSHA regulations. Appropriate measures will be taken to avoid damage to parts in storage or

during maintenance this includes maintaining an appropriate environment for parts storage with attention to reducing preventable accidents. Specific attention will be given to eliminating FOD. If parts are sensitive to ESD the appropriate preparations and precautions shall be taken to protect the parts from damage.

B - 4.6 Segregation of Parts

Parts and materials in inventory and also on the shop floor will be segregated into two main groups serviceable and unserviceable parts. Serviceable inventory will be labeled with their respective part numbers and lot numbers and have traceability paperwork attached. Unserviceable parts fall into the following categories. Repairable, Quarantined, Rejected. Unserviceable parts will be segregated from repairable parts and each category will have its own labeled and segregated storage area.

All parts and materials involved in maintenance shall have the component parts segregated into designated and labeled areas and shall not be intermixed with parts from another project or aircraft. The area must be clearly marked, displaying the aircraft registration number and work order number. If an individual part is not stored in a designated area it must always be accompanied by a white parts identification tag (IC-1005) or other appropriate identification tag found in (RS-QCM Ch 1.6)

B - 4.7 Tagging and Identification of Parts

Here is a list and description of appropriate parts, their templates can be found in the RSFM. All parts tags when attached to their respective part must be filled out in full.

White tag “identification tag” (IC-1005) - Used by technicians for the identification of parts or materials. This tag with information filled out is always required to accompany a part unless that part is properly identified in a designated area as described in (RS-QCM CH 1.5)

Green tag “repairable part” (IC-1002) - Will be attached to a repairable part that is no longer serviceable.

Yellow tag “serviceable part” (IC-1001) - To be attached to serviceable parts, which have received final inspection from an appropriate authorized inspector and are approved for return to service. The maintenance release statement is printed or stamped on the tag. Only authorized inspection personnel per the Authority Roster will sign the “Return to Service.” Upon installation of the part, the installation record of the tag will be completed. The completed tag will be placed with the work order. [Ref FAR § 145.211 (c)1(vii)]

Purple tag “quarantined part” identification tag (IC-1003). – Applied to parts who’s airworthiness status is unknown. This is normally the result of troubleshooting with replacement components to verify faults, or when a parts traceability cannot be established. The purple tag will remain applied to the part until it’s airworthiness or traceability is established and the part is properly tagged with a new tag and placed in its appropriate area.

Red tag “rejected part” (IC-1000) - Will be attached to rejected parts that are not serviceable or repairable. This decision is made by the Accountable Manager. All rejected parts that have been reviewed by the Accountable manager will be recorded in a log and mutilated to prevent accidental use on other aircraft.

B - 4.8 Procedures for Detecting and Reporting Suspected Unapproved Parts

Upon receipt of any incoming material to the repair station during the receiving inspection, a determination will be made as to the material’s status as damaged, "suspect" or approved. Any items received that are "suspect" as to conformity will be immediately brought to the attention of the Accountable Manager. The Accountable Manager will then notify the Administrator (as revised) in the prescribed manner, and as specified in AC 21-29 (as revised) for SUP Reporting Procedures.

B - 4.9 Hidden Damage Inspections

Only certified technicians are allowed to perform hidden damage inspections

A complete and thorough inspection for hidden damage must be accomplished in areas adjacent to any damaged area; aircraft know to have or suspected to have been involved in an accident. The scope of this inspection will be governed by the type of unit involved with special consideration accorded previous operating history, Malfunction or Defect Reports, Service Bulletins, applicable manufacturer manuals, guidance or letters, and Airworthiness Directives applicable to the unit involved. If discrepancy findings are discovered during the above steps, the findings will be documented in the same manner as all other discrepancies and corrected with standard process. When applicable the "Hidden Damage Inspection” discrepancy will be signed off by the respective Inspector. All results of the inspection will be communicated to the customer in a manner that is typical for all workorders. [Ref FAR 145.2.11 (c)1(iii)]

B - 4.10 LLPs Life Limited Parts

All life limited parts received into the parts system will include their current life limit and total accumulated time. If beyond their life limit the part will be rejected and follow the requirements for red tagged parts. If their life limit cannot be determined they will be designed as a quarantined part and segregated until a determination of its traceability and total life can be established and documented.

B - 5.0 Work Order System

B - 5.1 Work Order System Description

The inspection system of the repair station is comprised of several key components. Here's an overview of how the system works.

This repair station will track all aircraft maintenance using a system of work orders. The work-order process will be used any time maintenance is performed on an aircraft. This process is essential for compliance with FAA regulations, efficient maintenance, and

organized record keeping. The primary function of the work order is to manage the tracking of parts, and corrective actions for specific aircraft.

The work order system at our Part 145 repair station ensures a structured and compliant process for aircraft maintenance, beginning with pre-induction steps that capture customer information, secure work authorization, and organize maintenance actions into a comprehensive work order. Pre-work actions emphasize safety, with grounding tags and checklists applied to each aircraft to designate status and compliance needs. All required parts and components are documented, and an initial visual inspection identifies any existing issues. Scheduled inspections follow the manufacturer's maintenance instructions and FAA regulations, recording discrepancies in a log for customer review and authorization. Once approved, repairs are completed by mechanics who document their work, which is then inspected and signed off by authorized personnel. If no other technician is available, a mechanic may inspect their own work with approval, under one-time authorization. Final inspection includes a review of all records and a visual check, ensuring all airworthiness requirements are met before removing safety tags and completing final logbook entries. If further work is needed after RTS, a new work order is generated to ensure all actions are thoroughly documented and inspected. This system maintains standards of safety, compliance, and accountability throughout the inspection system. [Ref FAR § 145.211 (c)1(vii)]

B - 5.2 Electronic and Paper Work Orders

For the purposes of this manual, we will refer to the electronic work order system by default, but each major function of the work order system can be found in duplicate in the paper system. Using the paper system to track maintenance and compliance is generally reserved for any time when the Electronic system is unavailable. If such an event happens then it is the accountable manager's responsibility to convert the applicable information and records into the electronic system to maintain a cohesive record of maintenance performed by the repair station. The approved forms for this process can be found in the repair station forms manual.

All repair station or manufacturer forms or checklists that are used to facilitate maintenance for a specific work order will be filled out at the time of use and then subsequently retained in the work order record.

B - 5.3 RESERVED

B - 5.4 Pre-Induction

The process begins when Elevate MRO and a customer coordinate a requested work scope. The Assigned Lead notifies the Accountable Manager who will verify the requested work is in the Repair Station Ops Specs.

A Work Order will be opened through the electronic work order system with the work to be accomplished, including but not limited to inspections, repairs, modifications, and discrepancies. Technicians are assigned to the project. Depending on the complexity of the project, a lead technician may be assigned.

NOTE: In the event the electronic work order system is unavailable, a paper work order will be opened.

The Assigned Lead will review the work to be performed to preplan the parts, manpower and schedule that will be required. The Accountable Manager will assign an Inspector to the project and review the repair station needs. The article is inducted into the facility and given a preliminary inspection and is evaluated for necessary repair or inspection.

Prior to maintenance a work order with a unique number will be generated. This work order will be comprised of the customer information and aircraft information and a list of discrepancies or requests that have been approved of by the customer. This system maintains what work will be done on the aircraft, what parts services and other items are used on that aircraft and who performed both inspection and maintenance of the aircraft.

If a customer has special requirements for their operation regarding paperwork, process, or any function that deviates or adds to the current repair station system then this shall be documented work order. For example, a part 135 or part 121 operator will require their paperwork system to be satisfied with additional steps and documentation. The additional steps required to complete this shall be referenced in the workorder to ensure compliance is attained.

There shall be no work performed on any aircraft without an associated work authorization EMRO-1001 and work order generated.

When the aircraft arrives two tags will be affixed to the aircraft.

1. The first is a aircraft "Grounded Tag" (IC-1004) will be filled out and attached to the yoke or the throttle lever of the aircraft. Aircraft Grounded tag (IC-1004) may not be required when a customer/operators inspection system supersedes this requirement, and it is up to the judgment of the technician applying the tag to make this determination.
2. The second is the Exterior grounding tag "Entrance Grounding Tag" (OP-1001)" This Tag prevents premature release of the aircraft to the customer.

The technician initiating work on an aircraft is responsible for ensuring the Grounded tag (IC-1004) and "Entrance Grounding Tag" (OP-1001) is attached to the aircraft while the aircraft is unairworthy. The checklist and grounding tag is removed when the aircraft is released and retained as part of the work order record. [Ref FAR § 145.211 (c)1(vii)]

B - 5.5 Initial Inspection / Preliminary Inspection

All aircraft or articles for which work is scheduled and performed will receive a preliminary inspection. Preliminary inspections will be conducted on non-scheduled AOG aircraft as necessary based on the judgment of the inspector assigned to the task.

All initial / Preliminary inspection will be conducted by individuals who possess FAA A&P Certification or a repairman license with applicable training.

After the work order is set up and the aircraft or article is ready for work, a preliminary inspection will be performed and recorded in the work order. This is a general visual inspection of the exterior and interior of the aircraft. This is to identify safety hazards that

may impact maintenance to the aircraft. Particular attention will be made to identifying any evidence of fluid leaks, hangar rash, birds strike, as well as FOD damage, and any condition that may be hazardous when performing maintenance engine runs and operational checks.

A review of the aircraft or article will also be performed which will verify the status of the following:

3. Proper documentation and traceability of the article.
4. Applicable shipping damage or prior damage of the article.
5. State of preservation and or life limits.
6. AD and Service bulletin applicability.

All items required to be inspected or repaired will be added to the work order including all items requiring functional tests or tear down inspections.

Any discrepancies and unsafe conditions noted will be captured on Discrepancy Action Card (OP-1003) and retained with the aircraft paperwork these records will be reviewed and then added to the Electronic Workorder as required by the lead technician of the project these shall be reviewed before commencing work on the aircraft. These discrepancies and their disposition will be retained as part of the work order record.

B - 5.6 Inspection phase

After the initial inspection is completed, Work found in the workorder may be started. The order of this work should be considered to improve overall safety and efficiency but is at the discretion of the lead technician on the project. During this phase most of the effort should be used to complete inspections on the aircraft. This will allow additional lead time for the procurement of parts if they are found necessary.

If the work order contains instructions to complete an annual or 100-hour inspection the technician must use a checklist to guide their inspection. If additional forms or checklists are provided by the manufacturer or are available in the repair station form manual for specific tasks, then they shall be completed and retained with the work order record as needed based on the judgment of the performing technicians supervisor.

Any discrepancies and unsafe conditions noted will be captured on Discrepancy Action Card (OP-1003) and retained with the aircraft paperwork these records will be reviewed and then added to the Electronic work order as required by the lead technician of the project. In as much as it is possible the review and entering of discrepancy from the paper record to the electronic one should be regularly performed to avoid batch processing. This practice will help reduce errors in communication and reduces work burden. Lead technicians will be encouraged to review and submit discrepancy on a daily basis.

B - 5.6.1 Maintenance Inspection

Maintenance will be accomplished in accordance with the inspection checklist and/or inspection schedule provided for each specific model aircraft. The required inspections documented in the work order shall be comprehensive and will include all items that affect the airworthiness of the aircraft. Which includes can include and is not limited to

airworthiness directive, life limited parts, instructions for continued airworthiness, manufacturer Service letters, manufacturer elected service bulletins.

.

B - 5.7 Record of Inspection Test Results

When a record of the inspection of dimensions, tests or calibration is required by the manufacturer's technical data, such record shall be made on the Discrepancy Action Card (OP-1003) or the electronic work order system properly identified with the Work Order number. It must also be dated and initialed by the mechanic and/or Inspector performing the check or inspection.

B - 5.8 Repair Phase

All discrepancies generated by inspection phase will be reviewed and recorded in the electronic workorder, this will be submitted for approval by the customer and when returned each item that was approved will be presented to the technician for repair, each item that was denied will be retained for reference.

If a conflict arises where an item that affects airworthiness is denied by the customer and there is no solution found to correct the discrepancy while at the repair station, then when releasing the aircraft back to the customer the individual releasing the aircraft will sign an unairworthy logbook entry and provide a written list of discrepancies to the customer.

The Lead technician will direct work on the aircraft and use their judgment to efficiently and safety repair the aircraft. Each technician will sign for the work they perform. And each item that pertains to the airworthiness of the aircraft will be required to be inspected by an authorized inspector. This will be documented using the electronic work order system.

B - 5.8.1 Major Repair and Alteration: Aircraft and Components

For all major repairs or alterations, the repair station will ensure that the personnel performing and returning to service these discrepancies are trained and capable of performing their duties. Please refer to the training manual

The standard workorder system will be utilized to provide a record of the work performed. These records will contain a description of any Major Repairs or Alterations, noted defects, Service Bulletins, Airworthiness Directive note compliance, Service Letter compliance, type of special inspections, detailed remarks related to operational and leak checks, special nondestructive tests to be accomplished and the results, and/or corrective actions taken. When applicable to the discrepancy item, the approved engineering or other approved technical data authorizing the repair or alteration will be clearly indicated in the corrective action block. Where special drawings or documents are made to cover specific repair conditions, a copy of the documents will be kept in the work order file. As per 14 CFR Part 43 Appendix B, the Repair Station is not required to complete a Form FAA 337 (Major Repairs or Alteration form) on major repairs when it meets the recording requirements as found therein. Only properly trained inspectors will be permitted to complete form 337's on behalf of the repair station. The completion of Form FAA 337 will be at the discretion of the

Accountable Manager. For a Form FAA 337 that is completed for repairs or alterations accomplished, three copies will be made which will be distributed as follows: a copy will be kept in the work order file, the original form will be provided to the owner/operator for their records, and a copy will be forwarded to the FAA's Registration Branch, in Oklahoma City, Oklahoma.

All technicians will evaluate if the repair is major or minor using the applicable FARs with special attention to CFR 14 43 Appendix A and the guidance found in AC43-210.

B - 5.9 One-time Self Inspection Authority

In some cases due to availability of personnel and location, the technician completing the work if working alone and if vested with appropriate inspection authority, can inspect their own work. In in this scenario the Accountable Manager may use their discretion to authorize a one-time authorization of the technician to perform their own inspection of work performed provided that they have prior approval and has received specific guidance from the Accountable Manager that is appropriate to the task being performed. In this case, the technician will document his/her work in the blocks marked "Tech" and "Insp." The Technician/Inspector must comply with all Preliminary, In-Process Inspection, Hidden Damage, and Final Inspection requirements in accordance with the appropriate section of the Quality Control Procedures and Standards. [Ref FAR § 145.211 (c)1(vii)]. This authorization will normally be communicated in written form but also may be verbal.

This process is best accomplished by performing the work completely, including paperwork, as the technician, and then after a break going back and inspecting all the work, including paperwork, as an inspector. This effectively splits the job in two, as if two people were doing the work.

When complete the technician will make note of this procedure in their signoff. The signoff will include the following language "I am herby authorized by the repair station accountable manager to perform a one-time inspection of the work I performed in accordance with *RSQCM* Ch 2.5"

In the event there is no technician available who is authorized to perform RTS of the aircraft then the Accountable Manager may use their discretion to authorize a one-time authorization of the technician to perform the RTS process of the aircraft. In which case the technician will make note of this condition in their RTS signoff. The signoff in the work order will include the following language "I am herby authorized by the repair station accountable manager to perform a one-time return to service of this Article in accordance with *RSQCM* C- 4.8.

This capability should be used only when required by extenuating circumstances if this process being used frequently then a training assessment should be performed and gap plan and corrective actions implemented using the processes found in the training manual. Eliminating the regular need for this process. [Ref FAR § 145.213 (a)]

B - 5.10 Technician and Inspector Turnover / Continuity of Maintenance Responsibility

If for any reason work is stopped before being completed then a stopping point shall be established and all work completed will be communicated in a written turnover log, including the technician's name and signature.

If the electronic work order system is down, The Discrepancy Action Card (OP-1003) is used, otherwise the electronic work order system will be updated by each inspector by using their initials on OP-1003 or their inspector code (the electronic work order system) on all completed inspections, so that following inspectors can easily determine the status of a project. The purpose is to assure a continuing inspection responsibility for in- progress work inspections.

As the shift change occurs, the current shift updates the Turnover Log to reflect the work that needs to be completed by the next shift. This is also communicated person-to-person or via email. When the shift leaves, the log is completed or an email is sent to show the work that was completed by them. This log is kept with maintenance or in an email for quick review by each shift.

Alternatively, or in addition to, a copy of the maintenance manual can be printed, stamped "uncontrolled document," and each completed step will be initialed and dated by the technician performing maintenance, and include in-process inspections with inspector's initials and date performed. The document will be kept as part of the aircraft work order folder. Once the discrepancy is completed, the inspector will enter their inspector code signature and initials will be kept on file. [FAR Ref § 145.211 (c)2]

B - 5.11 Final Inspection and Release to Service

To release an aircraft or article back into service that the repair station has performed maintenance on the following process shall be competed. Only a appropriately rated inspector as authorized on the repair station inspection personnel roster will perform the following.

A paperwork review will be conducted to ensure that all discrepancies have been properly signed off and inspected. This review will confirm that all possible sources of data regarding the aircraft are reviewed for completeness, including all applicable forms and checklist. This includes proper documentation of parts installed and removed as well as confirmation of certificates of conformance with all applicable parts. All necessary paperwork that is required from vendors will be reviewed for completeness and accuracy. all AD's are complied with and that the aircraft is airworthy. Once it has been determined that there is no remaining work open on the workorder and that all completed work is properly documented then a visual inspection of the aircraft will be performed.

The individual performing the RTS of the aircraft will perform a visual inspection of the exterior and interior of the aircraft and will determine if it is airworthy with respect to the work performed. This inspection will be accomplished in a methodical manner with the purpose of reducing human error and ensuring that the aircraft is in an airworthy condition. If errors are found, then they will be documented using the standard discrepancy process.

Once compete the visual inspection is competed and all additional discrepancies satisfied the RTS inspector will document the approval for return to service.

[Ref FAR § 145.211 (c)1(vii), § 145.213 (a,b), § 145.155 (a), § 145.213 (d)]

B - 5.11.1 Maintenance Release

No aircraft will be returned to service unless the repair station is rated appropriately for that article.

No aircraft will be returned to service following an inspection, until all airworthiness discrepancies noted on the Discrepancy Action Card (OP-1003) or in the electronic work order system have been properly corrected and accepted and signed-off per 14 CFR 43.11.

No aircraft or item may be released for return to service until the work order file has been reviewed for completeness and final acceptance cleared by inspection. Particular attention shall be paid to Airworthiness Directive status, applicability and compliance. [Ref FAR § 145.211 (c)1(vii)]

The Accountable Manager is responsible for screening completed Work Orders covering work performed in their assigned area to assure that all items on the Work Order have been cleared, that there are no open discrepancies and that all major work accomplished is covered by aircraft manufacturers approved data. The Accountable Manager will periodically audit this system to assure compliance with this section

A maintenance release statement stamped and/or preprinted form prepared in accordance with 14 CFR Part 43, Appendix B, will be used to release items for return to service. Other records required by 14 CFR Part 43.9 and 43.11 will be executed as required, regardless of whether, a FAA Form 337 or maintenance release has been used to return the article to service. The appropriate Elevate MRO location, certification number and address will be used with the maintenance release statement.

"I certify the airframe, engine and/or component identified herein was repaired and inspected in accordance with the current Elevate MRO. Repair Station Manual System and the Federal Aviation Regulations under which the operator is certified, and was determined to be in an Airworthy Condition at this date and time with regards to the inspection(s) and/or maintenance performed, and is approved for return to service as per those requirements. Pertinent details of the repair are on file at this Repair Station under this work order." [Ref FAR § 145.211 (c)1(vii)] Only appropriately rated technicians will be authorized to fill out this form.

Then RTS inspector will then place the signed original hard copy Maintenance Release into the aircraft work order folder. [Ref FAR § 145.213 (a)]

B - 5.11.2 Maintenance Release Statement: Air Carrier "Example"

"I certify the airframe, engine and/or component identified herein was repaired and/or inspected in accordance with current instructions contained in Operators Manual or program, and the maintenance rules of the Federal Aviation Regulations under which the operator is certified, and was determined to be in an Airworthy Condition at this date and time with regards to the inspection(s) and/or maintenance performed, and is approved for

return to service as per those requirements. Pertinent details of the repair are on file at this Repair Station under work order No._____ Dated_____ , Signed_____, Certificate No. _____ ”

[Ref FAR § 145.211 (c)1(vii)]

B - 5.12 Work order records

The final work order will provide a copy of the work order to include all discrepancies and corrective actions, part serviceable tags, FAA Form 337, AD compliance records and the maintenance release.

As work is performed on articles such as appliances, accessories, and individual parts or components that do not have an individual maintenance record, work will be recorded using the appropriate maintenance release document, i.e., Form FAA 8130-3, or yellow tag for inclusion in the aircraft maintenance records.

For inspections performed requiring a 14 CFR Part 43.11 maintenance entry, create the entry using the applicable statements from 14 CFR Part 43.11 Print and manually sign the respective logbook entry for the article, airframe, engine, propeller or sign the logbook entry via electronic signature

Place a copy of the logbook entry in the aircraft work order folder and provide the original signed logbook entry to the operator upon completion of the aircraft work order, the Accountable Manager ensures all applicable documents are uploaded into the electronic work order system aircraft work order to include applicable checklists, part serviceable tags, FAA Form 337, AD compliance records and the maintenance release. [Ref FAR § 145.211 (c)1(vii)]

After work orders have been screened for completeness and accuracy and signed off, their physical paperwork is retained in the Maintenance Records Area. Such inspection and work records will be retained in a file folder at the Repair Station, for a period of not less than two years (as required by 14 CFR Part 145). Electronic records shall be retained for the same amount of time. [Ref FAR § 145.219 (d)]

B - 5.12.1 Major alteration or repair records

Routinely, major repairs and alterations will be performed. The work order packet for these events will contain includes a description of the work completed and the maintenance release and return to service documents. These documents will be copied and given to the customer. A separate copy will be retained by the repair station and a third copy filed appropriately with the FAA when required. (It is noted on the work order folder when the work order is originated that it is a major repair).

In all cases where a major alteration is involved when an item is returned to service a FAA form 337 and a signed work order and maintenance release will be given to the customer per 14 CFR Part 43.9 and 14 CFR Part 43, Appendix B. The Accountable Manager will review all Major alteration and repair documentation prior to release for return to service. The Inspector of the work will be responsible for establishing that the repair or alteration was made in accordance with the requirements of 14 CFR Part 43 and all

additional approval data and will sign the conformity statement (item 6) on the FAA Form 337.

Authorized personnel on the authority roster responsible for the approval for return to service of aircraft will indicate such approval by signing the approval for return to service (item 7) on FAA Form 337. Appropriate entries will be made in the aircraft record pertinent to the repairs and alterations accomplished by the Repair Station. Specific reference will be made by calendar date to the applicable FAA Form 337. The original FAA Form 337 will be provided to the owner/operator, with a copy forwarded to the FAA Registration Branch, and one copy retained in the work order file.

It is the responsibility of the individual authorizing return to service to assure the Aircraft Flight Manual is revised following any alteration or modification affecting weight and balance, with properly amended weight and balance data.

Aircraft components, appliances, and other items repaired or overhauled by the Repair Station specifications will be returned to service through the use of a maintenance release preprinted or stamped on the yellow serviceable parts tag, or Form FAA 8130-3 described in the section of this Manual. The authorized inspector under whose jurisdiction the work is accomplished will be responsible for the return to service release compliance. After the Return to Service is complete, the individual authorized on the Authority and Roster of Authorized Inspection Personnel will additionally perform the following per 14 CFR Part 43, Section 43.9 and 43.11 (as applicable)

B - 5.13 Paper Workorder Process

Using a fully paper system for paperwork is discouraged and should be used only if access to the electronic workorder system is lost. When work orders are fully documented using paper they will be recorded into the electronic work order system when access to the electronic work order system is restored.

Upon receipt of a work request for maintenance, the maintenance department will issue a **Elevate MRO** Repair Station work order, to authorize the work. The form will be given a number from The Work Order Log (OP-1002) that lists the date, the aircraft owner, the aircraft registration number, and serial number, and a brief summary of the work to be performed. That number will be the basic reference for that product's maintenance record (work order number).

Aircraft and parts tagging procedures are identical to the standard Work order system.

All work order packets consist of a folder with the numerical work order number on it, and the following:

Customer Invoice and a maintenance release logbook entry, any other pertinent data i.e.; serviceable tags, Form FAA 8130-3's, inspection procedures, etc. Paper work orders also include Discrepancy action card Form OP-1003 and OP-1004, a maintenance release logbook entry, and any other pertinent data i.e.; serviceable tags, Form FAA 8130-3's, inspection procedures, etc. and all aircraft tags OP-1001 (maintenance check list) , OP-1000 (work order setup form) [Ref FAR § 145.211 (c)1(vi-vii)]

A Discrepancy Action Card Form OP-1003 referencing the work order Number will be issued to the mechanic/inspectors assigned to the work to be accomplished. The Discrepancy Action Card will have listed in numerical order the discrepancies in the discrepancy column. The corrective actions will be documented on the right side of the card in the corrective action column to correspond with the appropriate discrepancy by the technician. The technician performing the work will place his initials in the mechanic block signifying the completion of the work. After a satisfactory inspection of the completed work the assigned inspector will indicate his inspection of the completed work by placing his initials in the inspector's block. The work order and Discrepancy Action Card will be supplemented as necessary with detailed inspection instructions along with applicable forms, to assure proper inspection and repair of the unit involved. The Discrepancy Action Cards will be sequentially numbered with the total number of forms used shown on each card. An original or copy of the completed printed and numbered work order will be retained in the work order file.

The work order packet is then reviewed by the Accountable Manager for completeness, and a log book entry is printed. Upon completion and acceptance of the work accomplished the log book and return to service entries are signed by the appropriate inspector.

The grounded tag is then removed from the aircraft by the inspector. Upon completion of the aircraft work order, the Accountable Manager ensures all applicable documents are uploaded into the electronic work order system aircraft work order to include applicable checklists, part serviceable tags, form FAA 337, ad compliance records and the maintenance release.

if discrepancy findings are discovered during the above steps, the findings will be documented in the electronic work order system or on the discrepancy evaluation technician notes form (OP-1004). Inspector will disposition per OP-1004 instructions. Discrepancy findings entered into the electronic work order system will be assured corrective action is completed, inspected, and accepted prior to release for return to service. The work will be re- inspected until found satisfactory, or the article will be rejected for return to service approval. In the event that the electronic work order system is not available, it will be documented on the paper work order form OP-1003

As the inspection progresses the secondary discrepancies that are found by the technicians are logged on Form OP-1004, Discrepancy Evaluation Technician Notes. From there, these discrepancies are evaluated and qualified by the inspector to determine airworthiness/serviceability of the item(s). Those items found by the inspector to be legitimate squawks requiring action (repair, inspection, etc.) are entered into the work order system, the customer is contacted and items are discussed, and approval is given.

In the event a discrepancy is declined by the customer, a rejection note will be placed in the work order system stating this or something similar, "customer declined any corrective action at this time."

If the discrepancy is an airworthy issue, a discrepancy list will be generated as well as a logbook entry that may read this or something similar: "I certify that this aircraft has been inspected in accordance with an ( ) inspection and a list of discrepancies and unairworthy

items as recorded above dated ( ) has been provided to the aircraft owner/operator. [Ref: 14 CFR Part 43.11(a) (5)]

When the work scope and any additional discrepancies are completed, and the corrective actions are documented by the technician in the correction action block of the discrepancy/action card. When the work accomplished meets the approval of the assigned inspector, their (the assigned inspector) signifies his/her approval by entering their to the accountable manager for final review and completion of a logbook sticker with a return to service entry, completing the work order. [Ref FAR § 145.211 (c)1(vii)]

B - 6.0 Security

B - 6.1 Security Policy

If a employee is terminated or is no longer in employment at the repair station then the accountable manager shall revoke their that employee's authorizations and update both the signature and inspection personnel rosters as applicable.

B - 6.2 Authorization Control

At all times the repair station will ensure that only individuals who are listed in the Signature roster and Inspection personnel roster perform their respective duties. As required the accountable manager will use whatever physical or digital means as he/she requires to control and audit the individuals who are authorized to perform work signoffs. The accountable manager will ensure that unqualified and unauthorized individuals will not perform work sign-offs.

B - 7.0 Technical Data

B - 7.1 Current Technical Data

The repair station will maintain in current condition the manufacturer's service manuals, instructions, service bulletins, airworthiness directives, instructions for continued airworthiness, engineering data, and aircraft specifications appropriate for which the repair station is rated. [Ref FAR § 145.211 (c)2]

The Accountable Manager is responsible for the maintenance and revising of the technical library.

Technical data is available and accessible for inspectors in any form including CDROM, paper, digital database, etc. All information is kept current or a sticker marked "for reference only" is placed on it.

Most technical data is web based and can be accessed via computers located throughout the maintenance facility. [Ref FAR § 145.211 (c)1(v)]

B - 7.2 Document Control

All forms issued by this repair station will be issued a document number that identifies the document. Forms will have the date specifying the revision status. A list of forms with their revision status will be maintained in the Forms Manual as part of the Repair Station Manual System. FAA accepted manuals issued by this repair station will have a front cover identifying document. Each will have a list of effective pages showing the revision status of each page in the manual.

FAA approved *RSQCM*, Training Manual, and any other controlled manual issued by this repair station will have a front cover identifying document. It will have a list of effective pages showing the revision status of each page in the manual.

The Repair station manuals will be located in the Maintenance Shared Drive and one hard copies as identified in the manual distribution list. [Ref FAR § 145.211 (c)1(v)]

B - 7.3 OEM Manuals and Technical Library Data Control

The Accountable Manager has the primary responsibility for the currency of the technical library. All technical information and instructions issued by the Repair Station will be maintained to their most current issue. The technical library consists of website subscriptions, computerized manuals, and paper manual reproductions of OEM (Original Equipment Manufacturer) manuals and regulatory information (such as CFRs, Advisory Circulars, Airworthiness Directives, etc.).

The repair station subscribes to a technical library service which is revised on a regular basis. OEM websites in which the manuals are located are controlled and audited by the OEM. Paper library manuals must be verified prior to each use to ensure the most recent revision is being used.

The technical library is available to all personnel. Copies may be made and used for the particular job. Upon completion of the work the copies are placed in the work order packet, destroyed or filed as “For Reference Only” at the discretion of the Accountable Manager.

All working copies used, of manuals and documents, will be maintained in good condition and made available to all maintenance personnel. Handwritten entries in controlled manuals are forbidden. All documents will be stored in a manner which protects them from dirt or damage. Adequate viewing devices, maintained in good condition, will be available for viewing of technical data in a form requiring such devices. All uncontrolled manuals or documents in the repair station will be identified as “For Reference Only” and segregated from controlled manuals or documents. [Ref FAR § 145.211 (c)1(v), § 145.211 (c)2]

B - 8.0 Proficiency of Inspection Personnel

B - 8.1 Proficiency of Inspection Personnel

The Accountable Manager will base the minimum requirements for inspection personnel on the requirements found in 14 CFR 145.155 and 145.157.

Prior to the assignment of inspection authority to an inspector candidate, the Accountable Manager will train the candidate inspector appropriate to the inspection authority intended. The training will be accomplished by classroom instruction and/ or on the job training as required. The training will include detailed instruction in Repair Station, and FAA, requirements and company quality expectations. A verbal or written exam may be required. Please refer to the repair station training manual (RS-TM) for a full set of training requirements and procedures. This includes procedures for Testing, Formal Training, and Initial and Recurrent Training.

Inspection personnel are required to be thoroughly familiar with all inspection methods, techniques, and equipment used in their area of responsibility, to determine the quality of airworthiness of an article undergoing maintenance, repair or alterations. All personnel will maintain proficiency in the use of the various types of inspection aids to be used for inspection of the items undergoing inspection, by the use of applicable manufacturer's maintenance, service, and inspection manuals. Available to all inspection personnel are current specifications involving inspection tolerances, limits, and procedures as set forth by the manufacturer of the product undergoing inspection, and other forms of inspection information such as FAA Airworthiness Directives, Manufacturers Bulletins, etc.

Ref FAR § 145.211 (c)1(iv), § 145.155 (a), §145.157, § 145.161]

B - 8.2 Inspectors, Technicians, And Supervisors

All supervisors, inspectors, and technicians are required to be thoroughly familiar with the requirements of this Manual, Title 14 Code of Regulations, Airworthiness Directives, Advisory Circulars, Manufacturers Maintenance Information i.e.; Maintenance Manuals, Service Letters and Bulletins, and Engineering Orders. The basic inspection system requires that after a task is completed the technician is too initial or place their name or code in the appropriate area in the electronic work order system discrepancy, prior to submitting the item to the inspector for final acceptance. Inspectors will indicate their acceptance of work performed, by placing their initials or code in the appropriate box, corresponding to the item on the electronic work order system discrepancy.

Ref FAR 145.209 (g), (, § 145.211 (c)1(vii), § 145.211 (c)2

B - 8.3 Inspectors, Mechanics, and Supervisors

The Accountable Manager will be responsible for assuring that all supervisors and inspectors are thoroughly familiar with the requirements of this Manual, 14 CFR,

Airworthiness Directives, Advisory Circulars, Manufacturers Service Letters, Bulletins and Engineering Orders.

Inspection personnel assigned to Repair Station operations are required to familiarize themselves with 14 CFR applicable to such operations with particular emphasis on the following:

1. FAR Part 21 - Certification Procedures for Products and Parts.
2. FAR Part 23 - Airworthiness Standards; Normal, Utility and Acrobatic
3. FAR Part 25 - Airworthiness Standards; Transportation Category Airplanes.
4. FAR Part 39 - Airworthiness Directives.
5. FAR Part 43 - Maintenance, Preventive Maintenance, Rebuilding and Alteration.
6. FAR Part 45 - Identification and Registration Marking.
7. FAR Part 65 - Certification: Airman Other Than Flight Crewmembers.
8. FAR Part 91 - General Operating and Flight Rules.
9. FAR Part 121 - Certification and Operations: Domestic, Flag, and Supplemental Air Carriers and Commercial Operators of Large Aircraft.
10. FAR Part 125- Certification and Operation Rules for Certain Large Airplanes.
11. FAR Part 135- Air Taxi Operators and Commercial Operators.
12. FAR Part 145- Repair Stations.

[Ref FAR § 145.211 (c)1(iv)]

B - 8.4 Required Inspection Items (RII)

Any maintenance operation, which, if improperly performed, could be critical to the safe flight of an aircraft, will be given a required inspection. An inspector on the authority roster, who is trained and approved by the air carrier familiar with all inspection methods, techniques, and equipment will be authorized by the air carrier to determine the quality of airworthiness of the article involved. When work is performed for an air carrier under the continuous airworthiness requirements of 14 CFR Part 121, 125, 129, and 135, the RII items specified by the air carrier will be maintained as RII items.

The air carrier's inspection program lists the work areas that are identified as Required Inspection Items (RII). The air carrier must approve and train each RII inspector per their program policy and procedures. Documentation of training from the air carrier will be placed into the employee's training folder. Please see the repair Station Training manual (RS-TM) for more information.

The training encompasses the RII procedures and policies in general and is not aircraft specific. Personnel who are authorized to inspect these work areas have the basic qualification to perform this type of work (i.e., flight controls, engine controls, etc.) and need no additional specific training Their duty is to inspect the work that has been completed to ensure that it was performed according to accepted maintenance procedures,

that the work is completed satisfactorily and that the paperwork is completed correctly in regard to job cards, work order sign-offs, log book entries, etc. [Ref FAR § 145.211 (c)1(iv)]

B - 9.0 Contractor and Outside Vendors

B - 9.1 Quality Control System for Non-Certificated Contract Maintenance Providers

Prior to commencing work with a contract maintenance provider, the contract maintenance function process will be reviewed and followed as per Repair Station Manual Section B - 6.8 Contract Maintenance Procedures.

Each contract maintenance provider must have a documented Quality Control system that will assure that the work performed on an article for Elevate MRO will meet airworthiness requirements. In the event that a provider does not have a quality control program, Elevate MRO will provide a Quality Control system that is based on Elevate MRO's inspection system found in this manual to be followed during the repair of the article.

The maintenance provider must designate an employee as the accountable manager for all work performed for Elevate MRO; this person will be the primary contact for the Accountable Manager during the implementation and follow-up of the quality control system.

Upon completion of any work performed by another agency on an article for Elevate MRO, that article will be inspected and tested (as the situation may dictate), by the Accountable Manager to verify that the work was performed in accordance with applicable federal regulations, Elevate MRO policies and procedures, and any applicable customer requirements. In addition, this inspection and testing will serve to verify that the quality of the parts, materials, and workmanship is in accordance with applicable regulations, certifications, and standards. At no time shall Elevate MRO release any parts fabricated by or articles having had work performed on them by a non-certificated Contracted Maintenance Provider until the Accountable Manager, has approved the materials and workmanship as meeting the above requirements.

If an article is sent to a Contract Maintenance Provider that is not an FAA certificated facility, then Elevate MRO is responsible for the airworthiness of the article as well as providing the return to service for the article. If the Repair Station cannot determine the quality of work by inspection or test, the work can be contracted only to an FAA certificated repair facility that is able to inspect and test the work performed for compliance with 14 CFR Part 43.

Any incoming article which has had work performed on it by a non-certificated Contract Maintenance Provider shall be kept segregated from regular stock or inventory until such time as the above receiving inspection has been completed this tagging system follows the standard tagging system as found in the Parts System Section C - 4.0

[Ref FAR § 145.211 (c)1(vi-vii)]

B - 9.2 Personnel Requirements

Each maintenance provider must designate an employee as the Accountable Manager for all work performed for **Elevate MRO**. In addition, the maintenance provider must ensure that it has a sufficient number of employees with the training or knowledge and experience in the performance of the maintenance tasks contracted to it by **Elevate MRO**.

NOTE: If work is to be accomplished on 121/135 aircraft then the contractor must agree to be DOT Drug Tested per requirements of approved drug testing program. [Ref FAR § 145.211 (c)1(vi)]

B - 9.3 Communications

At the beginning of the project a method of communication will be established (i.e., visits, e-mail, phone calls, etc.) to maintain continuity of the work being performed. A schedule of contact may also be set at that time in order to ensure a smooth workflow and an on time delivery.

These communications are vital in that they provide the necessary exchange information between **Elevate MRO** and the contractor as to the work being performed, quality control issues and other questions that may arise during the work scope.

Ref FAR § 145.211 (c)1(vi-vii)

B - 9.4 Ongoing Auditing of Non-Certificated Maintenance Providers

The size of the project will determine the amount of surveillance that needs to take place during the maintenance, repair, and/or alteration process. A small project may only require a beginning and ending visit, whereas a large project will require several visits during the work scope. It will be the responsibility of the Accountable Manager to establish the scope and frequency of the visits to maintain the level of quality control that is necessary for the work being performed. [Ref FAR § 145.211 (c)1(vi)]

B - 9.5 Non-certificated Maintenance Contract

A sample of the Non-Certificated Maintenance Contract (Form IA-1008) found in the Forms Manual. Other suitable forms may be substituted for the sample form as long as they contain similar information and a vendor authorization to the FAA for onsite inspections and meet the approval of the Accountable Manager.

B - 10.0 Calibration

B - 10.1 Record of Tests and Calibration of Precision Equipment

In accordance with 14 CFR 145.109 (b) all precision inspection and test equipment used will be checked and re-calibrated as necessary to assure accuracy. Each piece of equipment will be provided with a calibration label showing the due date of the next calibration, and none shall be used when not within the required inspection interval. Precision tools and test equipment will be stored in a manner to protect them from damage and contamination. All personnel using calibrated tooling must check the calibration dates prior to use. [Ref FAR § 145.211 (c)1(viii-ix)]. Newly purchased tools are considered in calibration for a period of 12 months from the date of purchase if they have accompanying calibration certificates.

If the calibration label is missing or unreadable on the tool, it must be red tagged and given to the Accountable Manager for verification of certification. Once certification has been re-verified, the Accountable Manager will create a new calibration label.

A suitable record shall be kept of the calibration system physically or digitally; this may be in the form of the Precision Tool Calibration Record (OP-1200) or any other form that, identifies the item, the required frequency of calibration, the dates of calibration, the date of next due calibration, who calibrated the item, and the method of calibration used. Each piece of shop equipment that is required to be calibrated has a calibration certification document that is kept in a binder.

Standards used to calibrate equipment must be traceable to the National Institute of Standards Technology (NIST) or an approved foreign country's standards by certificate from the testing facility. Frequency for calibration standards may vary for different units but must never exceed a 12 month interval.

All in house calibration methods will be explicitly documented and those performing the calibrations will be appropriately trained on the methods and techniques required. After in-house tool calibrations have been completed a calibration sticker will be applied. Test equipment used for in-house calibrations must be traceable to NIST. Tools that fail to meet the minimum accuracy tolerance prescribed shall labeled as rejected with a green repairable tag, removed from the tooling area and isolated under the control of the Accountable Manager until proper repair can be accomplished. [Ref FAR § 145.211 (c)1(viii)]

B - 10.2 Employee-Owned Inspection and Test Equipment

Calibrated tooling owned by technicians must also be periodically checked and re-calibrated as necessary to assure accuracy, per the requirements of 14 CFR 145.109 (b). The owner of the equipment is required to ensure their tooling is in calibration before using it to make an airworthiness determination. Some tools that can be calibrated but are not practical to calibrate may be marked "For Reference Only" and may not be used to make airworthiness determinations. Elevate MRO will maintain a list of technicians' calibrated tools and track these tools in the same manner as company owned calibrated tooling. [Ref FAR § 145.211 (c)1(viii-ix)]

B - 10.3 Control of Precision Tools and Test Equipment

Most precision tools used in the Repair Station operation are subject to 12-month interval check and calibration. Any piece of test equipment found in the Repair Station without a current calibration label, or in an out-of-date condition, shall not be used to make airworthiness determinations. Any out of calibration tooling items that are not labeled "For Reference Only" shall be will be given to the Accountable Manager for calibration. [Ref FAR § 145.211 (c)1(viii-ix)]

1. Tool Calibration Periods:
2. Precision Measuring Tools i.e.: (micrometers, depth,
3. gauges, dial indicators, etc.) 12 months
4. Voltmeters/Ammeters 12 months
5. Other Electronic Equipment 12 months
6. Pressure Gauges 12 months
7. Torque Wrenches 12 months
8. Battery Chargers 12 months
9. Calibrated tool default calibration period. 12 months

[Ref FAR § 145.211 (c)1(viii)]

If calibration intervals need to be modified to fit the new usage or wear needs the accountable manager will revise the calibration interval as required. The accountable manager will also monitor results of calibration checks and revise calibration intervals if data indicates a need for different calibration intervals.

B - 10.4 Use of Calibrated Tooling

It is the responsibility of the technician performing maintenance on behalf of the repair station to determine if calibrated tooling is required to accomplish maintenance functions. If so, they will adhere to the process in this manual when using calibrated tooling. Supervisory personnel will also monitor the use of calibrated tooling to ensure the tooling is in calibration and in compliance with the procedures for calibrated tooling use.

B - 10.5 Errors in Use

If a calibrated tool is discovered to be defective or calibration overdue the accountable manager will investigate every instance of that tool's use. If the tool was defective when airworthiness determinations were made, then that determination must be made again. If the aircraft has been released, then the owner/operator of the aircraft will be notified in writing to the airworthiness status of the aircraft and if the owner/operator approves of the rework a new workorder will be created to correct the issue with a work scope that will make a new airworthiness determination of the items in question.

Section C Manual Control and Revisions

C - 1.0 Manual Revision and Control

C - 1.1 Manual Revision Process

Repair station employees are encouraged to submit suggestions or errors found in the manuals by writing to the Accountable Manager. The Accountable manager is required to review all proposed changes and, if and at his/her discretion, will initiate applicable changes to the respective manuals. All revision changes will be clearly identified by the manual marking standard found in section D – 1.1.1 of this manual.

Revisions to repair station manuals will be the responsibility of the Accountable Manager. Revisions will be accomplished on a as needed basis.

This revision process is used for changes that exceed scope that pertain to temporary revisions. The Accountable Manager will initiate, review, and approve all revisions to repair station manuals, and will then coordinate with the FAA, and is responsible for submitting the revision for acceptance to the FAA, this is normally accomplished by submitting the manual revisions electronically (in a format readable by FAA computer systems to the Denver FSDO for acceptance. Additionality The appropriate Certificate Holding District Office (CHDO) be notified of each change made to the Repair Station Manual System.

The FAR's do not require FAA review and acceptance of revisions of accepted manuals before implementation (the Repair Station Training Program is an approved document and requires FAA approval prior to use)

In the event the FAA finds a revision unacceptable by regulation, the manual will be revised by the accountable manager or designee within 10 working days after receiving the notification from the FAA. The manual submitted can be used; however, the procedures in question and associated work being done in accordance with those procedures in the manual must be stopped until acceptable procedures are submitted to the FAA. The accountable manager will initiate the revision process for the unaccepted revisions, and the process listed below will be followed. [REF FAR § 145.207 (a-b), § 145.209 (j), § 145.211 (c)4] § 145.211 (d)]

C - 1.2 Distribution and Revisions

Each manual will have a control number and an assignment entry on the manual cover page. A Master List of Manuals (QA-1001) containing the manual number, assignment and revision status will be kept in the Repair Station Quality Assurance Office.

The FAA Accountable Manager, or Designee, will have those revisions deemed necessary for any section or part of this manual produced in a final paper form for coordination with the FAA Certificate Holding District Office (CHDO). The forms will be sent to the FAA accompanied by a letter Notifying the FAA of the changes made to the manual. The FAA Accountable Manager, or Designee, thereto, will approve & sign list of effective pages for the new revision. Sufficient copies will be made and distributed to provide revised pages for each manual holder.

Each repair station manual (electronic and hard copy) will include:

1. Document name
2. Page numbers
3. Revision number on each page
4. Issue date
5. Approvals documentation – as applicable
6. Acceptance documentation – as applicable
7. Revision status sheet
8. List of Effective Pages (LEP)
9. Revision bars on the left side of the page will accompany each area of change

Effective date of revision on each page

A copy of the repair station publications or appropriate portions may be copied or transmitted electronically from the master copy found on the Maintenance Shared Drive with approval of the Accountable Manager. This is an uncontrolled document and will be marked as reference only and include verification of the most current publication. All uncontrolled copies will be returned to the Accountable Manager for disposition. [REF FAR § 145.207 (c)]

Publications uploaded into the Shared Drive shall be marked with appropriate revision markings. [Ref FAR § 145.209 (j)(k), § 145.211 (c)4] Revision bars will be used to indicate revision of a line or paragraph. The new or altered text changed in the current revision will be indicated by a revision bar. In addition, the page number and date of the affected page(s) will receive a revision bar on the List of Effective Pages. Grammatical or Spelling errors will not be highlighted/shaded unless the context changes with the correction.

Upon receipt of a revision, each manual holder will be responsible for inserting the revised pages in its manual, record the revision on the manual's record of revision page, and return the acknowledgment form (provided with the revision) to the FAA Accountable Manager, or Designee, showing the holder has revised his or her manual. The FAA Accountable Manager, or Designee, will review the acknowledgment forms against the master distribution list to ensure that all manuals are revised.

A list of effective pages will be issued with each revision so each manual can be checked and kept current.

Form TR-1017 Manual Revision Acknowledgement Form will be sent to all employees when a new revision is accomplished and retained in the repair station records.

C - 1.3 Temporary revisions

Temporary revisions to this Manual may be implemented without FAA notification. This includes only minor changes that do not alter fundamental processes, safety protocols, or regulatory compliance requirements. Temporary revisions are limited to:

1. Spelling and grammar corrections.
2. Nomenclature updates (e.g., changes to titles, titles, or terminology).
3. Page reorganization.
4. Updates or minor adjustments to appendices, charts, or figures.

These changes do not require immediate FAA notification, as they do not impact the operational, procedural, or regulatory integrity of this Manual. However, all temporary revisions will be documented and incorporated into the Manual during the next formal revision cycle.

Process for Temporary Revisions:

Document each temporary revision, including the reason for the change, specific pages affected, and date of revision. The Accountable Manager must review and approve each temporary revision to confirm it meets the criteria for a minor change. Maintain a record of all temporary revisions in the Manual Revision Log. Include the revision date, affected sections, and type of change. Temporary revisions will be included in the standard revision process at the next scheduled Manual update and will be subject to the FAA's review if required. Any revision that impacts operational procedures, compliance, or FAA-approved processes will not be handled as a temporary revision and will follow the standard revision and FAA notification process. [Ref FAR § 145.209 (e), § 145.163 (d)]

C - 2.0 Quality Control Audit Program

C - 2.1 Overview / Standards

The repair station has a quality control audit program that is used to verify compliance with company's policies, procedures, practices, and standards to which it operates as a business and as an FAA Certified Repair Station. The audit process is used to audit the performance and safety of the repair station operations and to develop corrective actions for identified issues. The audit process uses root cause analysis to effectively correct problems on a long-term basis.

This section will address the scope of the program and the internal audit and corrective action policies and procedures. The audit program is designed to ensure the following:

For work performed in under the repair station certificate:

1. The repair station has the appropriate limited rating
2. The repair station possesses adequate housing and facilities.

Possesses recommended tools, equipment and materials, or equivalents:

3. Possesses current technical data
4. Possesses sufficient qualified personnel.

The auditing program will also ensure the following:

5. That all repair station documents and manuals are current effective and available to the user.
6. That maintenance is performed in accordance with the methods, standards, and techniques specified in the repair station's policies and procedures, manufacturer's maintenance manuals, and applicable CFR's. [Ref FAR § 145.211 (c)2]
7. Errors and omissions are monitored and corrected through the auditing of repair station maintenance records.
8. Errors and omissions of workmanship are constantly surveilled, identified, and corrected.
9. Repair station authorizations especially in relationship to return to return to return to service documentation are monitored for adherence to policy and that they are only executed by properly authorized individuals. [Ref FAR § 145.211 (c)1(vii)]
10. Proper receiving inspections of parts and materials are being performed.
11. There is adequate control of shelf-life limited parts.
12. Housekeeping requirements are met to assure a safe working environment.
13. Repairs and Alterations are classified and performed properly per appropriate data.

7. NOTE: This list is not exhaustive but indicated the direction of audit program.

C - 2.2 Audit Procedures

When auditing a vendor or a internal department of the repair station including the training program the auditor will select a particular procedure or function to review. The auditor then monitors and surveys the performance of that function and discusses any observed discrepancies with the department manager or the vendor's quality control contact person. These audits will include the review of all items found in section D 2.1. above.

An audit requires detailed fact finding and objective analysis. Apparent defects or questionable areas require a thorough review of all factors to establish the "root cause." The auditor must ensure that the area under audit is being managed and operated in accordance with the *RSQCM*" Section B - Repair Station Operations Procedures and Standards" and "Section C - Quality Control Procedures and Standards", Title 14 CFR Parts 43, 91, 145 regulations and appropriate manufacturers manuals as applicable.

For internal audits the forms IA-1000 and IA-1001 will be used. For external or Contract Maintenance Facility, audits the forms IA-1006 or IA-1007 will be used.

Audit results will be documented by the Repair Station Accountable Manager and transmitted to the appropriate stakeholder or the vendor's quality control contact person within one (1) week of completion of the audit. A Corrective Action Report (CAR) will be completed within forty-five (45) days of the original notification to document discrepant findings. Corrective actions will be derived from an analysis of the finding's extent and "root" cause to be sure that all affected activities or parts are identified. A follow-up audit

may be performed at the discretion of the Accountable Manager. All impacts to related or adjacent processes shall be monitored, for example, do process changes affect operations of the repair station outside of the United States are these changes acceptable or does the change require additional mitigation? If problems are detected the Corrective action plan will be amended as required.

The accountable manager will review all corrective action reports and ensure that the plan includes the necessary allocation of financial and human resources to ensure quality and safety standards are maintained with the implementation of the corrective actions outlined in the plan.

C - 2.3 Audit Responsibility

The Accountable manager is responsible for the overall implementation and management of the quality control audit program. The audit process will include the following:

- Establishing a self-audit plan for the surveillance of the repair station and its functions and External Vendor and contract maintenance providers.
- Using audit findings to perform root cause analysis and select corrective action solutions.
- Implementation of corrective action plans.
- Monitoring of corrective action effectiveness.
- Monitoring of unintended consequences of process change.

C - 2.3.1 Employee feedback and reporting.

Each employee is responsible for reporting to the Accountable Manager any discrepancy or nonconformance that they feel needs corrective action. Each employee is also responsible for completing assigned corrective action tasks within the time prescribed. Corrective action taken to resolve each audit finding must be focused on determining the “root cause” of the finding.

C - 2.3.2 Root Cause Analysis Process

Root Cause Analysis (RCA) is a systematic process used to determine the underlying causes of a problem in order to prevent recurrence, particularly crucial in aviation safety and operations. The process begins by clearly defining the problem, including what happened, when, where, and the impact. Following this, relevant data is gathered, such as maintenance records, incident logs, and interviews, and a timeline of events is constructed. Next, causal analysis is conducted using tools like the "5 Whys" or a Fishbone Diagram to brainstorm potential contributing factors. The aim is to differentiate between root causes and symptoms by validating findings with evidence. Once the root cause is identified, appropriate corrective actions are determined, focusing on feasible solutions that address the core issue. The implementation phase includes assigning responsibilities, setting timelines, and communicating the corrective action plan effectively. The effectiveness of the corrective actions is then monitored, and adjustments are made as needed. Finally, the RCA findings are documented in a detailed Corrective Action Report (CAR) Form IA-1004, and the

accountable manager is responsible for communicating the status of all CARs to share lessons learned across the organization and to prevent similar issues in the future. The Accountable Manager will be responsible for maintaining the CAR and ensuring that each CAR is completed on a timely basis. Follow-up audits will be performed to ensure the required corrective action has been implemented.

C - 2.4 Voluntary Disclosure Policy

Should an audit finding require immediate action that involves airworthiness, the Accountable Manager will, after assessing the impact of the finding, promptly notify the FAA as required through the appropriate website, and may notify the FAA at the local Flight Standards District Office.

Elevate MRO will participate in the FAA Voluntary Disclosure Reporting Program (VDRP) and the Aviation Safety Action Program (ASAP).

C - 2.5 Safety Responsibility

All audit findings and corrective actions directly impact the safety of operations at the repair station. The accountable manager or his/her delegates will understand their role in safety. During audits and corrective actions the individuals performing their roles will continually monitor their impact on the safety of the repair station operation.

C - 3.0 Standard Manual or Form Revision Process

If at any time the process outlined within the repair station manuals do not achieve their aims the accountable manager will revise the applicable manual or form with new policies procedures or processes that achieve the intended goals of this manual following the appropriate manual revision process below. [Ref FAR § 145.209 (e), § 145.163 (d)]

Repair station employees are encouraged to submit suggestions or errors found in the manuals by writing to the Accountable Manager. The Accountable manager is required to review all proposed changes and, if and at his/her discretion, will initiate applicable changes to the respective manuals. All revision changes will be clearly identified by the manual marking standard found in section D – 1.1.1 of this manual.

Revisions to repair station manuals will be the responsibility of the Accountable Manager. Revisions will be accomplished on a as needed basis.

This revision process is used for changes that exceed scope that pertain to temporary revisions. The Accountable Manager will initiate, review, and approve all revisions to repair station manuals, and will then coordinate with the FAA, and is responsible for submitting the revision for acceptance to the FAA, this is normally accomplished by submitting the manual revisions electronically (in a format readable by FAA computer systems to the Denver FSDO for acceptance. Additionality The appropriate Certificate Holding District Office (CHDO) be notified of each change made to the Repair Station Manual System.

The FAR's do not require FAA review and acceptance of revisions of accepted manuals before implementation (the Repair Station Training Program is an approved document and requires FAA approval prior to use)

After FAA approval/acceptance the Accountable Manager will, upload the acceptance documentation into the Shared Drive and post the manual summary of changes for all employees to sign. [REF FAR § 145.207 (d,e)] Then the Accountable Manager will upload the electronic revised manual into the Maintenance Shared Drive and update all controlled printed copies of the manual with the new revisions as listed in the manual distribution list in this manual. All repair station personnel will be trained int the method of access of physical and digital manuals issued by the repair station. Each person using the manuals is responsible for using the more current and up to date revision of that manual.

In the event the FAA finds a revision unacceptable by regulation, the manual will be revised by the accountable manager within 10 working days after receiving the notification from the FAA. The manual submitted can be used; however, the procedures in question and associated work being done in accordance with those procedures in the manual must be stopped until acceptable procedures are submitted to the FAA. The accountable manager will initiate the revision process for the unaccepted revisions, and the process listed above will be followed. [REF FAR § 145.207 (a-b), § 145.209 (j), § 145.211 (c)4] § 145.211 (d)]

C - 3.1 Temporary revisions

Temporary revisions to this Manual may be implemented without FAA notification. This includes only minor changes that do not alter fundamental processes, safety protocols, or regulatory compliance requirements. Temporary revisions are limited to:

5. Spelling and grammar corrections.
6. Nomenclature updates (e.g., changes to titles, titles, or terminology).
7. Page reorganization.
8. Updates or minor adjustments to appendices, charts, or figures.

These changes do not require immediate FAA notification, as they do not impact the operational, procedural, or regulatory integrity of this Manual. However, all temporary revisions will be documented and incorporated into the Manual during the next formal revision cycle.

Process for Temporary Revisions:

Document each temporary revision, including the reason for the change, specific pages affected, and date of revision. The Accountable Manager must review and approve each temporary revision to confirm it meets the criteria for a minor change. Maintain a record of all temporary revisions in the Manual Revision Log. Include the revision date, affected sections, and type of change. Temporary revisions will be included in the standard revision process at the next scheduled Manual update and will be subject to the FAA's review if required. Any revision that impacts operational procedures, compliance, or FAA-approved processes will not be handled as a temporary revision and will follow the standard revision and FAA notification process. [Ref FAR § 145.209 (e), § 145.163 (d)]

Temporary revision notification to FAA.

Section D Definitions and Abbreviations

D - 1.0 List of Abbreviations

A&P	FAA certificated Airframe & Powerplant Technician
AC	Advisory Circular
AD	Airworthiness Directive
Authority	A duty with responsibility granted to a person for a specific function.
CAR	Corrective Action Report
CFR	Code of Federal Regulations
CMFL	Contract Maintenance Function List
CMM	Component Maintenance Manual
Compliance	An item completely meeting the specified requirements
CRS	Certificated Repair Station
Delegate	Entrusting a person with an authority
EO	Engineering Order
FAA	Federal Aviation Administration
FAR	FAA Federal Aviation Regulation, 14 CFR, Title 14
FOD	Foreign Object Debris
FSDO	Flight Standards District Office
Includes	Contains, consists of; but not limited to
Inspector	A person with authority to review repairs, alterations, and verify aircraft and component inspects on in work aircraft and articles. All Inspectors are listed in the Roster of Inspection and Key Personnel .
LEP	List of Effective Pages
Maintenance	Inspection, repair (major or minor), alteration (major or minor), or preventive maintenance on an aircraft article or component.
Major Alteration	A design change not listed in the aircraft, engine, or propeller specifications which may appreciably affect weight, balance, structural strength, performance, powerplant operation, flight characteristics, or other qualities affecting airworthiness or is not done according to accepted practice or cannot be done by elementary operations.

Major Repair	A replacement of parts or reinforcement, when if improperly done, may appreciably affect weight, balance, structural strength, performance, powerplant operation, flight characteristics, or other qualities affecting airworthiness or is not done according to accepted practices, or cannot be done by elementary operations.
May	Not mandatory (word used in the permissive sense)
OHM	Overhaul Manual
OJT	On-the-Job Training
PMI	Principal Maintenance Inspector
PO	Purchase Order
QCM	Quality Control Manual / Quality Control Procedures and Standards
QMS	Quality Management System
Repair Station	FAA-approved facility for the purpose of performing maintenance on aircraft, powerplants, propellers, or component parts
RII	Required Inspection Item pertaining to CFR Part 121, 125, 129, or 135 operators or operators specifically advising RII requirements
RSFM	Repair station Forms Manual
RSM	Repairs station manual
QCM	Repair Station Quality Control Manual
RSTM	Repair station training Manual
STC	Supplemental Type Certificate
TC	Type Certificate
TCCA	Transport Canada Civil Aviation
Technician	A person performing maintenance such as an A&P, Repairman, Technician, or Trainee.
TPM	Training Program Manual
Trainee	Person working as a technician or repairman who holds no FAA certification in the type of work being performed.
Will (Shall)	A definite requirement and must be accomplished.
WO	Work Order