**GROUNDED **

DO NOT FLY

THIS AIRCRAFT IS GROUNDED DO NOT FLY

Keystone Aviation - MRO FAA Repair Station

CRS # K5SR339N
303 N 2370 W
Salt Lake City, UT 84116

NOTES:

Engine #1, #2, #3 engine
Inspections

DATE: 12/09/2024

WORK ORDER: 786

DO NOT REMOVE THIS TAG AUTHORIZED PERSONNEL WILL REMOVE THIS TAG FOR YOU WHEN AIRCRAFT IS APPROVED FOR RETURN TO SERVICE

REMOVED BY: OMoraC **DATE:** 12/13/24

F[illegible]: KA-11013 R2 DATE: 7/2019

KEYSTONE AVIATION

Maintenance Check List
(to be printed on red paper)

AIRCRAFT GROUNDED – TO BE REMOVED ONLY BY INSPECTOR

WO# SLC 786

Job: Engine #1, #2, #3 Borescope Inspections

Date In: 12/09/2024

Date Out: 12/13/24

Comments:

DO NOT TOW UNLESS DIRECTED BY MAINTENANCE

KA-007
Date: 8/2014

Work Order Setup Form

N#: 988NW W.O. 786 DATE IN: 12/11/24

PRELIMINARY MAINTENANCE CHECKLIST

PROJECTED DATE OUT:

		Inspector
1	Review Operations Specifications for rating approval	
2	Work scope defined with customer.	
3	Open Work Order in EBIS.	
4	Update aircraft times in EBIS/Client/Maintenance page.	
5	Perform preliminary inspection of Aircraft for condition of preserve, obvious damage, or missing components prior to maintenance. Any items entered on KA-008 form? Y ☒ N ☐	
6	Hidden damage inspection (if required), enter line item in EBIS.	
7	Prior to work being performed verify that no RII items are required per Keystone Aviation GMM chapter 5 for our 135 "10" or more aircraft.	
8	Perform an aircraft performance check as appropriate for work scope.	
9	Place aircraft in hangar or other appropriate location for defined work scope.	
10	Install "Maintenance Checklist form KA-007" on aircraft showing aircraft is grounded.	
11	Install KA-1013 "Grounded" tag on throttle.	
12	Place this check list with the work order package.	

POST MAINTENANCE CHECKLIST

		Tech & Insp	
13	All tools are accounted for.	CMO	
14	Check all switches, circuit breakers, and engine controls for proper position. Verify GEAR HANDLE DOWN. Verify flight control freedom and operation.	CMO	
15	Clean area around aircraft to be free of trash, electrical cords, air hoses, jacks, stands, and equip.	CMO	
16	Remove any protective coatings, carpet protectors, or seat covers.	CMO	
17	Clean aircraft as appropriate for work scope performed.	CMO	
18	Verify cowling rack and control table are empty of customer personal effects and aircraft documents. Remove signs.	CMO	
19	Check for completion of inspection sheets, discrepancy sheets, and EBIS entries.	CMO	
20	Verify all technicians are logged out of EBIS.	CMO	
		Inspector	
21	Aircraft final walk around performed by the Inspector.		
22	"Maintenance Checklist form KA-007" and KA-1013 removed from aircraft.		
23	Work Order is reviewed and closed		