VOLUME 6 SURVEILLANCE

CHAPTER 9 PART 145 INSPECTIONS

Section 23 Inspect a Part 145 Repair Station's Contract Maintenance Program

Source Basis:

- **Part 43, Maintenance, Preventive Maintenance, Rebuilding, and Alteration.**
- **Section 145.51(a)(3), (5), and (6), Application for Certificate.**
- **Section 145.59, Ratings.**
- **Section 145.61, Limited Ratings.**
- **Section 145.103, Housing and Facilities Requirements.**
- **Section 145.109, Equipment, Materials, and Data Requirements.**
- **Section 145.151, Personnel Requirements.**
- **Section 145.201, Privileges and Limitations of Certificate.**
- **Section 145.209, Repair Station Manual Contents.**
- **Section 145.211, Quality Control System.**
- **Section 145.213, Inspection of Maintenance, Preventive Maintenance, or Alterations.**
- **Section 145.217, Contract Maintenance.**
- **Section 145.219, Recordkeeping.**
- **Section 145.223, FAA Inspections.**

6-2103 REPORTING SYSTEM(S).

A. Safety Assurance System (SAS) Activity Recording (AR). Use activity code 3383 or 5383, as appropriate.

B. SAS. Use SAS automation and the associated Data Collection Tools (DCT).

6-2104 OBJECTIVE. This section provides guidance for inspecting a Title 14 of the Code of Federal Regulations (14 CFR) part 145 repair station's contract maintenance program (CMP).

6-2105 BACKGROUND.

A. The ability of a repair station to contract maintenance functions (only to another repair station) was originally an exception to a rigid list of equipment and material required to be located on the premises, and under the control, at an applicant or certificated repair station's (CRS) fixed location in order to obtain specified ratings. The exceptions were contained within each rating indicated in Civil Aeronautics Manual (CAM) 52 as an asterisked item. The asterisk (*) indicates that the applicant need not have equipment and material on their premises for this function provided that they contract that particular type of work to an outside agency having such equipment. That equipment and material list moved from CAM 52 to part 145 as appendix A during the recodification of the regulations in 1962.

B. The Federal Aviation Administration (FAA) expanded the repair station contract maintenance element in the 1980s by first proposing that Production Approval Holders (PAH) within their type certificate (TC) be allowed to contract maintenance to noncertificated manufacturers of their component. At this time, the PAH held a Manufacturer Maintenance Facility (MMF) under part 145 that was limited to their TC. The final 1988 rule expanded that privilege to all PAHs that held Repair Station Certificates. The FAA recognized that the responsibility of a U.S. CRS would be to ensure that the work was performed correctly.

C. During the June 21, 1999, rulemaking, the FAA proposed to expand the privilege to contract maintenance to all repair stations. A prohibition from issuing an approval for return to service only on a complete type-certificated product was included to prevent "paper only" repair stations, which would contract to broker major checks of aircraft without actually performing any maintenance tasks. The privilege to contract maintenance, up to and including the overhaul of components, but continuing to exclude completed type-certificated products, was included in the final rule. At the same time, the agency removed appendix A from part 145, which contained the asterisked (*) items.

D. Part 145, § 145.201(a)(2) permits a CRS to make arrangements with another person for the performance of maintenance, preventive maintenance, or alterations of any article for which the repair station holds a rating. Some repair stations may need to contract maintenance to an outside source because they do not have the housing, facilities, materials, or equipment on their premises and under their control for the type of maintenance. Other repair stations may need to contract maintenance to an outside source due to workloads, urgent situations, equipment malfunctioning, short-term business needs, customer requirements, or other unique situations. The intent of the FAA approving maintenance functions is to identify the capability of the repair station to make airworthiness determinations on the work performed by others under its control by contract. Contract maintenance functions that require FAA approval under § 145.217(a) are required only when the repair station extends its privileges to the contractor and the repair station assumes responsibility for the contractor's work by providing approval for the return to service. Maintenance function approval under § 145.217 must be current throughout the lifecycle of the repair station and in an acceptable format, such as listing the maintenance function in block 4 of FAA Form 8310-3, Application for Repair Station Certificate and/or Rating.

6-2106 PREREQUISITES AND COORDINATION REQUIREMENTS.

A. Prerequisites:

- Knowledge of the regulatory requirements of part 145.
- Knowledge of the Repair Station Manual (RSM) and Quality Control Manual (QCM).
- Completion of FAA Course 21058, Certification and Surveillance of Part 145 Repair Stations.
- On-the-job training (OJT) tasks as determined by management.
- SAS baseline training.

B. Coordination. This task may require coordination with other specialties, FAA offices, and the CRS. Aviation safety inspectors (ASI) should consider coordinated surveillance with other Flight Standards Service (FS) offices when appropriate.

6-2107 REFERENCES, FORMS, AND JOB AIDS.

A. References (current editions):

- Volume 1, Chapter 3, Section 1, Responsibilities of Aviation Safety Inspectors.
- Volume 10, Safety Assurance System Policy and Procedures.
- Volume 14, Chapter 1, Section 2, Flight Standards Service Compliance Action Decision Procedure.
- Advisory Circular (AC) 145-9, Guide for Developing and Evaluating Repair Station and Quality Control Manuals.

B. Forms. FAA Form 8310-3, Application for Repair Station Certificate and/or Rating.

C. Job Aids. None.

6-2108 GENERAL.

A. Reasons for Inspection. The ASI should conduct this inspection because of:

- Requests from a repair station to contract maintenance functions,
- SAS risk-based Comprehensive Assessment Plan (CAP),
- Previous surveillance efforts or followup actions,
- Allegations of improper maintenance, or
- Component failure trends or investigations.

B. Policy Review. The ASI should review the regulations and applicable FAA policy prior to approving contract maintenance functions. This includes special emphasis on the repair station's ability to maintain and revise the contract maintenance information under § 145.209(h), and their ability to qualify and surveil noncertificated persons performing maintenance or alterations for the repair station under § 145.211(c)(1)(vi).

6-2109 PART 145 REQUIREMENTS. The privileges in § 145.201(a)(2) allow a repair station to arrange for another person to perform maintenance, preventive maintenance, or alterations of any article for which the CRS is rated and within the limitations of its operations specifications (OpSpecs). The evaluation of what a CRS may contract starts with an understanding of the applicant's capabilities. When a person makes a repair station application, they must provide the maintenance functions they will contract, as well as a description of the housing, facilities, equipment, and materials that will be at the fixed location and under their control. In order for the repair station to contract a maintenance function, the repair station must meet the following regulations:

A. Section 145.51(a)(6)—Application for Certificate. Section 145.51(a)(6) requires an applicant for a Repair Station Certificate and rating to provide the agency with a list of the functions it will be contracting for approval. When the FAA has a form for a specific purpose, the "format acceptable to the FAA" is that form or the information required by the form. The maintenance functions should be listed in block 4 of FAA Form 8310-3 or in any other acceptable format with the relevant information.

B. Section 145.109(a)—Equipment, Materials, and Data Requirements. A repair station must have the necessary equipment, tools, and material appropriate for the maintenance or alterations under the repair station's certificate and OpSpecs. However, it does not need to have the tools, equipment, or material for the scope of work it is authorized to contract out pursuant to its FAA-approved maintenance functions. The exception to the rule "as otherwise prescribed by the FAA" allows the repair station to satisfy § 145.109(a) by way of approved maintenance functions under § 145.217. It is the repair station's responsibility to ensure the maintenance function contractor has the necessary equipment, tools, and material for the work performed.

C. Section 145.151—Personnel Requirements. Section 145.151 requires the repair station to ensure it has enough qualified personnel to plan, supervise, perform, and approve for return to service the work performed under its ratings and OpSpecs. This includes the knowledge and experience when conducting the test and/or inspection of the work performed by contractors to ensure the airworthiness of the article involved.

D. Section 145.157—Personnel Authorized to Approve an Article for Return to Service. Repair station personnel that approve for return to service an article under a contracted maintenance function must be proficient in the use of the various inspection methods, techniques, practices, aids, equipment, and tools that are appropriate to ensure the airworthiness of the article involved.

E. Section 145.209(h)—Repair Station Manual (RSM) Contents. Section 145.209(h) requires the CRS to have procedures for:

1) Maintaining and revising the contract maintenance function information required by § 145.217(a)(2)(i), including submitting revisions to the responsible Flight Standards office for approval. This is the actual maintenance function that is approved by the FAA, and any revision to add or remove maintenance function(s).

NOTE: Maintenance functions could be a single step, such as plating a part, or could be a series of steps, up to and including the overhaul of a component.

2) Maintaining and revising the contract maintenance information required by § 145.217(a)(2)(ii) and notifying the responsible Flight Standards office of revisions to this information. This is the listing of names and any applicable ratings held by each outside facility. This list must be made available to the FAA. The RSM must contain procedures on how the list is maintained and revised, including how often the repair station notifies the responsible Flight Standards office of revisions to this information. The repair station will determine who performs

the contract maintenance functions. FAA approval of the list of names of each outside facility required by § 145.217(a)(2)(ii) is not required.

F. Section 145.211(c)(1)(vi)—Quality Control (QC) System. The repair station must have a system and procedures for qualifying and surveilling noncertificated persons who perform maintenance, preventive maintenance, or alterations under a contract maintenance function. When the repair station decides to use noncertificated persons, it must qualify and oversee them to the extent necessary to determine if the work can be performed properly. The procedures required by § 145.217 ensure that the work is verified by test and/or inspection to make airworthiness determinations.

G. Section 145.213—Inspection of Maintenance, Preventive Maintenance, or Alterations. The repair station must conduct a final inspection of any work performed before the work is approved for return to service. This would include any work performed by a maintenance function contractor.

H. Section 145.215—Capability List (CL). The repair station may add articles to the CL if they hold the appropriate limited rating and complete the self-evaluation in accordance with their procedures. If articles are contracted to an outside source, the self-evaluation needs to account for maintenance function(s) performed by contractors before the article is added.

I. Section 145.217—Contract Maintenance. Section 145.217 requires the maintenance functions to be approved by the FAA and for the repair station to keep a list of the maintenance function contractors it uses to accomplish those functions. It also requires the CRS to remain directly in charge of noncertificated persons, and to verify by test and/or inspection all work performed by a noncertificated person was satisfactory before approving the work for return to service. Section 145.217 also contains the prohibition against providing "only approval for return to service of a complete type-certificated product" after a contractor has performed work, thereby prohibiting "paper only" repair stations. For example, contracting out a complete engine overhaul and providing only approval for return to service would not be approved by the FAA because the engine is a complete type-certificated product. Contracting out the complete overhaul of an engine starter could be approved by the FAA because the starter does not have its own TC.

NOTE: If the repair station cannot demonstrate that the noncertificated person follows an equivalent QC system for the work performed, or if the repair station does not have the capability or knowledge to verify by test and/or inspection that the work has been performed satisfactorily by the noncertificated person, the maintenance function may not be approved by the FAA. The repair station should evaluate the complexity of work performed by the noncertificated person and the requirements needed for the facilities, data, materials, equipment, tools, and personnel. The repair station could verify the quality of the work by the use of an independent accredited testing facility to assist the repair station during their qualification of prospective noncertificated persons (e.g., a third-party examination of a test coupon after a nitriding process). This type of verification is directed by the repair station.

J. Section 145.219—Recordkeeping. Section 145.219 requires the CRS to keep records that comply with 14 CFR part 43, specifically that would include part 43, §§ 43.9 and 43.11. Section 43.9(a)(3) requires the names of all persons performing maintenance, preventive maintenance, or alterations if other than the person (repair station) approving the work for return to service. This requirement means the names of the maintenance function contractors would need to be in the repair station's maintenance records.

K. Section 145.223—FAA Inspections.

1) A CRS may not contract the performance of a maintenance function on an article with a noncertificated person unless it provides in its contract with the noncertificated person that the FAA may make an inspection and observe the performance of the noncertificated person's work on the article.

2) Additionally, a CRS may not approve for return to service any article on which a maintenance function was performed by a noncertificated person if the noncertificated person does not permit the FAA to make the inspection.

6-2110 EXERCISING THE PRIVILEGES OF CONTRACT MAINTENANCE.

A. Privileges and Limitations of Certificate. The privileges in § 145.201(a)(2) are exercised when a repair station assumes the responsibility for the work performed by the maintenance function contractor. The repair station must:

1) Be certificated and appropriately rated for the article to be contracted out;

2) Obtain FAA approval of the maintenance functions in accordance with § 145.217; and

3) Take regulatory responsibility by issuing an approval for return to service under § 43.9 for the work performed by the maintenance function contractor.

B. Contracting Maintenance to Noncertificated Persons.

1) A CRS must ensure the work performed by a noncertificated person meets an equivalent QC system in accordance with §§ 145.201(a)(2) and 145.217(b)(1). When the CRS qualifies and conducts surveillance of a noncertificated person to establish an equivalent QC system, establishing equivalency of the noncertificated person may vary based on the type of work performed and their capability. Such standards (e.g., International Organization for Standardization (ISO) 9001 or Aerospace Standard (AS) 9100 series, National Aerospace and Defense Contractors Accreditation Program (Nadcap), 14 CFR part 21 PAH's QC system, or foreign part 145 CRS), may offer the repair station some assurance in determining an equivalent QC system and capability.

NOTE: Part 145 uses the term "noncertificated person" throughout multiple subchapters. The privileges and limitations of a repair station in § 145.201(a)(2) establish that noncertificated persons are persons not certificated under part 145.

2) A CRS may contract a maintenance function pertaining to an article to a noncertificated person, provided that:

a) The repair station remains directly in charge of the work performed by the noncertificated person in accordance with § 145.217(b)(2). A person directly in charge does not need to physically observe and direct each worker constantly, but they must be available for consultation on matters requiring instructions or decisions from a higher authority.

b) The CRS verifies by test and/or inspection that the work has been performed satisfactorily by the noncertificated person and that the article is airworthy before approving it for return to service in accordance with § 145.217(b)(3).

C. Contracting Maintenance to FAA CRSs. Some maintenance functions will need FAA approval even when they are performed by another CRS. If the originating repair station is taking regulatory responsibility by issuing an approval for return to service for the maintenance function performed by the contracted repair station, FAA approval is required. The regulations in § 145.217(b) that are applicable to noncertificated persons would not apply in these situations due to the fact that the contracted facility holds a part 145 certificate and has demonstrated to the FAA that they hold a QC system acceptable to the Administrator.

1) If the originating repair station chooses to exercise the privileges of its certificate by issuing an approval for return to service for a maintenance function contracted to another FAA CRS, the originating repair station must meet § 145.217(a) requirements, and must determine that the contracted repair station is properly rated to perform the maintenance.

2) The originating repair station may issue an additional approval for return to service under its privileges, such as tagging a previously maintained or altered article as inspected and/or tested, provided that the originating repair station:

a) Has the appropriate rating for the article; and

b) Conducts additional maintenance, preventive maintenance, or alteration, including inspections in accordance with § 43.13 and part 145.

3) If the original repair station requests maintenance to be performed by another FAA-certified repair station that holds the proper ratings and the maintenance performed was approved for return to service under § 43.9 by the contracted repair station, this is a contractual arrangement only and would not need FAA approval under § 145.217. The originating repair station would not be exercising its privileges for the work performed.

4) When exercising the privileges of their certificate under § 145.201(a)(2), the originating repair station is always responsible for performing a final inspection and certifying that the article is airworthy in accordance with § 145.213.

NOTE: Under § 43.17(c)(2), Approved Maintenance Organizations (AMO) holding appropriate ratings may, with respect to a U.S.-registered aircraft or other U.S. aeronautical products located in Canada, provide approval for return to

service. These AMOs are recognized as equivalent to FAA CRSs under the Maintenance Implementation Procedures (MIP).

D. RSM and QCM Requirements. The RSM must contain procedures for maintaining and revising the contract maintenance information required by § 145.217. AC 145-9 describes an acceptable means to develop manuals for compliance with contract maintenance regulations.

1) The RSM must contain the following procedures for obtaining FAA approval of the maintenance function to be contracted to outside facilities in accordance with § 145.209(h).

a) Procedures for maintaining and revising the maintenance functions required by § 145.217(a)(2)(i), including procedures for submitting revisions to the responsible Flight Standards office for approval.

NOTE: The list of maintenance functions under § 145.217(a)(2)(i) is the only information requiring FAA approval.

b) Procedures for maintaining and revising the contract maintenance information required by § 145.217(a)(2)(ii). The contracting information required by § 145.217(a)(2)(ii) must be maintained by the repair station and made available to the FAA. Section 145.209(h)(2) requires procedures for notifying the responsible Flight Standards office of revisions to this information, including how often the responsible Flight Standards office will be notified of revisions. FAA approval of the list of names of each contracted source required by § 145.217(a)(2)(ii) is not required. The information required to be maintained by the repair station must identify:

1. The name of each outside contracted source.

2. The type of certificate and ratings, if any, held by each source.

3. The actual maintenance function each source is conducting.

NOTE: Procedures should include the title of the person responsible for maintaining the CMP.

2) The QCM must describe the system and procedures used for qualifying and surveilling noncertificated persons (not certificated under part 145) to which it contracts those maintenance functions in accordance with § 145.211(c)(1)(vi).

a) The description and procedures required under the pertinent subparagraphs of § 145.211(c)(1) must include procedures to perform the incoming inspection, final inspection, and approval for return to service of the contracted articles.

b) There must be procedures in the manual to describe how the noncertificated person is initially qualified. It also should describe how the repair station ensures that the noncertificated person continues to follow a QC system equivalent to the repair station's QC system for the work performed under approved maintenance functions.

NOTE: The repair station cannot give a copy of its QCM to the noncertificated person and assume they will follow proper procedures. The repair station must conduct adequate audits to ensure equivalent QC procedures are established and followed. The repair station will determine the method of the audit (e.g., onsite, administrative, or virtual remote technology) based off of the complexity of work performed by the contractor.

c) Procedures should exist to ensure that specific repair instructions are communicated to the contractor.

d) If desired, procedures could include the method by which a maintenance function is added to the FAA-approved list on an emergency basis, but this procedure would not be required by regulation.

e) Procedures for coordinating communications between the repair station and the contracted source should be established. If the repair station performs any maintenance for an air carrier, the procedures should explain any special requirements (such as performing the work in accordance with the air carrier's programs or requirements). Procedures should describe how the repair station would address any problems with quality or delivery from the contractor.

NOTE: Contracting maintenance functions should not replace the requirements in meeting § 145.151 for adequately staffed and trained maintenance personnel. ASIs should pay attention to the repair stations that constantly apply to revise maintenance function lists to complete work. The ASIs should verify the repair station has the necessary trained personnel for the scope and complexity of the rating(s) they hold.

E. Contract Maintenance Function Approval. The maintenance function(s) should be listed in block 4 of FAA Form 8310-3, or the request may be received in any other acceptable format containing the required information.

1) The repair station must be appropriately rated, must have personnel with the knowledge and skills to inspect the contracted maintenance, and must have proper RSM/QCM procedures for maintenance function approval by the FAA.

2) The ASI must complete a SAS standard method configuration change request following the guidance in Volume 10, Chapter 2, Section 1 for items that change the CRS operating profile. SAS Vitals Information contains checkboxes for contract maintenance function approval, which requires the ASI to complete a SAS standard method configuration change request to evaluate the change.

NOTE: If the repair station had prior acceptance of procedures for contracting a maintenance function and is only requesting to add additional functions, updating SAS Vitals Information will create a configuration change to document the approval.

3) The ASI affirms approval of the maintenance function by completing FAA Form 8310-3, if applicable, and notifying the repair station by official means with a transmittal

document. The transmittal document may be in the form of an email, fax, cover letter, stamp of approval, or any other official media used by the FAA.

a) Provide a transmittal document to the repair station, indicating the date of FAA approval, office identification, description of maintenance function(s), and the name of the inspector approving the maintenance function(s).

b) A copy of the approved maintenance function transmittal document, along with the completed FAA Form 8310-3, should be placed in the CRS's office file.

4) If the maintenance function contracting requirements are not met, notify the repair station of the non-approval by initiating a transmittal document indicating the discrepancies or reason for not approving the contracted maintenance function(s).

F. Specialized Services Rating. Under a limited specialized service rating, any functions, tasks, or elements of independently developed process specifications that were approved by the FAA should not be contracted out under § 145.217. This is due to the fact that FAA approval is limited for use by that specific and authorized repair station. For additional information on specialized services, see Volume 2, Chapter 11, Section 6.

G. Recordkeeping. A CRS must retain records in English that demonstrate compliance with the requirements of part 43. Additionally, § 43.9(a)(3) requires the names of all persons performing maintenance, preventive maintenance, or alterations if other than the person (repair station) approving the work for return to service. This includes the names of the contract maintenance function providers to be included in the maintenance records for the work performed.

Figure 6-89. Maintenance Function Approval Matrix

NOTE: This matrix is used to assist the ASI in determining when FAA approval of a maintenance function is needed under § 145.217.

Contracted Maintenance is Performed By	FAA Approval Required?
Noncertificated Persons	YES, this is a maintenance function
CRS conducts the maintenance function, but does not provide approval for return to service under § 43.9	YES, this is a maintenance function
CRS conducts the maintenance function and does provide approval for return to service under § 43.9	NO, this is only a contractual arrangement

6-2111 PURCHASING ARTICLES, COMPONENTS, AND PARTS FROM FAA REPAIR STATIONS. When a repair station purchases maintained parts that have documentation meeting § 43.9 approval from another repair station (including exchanges and brokerages) and/or uses another CRS to perform work that is outside the original repair station's ratings, these activities are not considered to be contract maintenance functions for the purpose

of requiring FAA approval. In these instances, the purchasing repair station is not exercising the privileges of its certificate because they did not provide approval for return to service. When the originating repair station requests work or sells a previously maintained article (including type-certificated products), it is acting solely as a distributor. Although the originating repair station may induct the part through its receiving inspection process, it is merely relying on the work previously performed and approved for return to service at another CRS, and the originating repair station is not exercising the privileges of their certificate under § 145.201(a)(2).

6-2112 FACILITY INSPECTION PROCEDURES.

A. Review Applicable Information. Before inspecting the repair station, the ASI should carefully review the following:

1) Parts 43 and 145.

2) OpSpecs.

3) RSM/QCM and FAA-approved training program procedures.

4) SAS information associated with the repair station.

5) FS office files.

B. Conduct an In-Briefing. Brief the CRS on the purpose of the inspection. The in-brief may take place at the beginning of the inspection or at the beginning of each day. Detailed instructions for conducting the briefing are in Volume 1, Chapter 3, Section 1.

C. Review Maintenance Function Records. Review a representative sample of the maintenance records to verify the repair station is following their contracting maintenance procedures. Inspect for the following:

1) Only FAA-approved maintenance functions are being accomplished.

2) Contractor maintenance information required by § 145.217(a)(2)(ii) is available and maintained to document the name of each contracted source, the type of certificate, and ratings, if any, held by each facility.

NOTE: Only the contractors listed in the maintenance information under § 145.217(a)(2)(ii) are performing the approved maintenance function(s).

3) All articles are returned to the repair station through a receiving inspection and undergo a final inspection using the procedures in the QCM. The contractor should return all required records with the article.

4) The repair station's receiving inspection personnel for articles shipped to a certificated contractor should meet the requirements of § 145.155.

5) In addition to the above tasks, if the repair station contracts to a noncertificated person, sample the following:

a) The repair station's receiving inspection personnel for articles shipped to a noncertificated contractor should meet the requirements of §§ 145.155 and 145.157.

b) The repair station verifies, by test and/or inspection, that the work has been performed satisfactorily by the noncertificated person and that the article is airworthy before approving it for return to service in accordance with § 145.217(b)(3).

c) The repair station remains directly in charge of the work performed by the noncertificated person in accordance with § 145.217(b)(2). The noncertificated contractor should have completed the work as instructed.

d) The repair station should be able to demonstrate that the noncertificated persons followed a QC system equivalent to the system used by the repair station in accordance with §§ 145.201(a)(2) and 145.217(b)(1). The repair station's personnel making the determination should have experience and/or training in auditing outsourced maintenance providers and be familiar with the maintenance performed.

e) The repair station must have provisions for the FAA to inspect and observe the noncertificated facility for the work performed.

NOTE: The FAA may request to conduct an onsite inspection of the noncertificated person's facility for the maintenance performed. This inspection should be arranged through the CRS. The noncertificated person's facility should be sampled for an equivalent QC system in regard to the maintenance performed. Inspect for QC standards involving housing, tools, equipment, personnel, capability, and appropriate technical data. Any identified items should be communicated to the CRS for corrective action.

f) Use SAS AR code "3383/5383" to document onsite inspections of the noncertificated person's facilities.

6) Ensure that the CRS does not provide only approval for return to service of complete, assembled, type-certificated products following contract maintenance, preventive maintenance, or alterations in accordance with § 145.217(c).

6-2113 TASK OUTCOMES.

A. Conduct Debriefing. Brief the certificate holder (CH) on the results. Discuss all deficiencies, CH corrective actions, and FAA actions. The ASI can find instructions for conducting briefings in Volume 1, Chapter 3, Section 1.

B. Compliance and Enforcement Action. If safety issues and/or regulatory noncompliance are identified, follow the process contained in Volume 14, Chapter 1, Section 2 to determine the appropriate FAA compliance or enforcement action.

C. Complete the Task. Follow Volume 10 guidance for completion of SAS AR or the DCT.

6-2114 FUTURE ACTIVITIES. Follow Volume 10 to plan future risk-based surveillance in SAS.

RESERVED. Paragraphs 6-2115 through 6-2124.