

```

1. #include <stdio.h>
2. #include <math.h>
3.
4. int calculate(int a, int b);
5.
6. int main()
7. {
8. int x = 10      // ERROR: Missing semicolon (;)
                  // CORRECTION: int x = 10;
9. int y = 20;
10.
11. printf("Program Started\n");
12.
13. if(x = 10)     // ERROR: Assignment (=) used instead of comparison (==)
                  // CORRECTION: if(x == 10)
14. {
15. printf("X is 10\n");
16. }
17.
18. int marks = "Ninety"; // ERROR: String assigned to int variable
                          // CORRECTION: int marks = 90;
                          // OR: char marks[] = "Ninety";
19.
20. printf("%d\n", z); // ERROR: Variable z not declared
                          // CORRECTION: int z = 0;
21.
22. 100 = x;         // ERROR: Cannot assign value to a constant
                          // CORRECTION: x = 100;
23.
24. int arr[5];
25.
26. arr[10] = 50;    // ERROR: Array index out of bounds
                          // CORRECTION: arr[4] = 50;
27.
28. float *ptr = &x; // ERROR: Type mismatch (int address to float pointer)
                          // CORRECTION: int *ptr = &x;
29.
30. printf("%f\n", x); // ERROR: %f used for int variable
                          // CORRECTION: printf("%d\n", x);
31.
32. int a = 10;

```

```

33. int b = 0;
34.
35. printf("%d\n", a/b); // ERROR: Division by zero
    // CORRECTION: Ensure b != 0 before division
36.
37. char ch = 'AB'; // ERROR: Multi-character constant assigned to char
    // CORRECTION: char ch = 'A';
38.
39. if(x > y)
40. printf("X is greater");
41. else
42. printf("X is greater"); // ERROR: Same message in both branches
    // CORRECTION: printf("Y is greater");
43.
44. sqrt(25); // WARNING: Return value ignored
    // CORRECTION: double r = sqrt(25);
45.
46. show(); // ERROR: Function not declared/defined
    // CORRECTION: Define show() or remove call
47.
48. while(x < 15); // ERROR: Extra semicolon creates empty loop
    // CORRECTION: while(x < 15)
49. {
50.     x++;
51. }
52.
53. continue; // ERROR: continue outside loop
    // CORRECTION: Place inside a loop or remove
54.
55. break; // ERROR: break outside loop/switch
    // CORRECTION: Place inside loop/switch or remove
56.
57. int result = calculate(10); // ERROR: One argument passed instead of two
    // CORRECTION: calculate(10, 20);
58.
59. printf("%d\n", result);
60.
61. printf("Program Ended\n");
62.
63. return 0;
64. }

```

65.

66. `int calculate(int a, int b)`

67. `{`

68. `return a + b;`

69. `}`