HTML Tags Reference

Classic HTML Tags

<code>

Displays inline code in a monospace font.

Example: <code>console.log('Hello')</code>

<pre>

Displays preformatted text. Preserves spacing, tabs, and newlines.

Often used with <code>.

Example:

<pre><code>function test() {

  return true;

}</code></pre>

<kbd>

Represents keyboard input.

Example: <kbd>Ctrl</kbd> + <kbd>C</kbd>

<mark>

Highlights text with a background (usually yellow).

Example: <mark>Important</mark>

<time>

Represents a specific date or time. Useful for machine-readable timestamps.

Example: <time datetime='2025-04-20'>April 20, 2025</time>

HTML Tags Reference

New HTML5 Tags

<article>

Represents a self-contained piece of content, like a blog post or article.

<section>

Defines a section in a document. Useful for dividing content into logical blocks.

<nav>

Defines navigation links.

<aside>

Represents content that's tangentially related to the main content (like a sidebar).

<figure>

Used for images, diagrams, etc., often with a caption.

<figcaption>

Provides a caption for a <figure>.

<main>

Specifies the main content of a document.

<header>

HTML Tags Reference

Represents introductory content or a navigational group.

<footer>

Defines a footer for a section or page.

<details>

Creates a widget that the user can open and close (expand/collapse).

<summary>

Provides a summary or label for the <details> element.