

Basic Router Configuration

- These presentations are the result of a collaboration among the instructors at St. Clair College in Windsor, Ontario.
- Thanks must go out to Rick Graziani of Cabrillo College. His material and additional information was used as a reference in their creation.

Configuring and Testing Your Network

Configuring Cisco Devices: IOS Basics




```
version 12.2
!
hostname Router
!
!interface FastEthernet0/0
no ip address
duplex auto
speed auto
shutdown
!
interface Serial0/0
no ip address
shutdown
!
interface Serial0/1
no ip address
shutdown
```

Cisco IOS




- As with a computer, a router or switch cannot function without an operating system.
- Cisco calls its operating system the **Cisco Internetwork Operating System** or **Cisco IOS**.
- The Cisco IOS provides the following network services:
 - Basic routing and switching functions
 - Reliable and secure access to networked resources
 - Network scalability

Cisco IOS




- The Cisco IOS is accessed using the Command Line Interface (CLI).
- Features will vary based on the version of the IOS and the type of device.

Access Methods




Router Components

- The main internal components of a router are:
 - Random Access Memory (RAM)
 - Nonvolatile Random Access Memory (NVRAM)
 - Flash Memory (Flash)
 - Read Only Memory (ROM)
 - Console
 - Interfaces




Router Components

- Random Access Memory (RAM):
 - Stores routing tables
 - Holds ARP cache
 - Holds fast-switching cache
 - Performs packet buffering as shared RAM
 - Maintains packet-hold queues
 - Provides temporary memory for the configuration file of a router while the router is powered on
 - Loses content when a router is powered down or restarted




Router Components

- Nonvolatile Random Access Memory (**NVRAM**):
 - Provides storage for the startup configuration file
 - Retains content when a router is powered down or restarted




Router Components

- Flash Memory (**Flash**):
 - Holds the IOS image
 - Allows software to be updated without removing and replacing chips on the processor
 - Retains content when a router is powered down or restarted
 - Can store multiple versions of IOS software



Router Components


- Read Only Memory (ROM):
 - Maintains instructions for power-on self test (POST) diagnostics
 - Stores the bootstrap program and the basic operating system software



Router Components

- **Console:**


- The console port provides physical access for the initial configuration of the router or configuration changes.



- **Interfaces:**

- Connect routers to a network for packet entry and exit
- They can be on the motherboard or on a separate module

Configuration Files



- Network devices depend upon two types of software:
 - Operating system (IOS)
 - Configuration file

Cisco IOS Modes

```
Router>ping 192.168.10.5
```

User EXEC

```
Router#show running-config
```

Privileged EXEC

```
Router(config)#Interface FastEthernet 0/0
```

Global Configuration

```
Router(config-if)#ip address 192.168.10.1 255.255.255.0
```

Interface Configuration

The prompt changes to denote the current CLI mode.


```
Switch>ping 192.168.10.9
```

```
Switch#show running-config
```

```
Switch(config)#Interface FastEthernet 0/1
```


```
Switch(config-if)#Description connection to WEST LAN4
```

Moving Between User and Privileged EXEC



- Use *enable* to move from User to Privileged EXEC.
- Use *disable* or *end* to move back.

Basic IOS Command Structure



Router(config)#hostname MyRouter
MyRouter(config)#

Router(config)#interface fastethernet 0/0
Router(config-if)#

Router(config-if)# ip address 192.168.100.1 255.255.255.0
Router(config-if)#

Using CLI Help

Context Sensitive Help

Example of a sequence of commands using the CLI context sensitive help

```
Cisco#cl?  
clear clock  
Cisco#clock ?  
    set Set the time and date  
Cisco#clock set  
% Incomplete command.  
Cisco#clock set ?  
    hh:mm:ss Current Time  
Cisco#clock set 19:50:00  
% Incomplete command.
```

Command explanations

Incomplete command messages

Invalid input messages

Variable formats

```
Cisco#clock set 19:50:00 ?  
    <1-31> Day of the month  
    MONTH Month of the year  
Cisco#clock set 19:50:00 25 6  
                                ^  
Invalid input detected at '^' marker.  
Cisco#clock set 19:50:00 25 June  
% Incomplete command.  
Cisco#clock set 19:50:00 25 June ?  
    <1993-2035> Year  
Cisco#clock set 19:50:00 25 June 2007  
Cisco#
```

Using CLI Help

Command Syntax Check Help

The IOS returns a help message indicating that required keywords or arguments were left off the end of the command:

```
Switch#>clock set
% Incomplete command.
Switch#clock set 19:50:00
% Incomplete command.
```

The IOS returns a help message to indicate that there were not enough characters entered for the command interpreter to recognize the command.

```
Switch#c
% Ambiguous command: 'c'
```

The IOS returns a "^" to indicate where the command interpreter can not decipher the command:

```
Switch#clock set 19:50:00 25 6
                        ^
% Invalid input detected at '^' marker.
```

Using CLI Help

- Hot Keys and Shortcuts:
 - CLI Line Editing:
 - Several outlined in the text.
 - **Backspace** most often used.
 - Note that the **Delete** key is **NOT** recognized to delete invalid characters.

Using CLI Help

- Hot Keys and Shortcuts:
 - At the ----More---- Prompt:
 - If the screen fills up with a display, the More prompt will be displayed.

At the "-----More-----" prompt


The Enter Key	Displays the next line.
Space Bar	Displays the next screen.
Any other alphanumeric key	Returns to the EXEC prompt.

Using CLI Help

- **Break Keys:**
 - If you wish to abort a process or command.....

Break Keys	
Ctrl-C	When in any configuration mode, ends the configuration mode and returns to privileged EXEC mode. When in setup mode, aborts back to the command prompt.
Ctrl-Z	When in any configuration mode, ends the configuration mode and returns to privileged EXEC mode.
Ctrl-Shift-6	All-purpose break sequence. Use to abort DNS lookups, traceroutes, pings.

IOS Examination Commands



- In order to verify and troubleshoot network operation, we must examine the operation of the devices.
- The basic examination command is the **show** command.

IOS Examination Commands – show version

```
Router
Cisco#show version

Cisco Internetwork Operating System Software
IOS (tm) C2600 Software (C2600-JK8S-M), Version
12.2(12c), RELEASE SOFTWARE (fc1)
Copyright (c) 1986-2003 by cisco Systems, Inc.
Compiled Wed 05-Feb-03 16:36 by kellythw
Image text-base: 0x8000808C, data-base: 0x8156F2AC

ROM: System Bootstrap, Version 11.3(2)XA4, RELEASE
SOFTWARE (fc1)
R2 uptime is 4 weeks, 2 days, 17 hours, 9 minutes
System returned to ROM by reload
System image file is "flash:c2600-jk8s-mz.122-12c.bin"

cisco 2620 (MPC860) processor (revision 0x102) with
59392K/6144K bytes of memory

----- output omitted -----

Basic Rate ISDN software, Version 1.1.
1 FastEthernet/IEEE 802.3 interface(s)
2 Low-speed serial(sync/async) network interface(s)
1 ISDN Basic Rate interface(s)
32K bytes of non-volatile configuration memory.

16384K bytes of processor board System flash
(Read/Write)

Configuration register is 0x2102
```

IOS Version,
Name

RAM

INTERFACES

FLASH


Configuration
Register

IOS Examination Commands – show flash

```
Router
BHM#show flash
PCMCIA flash directory:
File Length Name/status
1 6007232 c1700-bnsy-1.212-11.p
[6007296 bytes used, 284160 available, 6291456
total]
6144K bytes of processor board PCMCIA flash (Read
ONLY)
BHM#
```


- Use the *show flash* command to verify that the router has sufficient memory to load a new Cisco IOS software image.

IOS Configuration Modes



Configuring and Testing Your Network


Applying a Basic Configuration



Naming Devices


- Importance of a Device Name:
 - Default “Router” or “Switch”
 - Host Name appears as the CLI prompt.
 - Confirmation that the correct device has been accessed.
 - Naming convention makes maintenance easier.
 - Start with a letter
 - No spaces
 - End with letter or digit
 - Only letters, digits and dashes
 - Maximum of 63 characters

Naming Devices



```
Router>  
Router>enable  
Router#  
Router#configure terminal  
Router(config)#  
Router(config)#hostname AtlantaHQ  
AtlantaHQ(config)#
```


Naming Devices



```
Switch>  
Switch>enable  
Switch#  
Switch#configure terminal  
Switch(config)#  
Switch(config)#hostname Flour_Bluff  
Flour_Bluff(config)#
```

Limiting Device Access

- **Configuring Passwords:**

- Passwords are the primary defense against unauthorized access to network devices.

Every device should have locally configured passwords to limit access.

- **Console password:**

- Limits device access using the console connection

- **Enable password:**

- Limits access to the privileged EXEC mode

- **Enable secret password:**

- Encrypted, limits access to the privileged EXEC mode

- **VTY password:** Limits device access using Telnet / SSH

Limiting Device Access

Console Password

```
Router(config)#line console 0  
Router(config-line)#login  
Router(config-line)#password cisco
```



Virtual Terminal Password

```
Router(config)#line vty 0 4  
Router(config-line)#login  
Router(config-line)#password cisco
```



Enable Password

```
Router(config)#enable password san-fran
```



Enable Password

```
Router(config)#enable secret <password>
```



Limiting Device Access

- Encrypting Password Display:
 - The *service password-encryption* command prevents ALL passwords from showing up as plain text when viewing the configuration files.


Perform Password Encryption

```
Router(config)#service password-encryption  
(set passwords here)  
Router(config)#no service password-encryption
```

service password-encryption uses a Cisco Level 7 encryption which is very easy to decrypt.

Limiting Device Access

- Login Banner:




Managing Configuration Files

running-config
(IOS running)

startup-config

IOS

Boot Program



Managing Configuration Files

```
Router#show startup-config  
%% Non-volatile configuration memory is not present
```

```
Router#show running-config  
Building configuration...
```

```
Current configuration:  
!  
version 12.0  
service timestamps debug uptime  
service timestamps log uptime  
no service password-encryption  
!  
hostname Router  
!  
ip subnet-zero  
!  
!  
interface Ethernet0  
  no ip address  
  no ip directed-broadcast  
  shutdown  
!  
interface Serial0  
  no ip address  
  no ip directed-broadcast  
  shutdown
```


No startup-config
file in NVRAM

Default running-config
file, created in RAM

Managing Configuration Files

running-config
resides here

startup-config
resides here




At boot up, running-config is *replaced* by startup-config....

Managing Configuration Files

running-config
resides here

**If the router loses power or
reboots, everything in RAM is lost
*including the running-config file.***




**Changes to the router are automatically put in
the running-config file.**

Managing Configuration Files

running-config
resides here

startup-config
resides here



To make sure that router changes are saved...
copy running-config startup-config

Managing Configuration Files

```
Router#copy running-config startup-config
Destination filename [startup-config]?
Building configuration...
```

```
Router#show startup-config
```

```
!
version 12.0
service timestamps debug uptime
service timestamps log uptime
no service password-encryption
!
hostname Router
!
!
ip subnet-zero
!
interface Ethernet0
  no ip address
  no ip directed-broadcast
  shutdown
!
```

The startup-config file is now identical to running-config and the router will have these changes if the router reboots.

Managing Configuration Files

```
Router# copy running-config startup-config
```

OR

```
Router# copy running startup
```

OR

```
Router# copy run start
```

*Any usage of the command or parameters,
so that they are
still uniquely recognizable.*

Managing Configuration Files

- Returning the Device to its Original Configuration:
 - **reload** command
 - Works **ONLY IF** the running configuration has **NOT** been copied to the startup configuration.

```
Router# reload
```

```
System configuration has been modified. Save?  
[yes/no]: n
```

```
Proceed with reload? [confirm] Press Enter
```

```
*Apr 13 01:34:15.758: %SYS-5-RELOAD: Reload  
requested by console.
```

```
Reload Reason: Reload Command.
```

Managing Configuration Files

- Backing Up Configurations Offline:
 - TFTP server
 - CD
 - USB Memory Stick
 - Text Files using the Clipboard.
 - Text files using HyperTerminal capture.
- Restoring Configurations:
 - TFTP Server
 - Paste to Host from a text file.

Managing Configuration Files

- A **TFTP server** will allow image and configuration uploads and downloads over the network.
- The TFTP server can be another router, or it can be a host system.

Managing Configuration Files

Flash

RAM

TFTP Server


Command

```
Router#ping tftp - address
Type escape sequence to abort
Sending 5, 100-byte ICMP Echoes to 210.93.105.1
timeout is 2 seconds:
!!!!.!
Success rate is 80 percent (4/5)
round trip min/avg/max = 68/68/168 ms
```


- Once it is installed or before you attempt to use it, **ALWAYS** make sure that the connectivity is there....

Managing Configuration Files

What can be copied?



Managing Configuration Files



- Configuration files can be captured and saved in text format using the text capture function of HyperTerminal (or any other emulator that has the function).

Configuring Interfaces

All interfaces are accessed by issuing the `interface` command at the global configuration prompt.

In the following commands, the `type` argument includes serial, ethernet, fastethernet, and others:

```
Router(config)#interface type port
Router(config)#interface type slot/port
Router(config)#interface type slot/subslot/port
```

**Router
Interfaces**

The following command is used to administratively turn off the interface:

```
Router(config-if)#shutdown
```

The following command is used to turn on an interface that has been shutdown:

```
Router(config-if)#no shutdown
```


The following command is used to quit the current interface configuration mode:

```
Router(config-if)#exit
```

When the configuration is complete, the interface is enabled and interface configuration mode is exited.

Configuring Interfaces


- Configuring a Router Ethernet Interface:



```
Router#configure terminal
Router(config)#
Router(config)#interface FastEthernet 0/0
Router(config-if)#ip address 192.168.10.1 255.255.255.0
Router(config-if)#no shutdown
Router(config-if)#exit
Router(config)#
```


Configuring Interfaces

- Configuring a Router Serial Interface:



```
Router#configure terminal
Router(config)#
Router(config)#interface Serial 0/2/0
Router(config-if)#ip address 192.168.11.1 255.255.255.0
Router(config-if)#clock rate 56000
Router(config-if)#no shutdown
Router(config-if)#exit
Router(config)#
```

Describing Router Interfaces



```
Router(config)#interface FastEthernet 0/0
Router(config-if)#description Building B Sales LAN
Router(config-if)#exit
```

Description is all text after this space

Interface description used for internal network documentation

```
Router(config)#interface Serial 0/0/0
Router(config-if)#description To Perth CKT-PT27834365-01
Router(config-if)#exit
```

Description is all text after this space


Configuring Interfaces

- Configuring a Switch:

```
Switch#configure terminal
Switch(config)#
Switch(config)#hostname Flour_Bluff
Flour_Bluff(config)#
Flour_Bluff(config)#interface FastEthernet 0/1
Flour_Bluff(config-if)#description To TAM switch
Flour_Bluff(config-if)#interface vlan 1
Flour_Bluff(config-if)#ip address 192.168.1.2 255.255.255.0
Flour_Bluff(config-if)#no shutdown
Flour_Bluff(config-if)#exit
Flour_Bluff(config)#ip default-gateway 192.168.1.1
Flour_Bluff(config)#exit
Flour_Bluff#
```


Configuring and Testing Your Network

Verifying Connectivity



Test the Stack

- PING:
 - From the command window on a PC.



```
C:\WINDOWS\system32\cmd.exe

C:\>ping 192.168.100.1

Pinging 192.168.100.1 with 32 bytes of data:

Reply from 192.168.100.1: bytes=32 time=1ms TTL=63
Reply from 192.168.100.1: bytes=32 time=1ms TTL=63
Reply from 192.168.100.1: bytes=32 time=1ms TTL=63
Reply from 192.168.100.1: bytes=32 time=1ms TTL=63

Ping statistics for 192.168.100.1:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 1ms, Maximum = 1ms, Average = 1ms

C:\>
```

Test the Stack

- PING:
 - From the router IOS.

```
R2-Central>ping 172.16.1.1
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 172.16.1.1, timeout is 2 seconds:
```

```
!!!!!!
```

```
R2-Central>ping 172.16.1.20
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 172.16.1.20, timeout is 2 seconds:
```

```
.....
```

```
R2-Central>ping 202.163.24.5
```

```
Type escape sequence to abort.
```


```
Sending 5, 100-byte ICMP Echos to 202.163.24.5, timeout is 2 seconds:
```

```
U.U.U
```

```
Success rate is 0 percent (0/5)
```

Test the Stack

- PING:
 - Testing the Loopback (127.0.0.1).



```
C:\WINDOWS\system32\cmd.exe

C:\>ping 127.0.0.1

Pinging 127.0.0.1 with 32 bytes of data:

Reply from 127.0.0.1: bytes=32 time<1ms TTL=128
Reply from 127.0.0.1: bytes=32 time<1ms TTL=128
Reply from 127.0.0.1: bytes=32 time<1ms TTL=128
Reply from 127.0.0.1: bytes=32 time<1ms TTL=128

Ping statistics for 127.0.0.1:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 0ms, Average = 0ms

C:\>
```

If successful, it means that the protocol stack on the PC is functioning properly from the Network through the Physical Layers.


Testing the Local NIC Assignment

```
IP Address. . . . . : 10.0.0.5  
Subnet Mask . . . . . : 255.255.255.0  
Default Gateway. . . . : 10.0.0.254
```



Verify the host NIC address is bound and ready for transmitting signals across the media by pinging its own IP address.

Testing the Router Interfaces



```
Router1#show ip interface brief
```

Interface	IP-Address	OK?	Method	Status	Protocol
FastEthernet0/0	192.168.254.254	YES	NVRAM	up	up
FastEthernet0/1	unassigned	YES	unset	down	down
Serial0/0/0	172.16.0.254	YES	NVRAM	up	up
Serial0/0/1	unassigned	YES	unset	administratively down	down

```
Router1#
```

```
Router1#ping 192.168.254.1
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 192.168.254.1, timeout is 2 seconds:  
!!!!
```

```
Success rate is 100 percent (5/5) round-trip min/avg/max = 1/2/4 ms
```

```
Router1#
```


```
Router1#traceroute 192.168.0.1
```

```
Type escape sequence to abort.
```

```
Tracing the route to 192.168.0.1
```

1	172.16.0.253	8 msec	4msec	8 msec
2	10.0.0.254	16 msec	16 msec	8 msec
3	192.168.0.1	16 msec	*	20 msec

Testing the Switch Interfaces



```
Switch1#show ip interface brief
```

Interface	IP-Address	OK?	Method	Status	Protocol
FastEthernet0/1	unassigned	YES	manual	up	up
.					
FastEthernet0/24	unassigned	YES	manual	down	down
Vlan1	192.168.254.250	YES	manual	up	up

```
Switch1#
```

```
Switch1#ping 192.168.254.1
```

Type escape sequence to abort.

Sending 5, 100-byte ICMP Echos to 192.168.254.1, timeout is 2 seconds:

!!!!!

Success rate is 100 percent (5/5) round-trip min/avg/max = 1/2/4 ms

```
Switch1#
```


```
Switch1#traceroute 192.168.0.1
```

Type escape sequence to abort

Tracing the route to 192.168.0.1


Step	Destination	Time	Time	Time
1	192.168.254.254	4 msec	2 msec	3 msec
2	172.16.0.253	8 msec	4 msec	8 msec
3	10.0.0.254	16 msec	16 msec	8 msec
4	192.168.0.1	16 msec	*	20 msec

Testing the Local Network



Successfully pinging another host on the same subnet verifies that both the local host and the other host are configured correctly.


Testing Gateway Connectivity



A successful ping verifies both the host and gateway configurations.

Testing Remote Connectivity

```
C:\>ping 192.168.0.253  
C:\>ping 192.168.0.254  
C:\>ping 10.0.1.254  
C:\>ping 10.0.1.1
```



Ping each hop between the local
and remote host.

Tracing and Interpreting Trace Results

C:\ping 10.1.0.2

Pinging 10.1.0.2 with 32 bytes of data:

Request timed out.

Request timed out.


Request timed out.

Request timed out.

Ping statistics for 10.1.0.2:

Packets: Sent = 4, Received = 0, Lost = 4 (100% loss)

The ping test failed.




1	2 ms	2 ms	2 ms	10.0.0.254
2	*	*	*	Request timed out.
3	*	*	*	Request timed out.
4	^C			

Host 1

Configuring and Testing Your Network

Monitoring and Documenting Networks



Basic Network Baselines

- **Network Baseline:**
 - Process for studying the network at regular intervals.
 - Ensure that the network is working as designed.
 - More than a single report.
 - Health of the network at a certain point in time.
 - Accomplished over a period of time.
 - Varying times and loads will assist in creating a better picture of overall network performance.
 - Copy and paste the results from an executed **ping, trace, or other relevant command** into a text file.
 - Compare the results over time.

Basic Network Baselines

Run the
same test.

At different
times.

Compare
the results.

FEB 2, 2007 08:14:43

C:\>ping 10.66.254.159

Pinging 10.66.254.159 with 32 bytes of data:

Reply from 10.66.254.159: bytes=32	time<1ms	TTL=128
Reply from 10.66.254.159: bytes=32	time<1ms	TTL=128
Reply from 10.66.254.159: bytes=32	time<1ms	TTL=128
Reply from 10.66.254.159: bytes=32	time<1ms	TTL=128

MAR 17, 2007 14:41:06

C:\>ping 10.66.254.159


Pinging 10.66.254.159 with 32 bytes of data:

Reply from 10.66.254.159: bytes=32	time<6ms	TTL=128
Reply from 10.66.254.159: bytes=32	time<6ms	TTL=128
Reply from 10.66.254.159: bytes=32	time<6ms	TTL=128
Reply from 10.66.254.159: bytes=32	time<6ms	TTL=128

Basic Network Baselines

- Network Baseline:
 - Results from a command can be captured and saved as a text file for future study.
 - PING
 - TRACEROUTE
 - CISCO IOS

Learning About the Nodes on the Network




```
C:\>arp -a
```

Internet Address	Physical Address	Type
10.0.0.2	00-08-a3-b6-ce-04	dynamic
10.0.0.3	00-0d-56-09-fb-d1	dynamic
10.0.0.4	00-12-3f-d4-6d-1b	dynamic
10.0.0.254	00-10-7b-e7-fa-ef	dynamic

IP- MAC Address Pair

Ping Sweep / MAC Scanner Tools



The screenshot shows the Colasoft MAC Scanner application window. The title bar reads "Colasoft MAC Scanner". The menu bar includes File, Edit, View, Scan, and Help. The toolbar contains icons for Export All, Export Selected, Copy, Delete, Find, and a Start button. A text field for "Local Subnet" is set to "192.168.1.0". The main area displays a table of discovered hosts. A red rectangle highlights the first three rows of the table. The status bar at the bottom indicates "Found 3 hosts."

IP	MAC Address	Host Name	Manufacturer
192.168.1.100	00:50:BA:1F:D6:98	FTY6T01	
192.168.1.101	00:1D:09:D9:D9:AC	ILS00068A-01.its.stclairc	
192.168.1.1	00:18:F8:49:B3:B4		

Switch Connections

```
Sw1-2950#show mac-address-table
```

Mac Address Table

Vlan	Mac Address	Type	Ports
All	0014.a8a8.8780	STATIC	CPU
All	0100.0ccc.cccc	STATIC	CPU
All	0100.0ccc.cccd	STATIC	CPU
All	0100.0cdd.dddd	STATIC	CPU
1	0001.e640.3b4b	DYNAMIC	Fa0/23
1	0002.fde1.6acb	DYNAMIC	Fa0/14
1	0006.5b88.dfc4	DYNAMIC	Gi0/2
1	0006.5bdd.6fee	DYNAMIC	Fa0/23
1	0006.5bdd.7035	DYNAMIC	Fa0/23
1	0006.5bdd.72fd	DYNAMIC	Fa0/23
1	0006.5bdd.73b0	DYNAMIC	Fa0/23
1	000e.0cb6.2b51	DYNAMIC	Fa0/2
1	000f.8f28.b7b5	DYNAMIC	Fa0/18
1	0011.1165.8acf	DYNAMIC	Fa0/1
1	0013.720b.40c3	DYNAMIC	Fa0/19
1	0080.9120.1766	DYNAMIC	Fa0/8
1	00a0.c949.702a	DYNAMIC	Fa0/15
1	00c0.b770.6c19	DYNAMIC	Fa0/22
1	00c0.b770.6c8e	DYNAMIC	Fa0/21
1	00c0.b770.6c8f	DYNAMIC	Fa0/20
1	00e0.1e68.0987	DYNAMIC	Fa0/17

Multiple devices connected to Fa0/23