



Inspiring Excellence

Network Layer

Routing Algorithm

Link State Routing

Lecture 13 | CSE421 – Computer Networks

Department of Computer Science and Engineering

School of Data & Science

Chapter 4: Network Layer


- 4.1 Introduction
- 4.2 Virtual circuit and datagram networks
- 4.3 What's inside a router
- 4.4 IP: Internet Protocol
 - Datagram format
 - IPv4 addressing
 - ICMP
 - IPv6
- 4.5 Routing algorithms
 - Distance Vector
 - Link state
 - Hierarchical routing
- 4.6 Routing in the Internet
 - RIP
 - OSPF
 - BGP

Distance Vector Routing Protocols



- **Distance Vector** routing protocols are like road signs.
 - Routers must make preferred path decisions based on a distance or metric to a network.

Link State Routing Protocols



- **Link-State** routing protocols are more like a road map.
 - They create a topological map of the network
 - Each router uses this map to determine the shortest path to each network.

Link-State Routing Protocols

- A **centralized algorithm**: finds the least-cost path using complete knowledge of the network.
- Also called **Shortest Path First (SPF)** protocols.
- Uses **Dijkstra's Algorithm** to compute the shortest path from one node to all others.
- Though it sounds complex, the basic idea is simple and easy to configure.

How it works

- Uses **Dijkstra's Algorithm (SPF)**.
- Every router knows the **full network map** (topology + link costs)
- Each router computes the **least-cost paths** from itself to all other
- The result is a **forwarding/routing table** (tells where to send packets)
- Algorithm runs in steps: after **k iterations** the router


Link-State Routing Process

5 Step Process :

1. Each router learns its **directly connected networks**.
2. Each router **talks to its neighbors** (sends Hello packets).
3. Each router creates a **Link-State Packet (LSP)** describing its links.
4. Each router **floods its LSP** to all other routers.
5. Every router builds a **complete network map** from all LSPs and runs Dijkstra to find the **best paths**.


Step 1: Directly Connected Networks

We will focus on the Link-State routing process from the perspective of R1.



- Each router learns about its own directly connected networks.
- When a router interface is configured with an IP address and subnet mask and activated, the interface becomes part of that network.
- Regardless of the routing protocols used, these directly connected networks are now part of the routing table.


Step 2: Hello Packets



- Each router is responsible for contacting its neighbors on directly connected networks.
- The router will not be aware of any neighbor routers on the link until it receives a Hello packet from that neighbor.


At that time, it establishes an adjacency with the neighboring router.

Step 2: Hello Packets




Step 2: Hello Packets

- A **neighbor** is any other router that is enabled with the **same link-state routing protocol**.
- These small Hello packets continue to be exchanged between two adjacent neighbors.
- These packets serve as a **keep alive** function to monitor the state of the neighbor.



Step 3: Build the Link-State Packet




- Each router builds a link-state packet (LSP) containing the state of each directly connected link.
- The LSP contains the link-state information about the sending router's links.
- The router only sends LSPs out interfaces where it has established adjacencies with other routers.

Step 4: Flooding Link-State Packets


No response to Hello
– no LSP sent.

Flooding of R1 LSP




- Each router floods the LSP to all neighbors, who then store all LSPs received in a database.
- Whenever a router receives an LSP from a neighboring router, it immediately sends that LSP out all other interfaces, **except the interface that received the LSP.**

Step 4: Flooding Link-State Packets




- Link-state routing protocols calculate the SPF algorithm **after the flooding** is complete.
- As a result, link-state routing protocols **reach convergence much faster** than distance vector routing protocols.

Step 4: Flooding Link-State Packets



- An **LSP** needs to be sent only:
 - During **initial startup** of the router or routing protocol.
 - Whenever there is a **change in the topology** (link going down or coming up) or a neighbor adjacency being established or broken.

Step 5: Constructing a Link-State Database



- Each router uses the LSPs to **construct a database** that is a **complete map of the topology** and computes the **best path** to each destination network.

R1: Building the SPF Tree

R1 Link State Database

R1 Links-states:

- Connected to neighbor R2 on network 10.2.0.0/16, cost of 20
- Connected to neighbor R3 on network 10.3.0.0/16, cost of 5
- Connected to neighbor R4 on network 10.4.0.0/16, cost of 20
- Has a network 10.1.0.0/16, cost of 2

LSPs from R2:

- Connected to neighbor R1 on network 10.2.0.0/16, cost of 20
- Connected to neighbor R5 on network 10.9.0.0/16, cost of 10
- Has a network 10.5.0.0/16, cost of 2

LSPs from R3:


- Connected to neighbor R1 on network 10.3.0.0/16, cost of 5
- Connected to neighbor R4 on network 10.7.0.0/16, cost of 10
- Has a network 10.6.0.0/16, cost of 2

LSPs from R4:

- Connected to neighbor R1 on network 10.4.0.0/16, cost of 20
- Connected to neighbor R3 on network 10.7.0.0/16, cost of 10
- Connected to neighbor R5 on network 10.10.0.0/16, cost of 10
- Has a network 10.8.0.0/16, cost of 2

LSPs from R5:

- Connected to neighbor R2 on network 10.9.0.0/16, cost of 10
- Connected to neighbor R4 on network 10.10.0.0/16, cost of 10
- Has a network 10.11.0.0/16, cost of 2



Step 5: Constructing a Link-State Database

R1's Link-State Database

LSPs from R2:

- Connected to neighbor R1 on network 10.2.0.0/16, cost of 20
- Connected to neighbor R5 on network 10.9.0.0/16, cost of 10
- Has a network 10.5.0.0/16, cost of 2

LSPs from R3:

- Connected to neighbor R1 on network 10.3.0.0/16, cost of 5
- Connected to neighbor R4 on network 10.7.0.0/16, cost of 10
- Has a network 10.6.0.0/16, cost of 2

LSPs from R4:


- Connected to neighbor R1 on network 10.4.0.0/16, cost of 20
- Connected to neighbor R3 on network 10.7.0.0/16, cost of 10
- Connected to neighbor R5 on network 10.10.0.0/16, cost of 10
- Has a network 10.8.0.0/16, cost of 2

LSPs from R5:

- Connected to neighbor R2 on network 10.9.0.0/16, cost of 10
- Connected to neighbor R4 on network 10.10.0.0/16, cost of 10
- Has a network 10.11.0.0/16, cost of 2

R1 Link-states:

- Connected to neighbor R2 on network 10.2.0.0/16, cost of 20
- Connected to neighbor R3 on network 10.3.0.0/16, cost of 5
- Connected to neighbor R4 on network 10.4.0.0/16, cost of 20
- Has a network 10.1.0.0/16, cost of 2




- As a result of the flooding process, router R1 has learned the link-state information for each router in its routing area.

Step 5: Constructing a Link-State Database


Destination	Shortest Path	Cost
R2 LAN	R1 to R2	22
R3 LAN	R1 to R3	7
R4 LAN	R1 to R3 to R4	17
R5 LAN	R1 to R3 to R4 to R5	27

Each router in the topology determines the shortest path **from its own perspective**.



- With a complete link-state database, R1 can now use the database and the shortest path first (SPF) algorithm to calculate the preferred path or **shortest path** to each network.

R1: Building the SPF Tree




- All LSPs have been processed using the SPF algorithm and R1 has now constructed the complete SPF tree.

Generating a Routing Table

SPF Information

- Network 10.5.0.0/16 via R2 serial 0/0/0 at a cost of 22
- Network 10.6.0.0/16 via R3 serial 0/0/1 at a cost of 7
- Network 10.7.0.0/16 via R3 serial 0/0/1 at a cost of 15
- Network 10.8.0.0/16 via R3 serial 0/0/1 at a cost of 17
- Network 10.9.0.0/16 via R2 serial 0/0/0 at a cost of 30
- Network 10.10.0.0/16 via R3 serial 0/0/1 at a cost of 25
- Network 10.11.0.0/16 via R3 serial 0/0/1 at a cost of 27



Building Routing Table

- Creation of the states of the links by each node, called the link state packets (LSP)
- Dissemination of LSPs to every other routers, called flooding (efficiently)
- Constructing a Link-State Database using LSPs
- Formation of a shortest path tree for each node
- Calculation of a routing table based on the shortest path tree

Advantages: Link-State Routing

- **Fast Network Convergence–**

- When a router receives a new LSP, it quickly floods it to all other routers.
- Updates spread very fast across the network.

- **Topological Map–**

- Each router builds a complete **map of the network** (SPF tree).
- From this, it can calculate the **shortest path** to every destination.


Advantages: Link-State Routing

• Hierarchical Design–

- Large networks can be divided into **areas**.
- This helps in **summarizing routes** and makes the network easier to manage.

• Event-driven Updates–

- After the first flooding, updates are sent only when there are **changes** (like a link goes down).
- Only the changed info is shared, not the entire routing table.



Comparison

	Distance Vector	Link State
Network view	Topology knowledge from the neighbor point of view	Common and complete knowledge of the network topology
Best Path Calculation	Based on fewest number of hops	Based on the link cost
Updates	Full routing table	Link State Updates
Algorithm	Bellman-Ford	Dijkstra
CPU and Memory	Low utilization	Intensive
hierarchical Structure	No	Yes
Convergence time	Moderate	Fast



THE END