

Basic Data Types

Outline

- 1 Types
- 2 Expressions
- 3 Statements
- 4 Strings
- 5 Integers
- 6 Floats
- 7 Booleans
- 8 Operator Precedence
- 9 Python Console

Types

Types

A data type is a set of values along with a set of operations defined on those values

Types

A data type is a set of values along with a set of operations defined on those values

The four basic data types:

Types

A data type is a set of values along with a set of operations defined on those values

The four basic data types:

- 1 `str` for sequences of characters

Types

A data type is a set of values along with a set of operations defined on those values

The four basic data types:

- 1 `str` for sequences of characters
- 2 `int` for integers

Types

A data type is a set of values along with a set of operations defined on those values

The four basic data types:

- 1 `str` for sequences of characters
- 2 `int` for integers
- 3 `float` for floating-point numbers

Types

A data type is a set of values along with a set of operations defined on those values

The four basic data types:

- 1 `str` for sequences of characters
- 2 `int` for integers
- 3 `float` for floating-point numbers
- 4 `bool` for true/false values

Expressions

Expressions

A literal is a representation of a data-type value

Expressions

A literal is a representation of a data-type value

Example:

Expressions

A literal is a representation of a data-type value

Example:

- `'Hello, World'` and `'Cogito, ergo sum'` are string literals

Expressions

A literal is a representation of a data-type value

Example:

- `'Hello, World'` and `'Cogito, ergo sum'` are string literals
- `42` and `1729` are integer literals

Expressions

A literal is a representation of a data-type value

Example:

- `'Hello, World'` and `'Cogito, ergo sum'` are string literals
- `42` and `1729` are integer literals
- `3.14159` and `2.71828` are floating-point literals

Expressions

A literal is a representation of a data-type value

Example:

- `'Hello, World'` and `'Cogito, ergo sum'` are string literals
- `42` and `1729` are integer literals
- `3.14159` and `2.71828` are floating-point literals
- `True` and `False` are boolean literals

Expressions

Expressions

An identifier is a representation of a name

Expressions

An identifier is a representation of a name

Each identifier is a sequence of letters, digits, and underscores, not starting with a digit

Expressions

An identifier is a representation of a name

Each identifier is a sequence of letters, digits, and underscores, not starting with a digit

Example:

Expressions

An identifier is a representation of a name

Each identifier is a sequence of letters, digits, and underscores, not starting with a digit

Example:

- `abc`, `Ab_`, `abc123`, and `a_b` are valid identifiers

Expressions

An identifier is a representation of a name

Each identifier is a sequence of letters, digits, and underscores, not starting with a digit

Example:

- `abc`, `Ab_`, `abc123`, and `a_b` are valid identifiers
- `Ab*`, `1abc`, and `a+b` are not

Expressions

An identifier is a representation of a name

Each identifier is a sequence of letters, digits, and underscores, not starting with a digit

Example:

- `abc`, `Ab_`, `abc123`, and `a_b` are valid identifiers
- `Ab*`, `1abc`, and `a+b` are not

Keywords such as `and`, `def`, `import`, `lambda`, and `while` cannot be used as identifiers

Expressions

Expressions

A variable is a name associated with a data-type value

Expressions

A variable is a name associated with a data-type value

Example: `total` representing the running total of a sequence of numbers

Expressions

A variable is a name associated with a data-type value

Example: `total` representing the running total of a sequence of numbers

A constant variable is one whose associated data-type value does not change during the execution of a program

Expressions

A variable is a name associated with a data-type value

Example: `total` representing the running total of a sequence of numbers

A constant variable is one whose associated data-type value does not change during the execution of a program

Example: `SPEED_OF_LIGHT` representing the known speed of light

Expressions

A variable is a name associated with a data-type value

Example: `total` representing the running total of a sequence of numbers

A constant variable is one whose associated data-type value does not change during the execution of a program

Example: `SPEED_OF_LIGHT` representing the known speed of light

A variable's value is accessed as `[<target>.<name>`

Expressions

A variable is a name associated with a data-type value

Example: `total` representing the running total of a sequence of numbers

A constant variable is one whose associated data-type value does not change during the execution of a program

Example: `SPEED_OF_LIGHT` representing the known speed of light

A variable's value is accessed as `[<target>.<name>`

Example: `total`, `SPEED_OF_LIGHT`, `sys.argv`, and `math.pi`

Expressions

Expressions

An operator is a representation of a data-type operation

Expressions

An operator is a representation of a data-type operation

+, -, *, /, and % represent arithmetic operations on integers and floats

Expressions

An operator is a representation of a data-type operation

`+`, `-`, `*`, `/`, and `%` represent arithmetic operations on integers and floats

`not`, `or`, and `and` represent logical operations on booleans

Expressions

Expressions

Many programming tasks involve not only built-in operators, but also functions

Expressions

Many programming tasks involve not only built-in operators, but also functions

Three kinds of functions:

Expressions

Many programming tasks involve not only built-in operators, but also functions

Three kinds of functions:

- 1 Built-in functions

Expressions

Many programming tasks involve not only built-in operators, but also functions

Three kinds of functions:

- 1 Built-in functions
- 2 Functions defined in standard libraries

Many programming tasks involve not only built-in operators, but also functions

Three kinds of functions:

- 1 Built-in functions
- 2 Functions defined in standard libraries
- 3 Functions defined in user-defined libraries

Expressions

Many programming tasks involve not only built-in operators, but also functions

Three kinds of functions:

- 1 Built-in functions
- 2 Functions defined in standard libraries
- 3 Functions defined in user-defined libraries

A function is called as `[<library>.]<name>(<argument1>, <argument2>, ...)`

Expressions

Many programming tasks involve not only built-in operators, but also functions

Three kinds of functions:

- 1 Built-in functions
- 2 Functions defined in standard libraries
- 3 Functions defined in user-defined libraries

A function is called as `[<library>.]<name>(<argument1>, <argument2>, ...)`

Example: `stdio.writeln('Hello, World')`

Expressions

Many programming tasks involve not only built-in operators, but also functions

Three kinds of functions:

- 1 Built-in functions
- 2 Functions defined in standard libraries
- 3 Functions defined in user-defined libraries

A function is called as `[<library>.]<name>(<argument1>, <argument2>, ...)`

Example: `stdio.writeln('Hello, World')`

Some functions (called void functions) do not return a value while others (called non-void functions) do return a value

Expressions

Expressions

Example

Expressions

Example



<code>int(x)</code>	returns the integer value of <code>x</code>
<code>float(x)</code>	returns the floating-point value of <code>x</code>
<code>str(x)</code>	returns string value of <code>x</code>

Example



<code>int(x)</code>	returns the integer value of x
<code>float(x)</code>	returns the floating-point value of x
<code>str(x)</code>	returns string value of x



`math`

<code>exp(x)</code>	returns e^x
<code>sqrt(x)</code>	returns \sqrt{x}

Example



<code>int(x)</code>	returns the integer value of x
<code>float(x)</code>	returns the floating-point value of x
<code>str(x)</code>	returns string value of x



math

<code>exp(x)</code>	returns e^x
<code>sqrt(x)</code>	returns \sqrt{x}



stdio

<code>writeln(x = '')</code>	writes x followed by newline to standard output
<code>write(x = '')</code>	writes x to standard output

Example



<code>int(x)</code>	returns the integer value of <code>x</code>
<code>float(x)</code>	returns the floating-point value of <code>x</code>
<code>str(x)</code>	returns string value of <code>x</code>



math

<code>exp(x)</code>	returns e^x
<code>sqrt(x)</code>	returns \sqrt{x}



stdio

<code>writeln(x = '')</code>	writes <code>x</code> followed by newline to standard output
<code>write(x = '')</code>	writes <code>x</code> to standard output



stdrandom

<code>uniformFloat(lo, hi)</code>	returns a float chosen uniformly at random from the interval <code>[lo, hi)</code>
<code>bernoulli(p = 0.5)</code>	returns <code>True</code> with probability <code>p</code> and <code>False</code> with probability <code>1 - p</code>

Expressions

Expressions

An expression is a combination of literals, variables, operators, and non-void function calls that evaluates to a value

Expressions

An expression is a combination of literals, variables, operators, and non-void function calls that evaluates to a value

Example:

Expressions

An expression is a combination of literals, variables, operators, and non-void function calls that evaluates to a value

Example:

- 2, 4

Expressions

An expression is a combination of literals, variables, operators, and non-void function calls that evaluates to a value

Example:

- 2, 4
- a, b, c

Expressions

An expression is a combination of literals, variables, operators, and non-void function calls that evaluates to a value

Example:

- 2, 4
- a, b, c
- $b * b - 4 * a * c$

Expressions

An expression is a combination of literals, variables, operators, and non-void function calls that evaluates to a value

Example:

- 2, 4
- a, b, c
- $b * b - 4 * a * c$
- `math.sqrt(b * b - 4 * a * c)`

Expressions

An expression is a combination of literals, variables, operators, and non-void function calls that evaluates to a value

Example:

- 2, 4
- a, b, c
- $b * b - 4 * a * c$
- `math.sqrt(b * b - 4 * a * c)`
- $(-b + \text{math.sqrt}(b * b - 4 * a * c)) / (2 * a)$

Statements

Statements

A statement is a syntactic unit that expresses some action to be carried out

Statements

A statement is a syntactic unit that expresses some action to be carried out

Import statement

```
import <library>
```

Statements

A statement is a syntactic unit that expresses some action to be carried out

Import statement

```
import <library>
```

Example

```
import stdio  
import sys
```

Statements

Statements

Function call statement

```
[<library>.]<name>(<argument1>, <argument2>, ...)
```

Statements

Function call statement

```
[<library>.<name>(<argument1>, <argument2>, ...)]
```

Example

```
stdio.write('Cogito, ')  
stdio.write('ergo sum')  
stdio.writeln()
```


Statements

Statements

Assignment statement

```
<name> = <expression>
```

Statements

Assignment statement

```
<name> = <expression>
```

Example

```
a = 'python3'  
b = 42  
c = 3.14159  
d = True  
e = None
```

a	b	c	d	e
'python3'	42	3.14159	True	None
str	int	float	bool	

Statements

Statements

Example (exchanging the values of two variables `a` and `b`)

```
a = 42
b = 1729

t = a # t is now 42
a = b # a is now 1729
b = t # b is now 42

stdio.writeln(a)
stdio.writeln(b)
```

Statements

Example (exchanging the values of two variables `a` and `b`)

```
a = 42
b = 1729

t = a # t is now 42
a = b # a is now 1729
b = t # b is now 42

stdio.writeln(a)
stdio.writeln(b)
```

```
1729
42
```

Statements

Statements

Equivalent assignment statement forms

```
<name> <operator>= <expression>  
<name> = <name> <operator> <expression>
```

where <operator> is **, *, /, //, %, +, or -

Statements

Equivalent assignment statement forms

```
<name> <operator>= <expression>  
<name> = <name> <operator> <expression>
```

where <operator> is **, *, /, //, %, +, or -

Example

```
x *= 5  
x = x * 5
```

Strings

Strings

The `str` data type represents strings (sequences of characters)

Strings

The `str` data type represents strings (sequences of characters)

A `str` literal is specified by enclosing a sequence of characters in matching single quotes

Strings

The `str` data type represents strings (sequences of characters)

A `str` literal is specified by enclosing a sequence of characters in matching single quotes

Example: `'Hello, World'` and `'Cogito, ergo sum'`

Strings

The `str` data type represents strings (sequences of characters)

A `str` literal is specified by enclosing a sequence of characters in matching single quotes

Example: `'Hello, World'` and `'Cogito, ergo sum'`

Tab, newline, backslash, and single quote characters are specified using escape sequences `'\t'`, `'\n'`, `'\\'`, and `'\''`

Strings

The `str` data type represents strings (sequences of characters)

A `str` literal is specified by enclosing a sequence of characters in matching single quotes

Example: `'Hello, World'` and `'Cogito, ergo sum'`

Tab, newline, backslash, and single quote characters are specified using escape sequences `'\t'`, `'\n'`, `'\\'`, and `'\''`

Example: `'Hello, world\n'` and `'Python\'s great'`

Strings

The `str` data type represents strings (sequences of characters)

A `str` literal is specified by enclosing a sequence of characters in matching single quotes

Example: `'Hello, World'` and `'Cogito, ergo sum'`

Tab, newline, backslash, and single quote characters are specified using escape sequences `'\t'`, `'\n'`, `'\\'`, and `'\''`

Example: `'Hello, world\n'` and `'Python\'s great'`

Operations:

Strings

The `str` data type represents strings (sequences of characters)

A `str` literal is specified by enclosing a sequence of characters in matching single quotes

Example: `'Hello, World'` and `'Cogito, ergo sum'`

Tab, newline, backslash, and single quote characters are specified using escape sequences `'\t'`, `'\n'`, `'\\'`, and `'\''`

Example: `'Hello, world\n'` and `'Python\'s great'`

Operations:

- Concatenation (+)

Example: `'123' + '456'` evaluates to `'123456'`

Strings

The `str` data type represents strings (sequences of characters)

A `str` literal is specified by enclosing a sequence of characters in matching single quotes

Example: `'Hello, World'` and `'Cogito, ergo sum'`

Tab, newline, backslash, and single quote characters are specified using escape sequences `'\t'`, `'\n'`, `'\\'`, and `'\''`

Example: `'Hello, world\n'` and `'Python\'s great'`

Operations:

- Concatenation (+)

Example: `'123' + '456'` evaluates to `'123456'`

- Replication (*)

Example: `3 * 'ab'` and `'ab' * 3` evaluate to `'ababab'`

Strings

Strings

Program: `dateformats.py`

Strings

Program: `dateformats.py`

- Command-line input: d (str), m (str), and y (str) representing a date

Strings

Program: `dateformats.py`

- Command-line input: d (str), m (str), and y (str) representing a date
- Standard output: the date in different formats

Strings

Program: `dateformats.py`

- Command-line input: *d* (str), *m* (str), and *y* (str) representing a date
- Standard output: the date in different formats

```
>_ ~/workspace/ipp/programs
```

```
$ _
```

Strings

Program: `dateformats.py`

- Command-line input: *d* (str), *m* (str), and *y* (str) representing a date
- Standard output: the date in different formats

```
>_ ~/workspace/ipp/programs
```

```
$ python3 dateformats.py 14 03 1879
```


Strings

Program: `dateformats.py`

- Command-line input: *d* (str), *m* (str), and *y* (str) representing a date
- Standard output: the date in different formats

```
>_ ~/workspace/ipp/programs
```

```
$ python3 dateformats.py 14 03 1879
14/03/1879
03/14/1879
1879/03/14
$ _
```

Strings

Strings

📄 dateformats.py

```
1 import stdio
2 import sys
3
4 d = sys.argv[1]
5 m = sys.argv[2]
6 y = sys.argv[3]
7 dmy = d + '/' + m + '/' + y
8 mdy = m + '/' + d + '/' + y
9 ymd = y + '/' + m + '/' + d
10 stdio.writeln(dmy)
11 stdio.writeln(mdy)
12 stdio.writeln(ymd)
```

Integers

Integers

The `int` data type represents integers

Integers

The `int` data type represents integers

An `int` literal is specified as a sequence of digits `0` through `9`

Integers

The `int` data type represents integers

An `int` literal is specified as a sequence of digits `0` through `9`

Example: `42` and `1729`

Integers

The `int` data type represents integers

An `int` literal is specified as a sequence of digits 0 through 9

Example: `42` and `1729`

Operations:

Integers

The `int` data type represents integers

An `int` literal is specified as a sequence of digits 0 through 9

Example: `42` and `1729`

Operations:

- Addition (+)

Integers

The `int` data type represents integers

An `int` literal is specified as a sequence of digits 0 through 9

Example: `42` and `1729`

Operations:

- Addition (+)
- Subtraction/negation (-)

Integers

The `int` data type represents integers

An `int` literal is specified as a sequence of digits 0 through 9

Example: `42` and `1729`

Operations:

- Addition (+)
- Subtraction/negation (-)
- Multiplication (*)

Integers

The `int` data type represents integers

An `int` literal is specified as a sequence of digits 0 through 9

Example: `42` and `1729`

Operations:

- Addition (+)
- Subtraction/negation (-)
- Multiplication (*)
- Division (/)

Integers

The `int` data type represents integers

An `int` literal is specified as a sequence of digits 0 through 9

Example: `42` and `1729`

Operations:

- Addition (+)
- Subtraction/negation (-)
- Multiplication (*)
- Division (/)
- Floored division(//)

Integers

The `int` data type represents integers

An `int` literal is specified as a sequence of digits 0 through 9

Example: `42` and `1729`

Operations:

- Addition (+)
- Subtraction/negation (-)
- Multiplication (*)
- Division (/)
- Floored division(//)
- Remainder (%)

Integers

The `int` data type represents integers

An `int` literal is specified as a sequence of digits `0` through `9`

Example: `42` and `1729`

Operations:

- Addition (`+`)
- Subtraction/negation (`-`)
- Multiplication (`*`)
- Division (`/`)
- Floored division (`//`)
- Remainder (`%`)
- Exponentiation (`**`)

Integers

Integers

Program: `sumofsquares.py`

Integers

Program: `sumofsquares.py`

- Command-line input: x (int) and y (int)

Integers

Program: `sumofsquares.py`

- Command-line input: x (int) and y (int)
- Standard output: $x^2 + y^2$

Integers

Program: `sumofsquares.py`

- Command-line input: x (int) and y (int)
- Standard output: $x^2 + y^2$

```
>_ ~/workspace/ipp/programs
```

```
$ _
```

Integers

Program: `sumofsquares.py`

- Command-line input: x (int) and y (int)
- Standard output: $x^2 + y^2$

```
>_ ~/workspace/ipp/programs
```

```
$ python3 sumofsquares.py 3 4
```

Integers

Program: `sumofsquares.py`

- Command-line input: x (int) and y (int)
- Standard output: $x^2 + y^2$

```
>_ ~/workspace/ipp/programs
```

```
$ python3 sumofsquares.py 3 4  
25  
$ _
```

Integers

Program: `sumofsquares.py`

- Command-line input: x (int) and y (int)
- Standard output: $x^2 + y^2$

```
>_ ~/workspace/ipp/programs
```

```
$ python3 sumofsquares.py 3 4
```

```
25
```

```
$ python3 sumofsquares.py 6 8
```

Integers

Program: `sumofsquares.py`

- Command-line input: x (int) and y (int)
- Standard output: $x^2 + y^2$

```
>_ ~/workspace/ipp/programs
```

```
$ python3 sumofsquares.py 3 4
25
$ python3 sumofsquares.py 6 8
100
$ _
```


Integers

1.1.1

1.1.2

1.1.3

1.1.4

1.1.5

1.1.6

1.1.7

1.1.8

1.1.9

1.1.10

1.1.11

1.1.12

1.1.13

1.1.14

1.1.15

1.1.16

1.1.17

1.1.18

1.1.19

1.1.20

1.1.21

1.1.22

1.1.23

1.1.24

1.1.25

1.1.26

1.1.27

1.1.28

1.1.29

1.1.30

Integers

✎ sumofsquares.py

```
1 import stdio
2 import sys
3
4 x = int(sys.argv[1])
5 y = int(sys.argv[2])
6 result = x * x + y * y
7 stdio.writeln(result)
```

Floats

Floats

The `float` data type represents floating-point numbers

Floats

The `float` data type represents floating-point numbers

A floating-point literal is specified as a sequence of digits with a decimal point

Floats

The `float` data type represents floating-point numbers

A floating-point literal is specified as a sequence of digits with a decimal point

Example: `3.14159` and `2.71828`

Floats

The `float` data type represents floating-point numbers

A floating-point literal is specified as a sequence of digits with a decimal point

Example: `3.14159` and `2.71828`

Scientific notation: `6.022e23` represents 6.022×10^{23} and `6.674e-11` represents 6.674×10^{-11}

Floats

The `float` data type represents floating-point numbers

A floating-point literal is specified as a sequence of digits with a decimal point

Example: `3.14159` and `2.71828`

Scientific notation: `6.022e23` represents 6.022×10^{23} and `6.674e-11` represents 6.674×10^{-11}

Operations:

Floats

The `float` data type represents floating-point numbers

A floating-point literal is specified as a sequence of digits with a decimal point

Example: `3.14159` and `2.71828`

Scientific notation: `6.022e23` represents 6.022×10^{23} and `6.674e-11` represents 6.674×10^{-11}

Operations:

- Addition (+)

Floats

The `float` data type represents floating-point numbers

A floating-point literal is specified as a sequence of digits with a decimal point

Example: `3.14159` and `2.71828`

Scientific notation: `6.022e23` represents 6.022×10^{23} and `6.674e-11` represents 6.674×10^{-11}

Operations:

- Addition (+)
- Subtraction/negation (-)

Floats

The `float` data type represents floating-point numbers

A floating-point literal is specified as a sequence of digits with a decimal point

Example: `3.14159` and `2.71828`

Scientific notation: `6.022e23` represents 6.022×10^{23} and `6.674e-11` represents 6.674×10^{-11}

Operations:

- Addition (+)
- Subtraction/negation (-)
- Multiplication (*)

Floats

The `float` data type represents floating-point numbers

A floating-point literal is specified as a sequence of digits with a decimal point

Example: `3.14159` and `2.71828`

Scientific notation: `6.022e23` represents 6.022×10^{23} and `6.674e-11` represents 6.674×10^{-11}

Operations:

- Addition (+)
- Subtraction/negation (-)
- Multiplication (*)
- Division (/)

Floats

The `float` data type represents floating-point numbers

A floating-point literal is specified as a sequence of digits with a decimal point

Example: `3.14159` and `2.71828`

Scientific notation: `6.022e23` represents 6.022×10^{23} and `6.674e-11` represents 6.674×10^{-11}

Operations:

- Addition (+)
- Subtraction/negation (-)
- Multiplication (*)
- Division (/)
- Exponentiation (**)

Floats

Floats

Program: `quadratic.py`

Floats

Program: `quadratic.py`

- Command-line input: a (float), b (float), and c (float)

Floats

Program: `quadratic.py`

- Command-line input: a (float), b (float), and c (float)
- Standard output: roots of the quadratic equation $ax^2 + bx + c = 0$

Floats

Program: `quadratic.py`

- Command-line input: a (float), b (float), and c (float)
- Standard output: roots of the quadratic equation $ax^2 + bx + c = 0$

```
>_ ~/workspace/ipp/programs
```

```
$ _
```

Floats

Program: `quadratic.py`

- Command-line input: a (float), b (float), and c (float)
- Standard output: roots of the quadratic equation $ax^2 + bx + c = 0$

```
> ~/workspace/ipp/programs
```

```
$ python3 quadratic.py 1 -5 6
```

Floats

Program: `quadratic.py`

- Command-line input: a (float), b (float), and c (float)
- Standard output: roots of the quadratic equation $ax^2 + bx + c = 0$

```
>_ ~/workspace/ipp/programs
```

```
$ python3 quadratic.py 1 -5 6  
Root # 1 = 3.0  
Root # 2 = 2.0  
$_
```

Floats

Program: `quadratic.py`

- Command-line input: a (float), b (float), and c (float)
- Standard output: roots of the quadratic equation $ax^2 + bx + c = 0$

```
>_ ~/workspace/ipp/programs
```

```
$ python3 quadratic.py 1 -5 6  
Root # 1 = 3.0  
Root # 2 = 2.0  
$ python3 quadratic.py 1 -1 -1
```

Floats

Program: quadratic.py

- Command-line input: a (float), b (float), and c (float)
- Standard output: roots of the quadratic equation $ax^2 + bx + c = 0$

```
>_ ~/workspace/ipp/programs
```

```
$ python3 quadratic.py 1 -5 6
Root # 1 = 3.0
Root # 2 = 2.0
$ python3 quadratic.py 1 -1 -1
Root # 1 = 1.618033988749895
Root # 2 = -0.6180339887498949
$ _
```

Floats



Floats

quadratic.py

```
1 import math
2 import stdio
3 import sys
4
5 a = float(sys.argv[1])
6 b = float(sys.argv[2])
7 c = float(sys.argv[3])
8 discriminant = b * b - 4 * a * c
9 root1 = (-b + math.sqrt(discriminant)) / (2 * a)
10 root2 = (-b - math.sqrt(discriminant)) / (2 * a)
11 stdio.writeln('Root # 1 = ' + str(root1))
12 stdio.writeln('Root # 2 = ' + str(root2))
```


Booleans

Booleans

The `bool` data type represents truth values (true or false) from logic

Booleans

The `bool` data type represents truth values (true or false) from logic

The two `bool` literals are `True` and `False`

Booleans

The `bool` data type represents truth values (true or false) from logic

The two `bool` literals are `True` and `False`

Operations:

Booleans

The `bool` data type represents truth values (true or false) from logic

The two `bool` literals are `True` and `False`

Operations:

- Logical not (`not`)

Booleans

The `bool` data type represents truth values (true or false) from logic

The two `bool` literals are `True` and `False`

Operations:

- Logical not (`not`)
- Logical or (`or`)

Booleans

The `bool` data type represents truth values (true or false) from logic

The two `bool` literals are `True` and `False`

Operations:

- Logical not (`not`)
- Logical or (`or`)
- Logical and (`and`)

Booleans

The `bool` data type represents truth values (true or false) from logic

The two `bool` literals are `True` and `False`

Operations:

- Logical not (`not`)
- Logical or (`or`)
- Logical and (`and`)

Truth tables for the logical operations

x	not x
False	True
True	False

x	y	x or y
False	False	False
False	True	True
True	False	True
True	True	True

x	y	x and y
False	False	False
False	True	False
True	False	False
True	True	True

Booleans

Booleans

Two objects of the same type can be compared using comparison operators — the result is a boolean value

Booleans

Two objects of the same type can be compared using comparison operators — the result is a boolean value

Comparison operators:

Booleans

Two objects of the same type can be compared using comparison operators — the result is a boolean value

Comparison operators:

- Equal (==)

Booleans

Two objects of the same type can be compared using comparison operators — the result is a boolean value

Comparison operators:

- Equal (==)
- Not equal (!=)

Booleans

Two objects of the same type can be compared using comparison operators — the result is a boolean value

Comparison operators:

- Equal (==)
- Not equal (!=)
- Less than (<)

Booleans

Two objects of the same type can be compared using comparison operators — the result is a boolean value

Comparison operators:

- Equal (==)
- Not equal (!=)
- Less than (<)
- Less than or equal (<=)

Booleans

Two objects of the same type can be compared using comparison operators — the result is a boolean value

Comparison operators:

- Equal (==)
- Not equal (!=)
- Less than (<)
- Less than or equal (<=)
- Greater than (>)

Booleans

Two objects of the same type can be compared using comparison operators — the result is a boolean value

Comparison operators:

- Equal (==)
- Not equal (!=)
- Less than (<)
- Less than or equal (<=)
- Greater than (>)
- Greater than or equal (>=)

Booleans

Booleans

Program: `leapyear.py`

Booleans

Program: `leapyear.py`

- Command-line input: `y` (int)

Booleans

Program: `leapyear.py`

- Command-line input: y (int)
- Standard output: whether y is a leap year or not

Booleans

Program: `leapyear.py`

- Command-line input: `y` (int)
- Standard output: whether `y` is a leap year or not

```
>_ ~/workspace/ipp/programs
```

```
$ _
```

Booleans

Program: `leapyear.py`

- Command-line input: `y` (int)
- Standard output: whether `y` is a leap year or not

```
>_ ~/workspace/ipp/programs
```

```
$ python3 leapyear.py 2020
```

Booleans

Program: `leapyear.py`

- Command-line input: `y` (int)
- Standard output: whether `y` is a leap year or not

```
>_ ~/workspace/ipp/programs
```

```
$ python3 leapyear.py 2020  
True  
$ _
```


Booleans

Program: `leapyear.py`

- Command-line input: `y` (int)
- Standard output: whether `y` is a leap year or not

```
>_ ~/workspace/ipp/programs
```

```
$ python3 leapyear.py 2020
True
$ python3 leapyear.py 1900
```

Booleans

Program: `leapyear.py`

- Command-line input: `y` (int)
- Standard output: whether `y` is a leap year or not

```
>_ ~/workspace/ipp/programs
```

```
$ python3 leapyear.py 2020
True
$ python3 leapyear.py 1900
False
$ _
```

Booleans

Program: `leapyear.py`

- Command-line input: `y` (int)
- Standard output: whether `y` is a leap year or not

```
>_ ~/workspace/ipp/programs
```

```
$ python3 leapyear.py 2020
True
$ python3 leapyear.py 1900
False
$ python3 leapyear.py 2000
```

Booleans

Program: `leapyear.py`

- Command-line input: `y` (int)
- Standard output: whether `y` is a leap year or not

```
>_ ~/workspace/ipp/programs
```

```
$ python3 leapyear.py 2020
True
$ python3 leapyear.py 1900
False
$ python3 leapyear.py 2000
True
$ _
```

Booleans

Booleans

leapyear.py

```
1 import stdio
2 import sys
3
4 y = int(sys.argv[1])
5 result = y % 4 == 0 and y % 100 != 0 or y % 400 == 0
6 stdio.writeln(result)
```

Operator Precedence

1	Postfix increment and decrement	<code>++</code>	<code>--</code>
2	Unary plus and minus	<code>+</code>	<code>-</code>
3	Bitwise NOT	<code>~</code>	
4	Bitwise left shift	<code><<</code>	
5	Bitwise right shift	<code>>></code>	
6	Bitwise AND	<code>&</code>	
7	Bitwise XOR	<code>^</code>	
8	Bitwise OR	<code> </code>	
9	Relational operators	<code><</code>	<code><=</code>
10	Equality operators	<code>==</code>	<code>!=</code>
11	Logical AND	<code>&&</code>	
12	Logical OR	<code>&&</code>	
13	Logical NOT	<code>!</code>	
14	Assignment	<code>=</code>	
15	Compound assignment	<code>+=</code>	<code>-=</code>
16	Conditional (ternary) operator	<code>?:</code>	
17	Comma	<code>,</code>	

Operator Precedence

Operator precedence (highest to lowest)

<code>**</code>	exponentiation
<code>+, -</code>	unary
<code>*, /, //, %</code>	multiplicative
<code>+, -</code>	additive
<code><, <=, >, >=</code>	comparison
<code>==, !=</code>	equality
<code>=, **=, *=, /=, //=, %=, +=, -=</code>	assignment
<code>is, is not</code>	identity
<code>in, not in</code>	membership
<code>not, or, and</code>	logical

Operator Precedence

Operator precedence (highest to lowest)

<code>**</code>	exponentiation
<code>+, -</code>	unary
<code>*, /, //, %</code>	multiplicative
<code>+, -</code>	additive
<code><, <=, >, >=</code>	comparison
<code>==, !=</code>	equality
<code>=, **=, *=, /=, //=, %=, +=, -=</code>	assignment
<code>is, is not</code>	identity
<code>in, not in</code>	membership
<code>not, or, and</code>	logical

Parentheses can be used to override precedence rules

Python Console

The Python Console¹ available in PyCharm can be used as an interactive calculator

¹To launch from terminal, run the command `python3`; and to return to the terminal, run the built-in function `exit()`

Python Console

The Python Console¹ available in PyCharm can be used as an interactive calculator

Example

```
>_ ~/workspace/ipp/programs
```

```
>>> _
```

¹To launch from terminal, run the command `python3`; and to return to the terminal, run the built-in function `exit()`

Python Console

The Python Console¹ available in PyCharm can be used as an interactive calculator

Example

```
>_ ~/workspace/ipp/programs
```

```
>>> 3 ** 2 + 4 ** 2
```

¹To launch from terminal, run the command `python3`; and to return to the terminal, run the built-in function `exit()`

Python Console

The Python Console¹ available in PyCharm can be used as an interactive calculator

Example

```
>_ ~/workspace/ipp/programs
```

```
>>> 3 ** 2 + 4 ** 2  
25  
>>> _
```

¹To launch from terminal, run the command `python3`; and to return to the terminal, run the built-in function `exit()`

Python Console

The Python Console¹ available in PyCharm can be used as an interactive calculator

Example

```
>_ ~/workspace/ipp/programs
```

```
>>> 3 ** 2 + 4 ** 2  
25  
>>> import math
```

¹To launch from terminal, run the command `python3`; and to return to the terminal, run the built-in function `exit()`

Python Console

The Python Console¹ available in PyCharm can be used as an interactive calculator

Example

```
>_ ~/workspace/ipp/programs
```

```
>>> 3 ** 2 + 4 ** 2  
25  
>>> import math  
>>> _
```

¹To launch from terminal, run the command `python3`; and to return to the terminal, run the built-in function `exit()`

Python Console

The Python Console¹ available in PyCharm can be used as an interactive calculator

Example

```
>_ ~/workspace/ipp/programs
```

```
>>> 3 ** 2 + 4 ** 2
25
>>> import math
>>> x = 2
```

¹To launch from terminal, run the command `python3`; and to return to the terminal, run the built-in function `exit()`

The Python Console¹ available in PyCharm can be used as an interactive calculator

Example

```
>_ ~/workspace/ipp/programs
```

```
>>> 3 ** 2 + 4 ** 2
25
>>> import math
>>> x = 2
>>> _
```

¹To launch from terminal, run the command `python3`; and to return to the terminal, run the built-in function `exit()`

The Python Console¹ available in PyCharm can be used as an interactive calculator

Example

```
>_ ~/workspace/ipp/programs
```

```
>>> 3 ** 2 + 4 ** 2
25
>>> import math
>>> x = 2
>>> math.sqrt(x)
```

¹To launch from terminal, run the command `python3`; and to return to the terminal, run the built-in function `exit()`

The Python Console¹ available in PyCharm can be used as an interactive calculator

Example

```
>_ ~/workspace/ipp/programs
```

```
>>> 3 ** 2 + 4 ** 2
25
>>> import math
>>> x = 2
>>> math.sqrt(x)
1.4142135623730951
>>> _
```

¹To launch from terminal, run the command `python3`; and to return to the terminal, run the built-in function `exit()`

Python Console

Python Console

Run `dir(<library>)` to get a list of attributes for a library

Run `dir(<library>)` to get a list of attributes for a library

Example

```
>_ ~/workspace/ipp/programs
```

```
>>> _
```

Python Console

Run `dir(<library>)` to get a list of attributes for a library

Example

```
>_ ~/workspace/ipp/programs
```

```
>>> dir(math)
```


Run `dir(<library>)` to get a list of attributes for a library

Example

```
>_ ~/workspace/ipp/programs
```

```
>>> dir(math)
['__doc__', '__loader__', '__name__', '__package__', '__spec__', 'acos', 'acosh', 'asin', 'asinh',
'atan', 'atan2', 'atanh', 'ceil', 'copysign', 'cos', 'cosh', 'degrees', 'e', 'erf', 'erfc', 'exp',
'expm1', 'fabs', 'factorial', 'floor', 'fmod', 'frexp', 'fsum', 'gamma', 'gcd', 'hypot', 'inf',
'isclose', 'isfinite', 'isinf', 'isnan', 'ldexp', 'lgamma', 'log', 'log10', 'log1p', 'log2', 'modf',
'nan', 'pi', 'pow', 'radians', 'sin', 'sinh', 'sqrt', 'tan', 'tanh', 'tau', 'trunc']
>>> _
```

Python Console

Python Console

Run `help(<library>)` to access documentation for a library

Python Console

Run `help(<library>)` to access documentation for a library

Example

```
>_ ~/workspace/ipp/programs
```

```
>>> _
```

Python Console

Run `help(<library>)` to access documentation for a library

Example

```
>_ ~/workspace/ipp/programs
```

```
>>> help(math)
```

Run `help(<library>)` to access documentation for a library

Example

```
>_ ~/workspace/ipp/programs
>>> help(math)

Help on built-in module math:

NAME
    math

FILE
    (built-in)

DESCRIPTION
    This module is always available. It provides access to the
    mathematical functions defined by the C standard.

FUNCTIONS
    acos(...)
        acos(x)

        Return the arc cosine (measured in radians) of x.
    ...
DATA
    e = 2.718281828459045
    pi = 3.141592653589793
>>> _
```

Python Console

Run `help(<library>.<name>)` to access documentation for a particular function from a library

Run `help(<library>.<name>)` to access documentation for a particular function from a library

Example

```
>_ ~/workspace/ipp/programs
```

```
>>> _
```

Run `help(<library>.<name>)` to access documentation for a particular function from a library

Example

```
>_ ~/workspace/ipp/programs
```

```
>>> help(math.sqrt)
```

Run `help(<library>.<name>)` to access documentation for a particular function from a library

Example

```
>_ ~/workspace/ipp/programs
```

```
>>> help(math.sqrt)
Help on built-in function sqrt in module math:

sqrt(...)
    sqrt(x)

    Return the square root of x.
>>> _
```