

DIDI-UDACITY CHALLENGE

INNOPOLIS UNIVERSITY TEAM
2ND PLACE


Examples: Car I


3D Point Cloud + Radar



IMU+GPS

Detection
and Tracking






Oliver Cameron
Zhaoyin Jia
Ilya Shimchik
Ruslan Mustafin
Peter Norvig
David Silver
Anthony Navarro

CEO, Voyage
Principal Engineer, DiDi Research Lab
Innopolis University
Innopolis University
Research Director, Google
Self-Driving Car Lead, Udacity
Self-Driving Product Lead, Udacity

Architecture



EKF Estimation

State vector:

$$x, y, \varphi, v, a, v_{ego}, \dot{\varphi}_{ego}, a_{ego}$$

System model:

$$x = (v \cos(\varphi) - v_{ego})dt + x \cos(\dot{\varphi}_{ego}dt) - y \sin(\dot{\varphi}_{ego}dt)$$

$$y = v \sin(\varphi)dt + x \sin(\dot{\varphi}_{ego}dt) - y \cos(\dot{\varphi}_{ego}dt)$$

$$\varphi = \varphi - \dot{\varphi}_{ego}dt$$


$$v = v + a dt$$

$$a = a$$

$$v_{ego} = v_{ego} + a_{ego}dt$$

$$\dot{\varphi}_{ego} = \dot{\varphi}_{ego}$$

$$a_{ego} = a_{ego}$$



Main features:

- Speed and rotation of a vehicle is considered
- Delay of sensors data is taken into account

Lidar Object Detection

Lidar




Remove EGO Vehicle

Find and remove Ground Plane

Clusterization


Select a cluster related to vehicle

Shape alignment around the cluster



Shape alignment

- Each particle is a parallelepiped with different parameters: x, y; width, length, height
- We generate a particle in the center of a found cluster using normal distribution
- Each parallelepiped plane has a different weight. The nearest plane has the maximum weight




Particle weight is


$$w = \sum_{i=1}^n w_{pl} e^{-\frac{d_i^2}{2\sigma}}$$

where w_{pl} stands for the weight of the nearest plane, d_i is the distance to the nearest plane from the point i , n is the number of points inside the parallelepiped σ is the weight coefficient of each cloud point

Object detection using Deep Learning (Camera)



Examples: Car II




Examples: Pedestrian

3D Point Cloud + Radar



IMU+GPS

Detection
and Tracking



Team

Background:
Research in the field of Robotics
at Innopolis University

- Nonlinear MPC for a race car
- Getting ready for a competition of autonomous racing cars



Reflections

Tried different approaches and neural networks

Increased performance thanks to reducing the number of cloud points

Added orientation to SSD network instead of using a separate CNN for orientation

Speeded up the development process due to the access to the high-performance GPU

Future work

Improve detection with lidar and stay in realtime

Use a larger training dataset to improve the quality of visual detection

Detect steering wheels position of a car

Multiple object tracking in realtime

Thank you!