DFA DELIVERY TRACKING SYSTEM

An Innovative Assignment for the subject of TOC

Department Of Computer Science & Engineering

Veer Surendra Sai University Of Technology, Burla

Submitted by:

Name: Trishna Das

Registration no.: 2302041055

Semester: 5th

Subject name: Theory of Computation(TOC)

1. Problem Definition

Managing the lifecycle of a package in a modern logistics system is an inherently state-dependent process. The sequence of operations is critical; for instance, a package must be picked up and marked as "In Transit" before it can be "Out for Delivery." Any deviation from this logical flow, such as an incorrect or out-of-sequence status update, can lead to significant problems, including data corruption, customer confusion, operational inefficiencies, and potential financial loss.

Traditional systems may rely on complex conditional logic or loosely enforced business rules, which can become brittle and difficult to maintain as the system scales. This creates a need for a more robust and formally verifiable system that can deterministically manage the state of every package. The core problem, therefore, is to design and implement a system that can reliably enforce the valid sequence of states and transitions for a package's journey, thereby ensuring absolute data integrity and operational predictability from the moment an order is placed to its final resolution.

2. Innovative Idea in My Project

The primary innovation of this project is the direct and transparent application of a formal concept from the Theory of Computation—the **Deterministic Finite Automaton (DFA)**—as the central logic engine for a real-world, full-stack application.

Many systems use state machines, but they often function as a hidden "black box" within the backend. This project differentiates itself by employing a **"glass box" approach**, making the underlying theoretical model a visible and interactive part of the user experience. This innovation is manifested through two key features:

- **The Live State Diagram:** The customer-facing tracking page does not just display a status like "In Transit." It simultaneously displays the complete DFA state diagram and visually highlights the package's current state in real-time. This creates an immediate and intuitive link between the abstract computer science model and the live, practical status of the delivery.
- **The Rule-Driven Administrative Interface:** The admin simulator is a direct reflection of the DFA's transition function (δ). Instead of presenting a static list of actions, the user interface is dynamically generated based on the package's current state. It only allows an admin to trigger events that are defined as valid transitions in the DFA's rule set. For example, if a package is "Out for Delivery" (state q2), only the "Delivery Successful" (event s) or "Delivery Failed" (event f) actions are enabled. This makes the theoretical rules tangible and demonstrates their enforcement in a practical setting.

3. Description

3.1 System Architecture and Design

This project is a full-stack, real-time delivery tracking system built with a Python (FastAPI) backend, a React frontend, and a MongoDB database. The entire system's architecture and logic are governed by a formally defined Deterministic Finite Automaton that models the complete package delivery lifecycle. The application provides a seamless user experience, from package creation to live tracking.

Application Workflow & Features

The user journey begins at the home page, where a new package can be created with a single click. The system automatically captures the user's current GPS location to serve as the package's origin point. Upon creation, a unique tracking ID is generated, allowing the user to navigate to a dedicated tracking page.



The tracking page is the core of the user experience. It features a real-time map displaying the package's current location, a timeline of its historical events, and, most importantly, a visual representation of the DFA State Diagram. This diagram dynamically highlights the package's current state (e.g., "q0 - Order Placed"), providing a direct, visual connection to the underlying computational model. The entire page updates live via WebSockets, ensuring the user always has the most current information without needing to refresh.



Technical Implementation

- **Backend:** A high-performance API built with **FastAPI (Python)** manages all business logic, including the enforcement of the DFA's transition rules. It handles data persistence with **MongoDB** and pushes real-time updates to clients using **WebSockets**.
- **Frontend:** A modern, responsive user interface built with **React and TypeScript**. It uses the **React Leaflet** library for map visualization and establishes a WebSocket connection to the backend to receive live data updates.



	currentLocation	currentState	history	trackingId
304b5"}	{"type":"Point","coordinates":[85.83339999999997,20.270600000000002]}	q6	[{"event":"CREATE","state":"q0","timestamp":{"$date":"2025-10-12T16:0…	C6soHxAHg6
304b6"}	{"type":"Point","coordinates":[85.83339999999997,20.270600000000002]}	q3	[{"event":"CREATE","state":"q0","timestamp":{"$date":"2025-10-12T16:0…	vg1ovSZ836
37b08"}	{"type":"Point","coordinates":[85.83339999999997,20.270600000000002]}	q0	[{"event":"CREATE","state":"q0","timestamp":{"$date":"2025-10-12T16:2…	Xb9PtcEC6Q
1eec5"}	{"type":"Point","coordinates":[85.83339999999997,20.270600000000002]}	q2	[{"event":"CREATE","state":"q0","timestamp":{"$date":"2025-10-12T16:2…	gUrVIkb5OI
36f22"}	{"type":"Point","coordinates":[85.83339999999997,20.270600000000002]}	q3	[{"event":"CREATE","state":"q0","timestamp":{"$date":"2025-10-12T16:4…	sMCDQCzKi1
35036"}	{"type":"Point","coordinates":[85.83339999999997,20.270600000000002]}	q4	[{"event":"CREATE","state":"q0","timestamp":{"$date":"2025-10-12T16:4…	3JMH05OL4Z
35037"}	{"type":"Point","coordinates":[85.83339999999997,20.270600000000002]}	q2	[{"event":"CREATE","state":"q0","timestamp":{"$date":"2025-10-12T16:4…	Nu96bhFCF7
35038"}	{"type":"Point","coordinates":[85.83339999999997,20.270600000000002]}	q4	[{"event":"CREATE","state":"q0","timestamp":{"$date":"2025-10-12T16:4…	oEiQYFViNh
35039"}	{"type":"Point","coordinates":[85.83339999999997,20.270600000000002]}	q6	[{"event":"CREATE","state":"q0","timestamp":{"$date":"2025-10-12T16:5…	GmpjSk7FCT
3503a"}	{"type":"Point","coordinates":[85.83339999999997,20.270600000000002]}	q4	[{"event":"CREATE","state":"q0","timestamp":{"$date":"2025-10-12T16:5…	EQWtErrziX
3503b"}	{"type":"Point","coordinates":[85.83339999999997,20.270600000000002]}	q3	[{"event":"CREATE","state":"q0","timestamp":{"$date":"2025-10-12T16:5…	RL5iFBLlbO
3503c"}	{"type":"Point","coordinates":[85.83339999999997,20.270600000000002]}	q3	[{"event":"CREATE","state":"q0","timestamp":{"$date":"2025-10-12T17:1…	50X1IuKTRb
af417"}	{"type":"Point","coordinates":[85.83339999999997,20.270600000000002]}	q6	[{"event":"CREATE","state":"q0","timestamp":{"$date":"2025-10-13T03:4…	bfxOG_IKQ8
913cb"}	{"type":"Point","coordinates":[85.83339999999997,20.270600000000002]}	q0	[{"event":"CREATE","state":"q0","timestamp":{"$date":"2025-10-13T03:5…	28yf2Y_R9y
48732"}	{"type":"Point","coordinates":[84.86839999999994,22.2254]}	q0	[{"event":"CREATE","state":"q0","timestamp":{"$date":"2025-10-16T07:0…	5QekyRQGGB

Mongodb Database

4. Societal Impact of the Project.

Increased Transparency and Consumer Trust

In the age of e-commerce, the period between purchase and delivery is often a source of anxiety for consumers. This project's model directly addresses this by providing a clear, real-time, and verifiable view of a package's journey. By showing not just *where* a package is but also its precise operational state, it demystifies the shipping process. This level of transparency builds significant trust between businesses and their customers and improves the overall user experience.

Improved Logistical Integrity and Efficiency

For businesses, a system built on a formal model like a DFA guarantees that operational protocols are rigorously followed. It programmatically prevents invalid or out-of-sequence status updates, which are a common source of errors in complex logistics chains. This leads to reduced errors, minimized fraud, and enhanced efficiency by providing reliable data for planning and resource allocation.

5. Conclusion

This project successfully achieved its primary goal of bridging the gap between theoretical computer science and practical software engineering. By implementing a full-stack delivery tracking system governed by a Deterministic Finite Automaton, it was demonstrated that formal models can serve as a robust and elegant foundation for building reliable, state-driven applications. The final product not only functions as modern logistics.