

Cheat Sheet

Cascading Style Sheets (CSS 3)

Powered by  **HOSTINGER**



LIST OF CONTENTS

CONTENT	PAGE	CONTENT	PAGE
BACKGROUND	1	PSUEDO-CLASS	9
BORDER	1	PSUEDO-ELEMENTS	9
TABLE	1	UI	9
BOX MODEL	2		
TRANSITIONS	2	UNITS	10
COLOR	3	ANGELS	10
FONT	3	ABSOLUTE MEASUREMENT	10
ANIMATIONS	4	COLORS	10
COLUMN	4	FREQUENCY	10
TEXT	4	RELATIVE MEASUREMENT	10
SPEECH	5	TIME	10
TEMPLATE LAYOUT	5		
3D / 2D TRANSFORM	6	SELECTOR TYPES	11
GRID POSITIONING	6		
HYPERLINK	6		
LIST AND MARKERS	6		
OUTLINE	6		
GENERATED CONTENT	7		
POSITIONING	7		
RUBY	7		
LINE BOX	8		
PAGED MEDIA	8		

Hostinger Tutorials

BACKGROUND

background	<i>background-image</i> <i>background-position</i> <i>background-size</i> <i>background-repeat</i> <i>background-attachment</i> <i>background-origin</i> <i>background-clip</i> <i>background-color</i>
background-attachment	scroll fixed
background-break	bounding-box each-box continuous
background-clip	<i>length</i> % border-box padding-box content-box no-clip
background-color	<i>color</i> transparent
background-image	<i>url</i> none
background-origin	border-box padding-box content-box
background-position	top left top center top right center left center center center right bottom left bottom center bottom right <i>x-% y-%</i> <i>x-pos y-pos</i>
background-repeat	repeat repeat-x repeat-y no-repeat
background-size	<i>length</i> % auto cover contain

BORDER

border	<i>border-width</i> <i>border-style</i> <i>border-color</i>
border-break	<i>border-width</i> <i>border-style</i> <i>color</i> close
border-bottom	<i>border-bottom-width</i> <i>border-style</i> <i>border-color</i>
border-bottom-color	<i>border-color</i>
border-bottom-style	<i>border-style</i>
border-bottom-width	thin medium thick <i>length</i>
border-collapse	collapse separate
border-color	<i>color</i>
border-image	<i>image</i> [<i>number</i> / % <i>border-width</i> stretch repeat round] none
border-left	<i>border-left-width</i> <i>border-style</i> <i>border-color</i>
border-left-color	<i>border-color</i>
border-left-style	<i>border-style</i>
border-left-width	thin medium thick <i>length</i>
border-right	<i>border-right-width</i> <i>border-style</i> <i>border-color</i>
border-right-color	<i>border-color</i>
border-right-style	<i>border-style</i>
border-right-width	thin medium thick <i>length</i>

TABLE

border-collapse	collapse separate
border-spacing	<i>length length</i>
caption-side	top bottom left right
empty-cells	show hide
table-layout	table-layout auto fixed

BORDER

border-top	<i>border-top-width</i> <i>border-style</i> <i>border-color</i>
border-top-color	<i>border-color</i>
border-top-style	<i>border-style</i>
border-top-width	thin medium thick <i>length</i>
border-width	thin medium thick <i>length</i>
border-radius	<i>border-top-right-radius</i> <i>border-bottom-right-radius</i> <i>border-bottom-left-radius</i> <i>border-top-left-radius</i>
border-top-right-radius	<i>length</i>
border-bottom-right-radius	<i>length</i>
border-bottom-left-radius	<i>length</i>
border-top-left-radius	<i>length</i>
box-shadow	inset [<i>length</i> , <i>length</i> , <i>length</i> , <i>length</i> <color>] none
border-style	none hidden dotted dashed solid double groove ridge inset outset

TRANSITIONS

transition	<i>transition-property</i> <i>transition-duration</i> <i>transition-timing-function</i> <i>transition-delay</i>
transition-delay	<i>time</i>
transition-duration	<i>time</i>
transition-property	none all
transition-timing-function	ease linear ease-in ease-out ease-in-out cubic-Bezier (number, number, number, number)

BOX MODEL

clear	left right both none
display	none inline block inlineblock list-item run-in compact table inlinetable table-row-group table-header-group tablefooter- group table-row table-column-group tablecolumn table-cell tablecaption ruby ruby-base ruby-text ruby-base-group ruby-text-group
float	left right none
height	auto <i>length</i> %
max-height	none <i>length</i> %
max-width	none <i>length</i> %
min-height	none inherit <i>length</i> %
min-width	none inherit <i>length</i> %
width	auto % <i>length</i>
margin	<i>margin margin-top</i> <i>margin-right</i> <i>margin-bottom</i> <i>margin-left</i>
margin-bottom	auto <i>length</i> %
margin-left	auto <i>length</i> %
margin-right	auto <i>length</i> %

BOX MODEL

margin-top	auto length %
padding	padding padding-top padding-right padding-bottom padding-left
padding-bottom	length %
padding-left	length %
padding-right	length %
padding-top	length %
marquee-direction	forward reverse
marquee-loop	infinite number
marquee-play-count	infinite integer
marquee-speed	slow normal fast
marquee-style	scroll slide alternate
overflow	visible hidden scroll auto no-display nocontent overflow-x overflow-y
overflow-style	auto marquee-line marquee- block
overflow-x	visible hidden scroll auto no-display nocontent
overflow-y	visible hidden scroll auto no-display nocontent
rotation	angle
rotation-point	position (paired value offset)
visibility	visibility visible hidden collapse

FONT

font	font-style font-variant font-weight font-size/line-height font-family caption icon menu message-box smallcaption status-bar
font-family	family-name generic-family inherit
font-size	xx-small x-small small medium large x-large xx-large smaller larger inherit length %
font-size-adjust	none inherit number
font-stretch	normal wider narrower ultra-condensed extracondensed condensed semi-condensed semiexpanded expanded extra-expanded ultraexpanded inherit
font-style	normal italic oblique inherit
font-variant	normal small-caps inherit
font-weight	normal bold bolder lighter 100 200 300 400 500 600 700 800 900 inherit

COLOR

color	inherit color
opacity	inherit number

TEXT

direction	ltr rtl inherit
hanging-punctuation	none [start end endedge]
letter-spacing	normal length %
punctuation-trim	none [start end adjacent]
text-align	start end left right center justify
text-align-last	start end left right center justify
text-decoration	none underline overline line-through blink
text-emphasis	none [[accent dot circle disc] [before after]?]
text-indent	length %
text-justify	auto inter-word interideograph inter-cluster distribute kashida tibetan
text-outline	none color length
text-shadow	none color length
text-transform	none capitalize uppercase lowercase
text-wrap	normal unrestricted none suppress
unicode-bidi	normal embed bidioverride
white-space	normal pre nowrap prewrap pre-line
white-space-collapse	preserve collapse preserve-breaks discard
word-break	normal keep-all loose break-strict break-all
word-spacing	normal length %
word-wrap	normal break-word

COLUMN

column-count	auto number
column-fill	auto balance
column-gap	normal length
column-rule	column-rule-width column-rule-style column-rule-color
column-rule-color	color
column-rule-style	border-style
column-rule-width	thin medium thick length
columns	column-width column-count
column-span	1 all
column-width	auto length

ANIMATIONS

animation	animation-name animation-duration animation-timing-function animation-delay animation-iteration-count animation-direction
animation-delay	time
animation-direction	normal alternate
animation-duration	time
animation-iteration-count	inherit number
animation-name	none IDENT
animation-play-state	running paused
animation-timing-function	ease linear ease-in ease-out ease-in-out cubic-Bezier (number, number, number, number)

SPEECH

cue	<i>cue-before</i> <i>cue-after</i>
cue-before	<i>uri</i> [silent x-soft soft medium loud x-loud] none inherit <i>number</i> %
cue-after	<i>uri</i> [silent x-soft soft medium loud x-loud] none inherit <i>number</i> %
mark	<i>mark-before</i> <i>mark-after</i>
mark-before	<i>string</i>
mark-after	<i>string</i>
pause	<i>pause-before</i> <i>pause-after</i>
pause-before	none x-weak weak medium strong x-strong inherit <i>time</i>
pause-after	none x-weak weak medium strong x-strong inherit <i>time</i>
phonemes string	<i>string</i>
rest	<i>rest-before</i> <i>rest-after</i>
rest-before	none x-weak weak medium strong x-strong inherit <i>time</i>
rest-after	none x-weak weak medium strong x-strong inherit <i>time</i>
speak	none normal spell-out digits literal-punctuation no-punctuation inherit
voice-balance	left center right leftwards rightwards inherit <i>number</i>
voice-duration	<i>time</i>

SPEECH

voice-family	inherit [<specific-voice, age, generic-voice, number>]
voice-rate	x-slow slow medium fast x-fast inherit %
voice-pitch	x-low low medium high x-high inherit <i>number</i> %
voice-pitch-range	x-low low medium high x-high inherit <i>number</i>
voice-stress	strong moderate none reduced inherit
voice-volume	silent x-soft soft medium loud x-loud inherit <i>number</i> %

TEMPLATE LAYOUT

box-align	start end center base
box-direction	normal reverse
box-flex	<i>number</i>
box-flex-group	<i>integer</i>
box-lines	single multiple
box-orient	horizontal vertical inlineaxis block-axis
box-pack	start end center justify
box-sizing	content-box padding-box border-box margin-box
tab-side	top bottom left right

LIST & MARKERS

list-style	<i>list-style-type</i> <i>list-style-position</i> <i>list-style-image</i>
list-style-image	none url
list-style-position	Inside outside
list-style-type	none asterisks box check circle diamond disc hyphen square decimal decimal-leading-zero lower-roman upper-roman lower-alpha upper-alpha lower-greek lower-latin upper-latin hebrew armenian georgian cjk-ideographic hiragana katakana hiragana-iroha katakana-iroha footnotes
marker-offset	auto length

GRID POSITIONING

grid-columns	none inherit [length percentage relative length]
grid-rows	none inherit [length percentage relative length]

OUTLINE

outline	<i>outline-color</i> <i>outline-style</i> <i>outline-width</i>
outline-color	color invert
outline-offset	inherit length
outline-style	None dotted dashed solid double groove ridge inset outset
outline-width	thin medium thick length

3D / 2D TRANSFORM

backface-visibility	visible hidden
perspective	none number
perspective-origin	[[[percentage> <length> left center right] [<percentage> <length> top center bottom]?] <length>] [[[left center right] [top center bottom]] <length>]
transform	none matrix matrix3d translate3d translateX translateY translateZ scale scale3d scaleX scaleY scaleZ rotate rotate3d rotateX rotateY rotateZ skewX skewY skew perspective
transform-origin	[[[<percentage> <length> left center right] [<percentage> <length> top center bottom]?] <length>] [[[left center right] [top center bottom]] <length>]
transform-style	flat preserve-3d

HYPERLINK

target	<i>target-name</i> <i>target-new</i> <i>target-position</i>
target-name	current root parent new modal string
target-new	window tab none
target-position	above behind front back

GENERATED CONTENT

bookmark-label	content attr string
bookmark-level	none integer
bookmark-target	self uri attr
border-length	auto length
content	normal none inhibit uri
counter-increment	none identifier number
counter-reset	none identifier number
crop	auto shape
display	normal none list-item
float-offset	length length
hyphenate-after	auto integer
hyphenate-before	auto integer
hyphenate-character	auto integer
hyphenate-lines	no-limit integer
hyphenate-resource	none uri
hyphens	none manual auto
image-resolution	normal auto dpi
marks	[crop cross] none
move-to	normal here identifier
page-policy	start first last
quotes	none string string string string

GENERATED CONTENT

string-set	identifier content-list
text-replace	none [<string> <string>]+

POSITIONING

bottom	auto % length
clip	shape auto
left	auto % length
position	static relative absolute fixed
right	auto % length
top	auto % length
z-index	auto number

RUBY

ruby-align	auto start left center end right distribute-letter distribute-space lineedge
ruby-overhang	auto start end none
ruby-position	before after right inline
ruby-span	attr(x) none

LINE BOX

alignment-adjust

auto | baseline | before-edge
| text-before-edge |
middle | central | after-edge
| text-after-edge | ideographic
| alphabetic | hanging
| mathematical
length
%

alignment-baseline

baseline | use-script | before-
edge | text-before-edge
| after-edge | text-after-
edge | central | middle
| ideographic | alphabetic |
hanging | mathematical

baseline-shift

baseline | sub | super
length
%

dominant-baseline

auto | use-script | nochange
| reset-size | alphabetic
| hanging | ideographic
| mathematical |
central | middle | text-after-
edge | text-before-edge

drop-initial-after-align

alignment-baseline

drop-initial-after-adjust

central | middle | after-edge
| text-after-edge | ideographic
| alphabetic |
mathematical
length
%

drop-initial-before-align

caps-height
alignment-baseline

drop-initial-before-adjust

before-edge | text-before-edge
| central | middle |
hanging | mathematical
length
%

drop-initial-value

initial
integer

drop-initial-size

auto
integer
%
line

inline-box-align

initial | last
integer

line-height

normal
number
length
%

LINE BOX

line-stacking

line-stacking-strategy
line-stacking-ruby
line-stacking-shift

line-stacking-strategy

inline-line-height | blockline-
height | max-height |
grid-height

line-stacking-ruby

exclude-ruby | include-ruby

line-stacking-shift

consider-shifts | disregardshifts

text-height

auto | font-size | text-size |
max-size

vertical-align

Baseline | sub | super | top
| text-top | middle | bottom
| text-bottom
length
%

PAGED MEDIA

fit

fill | hidden | meet | slice

fit-position

[top | center | bottom] | |
[left | center | right]
length
%

image-orientation

auto
angle

orphans

integer

page

auto
identifier

page-break-after

auto | always | avoid | left |
right

page-break-before

auto | always | avoid | left |
right

page-break-inside

auto | avoid

size

auto | landscape | portrait
length

windows

integer

UI

appearance	normal inherit [icon window desktop workspace document tooltip dialog button pushbutton hyperlink radiobutton checkbox menuitem tab menu menubar pull-down-menu pop-up-menu list-menu radio-group checkboxgroup outline-tree range field combo-box signature password]
cursor	auto crosshair default pointer move e-resize ne-resize nw-resize nresize se-resize sw-resize s-resize w-resize text wait help url
icon	auto inherit url
nav-index	auto inherit number
nav-up	auto inherit <id> [current root <target-name>]
nav-right	auto inherit <id> [current root <target-name>]
nav-down	auto inherit <id> [current root <target-name>]
nav-left	auto inherit <id> [current root <target-name>]
resize	none both horizontal vertical inherit

PSEUDO-CLASS

:active	an activated element
:focus	an element while the element has focus
:visited	a visited link
:hover	an element when you mouse over it
:link	an unvisited link
:disabled	an element while the element is disabled
:enabled	an element while the element is enabled
:checked	an element (form element control) that is checked
:selection	an element that is currently selected or highlighted by the user
:lang	Allows the author to specify a language to use in a specified element
:nth-child(n)	an element that is the n-th sibling
:nth-last-child(n)	an element that is the n-th sibling counting from the last sibling
:first-child	an element that is the first sibling
:last-child	an element that is the last sibling
:only-child	an element that is the only child
:nth-of-type(n)	an element that is the n-th sibling of its type.
:nth-last-of-type(n)	an element that is the n-th sibling of its type counting from the last sibling
:last-of-type	an element that is the first sibling of its type
:first-of-type	an element that is the last sibling of its type
:only-of-type	an element that is the only child of that type
:empty	an element that has no children
:root	root element within the document
:not(x)	an element not represented by the argument 'x'
:target	a target element as specified by a target in a URI

PSEUDO-ELEMENT

::first-letter	Adds special style to the first letter of a text
::first-line	Adds special style to the first line of a text
::before	Inserts some content before an element
::after	Inserts some content after an element

UNITS

ABSOLUTE MEASUREMENT

%	percentage
cm	centimeter
in	inch
mm	millimeter
pc	pica (1p = 12 points)
pt	point (1pt = 1/72 inch)

RELATIVE MEASUREMENT

ch	width of the "0" glyph found in the font for the font size used to render
em	1em = current font size of current element
ex	x-height of the element's font
gd	the grid defined by 'layout-grid'
px	pixel of the viewing device
rem	the font size of the root element
vh	the viewport's height
vw	the viewport's width
vm	viewport's height or width, whichever is smaller of the two

ANGLES

deg	degrees
grad	grads
rad	radians
turn	turns

FREQUENCY

Hz	hertz
kHz	kilo-hertz

TIME

ms	milli-seconds
s	seconds

COLORS

color name	red, blue, green, dark green
rgb(x,y,z)	red = rgb(255,0,0)
rgb(x%,y%,z%)	red = rgb(100%,0,0)
rgba(x,y,z, alpha)	red = rgba(255,0,0)
#rrggbb	red = #ff0000 (or shorthand = #f00)
hsl(hue, saturation, lightness)	red = hsl(0, 100%, 50%)
hsla(hue, saturation, lightness, alpha)	red = hsl(0, 100%, 50%)
flavor	An accent color (typically chosen by the user) to customize the user interface of the user agent itself
currentColor	computed value of the 'currentColor' keyword is the computed value of the 'color' property

Name	Info	Example
Universal	Any element	<code>* { font: 10px Arial; }</code>
Type	Any element of that type	<code>h1 { text-decoration: underline; }</code>
Grouping	Multiple elements of different types	<code>h1, h2, h3 { font-family: Verdana; }</code>
Class	Multiple elements of different types when you don't want to affect all instances of that type	<code>.sampleclass { text-decoration: underline; }</code>
Id	A single element type when you don't want to affect all instances of that type	<code>#sampleid { text-decoration: underline; }</code>
Descendant	An element that is below (in the document tree) another element—no matter how many levels below	<code>#gallery h1 { text-decoration: underline; }</code>
Child	An element that is directly below (in the document tree) another element	<code>#title > p { font-weight: bold; }</code>
Adjacent Sibling	All elements that share the same parent and elements are in the same immediate sequence	<code>h1 + p { font-style: italic; }</code>
General Sibling	All elements that share the same parent and elements are in the same sequence (not necessarily immediate)	<code>h1 ~ p { font-style: italic; }</code>
Attribute	An element with that matches the attribute listed	<code>E[selected]</code> - att whatever the value <code>E[att="val"]</code> - att with a specific value <code>E[rel~="next"]</code> - att with a value is a whitespace separated list <code>*[lang = "en"]</code> - att value either being exactly "val" or beginning with "val" immediately followed by "-" <code>E[att^="val"]</code> - att value that begins with the prefix "val" <code>E[att\$="val"]</code> - att value that end with the suffix "val" <code>E[att*="val"]</code> - att value contains at least one instance of the substring "val"