# Lab 3

Samrith Sanjoo.S
**1BM21CS185**

Create a topology consisting of 2 devices connected with the help of a router.

Using multiple routers:

Show ip commands and ping commands

Screenshot 1 — Router0 CLI:

```
          periodic downloaded static route

Gateway of last resort is not set

C    10.0.0.0/8 is directly connected, FastEthernet0/0
C    20.0.0.0/8 is directly connected, Serial2/0
S    40.0.0.0/8 [1/0] via 20.0.0.2
Router#configure terminal
Enter configuration commands, one per line.  End with CNTL/Z.
Router(config)#ip route 30.0.0.0 255.0.0.0 20.0.0.2
Router(config)#exit
Router#
%SYS-5-CONFIG_I: Configured from console by console
show ip route
Codes: C - connected, S - static, I - IGRP, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2, E - EGP
       i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2, ia - IS-IS inter area
       * - candidate default, U - per-user static route, o - ODR
       P - periodic downloaded static route

Gateway of last resort is not set

C    10.0.0.0/8 is directly connected, FastEthernet0/0
C    20.0.0.0/8 is directly connected, Serial2/0
S    30.0.0.0/8 [1/0] via 20.0.0.2
S    40.0.0.0/8 [1/0] via 20.0.0.2
                 [1/0] via 30.0.0.1
Router#
```


Screenshot 2 — Router1 CLI:

```
Router>enable
Router#configure terminal
Enter configuration commands, one per line.  End with CNTL/Z.
Router(config)#ip route 40.0.0.0 255.0.0.0 30.0.0.2
Router(config)#ip route 10.0.0.0 255.0.0.0 20.0.0.1
Router(config)#exit
Router#
%SYS-5-CONFIG_I: Configured from console by console
show ip route
Codes: C - connected, S - static, I - IGRP, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2, E - EGP
       i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2, ia - IS-IS inter area
       * - candidate default, U - per-user static route, o - ODR
       P - periodic downloaded static route

Gateway of last resort is not set

S    10.0.0.0/8 [1/0] via 20.0.0.1
C    20.0.0.0/8 is directly connected, Serial2/0
C    30.0.0.0/8 is directly connected, Serial3/0
S    40.0.0.0/8 [1/0] via 30.0.0.2
Router#
```

Router3 — IOS Command Line Interface

```
Router(config-if)#ip address 40.0.0.1 255.0.0.0
Router(config-if)#no shutdown
Router(config-if)#exit
Router(config)#exit
Router#
%SYS-5-CONFIG_I: Configured from console by console
enable
Router#configure terminal
Enter configuration commands, one per line.  End with CNTL/Z.
Router(config)#ip route 10.0.0.0 255.0.0.0 30.0.0.1
Router(config)#exit
Router#
%SYS-5-CONFIG_I: Configured from console by console
show ip route
Codes: C - connected, S - static, I - IGRP, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2, E - EGP
       i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2, ia - IS-IS inter area
       * - candidate default, U - per-user static route, o - ODR
       P - periodic downloaded static route

Gateway of last resort is not set

S    10.0.0.0/8 [1/0] via 30.0.0.1
S    20.0.0.0/8 [1/0] via 30.0.0.1
C    30.0.0.0/8 is directly connected, Serial2/0
C    40.0.0.0/8 is directly connected, FastEthernet0/0
Router#
```

PC0 — Command Prompt

```
Ping statistics for 20.0.0.2:
    Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),

PC>ping 40.0.0.1

Pinging 40.0.0.1 with 32 bytes of data:

Reply from 40.0.0.1: bytes=32 time=1ms TTL=253
Reply from 40.0.0.1: bytes=32 time=1ms TTL=253
Reply from 40.0.0.1: bytes=32 time=0ms TTL=253
Reply from 40.0.0.1: bytes=32 time=0ms TTL=253

Ping statistics for 40.0.0.1:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 0ms, Maximum = 1ms, Average = 10ms

PC>ping 40.0.0.2

Pinging 40.0.0.2 with 32 bytes of data:

Request timed out.
Reply from 40.0.0.2: bytes=32 time=1ms TTL=125
Reply from 40.0.0.2: bytes=32 time=1ms TTL=125
Reply from 40.0.0.2: bytes=32 time=0ms TTL=125

Ping statistics for 40.0.0.2:
    Packets: Sent = 4, Received = 3, Lost = 1 (25% loss),
Approximate round trip times in milli-seconds:
```

File   Edit   Options   View   Tools   Extensions   Help

Logical   [Root]   New Cluster   Move Object   Set Tiled Background   Viewport

PC0   — □ ✕

Physical   Config   **Desktop**   Custom Interface

Command Prompt   X

```
Ping statistics for 20.0.0.2:
    Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),

PC>ping 40.0.0.1

Pinging 40.0.0.1 with 32 bytes of data:

Reply from 40.0.0.1: bytes=32 time=11ms TTL=253
Reply from 40.0.0.1: bytes=32 time=11ms TTL=253
Reply from 40.0.0.1: bytes=32 time=10ms TTL=253
Reply from 40.0.0.1: bytes=32 time=8ms TTL=253

Ping statistics for 40.0.0.1:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 8ms, Maximum = 11ms, Average = 10ms

PC>ping 40.0.0.2

Pinging 40.0.0.2 with 32 bytes of data:

Request timed out.
Reply from 40.0.0.2: bytes=32 time=12ms TTL=125
Reply from 40.0.0.2: bytes=32 time=11ms TTL=125
Reply from 40.0.0.2: bytes=32 time=10ms TTL=125

Ping statistics for 40.0.0.2:
    Packets: Sent = 4, Received = 3, Lost = 1 (25% loss),
Approximate round trip times in milli-seconds:
```

Fa0   Fa0

PC-PT   PC-PT
PC0   PC1

Time: 00:55:23   Power Cycle Devices Fast Forward Time   **Realtime**

Routers   Scenario 0

1841 1941 2620XM 2621XM 2811 2901 2911 819 Generic Generic   New   Delete

                                                        Toggle PDU List Window

(Select a Device to Drag and Drop to the Workspace)   Fire Last Status Source Destination Type Color Time(sec) Periodic Num Edit Delete

29°C   ENG   15:07
Partly sunny   Search   IN   30-06-2023