

# Deep Q-Learning for NLP

Chris Kedzie

kedzie@cs.columbia.edu

Francisco Javier Arceo

fja2114@columbia.edu

August 24, 2016

## 1 Brain Dump

Input Data: Streaming Queries from the time of query until an hour before the time of query.

Step 1: ?

Step 2: ?

Output: Summarization of relevant Queries.

Last hidden layer of an LSTM-RNN will be a k-dimensional embedding of a given sentence.

Use Deep Q Learning framework based on [2] and [1].

## 2 Useful Links

Just adding some links to useful things

<http://trec.nist.gov/>

[http://icml.cc/2016/tutorials/deep\\_rl\\_tutorial.pdf](http://icml.cc/2016/tutorials/deep_rl_tutorial.pdf)

## References

- [1] Volodymyr Mnih, Adrià Puigdomènech Badia, Mehdi Mirza, Alex Graves, Timothy P. Lillicrap, Tim Harley, David Silver, and Koray Kavukcuoglu. Asynchronous methods for deep reinforcement learning. *CoRR*, abs/1602.01783, 2016.
- [2] Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Alex Graves, Ioannis Antonoglou, Daan Wierstra, and Martin A. Riedmiller. Playing atari with deep reinforcement learning. *CoRR*, abs/1312.5602, 2013.