

News event: Events for the versatile news system

Extension Key: roq_newsevent

Language: en

Version: 1.0.6 (rev. 60)

Keywords: forEditors, forAdmins, forBeginners, forIntermediates

Copyright 2006-2012, ROQUIN B.V., <extensions@roquin.nl>

This document is published under the Open Content License
available from <http://www.opencontent.org/opl.shtml>

The content of this document is related to TYPO3
- a GNU/GPL CMS/Framework available from www.typo3.org

Table of Contents

News event: Events for the versatile news system.....	1	Configuration.....	7
Introduction.....	3	Plugin.....	7
What does it do?.....	3	TypoScript reference.....	7
Screenshots.....	3	Database reference.....	8
User's manual.....	4	Tutorial.....	9
About news event records.....	4	General.....	9
Administration.....	5	How to add an event section to your site.....	9
Archiving.....	5	Updating from version 2.0.x.....	10
RSS.....	5	Updating from version 2.1.2 to 2.1.3.....	12
iCalendar (ICS).....	5	Known problems.....	13
		To-Do list.....	14
		ChangeLog.....	15

Introduction

What does it do?

The news event extension extends the versatile news system extension with additional event functionality. The news event extension is based on Extbase and Fluid.

Screenshots

This section shows screenshots of the news event extension. Please note that only the settings which are applicable for the news event extension are visible.




Image 1: News plugin with available event views




Image 2: Mark a news record as event, and add event data

User's manual

About news event records

The records can be created on any page, however it is recommended to create a separate sysfolder for news event records (next to a sysfolder in which you store your news records).

See the [Tutorial](#) section for more information about how to use the news event extension.

News event records

Field:	Description:	Required:
Is event	Mark a news records as an event. If this has been enabled, the news record will be recognized as an news event record.	No
Start date	Start date of the event. Note: If the start date has been left empty or undefined, the event will not be visible in the frontend.	Yes
Start time	Start time of the event.	No
End date	End date of the event. This makes an event multiple days unless this date is the same as the start date. In this case you don't have to define the end date.	No
End time	End time of a the event.	No
Location	Location where the event takes place. For instance: Washington D.C.	No

Administration

Archiving

News records are archived by using the archive date restriction or time restriction settings. These settings are not used for news events records, and archiving for events works a bit differently. Events which are current or will occur in the future (based on the event data) are known as 'active', and all past events are known as 'archived'. You must select either 'active' or 'archived' when configuring an added news plugin for news events. See the section [Configuration](#) → [Plugin](#) for more information.

RSS

News event supports RSS feeds, which is handled like an event list view plugin. You can create an RSS feed exactly the same as adding an RSS feed for News. See the manual for the news system extension for more information. The default template for the output is stored in: Resources/Private/Templates/News/EventList.xml.

The xml file type is achieved by setting:

```
plugin.tx_news.settings.format = xml
```

iCalendar (ICS)

Next to RSS, the news event extension also supports the iCalendar (ICS) format. See: <http://en.wikipedia.org/wiki/ICalendar> for more information about the iCalendar format.

The news event extension comes with two default ICS templates:

- For listing all events (like the Event List view), which is located in: Resources/Private/Templates/News/EventList.ics;
- per single event (like the Event Detail view), which is located in: Resources/Private/Templates/News/EventDetail.ics.

Both default templates use the same partial, which is located at: Resources/Private/Partials/Events/Item.ics.

ICS support by embedding the plugin with TypoScript

This section describes how you can create an ICS page for all and/or single events on your website by using TypoScript.

ICS for all events

See the TypoScript below as an example in which all active events are shown:

```
page = PAGE
page {
    typeNum = 9828
    10 < tt_content.list.20.news_pi1
    10 {
        switchableControllerActions {
            News {
                1 = eventList
            }
        }
        settings {
            format = ics
            archiveRestriction = active
            startingpoint = [sysFolderID]
        }
    }
}

config {
    disableAllHeaderCode = 1
    xhtml_cleaning = none
    admPanel = 0
}
```

```

        disablePrefixComment = 1
        metaCharset = utf-8
        additionalHeaders = Content-Type:text/calendar;charset=utf-8
    }

```

As shown in the TypoScript above a the string *Content-Type:text/calendar;charset=utf-8* will be added to the HTTP header with the additionalHeaders setting, which causes the ICS page to be interpret as an iCalendar file.

Because of this, the ICS data can be included directly into the website user's local calendar (like Apple iCal, Google Calendar, Microsoft Outlook etc.). Depending on the browser, the website user will be prompted with a pop-up box if the current event should be added to his or her local calendar.

ICS for single events

If you want to create a single ICS per event, you can use the same TypoScript code as above, but you'll need to set the controller action to eventDetail instead of eventList:

```

SwitchableControllerActions {
    News {
        1 = eventDetail
    }
}

```

You could include a typolink to a single event ICS on your single event matching the corresponding event, so that a visitor can add the event directly to his or her local calendar.

RealURL configuration for ICS

If you use RealURL for speaking URL's, you can include the following code in your RealURL configuration for your ICS pages:

```

$TYPO3_CONF_VARS['EXTCONF']['realurl'] = array(
    '_DEFAULT' => array(
        'fileName' => array(
            'defaultToHTMLsuffixOnPrev' => true,
            'index' => array(
                'eventlist.ics' => array(
                    'keyValues' => array(
                        'type' => 9828,
                    ),
                ),
                'event.ics' => array(
                    'keyValues' => array(
                        'type' => 9829,
                    ),
                ),
            ),
        ),
    ),
);

```

Please make sure that the type matches the corresponding typeNum defined in your TypoScript. In this example the types 9828 and 9829 are used, but of course you can use your own type numbers. This is also applicable to the name of the pages, which are eventlist.ics and event.ics.

Configuration

Plugin

The news event extension adds three additional views. Next to these views, some other settings will work a bit differently comparing to the news system. See the table below for an explanation of these settings:

Property:	View:	Description:	Key:
What to display	All	Selection of view: <ul style="list-style-type: none"> Event List view: List of all news event records which fit the configuration Event Detail view: Shows the complete news event record Event Date menu: Date menu based on the dates (by default years) of news event records 	-
Sort by	None	Define the sorting of displayed news records. This field will be ignored. This setting can only be configured by using Typoscript configuration, see the TypoScript reference for more information.	orderBy
Sort direction	None	Define the sorting direction which can either be ascending or descending. This field will be ignored. Sorting will be handled by the 'Sort by' setting, which can be overridden by using Typoscript configuration, see the TypoScript reference for more information.	orderDirection
Archive	Event List view, Event Date menu	Next to 'No constraint', two modes are available: Only active (non archived) All current and future news event records (based on event dates and time) are shown. Archived All news event records with event dates in the past are shown. Note: News (event) records can hold an optional archive date. This archive date in news event records will be ignored , and only the archive restriction as described above will be used.	archiveRestriction
Date field to use	Date menu	The date menu builds a menu by year and month and the given news records. This field will be ignored. By default the field 'EventStartdate' will be used as dateField, and can be overridden by using Typoscript configuration, see the TypoScript reference for more information.	dateField

See the news system documentation for a description of all plugin settings.

TypoScript reference

This section describes additional news system TypoScript settings, which are available for news events.

A simple way to get to know the default settings is to look at the file
EXT:roq_newsevent/Configuration/TypoScript/setup.txt

News settings (iCal support)

See the table below for the general news settings, used by news event, which are defined by using:
plugin.tx_news.settings.<property>.

Property:	Data type:	Description:	Default:
format	string	Set a different format for the output. Use e.g. "ics" for iCalendar "xml" or for RSS feeds.	html

News event settings

See the table below for the specific news event settings, which are defined by using: `plugin.tx_news.settings.event.<property>`.

Property:	Data type:	Description:	Default:
orderByAllowed	string	List of fields, which are allowed for sorting. This setting appends the <code>plugin.tx_news.settings.orderByAllowed</code> setting	<code>tx_roqnewsevent_startdate</code> , <code>tx_roqnewsevent_starttime</code>
orderBy	string	Field ordering, which is used to sort event records	<code>tx_roqnewsevent_startdate ASC</code> , <code>tx_roqnewsevent_starttime ASC</code>
archived.orderBy	string	Field ordering, which is used to sort archived event records	<code>tx_roqnewsevent_startdate DESC</code> , <code>tx_roqnewsevent_starttime DESC</code>
dateField	string	Field to use for dateMenu	<code>EventStartdate</code>
startingpoint	string	Page id of the event sysfolder	<code>plugin.tx_news.settings.startingpoint</code>
detailPid	string	Page id of the event detail view	<code>plugin.tx_news.settings.detailPid</code>
backPid	string	Page id for the event detail view to return to	<code>plugin.tx_news.settings.backPid</code>

News event view settings

See the table below for the specific news event view settings, which are defined by using: `plugin.tx_news.view.event.<property>`. You can override these settings if you want to use your own Fluid templates for news event.

Property:	Data type:	Description:	Default:
templateRootPath	dir	Root path for the fluid templates for news event. The plugin has one controller with three actions (named "eventDateMenu", "eventList" and "eventDetail"). Accordingly there have to be at least three fluid templates at the following locations (relative to the template root path): <ul style="list-style-type: none"> News/EventList.html News/EventDetail.html News/EventDateMenu.html Additionally for ICS and RSS/XML support three additional templates also have to at the following locations (also relative to the template root path): <ul style="list-style-type: none"> News/EventList.ics News/EventDetail.ics News/EventList.xml 	<code>EXT:roq_newsevent/Resources/Private/Template/</code>
partialRootPath	dir	Root path for the fluid partials of the plugin. The default Fluid templates use several default partials. If you override the default templates this might become irrelevant.	<code>EXT:roq_newsevent/Resources/Private/Partial/</code>
layoutRootPath	dir	Root path for the fluid layouts of the plugin (not used by default)	<code>Undefined</code>

Database reference

This section describes the news event database fields, which are added to the news table 'tx_news_domain_model_news' to store all event data.

Additional database columns

Property:	Data type:	Description:
<code>tx_roqnewsevent_is_event</code>	<code>tinyint(1), unsigned</code>	Determines if a news record is of type news event
<code>tx_roqnewsevent_startdate</code>	<code>int(11)</code>	The event start date
<code>tx_roqnewsevent_starttime</code>	<code>int(11)</code>	The event start time

Property:	Data type:	Description:
tx_roqnewsevent_enddate	int(11)	The event end date (for multiple day events)
tx_roqnewsevent_endtime	int(11)	The event end time
tx_roqnewsevent_location	varchar(255)	The location of the event

Tutorial

General

Since this extension extends the versatile news system extension, it is recommended to first read the news system documentation. All the described news system settings in this documentation apply to the news event extension as well, and this section only describes the additional event features of news event.

How to add an event section to your site

This section describes how to implement the extension news event in your TYPO3 installation.

Installation

Before you can install this extension, please make sure the news system extension (including the system extensions: Extbase and Fluid) has been installed. See the news system documentation for more information.

After the installation of the news system you can install the news event extension in the same way:

1. Switch to the module "Extension Manager".
2. Get the extension from the Extension Manager (TER)

Preparation: Include static TypoScript

Be aware that before any plugin can be rendered in the frontend it is necessary to include the static TypoScript of news event. This is very easy:

1. Switch to the template module and to the your template record.
2. Add the news extension to the "Include Static" list.

Important: make sure that you include the news event static template **after** the news system static template!

Create news event records

Before any news events can be shown in the front-end they must be created by adding news event records:

1. Therefore, create a new sysfolder and switch to the list view (it is preferable to create a separate sysfolder for news event records next to your news records to keep your records organized)
2. Optionally you can create a separate news category for news events. See the news system documentation for more information.
3. Use the icon in the topbar "Create new record" and search for "News system" and its records. You should see "News", "News category" and "News Tag". Click on "News" to create a new news record.
4. Click on the 'Event' tab and check the 'Is event' checkbox to mark the news record as an event (see: [Image 2](#)).
5. Fill in the necessary event information (at least an event start date), which is required to make the event visible in the frontend. Please note that events without a start date will not be visible in the front-end.

Add a plugin to a page

Add a new page (for instance 'Upcoming events') to which you can add the news system plugin. See the news system documentation to read more on how to add this plugin. When you have added the plugin to the newly created page, edit the plugin settings, and:

1. Change the 1st select box from 'What to display' to 'List view' beneath the 'Event' section in the select box (see: [Image 1](#)).
2. Select 'Only active (non archived)' below 'Archive' to only show all current and future events. Past events will be shown if 'Archived' has been selected. You can use this on a separate page (on which you've added the plugin as well) to create an event archive section.
3. Point the starting point to the sysfolder pid where you have stored the news event records.
4. Save the plugin.

Optionally, you can create a separate event detail and list page, as described in the news system documentation (see section: 'Add a plugin to a page'). In the example above the list view and detail view is the same page. Because of this the plugin setting 'Show a single news record' has been left empty.

Viewhelpers

Every Fluid ViewHelper starts with `<f:.` and you can always check out the code at `typo3/sysex/f/Classes/ViewHelpers/.` As an example the ViewHelper `<f:link.page` can be found at `typo3/sysex/f/Classes/ViewHelpers/Link/PageViewHelper.php`.

Any other ViewHelper from other extensions can be used by using a namespace declaration like:

```
{namespace e=Tx_RoqNewsevent_ViewHelpers}
```

Then ViewHelpers of EXT:RoqNewsevent (which can be found in `roq_newsevent/Classes/ViewHelpers`) can be used with the prefix `e:.`

Updating from version 2.0.x

Please read this section carefully, if you already have news event version 2.0.x installed, and want to update to version 2.1.x of news event.

What has been changed?

Earlier, with version 2.0.x, news event added a new news type called 'Event', as show below:




Image 3: The removed 'Event' news type

This type has been removed, and replaced with a checkbox 'Is event' in the event tab from versions 2.1.0.

Because of this, the news types 'External Page' and 'Internal Page', also can be used for events. This was not possible in the way we handled events in previous versions.

Ok, but what does this mean?

This means that the way news event records are stored has been changed. Because of this, you need to update older news events records to the new format after performing the update, by running the update script. Otherwise the older records will not be recognized as news event records.

Update and running the update script

1. First, update the news event extension to the latest version by using the TYPO3 'Extension Manager' like you normally would do.
2. After you've successfully performed the update, go to the "Loaded extensions" list in the TYPO3 "Extension Manager", and click on the News event extension.
3. Click on the Extension manager selectbox on the top, and check if the item 'UPDATE!' is available from the selectbox in the top, as shown in the image below:




Image 4: Run the update script

4. If this option is not available, you've already performed this update or there are no news records available which must be updated.
 1. Finally, click on 'UPDATE!' to update all old news event database records. From now all older news event records are converted to the newer format. Please note: The 'UPDATE!' option will disappear when the update has performed successfully.




Image 5: Result of the update script

Updating from version 2.1.2 to 2.1.3

Please read this section carefully, if you already have news event version 2.1.2 installed, and want to update to version 2.1.3 of news event.

What has been changed?

The link view helper for linking the event to the event detail page.

Ok, but what does this mean?

You only have to change the link view helper in the fluid template. First you need to remove all the action arguments in the fluid templates for the e:link tag. So change:

```
<e:link newsItem="{newsItem}" settings="{settings}" action="eventDetail">
```

Into:

```
<e:link newsItem="{newsItem}" settings="{settings}">
```

For the fluid templates:

- /Partials/EventList/Item.html
- /Templates/News/EventDetail.html

And finally you have to change in the /Templates/News/Eventlist.xml the n:link into an e:link. So change:

```
<n:link newsItem="{newsItem}" settings="{settings}" configuration="{returnLast:'url'}" hsc="TRUE"></n:link>
```

Into:

```
<e:link newsItem="{newsItem}" settings="{settings}" configuration="{returnLast:'url'}" hsc="TRUE"></e:link>
```

Known problems

Please let me know if you have any suggestions, tips, or questions about the news event extension. Further progress, and other information can be found at TYPO3 forge: http://forge.typo3.org/projects/extension-roq_newsevent.

The bugtracker at http://forge.typo3.org/projects/extension-roq_newsevent/issues holds all known bugs of the news event extension.

If you think you have found a bug, please report (if not already done) at TYPO3 forge and attach at least those information to make it as easy as possible to resolve it:

- Understandable title & description: Please use English and include how the bug can be reproduced
- Version of: TYPO3, News system extension, and News event extension
- If possible: an attached patch would be very nice!

To-Do list

See the roadmap section on Forge: http://forge.typo3.org/projects/extension-roq_newsevent/roadmap.

ChangeLog

See the Wiki section on Forge for Release notes: http://forge.typo3.org/projects/extension-roq_newsevent/wiki.