

Summary of Test Results

LightLab International Allentown, LLC report number: LLIA002330-004

Catalog Number: Bestqool Pro300

Portable, formed steel housing, two aluminum LED mounting plates
with three fans above LEDs, clear flat plastic enclosure.

300 dual chip LEDs - 300 red and 300 infrared chips with clear conical plastic optic below each LED

Three XJS-12W-S fans supply and six unmarked LED drivers



Irradiance measurements acquired with LLIA asset #A108-Gigahertz-Optik BTS2048-VL-TEC Spectral Irradiance Meter. Irradiance measurements taken in the LightLab goniophotometer room with stray light reduction. The test subject was allowed to reach stabilization according to IES LM-79-19 criteria prior to measurements. The test subject was measured in laboratory conditions.

Prepared For:
Bestco Health, LLC
7901 4th Street North
St. Petersburg, FL 33702, USA

The laboratory has not participated in the selection of samples to be tested. All testing is performed on the understanding that the significance of the report is limited to the extent that the test sample is representative of production units. Prorating the performance of the sample for the use of other component combinations (such as lamp / LED / Ballast / driver), or for use in different environmental conditions than that tested, may produce erroneous results. This report is free of erasures and corrections.

Test Date: 3/6/2024


Michael L.
Grather
Digitally signed by
Michael L. Grather
Date: 2024.03.08
17:48:46 -05'00'
Summary Report Template V1-1

North America (issuing laboratory)

LightLab International Allentown, LLC
905 Harrison Street, Suite 135
Allentown, PA 18103 USA
Ph: +1 484-273-0705
Fx: +1 484-209-5779
www.lightlaballentown.com

Australasia & S.E. Asia

LightLab International
50 Redcliffe Gardens Drive
Clontarf - Queensland, 4019, Australia
Ph : +61 7 3283 7862
Fx : +61 7 3283 8751
www.lightlabint.com



Summary of Test Results

LightLab International Allentown, LLC report number: LLIA002330-004

Catalog Number: Bestqool Pro300

Portable, formed steel housing, two aluminum LED mounting plates
with three fans above LEDs, clear flat plastic enclosure.

300 dual chip LEDs - 300 red and 300 infrared chips with clear conical plastic optic below each LED

Three XJS-12W-S fans supply and six unmarked LED drivers

120.0Vac, 4.928A, 500W, 0.991PF, 9.6%THD(i)

Irradiance was measured at multiple distances directly below the center of the LED array.

Test Location	Measured Irradiance (mW/cm ²)	Power Consumption (W)
3" below	106	500
6" below	68.9	500
12" below	58.97	500

