

# KERAUNOS

Electromagnetic Launch from the Moon, Mars, and Earth

---

Maglev Space Launch System · SELENE · BRONTE · ASTERIA · ARES

**Samuel Edwards**

Perpetual Technologies · Engineering Whitepaper

**Revision 2, June 12, 2026.** Fact-checked edition: every external claim re-verified against sources as of this date; physics re-derived; BRONTE site engineering replaced with the Chimborazo Design Map study (Annex A).

## 0. Executive Summary

Earth, with its thick atmosphere, is the hardest body in the system to launch from electromagnetically. So the program starts on the Moon, where the machine is native, and works outward. The full Earth injector is the long-horizon prize. It is not the opening move.

| Launcher    | Body           | Phase                                  | Character                                                                                                                                                                                                             |
|-------------|----------------|----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| SELENE      | Moon           | 1, Proof of concept                    | No atmosphere: no tube, no plasma window, no aero-shell. Starter track 1–3 km; at 100 g, 2.9 km clears lunar escape in 2.4 s. The first segment is a working exporter, not a demo.                                    |
| BRONTE      | Earth          | 2–3, Chimborazo + ASTERIA, in parallel | A 14 km first build on a ~21.3 km straight through-mountain line at Chimborazo, Ecuador; tunnel muzzle at 5,900 m. Proves tube, plasma window, and aero-shell at sub-scale. DoD hypersonic test contracts pay for it. |
| ASTERIA     | Airless bodies | 2–3, (concurrent with BRONTE)          | SELENE-class launchers stamped onto Phobos, Deimos, Ceres, the Belt. The core bet, runs alongside Chimborazo, not after it.                                                                                           |
| ARES        | Mars           | 4, The port                            | Mars atmosphere is 0.6% of Earth's; the tube is featherweight. ARES closes the return-trip problem every settlement plan dies on.                                                                                     |
| BRONTE full | Earth          | 5, The endgame                         | The ~21.3 km straight Mach-11 line, then beyond, built only after Chimborazo Phase 1 validates cost and subsystems.                                                                                                   |

### SELENE: Moon (Phase 1)

| Parameter          | Value                            | Notes                                                                                                                                                                                                                               |
|--------------------|----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Track (PoC)        | 1–3 km, 50–100 g                 | At 100 g: 1.5 km = orbit speed (1.72 km/s); 2.9 km = escape (2.38 km/s) in 2.4 s                                                                                                                                                    |
| Track (cargo)      | 10–12 km, 30 g                   | 2.43–2.66 km/s; escape with margin; ~9 s ride                                                                                                                                                                                       |
| Track (passengers) | ~50 km, 3 g                      | 1.72 km/s to low lunar orbit in 58 s (escape-rated 3 g line: ~96 km, future)                                                                                                                                                        |
| Energy per kg      | 0.41 kWh orbit / 0.78 kWh escape | Orbit $\approx$ 1/22 of Earth's 8.9 kWh/kg-to-LEO; escape $\approx$ 1/11                                                                                                                                                            |
| Atmosphere         | None                             | No tube, no plasma window, no aero-shell. The track is the launcher.                                                                                                                                                                |
| Payload bore       | Ø3 m                             | 7,069 kg per shot (Ø2.5 m × 2.9 m bay, 14.1 m <sup>3</sup> at 500 kg/m <sup>3</sup> bulk); REBCO ring mass scales with circumference, not bore area, so Ø3 m adds only 3.6 t of superconductor vs Ø1 m for a 9× payload volume gain |
| Cooling            | 20 K closed-loop cryoplant       | Sealed cryostats hold every coil at 20 K; shadowed cold sinks and ~250 K regolith at 2 m depth help, sunlit surfaces swing far hotter, so the cryostat does the real work                                                           |

**BRONTE + ASTERIA: Earth & Airless Bodies (Phase 2–3, Chimborazo Project, concurrent with vacuum-world deployment)** © 2026 Perpetual Technologies. All rights reserved.

| Parameter        | Value                                       | Notes                                                                                  |
|------------------|---------------------------------------------|----------------------------------------------------------------------------------------|
| Site             | Chimborazo, Ecuador                         | Summit 6,263 m; 1.47°S; massif sits on a 4,000 m plateau                               |
| Phase-1 build    | 14 km, portal ~2,920 m                      | Eastern (upper) 14 km of the full straight line; lower-flank portal                    |
| Exit             | Tunnel muzzle 5,900 m, 12.3° east           | Single straight 12.3° grade, no curve at all; ~363 m below peak elevation              |
| Exit air         | $\rho \approx 54\%$ SL ( $p \approx 47\%$ ) | Peak drag and heating roughly halved; weaker ground-level boom                         |
| Equatorial bonus | +465 m/s free                               | Fires east; net launcher requirement to LEO ~7.5 km/s, not ~8                          |
| Performance      | Mach 9.1 (30 g) / 2.9 (3 g)                 | Full ~21.3 km straight line later: Mach 11.2 cargo / 3.5 at human-rated 3 g            |
| Revenue          | \$50K–\$500K per test run                   | Hypersonic test services from day one, the market Auriga Space is already selling into |

## ARES: Mars (Phase 4)

| Parameter      | Value                          | Notes                                                                 |
|----------------|--------------------------------|-----------------------------------------------------------------------|
| Atmosphere     | ~6 mbar (0.6% of Earth)        | Featherweight tube; the planet does 99.4% of the plasma window's job  |
| Track (orbit)  | ~180 km, 3.3 g                 | Low Mars orbit (~3.4 km/s) in a 105 s run                             |
| Track (escape) | ~390 km, 3.3 g                 | Mars escape (~5.0 km/s) in a 155 s run                                |
| Energy per kg  | 1.6 kWh orbit / 3.5 kWh escape | Between Moon and Earth in scale; far easier than Earth in engineering |
| Staging        | Phobos and Deimos              | Catch points and depots; SEP tugs fly the interplanetary legs         |

# 1. SELENE: The Moon Machine

*The Moon has no atmosphere. That sentence deletes every hard engineering problem on the Earth list.*

On the Moon these things do not exist: the vacuum tube (the track is already in vacuum), the plasma window (no atmosphere to keep out), the aero-shell, the blast shutters, the transpiration cooling. The track lays on regolith, braced and aligned. That is the system.

The starter track is **1–3 km**, airport-runway length, with a **Ø3 m payload bore**. At 100 g, a 1.5 km run reaches lunar orbit speed (1.72 km/s); a 2.9 km run clears escape (2.38 km/s) in 2.4 seconds. Water, regolith, and metal don't mind the g-load. The very first segment isn't a demo. It is a working exporter.

SELENE track from  $a = v^2/2L \Rightarrow v = \sqrt{2aL}$ , launch  $a = 100 \text{ g} = 981 \text{ m/s}^2$ :

Orbit:  $L = 1.5 \text{ km} \Rightarrow v = \sqrt{2 \times 981 \times 1,500} = 1,716 \text{ m/s} = \mathbf{1.72 \text{ km/s}}$  (low lunar orbit)

Escape:  $L = 2.9 \text{ km} \Rightarrow v = \sqrt{2 \times 981 \times 2,900} = 2,385 \text{ m/s} = \mathbf{2.38 \text{ km/s}}$ ,  $t = v/a = \mathbf{2.4 \text{ s}}$

Launch energy:  $E = \frac{1}{2}v^2 = \frac{1}{2} \times 2,385^2 = 2.84 \times 10^6 \text{ J/kg} = \mathbf{0.79 \text{ kWh/kg}}$  (vacuum: no tube, no kick to escape)

**0.78 kWh per kg to escape.** Lunar escape costs roughly one-eleventh of Earth-to-LEO launch energy (0.78 vs 8.9 kWh/kg at 8 km/s); lunar orbit, about one-twenty-second. From the Moon you are already partway to everywhere: a Mars-transfer trajectory from the lunar surface costs ~3.0 km/s total, about **1.25 kWh/kg**, roughly one-seventh of Earth-to-LEO energy, and roughly one-fifteenth the energy of flying the same trip up from Earth's surface.

**The south pole is the right site.** Shackleton-rim and Connecting-Ridge sites see sun 80–90% of the time; permanently shadowed cold traps sit next door; Earth hangs permanently on the horizon for communications. Rev 2 honesty on two Rev 1 claims: polar *surface* temperatures swing widely (shadow cryo-cold to ~200 K+ in sun), so the 20 K coils live in sealed cryostats regardless, the real thermal gift is vacuum, cold sky, and ~250 K regolith two meters down. And the ice: the famous "600 million tonnes" belongs to *north-pole* crater radar (Mini-SAR 2010). For Shackleton itself the honest statement is bounded, radar and reflectance permit up to ~5–10 wt% ice in wall regolith, with no credible tonnage yet; Chang'e-7 (launch ~Aug 2026) goes to ground-truth exactly this. The architecture survives the uncertainty: regolith, oxygen, and metal exports close the early business even in the lean-ice case.

**The physics has been settled for fifty years.** Gerard O'Neill's NASA Ames summer studies (1976–77) developed the lunar mass driver; Mass Driver One was demonstrated in 1977. A San José State University engineering study (E. Miller, 2023) sizes a polar machine launching 25.4 kg pellets at 2.4 km/s every 10 seconds on 8.7 MW of solar power, ~1.0 MA per bucket coil, SELENE's starter track is exactly that class of machine. What killed every previous program was the same thing: all government funding, no revenue until a Moon base already existed. Cislunar freight removes that deadlock.

**The product is propellant, and mass itself.** Polar ice (wherever the surveys land), electrolyzed to LOX/LH2 or processed with imported carbon to methalox, becomes propellant for every vehicle in cislunar space, delivered to L1/L2 depots at roughly 10× less than lifting the same kilogram from Earth. Regolith is radiation shielding; sintered metal is structure. The Moon doesn't need factories to matter, it needs to be a source of cheap mass, and it already is.

SELENE scaling ladder: five build steps, each funded by the last

**SELENE grows by ladder.** Every phase is revenue-positive before the next starts. The physics of  $v = \sqrt{2aL}$  means track length is the only dial: longer = faster (at fixed g) or gentler (at fixed speed). No redesign between phases, only more track.

SELENE scaling math (vacuum, no drag, no kick stage needed to escape):  $v = \sqrt{2aL}$ ,  $t = v/a$ ,  $E = \frac{1}{2}v^2$   
Phase 1a (100 g = 981 m/s<sup>2</sup>, L = 1.5 km):  $v = \sqrt{2 \times 981 \times 1,500} = 1.72 \text{ km/s}$  (LLO),  $t = 1.8 \text{ s}$ ,  $E = 0.41 \text{ kWh/kg}$   
Phase 1b (100 g, L = 2.9 km):  $v = \sqrt{2 \times 981 \times 2,900} = 2.38 \text{ km/s}$  (lunar escape),  $t = 2.4 \text{ s}$ ,  $E = 0.79 \text{ kWh/kg}$   
Phase 2 (30 g = 294 m/s<sup>2</sup>, L = 10–12 km):  $v = 2.43\text{--}2.66 \text{ km/s}$  (escape-plus margin),  $t = 8\text{--}9 \text{ s}$ ,  $E = 0.79 \text{ kWh/kg}$   
Phase 3 (30 g, L = 30 km):  $v = \sqrt{2 \times 294 \times 30,000} = 4.20 \text{ km/s}$ ,  $t = 14.3 \text{ s}$ ,  $E = 2.45 \text{ kWh/kg}$   
Phase 4 (3 g = 29.4 m/s<sup>2</sup>, L = 50 km):  $v = \sqrt{2 \times 29.4 \times 50,000} = 1.72 \text{ km/s}$  (LLO, human-rated),  $t = 58 \text{ s}$ ,  $E = 0.41 \text{ kWh/kg}$   
Phase 5 (3 g, L = 96 km):  $v = \sqrt{2 \times 29.4 \times 96,000} = 2.38 \text{ km/s}$  (escape, human-rated),  $t = 81 \text{ s}$ ,  $E = 0.78 \text{ kWh/kg}$

| Phase                | Track    | g-load | Exit speed         | Ride time | Energy/kg   | Payload class                                                                   |
|----------------------|----------|--------|--------------------|-----------|-------------|---------------------------------------------------------------------------------|
| 1a — PoC orbit       | 1.5 km   | 100 g  | 1.72 km/s (LLO)    | 1.8 s     | 0.41 kWh/kg | Bulk: regolith, metal pellets                                                   |
| 1b — PoC escape      | 2.9 km   | 100 g  | 2.38 km/s (escape) | 2.4 s     | 0.79 kWh/kg | Bulk, ice pellets, propellant                                                   |
| 2 — Cargo            | 10–12 km | 30 g   | 2.43–2.66 km/s     | 8–9 s     | 0.79 kWh/kg | Packaged cargo, tanks, equipment                                                |
| 3 — High-speed cargo | ~30 km   | 30 g   | 4.20 km/s          | 14 s      | 2.45 kWh/kg | Bulk propellant; direct cislunar injection without kick stage, 76% above escape |
| 4 — Crew to LLO      | ~50 km   | 3 g    | 1.72 km/s (LLO)    | 58 s      | 0.41 kWh/kg | Crew capsule; departs LLO on own propulsion                                     |
| 5 — Crew to escape   | ~96 km   | 3 g    | 2.38 km/s (escape) | 81 s      | 0.78 kWh/kg | Crew direct TLI; no kick stage to reach Earth vicinity                          |

The **Ø3 m bore** is consistent across all phases: same stator ring, same bucket geometry, same cryo circuit. Track length and solar power are the only things that grow. At Ø3 m, the Ø2.5 m × 2.9 m payload bay holds 7,069 kg of bulk material at 500 kg/m<sup>3</sup> (14.1 m<sup>3</sup>); the REBCO ring adds just 6.7 t of superconductor over the 2.9 km Phase 1b track, co-manifested on a single Starship mission. Amortised over a 10-year operating life, delivered cost lands at roughly **\$3.50/kg** to cislunar orbit, 50–500× cheaper than any rocket.

The SELENE kit is the template for every airless body worth working: Phobos, Deimos, Ceres, the Belt. Design once, stamp copies. ASTERIA is the real bet. (*The SELENE South Pole Design Map, Annex A, follows this section.*)

The dust problem, and why a contactless launcher is the right answer

Lunar regolith is the nastiest material in the inner solar system to run machinery in: jagged, never weathered, electrostatically charged, and it gets into everything. It is a first-order design driver, not a footnote, and the south-pole site makes it worse.

Apollo ground truth: dust on radiators overheated Apollo 16 instruments (it kills emissivity); Apollo 12 suit seals leaked 0.25 psi/min vs a 0.30 limit; gauge faces abraded unreadable. NASA's 2005 tally: vision loss · false readings · clogged mechanisms · abrasion · thermal-control loss · seal failure · inhalation.  
Polar twist: near the terminator, UV / solar-wind charging drives ~300 V sunlit-vs-shadow potentials and **electrostatic dust levitation**; shadowed ground has no charge-dissipation path, dust clings and will not let go. SELENE's ridge sits in exactly this terminator zone.

**SELENE is unusually well-suited to fight it, because the launcher is contactless.** Most Apollo dust failures were mechanical, seals, bearings, sliding contact. SELENE's drive has none in the load path:

- **Maglev = no rolling or sliding contact.** The pod rides a 200 mm vacuum gap; there are no wheels, rails, or bearings for dust to abrade or clog, the exact failure mode that wrecked Apollo hardware is simply absent on a contactless track.
- **Magnets sealed at 20 K.** The REBCO coils live in sealed cryostats; dust never reaches the conductors or the cold mass.
- **Electrodynamic Dust Shield (EDS) on the vulnerable surfaces.** Radiators and solar arrays are the real victims (dust drops emissivity and power). NASA's EDS, travelling-wave electric fields, no moving parts, cleared dust from glass and thermal radiators on Firefly's Blue Ghost lander in March 2025; SELENE coats its radiators, arrays, and optics with it, mounted vertically and elevated on the embankment.
- **Launch dust dome.** The EOS-1 pod's front heat shield doubles as a dust dome, containing the regolith lofted at release.
- **Charge management.** Grounded, conductive surfaces plus EDS bleed off the terminator's static, so dust has a path to leave rather than cling.

**Built by robots, not boots.** Dust is also a health hazard (Apollo "lunar hay fever"; the inhalation risk in the 2005 list), so SELENE is assembled mostly by machines: Optimus-class humanoid robots (Tesla's Optimus, NASA's dust-rated Valkyrie, Aptronik's Apollo) plus excavator and regolith-moving rovers, autonomous and teleoperated, with humans supervising and repairing rather than shovelling regolith by hand. The same EDS and sealed-joint approach protects the robots' own actuators. **Honest residuals:** radiators, optics, and robot joints still need active dust management for years, and the polar charged-dust environment is not yet flight-characterised, Chang'e and Artemis surface data will tighten it. (NASA EDS on Blue Ghost, Mar 2025; Apollo dust effects, NASA 2005; terminator charging ~300 V, lunar-surface-charging literature.)

## What SELENE earns

**CAPEX (PoC):** no tube, no plasma window, a short surface track, first coils, a ~10 MW solar plant, cryo and radiators ride 1-2 heavy-lift flights → ~\$1-3B, an order of magnitude below BRONTE's \$10-20B.

**REVENUE (cislunar, sold in space, see §13):**

Propellant / oxygen / structural metal to L1-L2 depots: demand-limited by the cislunar market (~\$1.8B/yr today, growing with depots, SEP tugs, and Mars staging) → ~\$0.5-2B/yr near-term, scaling toward multiple \$B/yr.

© 2026 Perpetual Technologies. All rights reserved.  
He-3 (quantum-cryogenics luxury, \$13.4): Interlune-scale ~1.3 kg/yr (10,000 L) × ~\$20M/kg →

~\$25M/yr, a high-margin kicker.

Launch electricity is ~\$0.02–0.05/kg (0.41–0.78 kWh/kg), negligible; margin is set by capex amortization and ISRU processing energy, not the launcher.

**SELENE is the better business:** roughly **10× lower capex than BRONTE and revenue from day one** into a cislunar market that only grows, which is exactly why SELENE (Phase 1), not Earth, opens the program. (Cislunar market and He-3 figures from \$13 deep-research pass; energy from \$2.)

## Return missions: from the Moon back to Earth and cislunar space

The Ø3 m bore is not a one-way gun. Every pod carries a PICA heat shield that doubles as a dust dome at launch and an entry shield at Earth entry. Three mission types are available from Phase 1b onward, with no redesign of the track.

- **Direct atmospheric entry (samples, He-3, high-value cargo).** The launch must be **retrograde to the Moon's 1.02 km/s orbital motion**, at roughly 2.5 km/s. Escape speed alone (2.38 km/s) just parks the payload in the Moon's own orbit around Earth; firing backward against that motion lowers the transfer ellipse's perigee until it grazes the atmosphere. The pod then coasts 3–5 days down that ellipse (apogee at the Moon, perigee at Earth) and arrives at ~11 km/s, Apollo-class re-entry geometry. The PICA shield survives, parachutes deploy at ~10 km, ocean or land recovery. No additional propulsion required.
- **Satellite dispensers (smallsats, relay birds, lunar-manufactured payloads).** The Ø3 m bore carries up to ~7 t of satellites per shot. By volume that is roughly 15–20 × 100 kg ESPA-class smallsats in the Ø2.5 m × 2.9 m bay, or a single 3–5 t bus. Military-qualified electronics routinely survive 100 g; standard artillery-grade electronics are qualified to 15,000–20,000 g. The pod coasts to the dispense point and releases the stack; each satellite then applies its own onboard  $\Delta v$ : ~200 m/s for a lunar orbit or L1/L2 halo, ~800 m/s for a GEO transfer. Earth LEO is not free, it needs a dedicated kick stage (~3,100 m/s) because the stack arrives at Earth at lunar-return speed. The natural market is cislunar: lunar-orbit relays, L1/L2 hubs, and GEO comms delivered at ~\$3.50/kg vs \$3,000–10,000/kg from Earth.
- **Cislunar depot supply (propellant, water, bulk metal).** A 150–250 m/s course-correction burn after escape targets an L1 or L2 depot directly. Pod docks via berthing arm or active capture. Propellant and water transfer; pod returns to Moon on the next descent window. This closes the loop that makes cislunar logistics self-funding: lunar ice extracted, electrolysed, launched, delivered to the depot that fuels every mission beyond Earth orbit.

The PICA shield was always on the pod to handle the dust event at launch. Sizing it for 11 km/s Earth entry costs negligible additional mass. The return capability is not an add-on. It is already flying.