

Seminar 11

week 11 (12 December 2022 – 16 December 2022)

1. Discussion of what is a type checker.

Toy language syntax:

Type ::= int

| **bool**

| **string**

| **Ref Type**

| **void**

Stmt ::= Stmt; Stmt

| **Id = Exp**

| **Type Id**

| **print(Exp)**

| **If Exp Then Stmt1 else Stmt2**

| **Nop**

| **openRFile(Exp)**

| **readFile(Exp, id)**

| **closeRFile(Exp)**

| **new(Id, Exp)**

| **wH(Id, Exp)**

| **while Exp Stmt**

| **fork(Stmt)**

Value ::= Number

| **True**

| **False**

| **String**

| **(value, Type) //ref value**

Exp ::= Value

| **id**

| **rH(Exp)**

| **Exp1 + Exp2**

| **Exp1 - Exp2**

| **Exp1 * Exp2**

| **Exp1 / Exp2**

| **Exp1 and Exp2**

| **Exp1 or Exp2**

| **Exp1 < Exp2**

| **Exp1 <= Exp2**

| **Exp1 == Exp2**

| **Exp1 != Exp2**

| Exp1 > Exp2
| Exp1 >= Exp2

Types

2 : int

id : type (given by the programmer)

Type rules

1: int 2:int

1 + 2 : int

is reading as:

-- 1+2 has type int IF 1 has type int and 2 has type int

or

-- IF 1 has type int and 2 has type int THEN 1+2 has type int

1: int v:??

1 + v : int

G- type environment, defined as a list of pairs (id:type)

G|-1: int G|-v:int

----- where G=[v:int]

G|-1 + v : int

Type rules for Values

G|- Number : int

G|-True:bool

G|-False:bool

G|-String:string

G|- val: int

 $G \vdash (\text{val}, \text{type}) : \text{Ref type}$

Type rules for Expressions

$(\text{id}:t)$ is in G

 $G \vdash \text{id}:t$

$G \vdash e1:\text{int} \quad G \vdash e2:\text{int}$

 $G \vdash e1 + e2:\text{int}$

the same rule for $-, *, /$

$G \vdash e1:\text{bool} \quad G \vdash e2:\text{bool}$

 **$G \vdash e1 \text{ and } e2:\text{bool}$
the same rule for or**

$G \vdash e1:\text{int} \quad G \vdash e2:\text{int}$

 **$G \vdash e1 < e2:\text{bool}$
the same rule for $\leq, ==, !=, >, \geq$**

$G \vdash e1 : \text{Ref } t1$

 $G \vdash \text{rH}(e1): t1$

Type rules for Statements

$G \vdash s1:\text{void}, G1 \quad G1 \vdash s2:\text{void}, G2$

 $G \vdash s1; s2: \text{void}, G2$

$G \vdash \text{id}:t1 \quad G \vdash \text{exp}:t2 \quad t1 == t2$

 $G \vdash \text{id} = \text{exp}: \text{void}, G$

G|- type id : void, G+[(id:type)]

G|- exp:t

G|- print(exp): void,G

G|- e : bool

G|- s1:void,G1

G|- s2:void,G2

G|- if e then s1 else s2 : void,G

G|- nop:void, G

G|- exp:string G|-id:int

G|- readFile(exp,id):void,G

G|- exp:string

G|- openRFile(exp):void, G

G|- exp:string

G|- closeRFile(exp):void, G

G|- exp:t G|- id:Ref t

G|- new(id,exp):void, G

G|- exp:t G|- id:Ref t

G|- wH(id,exp):void, G

G|- exp:bool G|- stmt:void,G1

G|- while exp stmt:void, G

G|- stmt:void,G1

G|- fork(stmt):void, G

2. **Discussion of the assignment A6. The deadline of the assignment A6 is week 13 (9 - 13 January 2023).**