Modern Tools in Machine Learning.

Samuel Schepp
Technische Hochschule Mittelhessen
Fachbereich MNI
Master-Seminar
samuel.schepp@mni.thm.de

Abstract

This paper introduces common machine learning tools like TensorFlow, PyCharm, and PyPlot, which are used to setup and run machine learning tasks with neural networks. A common "Hello World" script will be developed to show the concept and ideas of these tools. It will make use of the "Fashion MNIST dataset" by Zalando, which will be explored in detail.

In addition, there will be shown, how to run trainings on a graphics card and what TensorFlow is not doing.

1 MNIST Datasets

To get started with machine learning, there needs to be data that a model can read and produces a result of. In addition, a model needs much more data to train. In the "Hello World" example, which will be developed later, there will be used the "Fashion MNIST dataset", which is created by Zalando, an online fashion store. Zalando is developing solution, which can detect and classify pictures of cloth. Their current focus is machine learning.

A MNIST dataset contains four individual sets. The first set is a list of images, which will be used to train on. The second set is a list of class names, that refers to the actual thing, that is shown on the image at the same index. That means, that image 4 might show a jacket, the class name on set 2, index 4 says "jacket". These two datasets can now be used to train a model, which should recognize the image.

The remaining two datasets are again pictures and class names of cloth. These are used to test the model. The images are new and different ones, to make sure, the model is not over fitting. Over fitting means, that the model is only capable of recognizing the given dataset, but is likely to fail on unknown and new pictures.

1.1 Origin

The acronym "MNIST" database stands for "Modified National Institute of Standards and Technology database". It is a large database of handwritten digits, that is used to train neural networks and image processing systems. There are 60,000 training and 10,000 testing images, which are normalized, centered and 28 by 28 pixel in size. It is easy for convolutional neural networks, to classify these images at a failure rate of under 1 percent.

The images are encoded in a simple byte-array based format, so no conventional image application can open them. TensorFlow is able to decode the images and use them as input, since it became a common format.

Figure 1: The original MNIST database with handwritten digits

1.2 Examples

Since the MNIST database is popular amongst machine learning scientists, it became a stan-

dard format for other content. Zalando uses it, to provide example data to the public and try out different learning systems.

They created a database which contains clothing and its names (class). It has a size of 26 MB for training and 4.3 MB for test samples. There are 10 classes of clothing: T-shirt/top, trouser, pullover, dress, coat, sandal, shirt, sneaker, bag and ankle boot. It is not a coincidence, that the count of classes here is the same as the original set, which contains handwritten digits. A system, that can train the handwriting, can also train and recognize the clothing, without any reimplementation.

Figure 2: Snippet of the Zalando fashion MNIST.

TensorFlow is able to directly load the fashion MNIST, since it is part of the python package.

```
from tensorflow import keras

fashion_mnist = keras.datasets.
    fashion_mnist
(train_images, train_labels), (test_images
    , test_labels) = fashion_mnist.
    load_data()
```

Listing 1: Loading the fashion MNIST in TensorFlow (Python)

The tuples contain TensorFlow-friendly data, that can directly be used in Keras, which is TensorFlow's high level API to configure and run neural networks.

2 TensorFlow

TensorFlow is a software platform for numerical computation, with focus on neural networks and deep learning. It is developed by Google's AI organization and provides frameworks for many scientific domains.

It provides hardware accelaration for graphics cards and it own chips called "TensorFlow Processing Unit" (TPU).

Most of the time, the Python package is adequate to perform many basic and advanced machine learning tasks.

2.1 Keras

The Pyhton package of TensorFlow contains Keras, which is a high level interface to several deep learning back ends, like Theano, Microsoft Cognitive Toolkit and TensorFlow.

It is the default API for TensorFlow, although it is a independent open source project. That means you will be able to run deep learning algorithms, that are developed for TensorFlow, on different frameworks.

2.2 TensorFlow.js

To train and deploy models for the browser or Node.js, there is the TensorFlow.js JavaScript package. It provides the common low-level algebra library and a high level, Keras-like API for building and running neural networks. In addition, it allows users to convert pre-existing TensorFlow models, to run them in the browser or in a Node.js environment.

This allows JavaScript applications to directly integrate machine learning capabilities into their stack and out source computing power to the client devices, instead of the server.

2.2.1 Browser

The framework can be used directly as a script import from the CDN repository "https://www.jsdelivr.com",

```
<script src="https://cdn.jsdelivr.net/npm/
    @tensorflow/tfjs@0.14.1/dist/tf.min.js"
    ></script>
```

Listing 2: Loading TensorFlow.js in the browser via CDN

Now, the Keras API is available for usage and a model can be trained or ran on the

browser's JavaScript engine. Hardware acceleration is available via WebGL, which provides a run performance, that is only two times slower then the native Python implementation. For large models, training is up to 15 times slower.

2.2.2 Node.js

For Node.js, there is another package available, which is called "tfjs-node". It uses the native C++ bindings of TensorFlow, but provides the same interface as the browser version. This enables developers to interchange TensorFlow code between browser and server, without any rewrites.

To use the package, install it via NPM.

```
npm install @tensorflow/tfjs-node
```

Listing 3: Installing TensorFlow.js for Node.js

The package has access to all of the common hardware accelaration interface of the operating system, like NVIDIA CUDA, which allows models to train and run on a graphics card. That means, that is is possible to write JavaScript neural network code, which runs with maximum performance.

2.3 TensorFlow lite

To use models in mobile applications, there is the "TensorFlow Lite" library, which can be integrated in to existing native iOS and Android mobile applications. It is a C++ library, which comes with native API bindings for the respecting development environments.

Models, that are created in the classic TensorFlow python environment have to be converted to a lightweight and flattened model, that can be shipped with the mobile application.

Even complex models, that are used to classify images in 1000 categories are only 17 MB in size.

The key requirement of a mobile application that uses machine learning is speed and battery performance. TensorFlow Lite is optimizing models by making a trade off between model complexity and size. The tools are helping developers to fine tune the model size, by allowing adjustments even while converting the model.

A common image classification model's accuracy A is growing with file size D by a factor of $H = \sqrt{D}$. As a consequence, the models file size can be optimized at first, without compromising much performance. A model can also be optimized by avoiding over fitting and training with distinguished and useful data. However, these steps require adequate scientific approaches.

2.3.1 Usage example iOS

To use TensorFlow Lite models in an iOS applications, the C++ library has to be built from source and linked against. This is achieved by cloning the repository and running some shell scripts in the directory. A library is built, which is called "libtensorflow-lite.a". The iOS project now has to be configured with the correct library and header search paths.

The API is a low level interface and some boilerplate code is needed to make a simple image recognition demonstration working. To classify an image, the model has to run against a pixel buffer `CVPixelBufferRef` and the result will be written into a vector of class labels and their probability `std::vector<std::pair<float, int >>`. This requires about 100 lines of objective C and C++ code.

For a more simple API, Apple created CoreML, which is yet restricted to common use cases like image and text classification. It also supports TensorFlow lite models.

2.4 Limits

3 PyPlot

4 Hardware Acceleration

5 Hello World

References

Fashion-MNIST

https://github.com/zalandoresearch/fashion-mnist

Accessed: 2019-01-12.

Zalando Research

https://research.zalando.com

Accessed: 2019-01-12.

MNIST Database

http://yann.lecun.com/exdb/mnist/

Accessed: 2019-01-12.

TensorFlow Processing Unit

https://cloud.google.com/tpu/?hl=de

Accessed: 2019-01-12.

TensorFlow Lite

https://www.tensorflow.org/lite/performance/best_practices

Accessed: 2019-01-15.

Mobilenet_v2 Model

https://github.com/tensorflow/models/blob/master/research/slim/nets/mobilenet_v1.md

Accessed: 2019-01-15.