Generalist

An Interactive Agent Runtime with Executable Protocol Models

Generalist Project

September 2026

Abstract

Generalist is a Unix command-line agent implemented in Rust. It combines a provider-independent conversation loop, an interactive terminal controller, permissioned tools, Python orchestration, and explicit project-scoped archives. The design problem examined here is how to preserve user intent and valid conversation state while provider requests, tool execution, cancellation, permissions, and persistence proceed asynchronously.

Three finite TLA$^+$ specifications describe conversation ownership, episodic capture, and archive scope routing. A deterministic harness records selected implementation actions and checks them against the original specification operators. Deliberate trace corruptions and model faults test whether the gate rejects meaningful violations. Expanding the harness exposed four gaps in the previous specification/instrumentation connection; a separate Rust regression exposed steering consumption after cancellation at a truncated-response boundary. This paper explains the implementation, the corrections, and the scope of the evidence. The result is bounded model checking and sampled implementation validation, with explicit assumptions about event observation, external effects, and durability.

1 Problem and design priorities

An agent's control loop is short in outline: send history to a model, execute requested tools, append results, and request another completion. The surrounding runtime is harder. A user can submit another instruction while a request is pending, deny a tool, edit a queue, or interrupt work while an external process is changing files. An autosave may lag behind accepted input. A provider can return a partial tool call, duplicate call identifiers, an unexpected native tool name, or an error after earlier tools have already run.

Generalist treats these as protocol problems with identifiable owners and transition boundaries. It aims to preserve stable prompt identity, paired tool history, correlated permission decisions, and explicit archive scope. It also keeps the terminal responsive without making rendered text the authority for conversation state. These properties are useful even when the language model's reasoning or final answer is wrong.

The contribution of this artifact is an implementation and an auditable verification workflow. It is not a new language-model training method or a claim of priority for agent orchestration or trace validation. ReAct studies interleaved reasoning and actions; SWE-agent studies interfaces through which models operate on software environments [8, 7]. Generalist's focus here is the host protocol around such interactions. This paper reports no comparative task-success or inference-speed result.

2 Architecture and authority

The library separates the agent loop from provider adapters, tools, and the terminal interface. `src/agent/` owns conversation mutation. The binary controller in `src/main.rs` and `src/tui/` coordinates terminal input, permission events, queue changes, and display updates. `src/runtime.rs` contains shared queue claims and cancellation controls. Provider adapters use one completion vocabulary; local inference is an optional feature.




Figure 1: Ownership and principal data paths. Display events are projections; external tool effects are not rolled back by conversation cancellation.

One Tokio task polls the terminal reactor and the non-`Send` agent future. The prompt queue uses `Rc<RefCell<...>>`; this expresses single-thread ownership rather than a cross-thread scheduling protocol. Blocking persistence work is delegated to dedicated workers. The model describes abstract control locations, while the implementation uses Rust ownership, structured control flow, and RAII claims. It does not maintain a second mutable copy of every model variable.

State	Authoritative owner	Derived or delayed view
Conversation and active goal	Agent, then controller at a valid checkpoint	Terminal transcript and autosave snapshot
Queued input	Shared prompt queue with stable IDs	Queue modal and restored composer text
Permission request	Permission handler/broker for a live invocation	Modal or remembered-policy notification
Saved conversation	Scope-bound history store	Sanitized archive search result
Episode capture	One SQLite worker per opened memory client	Status, search summaries, and exported text

Table 1: Authority is separate from presentation and asynchronous persistence.

2.1 Prompt identity, delivery, and settlement

Every queued prompt has an ID, text, delivery mode, and origin. Equal text does not imply equal identity. A follow-up begins another turn; a steer is eligible for the active turn's next valid history boundary. With no active turn, the controller admits follow-ups. After settlement, residual steers become follow-ups because their previous owner no longer exists.

A two-phase claim removes entries from the visible queue. Committing a claim records their delivery; dropping an uncommitted claim restores them to the front. The controller records the initial user message and commits its start claim without an intervening await. Steering similarly claims all eligible entries in relative FIFO order, appends them to valid history, and commits the claim synchronously. Queue edits address IDs, so duplicate text and concurrent presentation changes do not select another item accidentally.

An optional persistent goal is host instruction state. Normal turn settlement can schedule one host-authored follow-up while the objective remains active. The reserved `update_goal` control is owned by the agent and cannot be registered or shadowed as an ordinary capability. Host continuation provenance survives queueing and persistence and is omitted from episodic user text. The implementation's completion control records the model's completion signal; it does not independently prove that the user's real-world objective was met.

2.2 History is the transaction boundary

An accepted assistant tool-use batch must receive exactly one result per call in the immediately following user message. The executable predicate `history_tool_protocol_is_valid` checks matching IDs, duplicates, orphan results, and role placement. Invalid protocol boundaries cannot be persisted through the history store. The agent retains earlier valid history when a later provider request fails.

A provider response is accepted only after host byte, block, and tool-count limits pass. Streamed text is a preview until the full response is committed. Refusal and truncated tool calls produce synthetic results instead of executing the affected calls. A normal tool denial stops later calls in the same outer batch and pairs each skipped call. Cooperative cancellation pairs unfinished calls with an explicit unknown-completion result. This protects the next provider request's protocol; it cannot undo a file edit or network operation.

At cancellation boundaries, a completed future and an interrupt may both be ready. Tokio's selection semantics make cancellation safety a property of the chosen operations and their ownership, not merely of using `select!` [6]. Generalist rechecks cancellation before consuming steering after a tool batch. The audit extended that check to the synthetic-result path for truncated responses.

3 Tools, permissions, and trust boundaries

By default, the model-facing capability is a Python runner. It can invoke registered capabilities through a generated `tools` module, allowing several calls within one provider round. Tool definitions are stable in registration order, and large code-only schemas can be disclosed on demand. An undeclared native call is returned as a protocol error without permission checking or execution. A library caller may disable code mode or supply a registered Python capability, so this default is not universal to every library configuration.

The outer script and its bridged calls pass through the registry's shared permission entry point. Remembered ordinary-tool policy and session-only exact input grants remain separate. Archive operations receive an additional structural capability: only the registry can construct a `ToolAuthorization` after approving the exact name and JSON input. An archive tool derives a narrower `DisclosureGrant` binding operation, filter, query or identifier, and expected returned scope. Public cross-scope storage APIs recheck that grant. This makes omission of an ordinary permission call insufficient to obtain a storage capability.

3.1 Why a denied request is not a completed tool

The outer tool/result protocol and the permission protocol have different granularity. Consider one Python call that catches two denied bridge requests:

Observed action	Outstanding outer results
`ProviderToolBatch(1)`	1
Allow the Python request	1
Deny the first bridge request	1
Deny the second bridge request	1
`CompleteTool` for Python	0
`SettleTurn`	0

The earlier model incremented its result counter during `DenyPermission`. That conflated an inner decision with an outer result. The corrected action retires the live request and marks a denial; result accounting is a separate `CompleteTool` transition. Trace emission is shared by registered tools and the built-in runner, so outer Python decisions no longer disappear from observed executions. A script may catch bridge errors, but the host still propagates the denial in the outer structured outcome.

3.2 Subprocess containment

The normal CLI configures project-scoped subprocess policies for Python, shell, patch, and solver execution. The implementation includes macOS Seatbelt and Linux Landlock/seccomp or Bubblewrap paths. Landlock is an unprivileged kernel access-control mechanism whose supported rights depend on the available ABI [2]. Generalist must check concrete platform support; a model of permission requests does not validate a kernel sandbox.

Subprocess ownership includes bounded I/O, timeouts, and process-group cleanup. There are no aggregate CPU, memory, process, or disk quotas. In particular, macOS cleanup cannot guarantee finding an adversarial child that changes process group and is reparented. Host file tools, configured MCP servers, unrestricted library defaults, and an explicitly selected host bypass mode have their own authority. The system is a local developer tool with layered controls, not a hostile multi-tenant isolation boundary. These controls do not establish prompt-injection resistance or truthfulness of model-generated text.

4 Persistence and explicit memory

Project scope is derived from the workspace; global scope is a deliberate choice. A global archive is not an implicit fallback when the current project has no results. The scope-bound history store rejects state claiming a different scope. Cross-scope model reads require categorical filters and the structural grant described above. Host inspection commands and model-mediated archive access are distinct entry points.

An autosave checkpoint contains a complete valid history boundary, goal, remembered policy, and queue. The controller sends it to a dedicated writer that may coalesce waiting snapshots. File writes use a temporary file, flush, atomic replacement, and parent-directory flush. A checkpoint event means that the in-memory boundary is accepted, not that disk already contains it. Orderly shutdown flushes pending work or reports failure. A process crash before the new snapshot is written can lose the latest accepted state while retaining the previous complete save. The TLA$^+$ models do not include this disk queue or crash recovery.

Episodic memory is an opt-in inspection feature. A worker records a bounded projection of a settled turn: user and assistant text, provider/model and outcome metadata, tool names, and result error flags. Retention types cannot carry tool inputs, tool-result bodies, reasoning, signatures, or redacted reasoning payloads. This is structural omission of particular channels; user or assistant prose can still contain secrets. There is no general secret redactor.

The worker uses SQLite transactions and WAL. SQLite documents atomic commit and WAL checkpoint behavior separately [4, 5]; a green Generalist model cannot substitute for those storage assumptions. Paused capture skips publication, insertion failure must publish no partial row, and forgetting removes a current live row. Deletion does not erase prior exports, backups, or text already disclosed into a conversation. The request channel and live store have no quota. There is no automatic retrieval into prompts, model-authored memory-write tool, consolidation service, or collaborative memory protocol in the implemented prototype.

5 What the formal models say

A TLA$^+$ specification describes initial states and allowed transitions; safety properties constrain reachable states, while temporal properties require explicit progress assumptions [1]. Generalist uses three separate finite specifications. Their constants define the checked instances, not an unbounded theorem about every queue length or runtime execution.

For the async model, key predicates include

$$\text{toolResults} \leq \text{toolUses}, \qquad \text{phase} = \text{idle} \iff \text{activeTurn} = \text{NoPrompt}.$$

At a history-valid boundary, tool counts must agree. Queue identities and committed prompt order are checked separately, because equal counts alone cannot establish correct pairing or prompt delivery. The Rust history predicate checks concrete tool IDs; the finite async model abstracts tools to counts and permission requests to fresh abstract identities.

Model	Principal state and safety	Progress boundary
`AsyncRuntime`	One active turn; unique queue/claim identities; tool-result counts; live permission ownership; committed history order	Busy periods settle under controller fairness, including eventual permission resolution
`MemoryRuntime`	Immutable current scope; FIFO pending episodes; disjoint live/skipped/failed/forgotten lifecycle; permissioned disclosure	Pending episodes resolve under fairness of processing the queue head
`ArchiveScopeRuntime`	Explicit startup scope; writes remain in active scope; a representative disclosure matches its request and authorization witness	Safety only; no retrieval or filesystem liveness theorem

Table 2: Each specification abstracts different authoritative state. The repository does not prove their composition.

5.1 Fairness and finite bounds

The checked async configuration contains three prompt IDs, two request IDs, up to two tools per response, two provider rounds, and one recoverable claim failure. Weak fairness of agent progress assumes that enabled controller work, including a pending permission decision, eventually proceeds. Finite prompt, request, round, and failure budgets are part of the termination argument. Copy-mode rendering is abstracted away: automatic permission decisions and host goal scheduling may progress while a frame is paused. The previous display-state guards incorrectly blocked both cases. Removing that state also removes an eventual-resume property that merely restated its fairness assumption; terminal behavior remains a concrete test obligation.

The memory configuration has two episode IDs and three scope labels, with a fixed current project. The archive configuration has three scopes, two history IDs, and two memory IDs, including representative pre-existing global and foreign records. The memory model does not itself trace arbitrary pre-existing foreign database contents. None of these bounds proves that a live provider, a filesystem, or an external tool eventually returns. Model-checker fingerprints also have a nonzero collision probability.

5.2 Connecting Rust execution to model actions

The opt-in `src/model_trace.rs` sink records at existing implementation boundaries. Normal construction installs no sink. Trace records omit prompt text, tool JSON, provider content, and project paths; opaque IDs preserve identity relationships. The conformance driver uses fresh temporary stores and deterministic provider and permission fixtures. It also asserts concrete outcomes, queue contents, and valid checkpoint history.

The renderer maps those IDs into a finite domain and imports the original model. For trace event e_i, the wrapper requires

$$\mathrm{Next}(s, s') \ \wedge \ \mathrm{Action}_{e_i}(s, s') \ \wedge \ i' = i + 1.$$

For dispatch and steering claims, observed IDs further constrain the modeled post-state. `TraceCompletes` requires consumption of the entire sequence under fairness of the constrained trace step. Every state invariant is copied from the base configuration rather than maintained in a parallel list. The wrapper replaces the model's long-running liveness properties with finite trace completion. Its round bound comes from the scenario's actual agent configuration; identity domains come from recorded events.

This workflow follows the idea of validating implementation traces against specifications described by Merz and collaborators [3]. In this artifact, fixing each named action and its arguments yields a deterministic abstract path; missing enabled transitions cause a temporal counterexample. It is still predominantly action observation, not an observation of every Rust state variable. Misplaced or missing instrumentation can conceal a runtime defect. Generated permission IDs represent policy invocations rather than an independent measurement of the UI broker's reply IDs. Memory start/settlement events occur together at capture submission, so the sample does not measure live provider/worker overlap. These are limits of the refinement evidence.

6 Audit findings and verification value

The original gate accepted three sampled wrappers and rejected three mutated traces. The expanded async scenarios were first run against the previous model and instrumentation. Four failed: multi-call denial, denial of the outer Python request, multiple denied bridge calls, and an undeclared native call. The ordinary Rust outcomes and paired histories already worked in these cases; the failures exposed defects in their formal representation.

Finding	Correction	Evidence category
Denial consumed a result prematurely	Separate permission retirement from outer completion	Old expanded trace rejected; corrected trace accepted
Python permission omitted from tracing	Share the registry permission entry point	Outer and nested Python traces
Skipped/rejected results omitted from tracing	Emit completion for every synthetic outer result	Batch-denial and undeclared-call traces
Cancellation consumed queued steering	Check cancellation before truncated-batch steering	Failing-then-passing Rust regression and observed scenario
Old token measurement survived changed context	Invalidate on history/provider changes; saturate counters	Focused Rust regression
Saved names appeared in exported traces	Map save/read/delete names to consistent opaque IDs	Redaction regression and storage trace

Table 3: Formal-representation defects are distinguished from runtime defects.

The cleanup removes duplicated permission handling and TLC discovery, replaces manual tool-batch indexing with an owning iterator, routes goal-continuation allocation through the ordinary queue path, and consolidates historical traceability narratives into maintained mappings. Queue traces now include editing/removal, reclassification, movement, restoration, and the actual IDs claimed. The renderer derives constants for observed traces and imports the configured invariant list, reducing opportunities for the checker and its fixtures to drift apart.

6.1 Negative tests test the gate itself

Trace mutations remove result/repair events, move continuation before a result, lose a denial or steering commit, replay a permission reply, lose a queue deletion, disclose a forgotten episode, or change an archive filter. They must fail because the constrained trace cannot complete. A syntax error or failed Java launch is not accepted as a successful negative test.

A second layer changes one action in each original specification. Prematurely returning to idle while retaining a turn must violate `SingleTurnOwnership`. Publishing an episode without draining its queue entry must violate `EpisodeLifecycleIsDisjoint`. Allowing a history disclosure without its scope guard must violate `DisclosureMatchesRequestedScope`. The gate requires these named invariant counterexamples. This demonstrates sensitivity to three concrete faults; it is not evidence that every useful invariant or every possible fault has been enumerated.

6.2 Reproduction and evidence boundaries

The audited local source passed 16 observed traces, 25 rejecting trace mutations, and three rejecting model faults. The exhaustive runs completed with the counts below; they refer to the checked finite configurations.

Model	Generated states	Distinct states	Depth
`AsyncRuntime`	306,655	65,475	26
`MemoryRuntime`	7,627	1,690	16
`ArchiveScopeRuntime`	519,516	59,725	13

The Rust gate passed 318 library tests, 36 binary tests, two integration tests, six example tests, and two documentation examples. Two live provider-catalog tests were explicitly ignored. Native MLX execution is not established by the stub-compatible build. All figures describe local validation, not hosted CI or live provider evaluation.

The maintained commands are:

```
make conformance
make tla
make check
make whitepaper
```

The first generates real traces and runs both kinds of negative checks. The second also explores all three checked model configurations. The third adds Rust tests, all-feature stub-compatible compilation, formatting, strict Clippy, Rust documentation, ShellCheck, and repository corpus/hook checks. Native MLX execution is a separate machine-specific path; the all-feature stub gate does not certify native model loading or performance.

The accompanying `whitepaper/evidence/validation.md` records the actual run results and source hashes. It is the numerical evidence ledger for this paper. Earlier recorded successes do not validate later source changes. The current sample omits copy-mode interaction, arbitrary restored archives, foreign-row batches, capture failures, some claim rollback paths, and complete provider/subprocess behavior. Those require their corresponding tests, platform execution, and review. No hosted release, public deployment, or independent security certification is implied.

7 Limitations and maintenance direction

Formal specifications add value when they force a concrete protocol distinction and when the implementation can fail their checks. Here they exposed the mismatch between inner permission decisions and outer tool results, and the expanded traces prevented several unobserved branches from inheriting an unearned green result. Deterministic Rust regressions remained essential for cancellation timing and context accounting, which the abstract state does not fully observe.

The largest assurance gaps are the remaining observation boundary, model composition, and external effects. Future work should prioritize an observed failure or consequential new behavior: extend scenarios when a transition changes, add partial state observations when action names cannot discriminate a bug, and model a worker or durable queue only when a specific property needs that state. Increasing state counts or adding a model without a falsifiable property is not a verification milestone.

The intended maintenance rule is concrete: read the changed control flow, identify its authoritative mutation and cancellation boundary, update the applicable action and live mapping, add a deterministic execution, and require both valid traces and meaningful faults to be classified correctly. This keeps the formal artifact coupled to engineering decisions while preserving an honest boundary around what has been checked.

References

[1] Leslie Lamport. *Specifying Systems: The TLA+ Language and Tools for Hardware and Software Engineers*. Addison-Wesley, 2002. URL: https://lamport.azurewebsites.net/tla/book.html.

[2] Linux Kernel Contributors. Landlock: Unprivileged access control, 2026. Kernel documentation, accessed September 6, 2026. URL: https://www.kernel.org/doc/html/latest/userspace-api/landlock.html.

[3] Stephan Merz. Validating traces of distributed systems against TLA+ specifications. TLA+ Community Meeting, Milan, 2024. Joint work with Horatiu Cirstea, Markus Kuppe, and Benjamin Loillier. URL: https://conf.tlapl.us/2024-fm/slides-merz.pdf.

[4] SQLite Authors. Atomic commit in SQLite, 2026. Documentation, accessed September 6, 2026. URL: https://sqlite.org/atomiccommit.html.

[5] SQLite Authors. Write-ahead logging, 2026. Documentation, accessed September 6, 2026. URL: https://sqlite.org/wal.html.

[6] Tokio Contributors. The select! macro: Cancellation safety, 2026. Documentation, accessed September 6, 2026. URL: https://docs.rs/tokio/latest/tokio/macro.select.html.

[7] John Yang, Carlos E. Jimenez, Alexander Wettig, Kilian Lieret, Shunyu Yao, Karthik Narasimhan, and Ofir Press. SWE-agent: Agent-computer interfaces enable automated software engineering. In *Advances in Neural Information Processing Systems*, 2024. URL: https://arxiv.org/abs/2405.15793.

[8] Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik Narasimhan, and Yuan Cao. ReAct: Synergizing reasoning and acting in language models. In *International Conference on Learning Representations*, 2023. URL: https://arxiv.org/abs/2210.03629.