

Diagrama Entidad-Relación

HR Cloud Manager — Sistema de Gestión de Recursos Humanos para PYMEs

USERS

idBIGINTPK

nameVARCHAR(255)

emailVARCHAR(255)UK

passwordVARCHAR(255)

company_nameVARCHAR(255)

roleENUMadmin | manager | hr | employee

created_byBIGINTFK → users

employee_idBIGINTFK → employees

is_activeBOOLEAN

created_atTIMESTAMP

updated_atTIMESTAMP

EMPLOYEES

idBIGINTPK

user_idBIGINTFK → users

first_nameVARCHAR(100)

last_name VARCHAR(100)

email VARCHAR(255)

document_type ENUM(CI | RUT | DNI | PAS.

document_number VARCHAR(20)

hire_date DATE

department VARCHAR(100)

position VARCHAR(100)

salary DECIMAL(12,2)

status ENUM(active | inactive | suspended)

deleted_at TIMESTAMPSoft Delete

ATTENDANCES

id BIGINTPK

employee_id BIGINTFK → employees

date DATEUK (emp+date)

check_in DATETIME

check_out DATETIME

status ENUM(present | absent | late...

late_minutes INT

notesTEXT

created_atTIMESTAMP



VACATION_REQUESTS

idBIGINTPK

employee_idBIGINTFK → employees

start_dateDATE

end_dateDATE

days_requestedINT

reasonTEXT

statusENUMpending | approved | rejected

approved_byBIGINTFK → users

approved_atDATETIME

rejection_reasonTEXT

created_atTIMESTAMP



DOCUMENTS

idBIGINTPK

employee_idBIGINTFK → employees

user_idBIGINTFK → users

title VARCHAR(255)

type ENUM(contract | cert | payroll...

file_path VARCHAR(500)

file_name VARCHAR(255)

file_size INT

expiry_date DATE

created_at TIMESTAMP

 NOTIFICATIONS

id BIGINT PK

user_id BIGINT FK → users

title VARCHAR(255)

message TEXT

type ENUM(info | success | warning | error

is_read BOOLEAN

related_id BIGINT

related_type VARCHAR(50)

created_at TIMESTAMP



Relaciones entre entidades

users → employees 1 : N

Un usuario (admin) gestiona muchos empleados.

employees.user_id = users.id

users → users 1 : N

Un admin puede crear múltiples sub-usuarios.

users.created_by = users.id

users → employees 1 : 1

Un usuario empleado está vinculado a su registro HR.

users.employee_id = employees.id

employees → attendances 1 : N

Un empleado tiene muchos registros de asistencia.

attendances.employee_id = employees.id

employees → vacation_requests 1 : N

Un empleado puede tener muchas solicitudes de vacaciones.

vacation_requests.employee_id = employees.id

employees → documents 1 : N

Un empleado puede tener muchos documentos adjuntos.

documents.employee_id = employees.id

users → vacation_requests 1 : N

Un usuario (admin/hr) aprueba/rechaza solicitudes.

`vacation_requests.approved_by = users.id`

users → notifications 1 : N

Un usuario recibe muchas notificaciones del sistema.

`notifications.user_id = users.id`

PK Clave primaria

FK Clave foránea

UK Clave única

ENUM Valores predefinidos