

ASTERION FIELD-COUPLED TRANSIT ARCHITECTURE

A Non-Rocket, Multi-Regime Spacecraft Concept for Constraint-Minimized Solar-System and Precursor Interstellar Travel

SAMUELSON G

Independent Researcher

Corresponding author: gsamuelsonguna@gmail.com

ORCID: 0009-0005-8744-8178

Article type: Conceptual Design Study / Perspective

Version 1.0 — 12 July 2026

Scientific status statement. No known spacecraft can travel “without restrictions.” Conservation of momentum, relativity, thermodynamics, radiation, material strength, navigation uncertainty, and energy availability remain fundamental constraints. This paper therefore proposes a restriction-minimizing architecture and a falsifiable research programme; it does not report a built vehicle, experimental validation, or faster-than-light capability.

Abstract

Conventional spacecraft are organized around launch-vehicle geometry, onboard propellant, and a single dominant propulsion system. Those choices make missions highly dependent on the rocket equation, narrow launch windows, destination-specific stages, and limited braking options. This conceptual design study asks a deliberately radical but physics-bounded question: what would a spacecraft look like if it were designed primarily for travel in space rather than for ascent through an atmosphere? The proposed Asterion architecture replaces the familiar rocket-shaped vehicle with a distributed annular craft whose propulsion is field-coupled and multi-regime. It combines externally supplied photon or pellet-beam momentum, deployable solar and electric sails, a plasma-inflated magnetic sail, optional fission- or fusion-electric onboard power, destination-side braking, high-temperature radiator petals, replaceable forward shielding, autonomous reconfiguration, and in-space assembly. A separate spacetime-metric laboratory branch is retained only as a fundamental-physics experiment and contributes no credited mission performance. Governing equations for beam thrust, heat rejection, charged-particle deflection, and relativistic impact energy are used to expose the design's dominant constraints. An illustrative 1,000 kg probe accelerated by a 100 GW idealized reflected beam with 85% effective momentum coupling would experience approximately 567 N, reaching 300 km/s in about 6.1 days over roughly 0.53 AU, while simultaneously creating severe optical, structural, pointing, and thermal challenges. The study concludes that the most defensible path to radically improved mobility is not a single "impossible engine," but an infrastructure-supported vehicle that changes propulsion mode with environment and mission phase. The paper defines evidence gates, failure modes, and a staged demonstration roadmap intended to prevent speculative elements from being confused with engineering readiness.

Keywords: advanced propulsion; beamed energy; electric sail; magnetic sail; plasma propulsion; fusion propulsion; interstellar precursor; spacecraft architecture; in-space assembly; technology readiness

Nomenclature

Table 1. Symbols and abbreviations used in this paper.

Symbol	Meaning	Unit / note
A	area; context distinguishes sail, radiator, or interaction area	m ²
c	speed of light in vacuum	299,792,458 m/s
C_R	radiation-pressure coefficient	1 absorbing; up

Symbol	Meaning	Unit / note
		to 2 ideal reflection
E_imp	impact kinetic energy	J
F_ph	photon-beam thrust	N
gamma	Lorentz factor	dimensionless
HTS	high-temperature superconductor	technology family
ISM	interstellar medium	gas, plasma, dust
P	incident beam power	W
Q	waste heat to be rejected	W
TRL	technology readiness level	1-9 convention
v_e	effective exhaust velocity	m/s

1. Introduction

The dominant visual grammar of spaceflight remains the rocket: a slender pressure vessel, large propellant fraction, engines at one end, payload at the other, and a structure optimized to survive launch through an atmosphere and gravity well. That form is rational for launch, but it need not be rational for a vehicle that spends nearly all of its operating life in vacuum. Once assembled in orbit, a spacecraft is not required to be aerodynamic, vertically stacked, or committed to one propulsive interaction.

The phrase “without any restrictions” is physically unattainable. Even a hypothetical perfectly efficient propulsion system cannot remove the finite speed of causal influence, the need to exchange momentum, the energy cost of acceleration, waste-heat rejection, collision hazards, or the reliability burden of long missions. A productive research objective is therefore to remove avoidable restrictions while making unavoidable limits explicit.

This paper introduces Asterion, a field-coupled transit architecture. The name denotes a vehicle family rather than a single ship. Its defining idea is environmental and infrastructural coupling: the craft does not carry every joule and every kilogram of reaction mass needed for the entire mission. Instead, it can accept momentum from photons, charged particle beams, solar or stellar wind, injected plasma, or onboard electric/fusion exhaust, and can reverse or combine those interactions for braking. The architecture is intentionally modular so that a mission can remain useful even when its most advanced subsystem is unavailable.

The contribution is not a claim of a breakthrough drive. It is a synthesis that (1) derives a spacecraft form from deep-space functions rather than launch-vehicle heritage; (2) separates demonstrated, emerging, and speculative physics; (3) integrates acceleration and destination braking from the beginning; (4) treats power and thermal rejection as co-equal with propulsion; and (5) defines a staged, falsifiable programme in which every step produces measurable evidence.

1.1 Research questions

- Which restrictions of current spacecraft are architectural rather than fundamental?
- Can one vehicle use several momentum-coupling mechanisms without becoming prohibitively complex?
- How should a radically non-rocket spacecraft handle braking, radiation, dust, thermal rejection, and maintenance?
- What evidence gates can keep speculative spacetime concepts separate from credible engineering?

1.2 Scope

The baseline architecture targets uncrewed and eventually crew-capable travel from cislunar space to the outer solar system and precursor interstellar distances. Earth launch, atmospheric ascent, and planetary landing are outside the vehicle's primary function and are delegated to separate launchers, elevators, tethers, mass drivers, landers, or local logistics systems. Faster-than-light travel is not assumed.

2. Why Current Spacecraft Remain Restricted

2.1 The rocket equation and carried reaction mass

For an ideal rocket, mission delta-v is linked exponentially to mass ratio:

$$\Delta v = v_e \ln(\{m_0\}/\{m_f\}) \quad (1)$$

Equation (1) does not make rockets obsolete; it explains why carrying both energy and reaction mass becomes increasingly punitive as required delta-v grows. Chemical propulsion remains unmatched for high thrust and launch, but its exhaust velocity limits deep-space mass efficiency. Electric propulsion raises exhaust velocity but typically lowers thrust and shifts the constraint to electrical power and radiator mass. Nuclear thermal propulsion approximately doubles chemical specific impulse but still consumes stored propellant. No single onboard engine removes all of these trade-offs.

2.2 Launch-derived geometry

A cylindrical spacecraft fits a fairing and handles axial launch loads. In deep space, however, a broad annular geometry can support superconducting coils, rotation, distributed redundancy, large radiators, and separable shielding. In-space assembly and reusable beam or power infrastructure allow the transit vehicle to be wider than any launch shroud and to replace damaged external panels without discarding the pressure habitat.

2.3 Destination braking

Many high-speed concepts emphasize departure acceleration and under-specify arrival. A flyby probe can tolerate this asymmetry; a transport vehicle cannot. Carrying the propellant needed to cancel arrival velocity recreates the mass-ratio problem. Asterion therefore treats magnetic-sail drag, electric-sail drag, destination beam stations, detachable catcher sails, and onboard high-exhaust-velocity propulsion as parallel braking options.

2.4 Thermal rejection

In vacuum, high-power systems cannot rely on atmospheric convection. Waste heat must reach a radiating surface and leave primarily as infrared radiation. For an idealized radiator:

$$A_{rad} = \frac{Q}{[\epsilon\sigma(T_{rad}^4 - T_{space}^4)]} \quad (2)$$

At emissivity 0.9, rejecting 10 MW at 500 K requires an ideal area of about 3,135 m², whereas at 1,000 K the ideal area falls to about 196 m². High radiator temperature reduces area but increases material, fluid, crew-isolation, and conversion-system difficulty. Any concept that discusses gigawatts of propulsion power without a heat path is incomplete.

Thermal rejection remains a hard spacecraft constraint




Figure 1. Ideal radiator area versus temperature for 1, 10, and 100 MW of waste heat. This calculation shows why power density and radiator temperature are central spacecraft design variables.

2.5 Relativity, causality, and speculative shortcuts

Special relativity prevents massive objects from being accelerated through local spacetime to or beyond c with finite energy. General relativity admits mathematically unusual geometries, including warp metrics and traversable wormholes, but mathematical solutions are not engineering designs. Alcubierre's original metric required negative energy density; later work has explored broader classes, including positive-energy subluminal shells. Other analyses show that physically reasonable superluminal warp drives violate energy conditions. Even positive-energy constant-velocity models do not provide a practical method to create, accelerate, steer, or power the required spacetime configuration. Consequently, the Asterion baseline allocates zero mission performance to warp or wormhole concepts.

Table 2. Restrictions, their physical status, and the proposed architectural response.

Restriction	Status	Asterion response
Rocket mass ratio	Fundamental for vehicles carrying reaction mass	Shift part of energy and momentum exchange to external beams and environmental sails; retain onboard propulsion for resilience.
Speed of light	Fundamental causal limit in established physics	Target high subluminal cruise speeds; do not credit FTL performance.

Restriction	Status	Asterion response
Waste heat	Fundamental thermodynamic constraint	Large deployable radiators, high-temperature loops, duty cycling, and distributed power modules.
Radiation	Environmental; partially mitigable	Hydrogen-rich storm shelter, replaceable passive shielding, and experimental HTS magnetic shield.
Dust and gas impacts	Environmental; grows sharply with speed	Small forward cross-section, graphite/Whipple layers, sensing, sacrificial particle cloud, path selection, and speed limits.
Destination braking	Architectural and mission-specific	Magsail/e-sail drag, destination beam, detachable catcher, and onboard electric/fusion reserve.
Launch fairing	Infrastructure constraint, not deep-space physics	Orbital assembly, modular launch, robotic construction, and servicing.
Component lifetime	Engineering and logistics constraint	Segmented replaceable modules, autonomous inspection, graceful degradation, and spare fabrication.

3. Methodology

3.1 Conceptual design method

The study uses morphological synthesis rather than optimization around a single engine. Functions were decomposed into launch independence, acceleration, cruise, braking, power, thermal rejection, shielding, guidance, maintenance, and habitation. Candidate mechanisms were retained only when they obey conservation laws and possess either experimental evidence or a clear falsification path. The resulting architecture was then checked against cross-coupling constraints: a large sail affects pointing; a high-power drive enlarges radiators; a magnetic shield affects instruments; and a rotating habitat affects deployment and control.

3.2 Evidence classification

Table 3. Evidence and maturity classes used in this study.


Class	Definition	Examples in this paper	Design treatment
A — demonstrated	Principle and relevant hardware demonstrated in flight or mature ground	Solar sailing, electric propulsion, radiators, autonomous navigation,	May be credited in near-term demonstrators.

Class	Definition	Examples in this paper	Design treatment
	systems	robotic assembly elements	
B — laboratory / subsystem	Key effect measured, but not at required scale or environment	HTS coils, high-power laser arrays, charged tethers, magnetic shielding tests	Credited only with explicit scaling risk.
C — credible concept	Consistent with known physics but major integrated demonstrations absent	Pellet beam, plasma-inflated magsail, direct fusion drive, pulsed fusion propulsion	Used as optional growth capability.
D — fundamental speculation	Mathematical or exploratory physics without an engineering route	Warp metrics, traversable wormholes, vacuum-energy propulsion	Quarantined from mission performance.
X — unsupported	Violates conservation laws or lacks reproducible evidence	Reactionless drives with no external momentum exchange	Excluded.

3.3 Evaluation criteria

- Net momentum accounting and external reaction partner are identifiable.
- Energy source, conversion losses, and waste-heat path are stated.
- Acceleration and braking are both addressed.
- Failure does not automatically destroy the pressure habitat.
- The subsystem has a measurable ground or orbital experiment.
- Performance claims are separated from illustrative targets and from speculative research.

4. Proposed Asterion Architecture



ASTERION FIELD-COUPLED TRANSIT VEHICLE — functional schematic; not to scale

Figure 2. Functional architecture of the Asterion field-coupled transit vehicle. The geometry is optimized for operations in vacuum, not for atmospheric launch. The schematic is not to scale.




Figure 3. ASTERION FIELD-COUPLED TRANSIT ARCHITECTURE
System Overview

4.1 Annular primary structure

The vehicle is built around a segmented annulus. For robotic missions the ring contains instruments, power electronics, propellant cartridges, and thermal manifolds. For crewed variants the annulus can rotate slowly or operate as one end of a tethered two-body artificial-gravity system. The ring distributes loads from superconducting coils around its circumference and allows damaged sectors to be isolated. A central void reduces material in regions that contribute little to pressure volume or coil support and provides a passage for telescopes, beam alignment, docking, and cargo transfer.

4.2 Power and energy spine

A detachable axial spine carries the highest-energy equipment away from the habitat: reactor or fusion module, power conversion, pulse-forming networks, propellant tanks, and high-temperature radiators. The separation distance reduces radiation and allows a failed power unit to be jettisoned or replaced. Near a beamport, the spine may be largely dormant because external energy performs the main acceleration. Far from infrastructure, fission-electric propulsion is the conservative growth option; a direct or pulsed fusion system is a Class C option requiring substantial physics and engineering progress.

4.3 Deployable momentum-coupling surfaces

Instead of one permanent sail, Asterion uses interchangeable coupling states:

- A reflective or diffractive membrane for solar and laser radiation pressure.
- A receiver geometry for a controlled pellet or particle beam, using electromagnetic capture rather than direct structural impact where possible.
- Long positively charged tethers for electric-sail interaction with solar or stellar wind.
- A plasma-inflated magnetic bubble generated by HTS coils and plasma injection, providing a large effective interaction area with comparatively small physical hardware.
- A compact high-speed configuration in which all large surfaces retract behind the forward shield.

These modes are not expected to operate simultaneously at full scale. The spacecraft reconfigures with distance, environment, velocity, and mission phase.




Figure 4. Conceptual operating domains of the multi-regime architecture. Mode boundaries depend on solar-wind conditions, infrastructure, vehicle mass, and mission geometry.

4.4 HTS field system

A toroidal high-temperature-superconductor coil array has four potential functions: active radiation shielding, magnetic-sail interaction, beam or plasma coupling, and high-authority attitude control through interaction with charged flows. A dipolar torus can be arranged to reduce field inside the habitat, but magnetic shielding remains a demanding subsystem with mass, quench, secondary-radiation, cryogenic, and structural risks. It is therefore an augmentation, not a substitute for passive storm shelters and conventional radiation design.

4.5 Forward protection stack

At high speed the vehicle presents its smallest cross-section to the velocity vector. A replaceable stack contains low-density bumper layers, graphite or refractory tiles, spaced Whipple elements, plasma sensors, and a shadow shield protecting the habitat. Ahead of the physical shield, the craft can release a sparse cloud of micron-scale particles or plasma whose purpose is to pre-ionize or fragment incoming grains before they reach the primary structure. This technique transfers risk rather than eliminating it: the cloud must be controlled, cannot stop large objects, and itself creates navigation and contamination concerns.

4.6 Thermal architecture

Radiators deploy perpendicular to the dominant heat and optical environment and can operate at multiple temperature levels. Electronics and habitat loops remain comparatively cool; power conversion and propulsion loops operate hot to reduce area. Heat storage permits short high-power beam-capture or maneuver intervals followed by longer rejection periods. Radiators are segmented so that a puncture or leak does not disable the entire vehicle.

4.7 Autonomous control and self-maintenance

Field-coupled propulsion requires continuous estimation of beam alignment, tether shape, plasma state, coil current, thermal margin, and flexible-body dynamics. The vehicle therefore uses fault-tolerant autonomy with independent safety kernels. Robotic crawlers inspect membranes, replace tiles and electronics, patch micrometeoroid damage, and manufacture low-complexity spares. Autonomy is necessary because communication delay prevents close human control beyond the inner solar system; it must remain auditable because an error in a high-power beam or superconducting system can be catastrophic.

Table 4. Principal Asterion subsystems and their roles.

Subsystem	Primary role	Secondary role	Major unresolved issue
Annular ring	Habitat or payload support; coil structure	Rotation, docking, redundancy	Mass and assembly complexity
Photon / beam membrane	External acceleration	Power reception, communications aperture	Thermal stability and beam riding
Charged tether set	Electric-sail propulsion	Spin control, plasma diagnostics	Deployment and arcing
HTS coil torus	Magnetic/plasma sail	Radiation mitigation, attitude control	Quench protection and structural forces
Power spine	Onboard electricity and reserve propulsion	Mission power after arrival	Specific power and heat rejection
Forward shield	Dust and gas protection	Instrument shadowing	Mass growth at high cruise speed
Radiator petals	Reject waste heat	Sunshade and configuration control	Area, puncture tolerance, high-T materials
Autonomous service robots	Inspection and repair	Assembly and reconfiguration	Verification of long-duration autonomy
Metric laboratory	Test speculative spacetime hypotheses	Precision metrology	No demonstrated propulsive effect

Subsystem	Primary role	Secondary role	Major unresolved issue
payload			

5. Propulsion and Braking Modes

5.1 Photon-beam acceleration

For incident optical power P and effective radiation-pressure coefficient C_R , ideal thrust is:

$$F_{ph} = \frac{C_R P}{c} \quad (3)$$

A perfectly absorbing surface has C_R approximately 1; an ideal specular reflector approaches 2. Real designs lose momentum coupling through absorption, scattering, beam spill, deformation, and non-normal incidence. Beam acceleration is attractive because the massive power source remains at the beamport, but the beam array, pointing control, atmospheric propagation if ground based, sail thermal limit, and political safety regime become part of the transportation system.

5.2 Pellet- or particle-beam coupling

Pellet-beam concepts attempt to improve momentum transfer and range for heavier payloads by accelerating microscopic particles and coupling them to a magnetic or plasma receiver. NASA-supported conceptual work has examined hypervelocity pellets above 120 km/s and a one-ton-class mission to 500 AU in under 20 years. This is an infrastructure concept, not a demonstrated propulsion system. Key challenges include pellet formation, beam divergence, electromagnetic capture efficiency, erosion, synchronization, and safe termination of missed particles.




Figure 5. PHOTON / PARTICLE-BEAM PROPULSION CONCEPT

5.3 Solar, electric, and magnetic sailing

Solar sails exchange momentum with photons and need no propellant. Electric sails use charged tethers to deflect solar-wind ions. Magnetic sails use a current-generated magnetic field, sometimes inflated by plasma, to couple to charged particle flow. These modes provide low continuous thrust and are sensitive to plasma environment. Their value is greatest when time is available and when they eliminate stored reaction mass. They are also attractive for braking because a large electromagnetic interaction area can be deployed without consuming an equivalent propellant mass.

5.4 Onboard electric or fusion reserve

A field-coupled vehicle still needs independent maneuver authority for collision avoidance, failed beam acquisition, final orbit insertion, and destinations lacking infrastructure. Near-term versions can use solar-electric or fission-electric propulsion. Fusion concepts offer both higher exhaust velocity and high electrical power but remain below flight readiness. The baseline rule is graceful degradation: loss of an advanced drive should lengthen the mission or reduce payload, not remove all navigation and braking capability.

5.5 Braking architecture

- Destination beam: the most controllable option where infrastructure is already present.
- Magnetic or electric sail: propellantless braking against stellar wind, magnetosphere, or ISM, with long lead time and large uncertainties.

- Detachable catcher sail: a large low-mass element optimized only for deceleration and discarded after capture.
- Onboard high-exhaust-velocity propulsion: flexible but restores mass and thermal penalties.
- Flyby mode: acceptable for small probes, not for transport or orbital science requiring long observation.

6. Analytical Feasibility Checks

6.1 Illustrative beam-acceleration case

Consider a 1,000 kg uncrewed vehicle illuminated by a 100 GW beam. With effective momentum coupling equal to 85% of ideal reflection, $C_R = 1.7$. Equation (3) gives approximately 567 N and an acceleration of 0.567 m/s², neglecting mass loss and relativistic correction. The vehicle reaches 300 km/s after approximately 529,000 s (6.1 days) and travels about 0.53 AU during acceleration. These figures are arithmetic consequences of the assumed beam power, not a forecast. Maintaining a 100 GW beam on a lightweight moving receiver across that distance would require extraordinary optics, thermal control, pointing, sail stability, and exclusion-zone governance.

6.2 Thermal closure

Suppose only 0.1% of a 100 GW optical beam is absorbed. The absorbed power is 100 MW, already requiring roughly 1,960 m² of ideal radiator area at 1,000 K if the heat can be transferred efficiently, or roughly 31,000 m² at 500 K. A sail cannot simply conduct all absorbed energy to a remote radiator without severe mass and temperature gradients; therefore ultra-low absorptivity, short duty cycles, spectral tailoring, and direct re-radiation from the sail are essential. Beam propulsion is often limited by thermal survivability before momentum physics.

6.3 Relativistic particle and dust impacts

The kinetic energy of a particle of rest mass m at speed v is:

$$E_{imp} = (\gamma - 1)mc^2, \quad \gamma = \frac{1}{\sqrt{1 - \frac{v^2}{c^2}}} \quad (4)$$

A one-microgram grain striking at 0.1c carries about 0.45 MJ; at 0.2c it carries about 1.85 MJ. Even much smaller grains can ablate or crater thin structures. Published analyses of 0.2c probes find serious erosion and track damage from interstellar gas and dust. This imposes a speed-dependent protection mass and may make the safe velocity of a large crewed craft far lower than the velocity of a gram-scale edge-on probe.

6.4 Charged-particle deflection

A charged particle's characteristic gyroradius in a magnetic field is approximately:

$$r_L = \frac{\gamma m v_{\perp}}{|q|B} \quad (5)$$

Equation (5) shows why low-energy solar-wind particles can be deflected over large magnetic structures, while the highest-energy galactic cosmic rays require enormous field integrals and can create secondary radiation. A magnetic sail can therefore be effective for momentum exchange without automatically being a complete crew radiation shield.

6.5 Performance landscape




Figure 6. Illustrative comparison of payload mass and cruise-speed domains. Regions are intentionally broad because mission assumptions differ; the Asterion region is a design target, not validated performance.

Table 5. Representative propulsion modes and principal trade-offs.

Mode	Reaction partner / energy	Strength	Primary limitation	Maturity
Chemical rocket	Stored propellant	High thrust;	Low exhaust velocity;	A

Mode	Reaction partner / energy	Strength	Primary limitation	Maturity
	and chemical energy	mature	exponential propellant burden	
Solar electric	Stored propellant; solar electricity	High exhaust velocity; flight proven	Low thrust; solar flux decreases with distance	A
Fission electric	Stored propellant; reactor electricity	Independent of sunlight; high mission flexibility	Reactor, conversion, radiator and policy burden	B/C
Solar sail	Solar photons	No propellant; simple momentum source	Low pressure; large fragile membrane	A/B
Electric sail	Solar-wind ions	No conventional propellant; large effective area	Plasma variability and tether deployment	B
Magnetic/plasma sail	Solar wind, plasma beam or ISM	Acceleration and braking; field is deployable	Large-field scaling and plasma physics	B/C
Laser beam sail	External photons	Very high specific impulse; source stays behind	Beam infrastructure, pointing and thermal limits	B/C
Pellet beam	External hypervelocity particles	Potentially heavier payloads and longer range	Beam production, capture, erosion and safety	C
Fusion drive	Fusion products and propellant	High exhaust velocity plus onboard power	No flight-ready compact fusion system	C
Warp / wormhole	Spacetime geometry	Would alter distance/time relationship if realizable	No demonstrated source, control method, or engineering path	D

7. Illustrative Mission Concepts

7.1 Reusable cislunar-to-Mars cargo tug

A near-term Asterion demonstrator would not attempt interstellar speed. It would be assembled in cislunar space and use a combination of solar-electric propulsion, a modest reflective sail, and beamed power during departure. The annular architecture would test modular construction, radiator deployment, autonomous inspection, and magnetic-field control. Cargo could transfer to separate landers at Mars. The success criterion would be repeated reuse with lower propellant consumption and more flexible departure windows, not record speed.

7.2 Heliopause and 500 AU precursor

A 100-1,000 kg robotic precursor is the most credible long-range target. A close-Sun solar-sail maneuver or beam/pellet boost could establish cruise speed above current deep-space probes. The sail would retract for cruise, leaving a narrow shielded configuration. A plasma or magnetic sail would support course correction and possibly partial braking near a target region. NASA-supported studies separately suggest extreme solar sailing above 300 km/s for very lightweight craft and pellet-beam transport of a one-ton payload to 500 AU in less than 20 years; Asterion treats these as bounding concepts rather than directly additive performance.

7.3 Interstellar robotic flyby

A robotic interstellar flyby version would be much smaller than a crewed transport and would likely abandon the full annular habitat. It could retain the architecture's principles—external beam acceleration, edge-on cruise, sacrificial shielding, distributed wafer-scale sensors, and magnetic or photonic attitude control. At velocities approaching a significant fraction of c , dust, aiming accuracy, communications, and sail stability dominate. Destination braking would require pre-positioned infrastructure, a highly capable magnetic sail, or a mission duration much longer than a pure flyby.

7.4 Crewed outer-solar-system transport

Crewed missions require low acceleration, radiation control, abort capability, medical autonomy, artificial gravity, psychological habitability, and much larger shielding mass. The paper does not claim that the same beam power and cruise speeds suitable for small probes can be scaled directly to humans. A crewed Asterion would likely operate at tens to low hundreds of kilometres per second, using long acceleration arcs and a much more conservative dust environment. Its principal advantage would be reusable infrastructure and multiple braking options rather than near-relativistic speed.




Figure 7. MISSION PROFILE EXAMPLE
(Interplanetary Transit: Earth to Mars)

8. Risks, Failure Modes, and Safety

Table 6. Preliminary failure-mode and mitigation analysis.

Hazard	Failure effect	Detection	Mitigation / safe state
Beam misalignment	Sail loss, unintended illumination, navigation error	Independent optical trackers and ground/space cross-checks	Fast beam cutoff, segmented array, exclusion corridor, passive sail detuning
Sail thermal runaway	Membrane deformation or vaporization	Distributed temperature and wavefront sensing	Reduce power, change incidence, deploy fresh segment, abort beam phase
HTS quench	Loss of field; heating; structural impulse	Voltage taps, acoustic and field sensors	Energy dump, segmented coils, passive shielding remains

Hazard	Failure effect	Detection	Mitigation / safe state
Tether break or arcing	Loss of thrust; spin imbalance	Current and shape estimation	Isolate tether, counterbalance, retract set, switch mode
Radiator puncture	Coolant loss and overheating	Pressure decay and thermal imaging	Loop isolation, reserve panels, power shutdown
Dust impact	Shield penetration or attitude impulse	Forward radar/lidar/plasma flash sensors	Layered shield, redundant modules, speed cap, path adjustment
Autonomy fault	Incorrect configuration or unsafe command	Diverse voting computers and invariant monitors	Revert to low-energy configuration; human review when delay permits
Reactor/fusion fault	Power loss or radiation release	Neutron, gamma, temperature and flow sensors	Jettison or isolate power spine; battery survival mode
Destination braking shortfall	High-speed flyby or loss of capture	Long-range navigation and sail-state prediction	Begin braking early, use multiple modes, preserve onboard reserve

8.1 Beam governance

A multi-gigawatt beam array is also a hazardous directed-energy system. Civil use would require cryptographic command authority, independent range safety, transparent ephemerides, international notification, physical beam stops where possible, and a design that cannot illuminate Earth, aircraft, satellites, or inhabited surfaces at dangerous intensity. Propulsion performance cannot be separated from governance.

8.2 Nuclear and fusion safety

Nuclear modules should be launched subcritical and activated only in approved orbits, with disposal and end-of-life plans. Fusion systems do not eliminate radiation, activation, tritium or fuel-cycle issues. Long-lived high-power craft also raise planetary-protection, debris, and salvage questions.

8.3 Scientific integrity

The architecture explicitly rejects the practice of presenting a metric solution, simulation image, or unexplained thrust signal as a transportation breakthrough. Replication, null experiments, uncertainty budgets, momentum accounting, and independent review are

mandatory. Unsupported reactionless propulsion is excluded until a reproducible external momentum exchange is identified.




Figure 8. PROTECTION SYSTEMS

9. Development and Validation Roadmap




Figure 9. Evidence-gated development roadmap. Each phase must produce a repeatable physical measurement before integration proceeds.

9.1 Phase 0 — models and falsification

Create open reference models for beam propagation, sail thermoelastic stability, charged-tether plasma interaction, magnetic-sail thrust, coil quench, dust damage, and complete vehicle mass/power/thermal closure. Reproduce published results and define test articles before proposing a full vehicle.

9.2 Phase 1 — component experiments

- Measure force and stability of reflective/diffractive sails under high-intensity beams.
- Demonstrate kilometre-class tether manufacturing, deployment, voltage control, and micrometeoroid tolerance.
- Measure plasma-inflated magnetic interaction area and thrust in relevant plasma facilities.
- Demonstrate segmented HTS coil quench protection and low-field habitat interior.
- Operate high-temperature, puncture-tolerant radiator loops for mission-scale lifetimes.

9.3 Phase 2 — orbital field-sail demonstrator

A 10–100 kg uncrewed demonstrator should deploy a ring or spoke structure, operate a charged tether and small magnetic bubble, receive a low-power optical beam, and measure

net momentum exchange with an uncertainty small enough to close the force budget. The vehicle must recover from a failed deployment and safely deorbit or move to disposal.

9.4 Phase 3 — beamport and braking test


A space-based beamport accelerates and then decelerates a cooperative target over a closed test range. Success requires independent tracking, thermal closure, autonomous beam riding, and safe cutoff. A pellet-beam variant should begin at laboratory velocity and gram targets before any orbital trial.

9.5 Phase 4 — deep-space precursor

The first system-level mission should target 50-150 AU, where communication delay, radiation, sail retraction, autonomous repair, and long-duration thermal management can be evaluated without committing to a century-scale programme. A secondary objective can test partial magnetic-sail braking against the solar wind or injected plasma.

9.6 Metric-physics branch

Precision cavities, atom interferometers, superconducting rings, and vacuum-field experiments may be flown as payloads, but they remain scientifically separate. Advancement requires a preregistered prediction, a control configuration, independent replication, and an effect that cannot be explained by electromagnetic, thermal, mechanical, or data-analysis artifacts. Until then, this branch has no role in propulsion sizing or mission schedules.



All dates are illustrative and depend on funding, technology maturation, and international collaboration.

Figure 10. DEVELOPMENT ROADMAP (Technology Readiness)

10. Discussion

The proposed vehicle is “totally different” from a current rocket in form and operational logic, but it is not divorced from existing science. Its novelty comes from integration: infrastructure-based acceleration, environmental sails, annular structure, reconfiguration, and braking are designed as one system. This approach resembles maritime transportation more than a projectile. Ports contain most of the energy infrastructure; vessels are reusable; routes and safe corridors matter; and different propulsion modes operate in different environments.

The price of reducing onboard propellant is dependence on infrastructure. Beamports are expensive, politically sensitive, and useful only along prepared routes. Field sails add flexible structures and plasma uncertainty. Fusion may never achieve the required specific power. Magnetic shielding may prove too heavy. At high speed, shielding mass can erase propulsion gains. Asterion is therefore best understood as a research architecture that can shrink toward near-term cislunar vehicles or grow toward interstellar precursors depending on evidence.

The architecture also changes how “range” is defined. A conventional spacecraft carries a finite propellant budget; a sailcraft can continue to exchange momentum as long as an external flux is available, but acceleration decreases or reverses with environment. Range

becomes a network and reliability problem rather than only a tank-volume problem. This is a meaningful reduction in restriction, not the removal of physics.

A central limitation of this paper is the absence of a full trajectory optimization, finite-element structural model, electromagnetic compatibility analysis, detailed life-support design, and cost model. Numerical values are illustrative and drawn from heterogeneous concepts with different assumptions. The next publication should focus on one mission and close mass, power, thermal, pointing, and braking budgets with uncertainty ranges.

11. Conclusion

No credible design can make space travel free of all restrictions. The most important limits—conservation laws, causality, heat rejection, radiation, collision energy, and reliability—cannot be designed away. Nevertheless, many restrictions associated with present spacecraft arise from carrying launch geometry and onboard propellant logic into an environment where they are no longer mandatory.

Asterion proposes a different answer: a wide, annular, in-space-assembled vehicle that couples to external photons, beams, plasma, solar wind, and onboard high-exhaust-velocity systems as conditions change. It places braking, shielding, radiators, maintenance, and governance on the same level as acceleration. Its baseline is subluminal and consistent with known conservation laws. Its fusion and pellet-beam options are explicitly developmental. Its spacetime-metric branch is explicitly experimental and receives no mission credit.

The defensible route to transformative mobility is therefore not to search for a single engine that ignores constraints, but to build a transportation ecosystem that uses the right interaction in the right region, leaves heavy energy infrastructure at reusable ports, and advances only through measured evidence gates. A successful programme would first produce safer, reusable cislunar and planetary vehicles; only later, if power, materials, control, and shielding permit, would the same architecture support rapid outer-solar-system and precursor interstellar missions.

Declarations

Author contribution: SAMUELSON G is listed as the sole author and is responsible for the conceptual framing, interpretation, and final manuscript.

Funding: No external funding was received for this work.

Competing interests: The author declares no competing financial or non-financial interests. Just out of curiosity about space travel.

Data availability: No new experimental dataset was generated. Numerical examples are reproducible from the equations and assumptions stated in the text.

Ethics approval: Not applicable; the study does not involve human participants, animals, or personal data.

Consent to participate and publish: Not applicable.

Scientific disclaimer: This is a conceptual design study, not evidence of a functioning spacecraft, fusion engine, magnetic shield, warp drive, or wormhole. Mission values are illustrative unless explicitly attributed to a cited source.

Acknowledgments

The author acknowledges the researchers and public agencies whose open technical reports and peer-reviewed publications make independent conceptual synthesis possible.

References

- [1] Tsiolkovsky, K. E. Exploration of Cosmic Space by Means of Reaction Devices. Scientific Review, 1903. (Historical source for the ideal rocket equation.)
- [2] Sutton, G. P., and Biblarz, O. Rocket Propulsion Elements, 9th ed. Wiley, 2017.
- [3] Forward, R. L. “Roundtrip Interstellar Travel Using Laser-Pushed Lightsails.” Journal of Spacecraft and Rockets 21, no. 2 (1984): 187-195. <https://doi.org/10.2514/3.8632>.
- [4] Lubin, P. “A Roadmap to Interstellar Flight.” Journal of the British Interplanetary Society 69 (2016): 40-72; arXiv:1604.01356.
- [5] Manchester, Z., and Loeb, A. “Stability of a Light Sail Riding on a Laser Beam.” Astrophysical Journal Letters 837 (2017): L20. <https://doi.org/10.3847/2041-8213/aa619b>.
- [6] Davoyan, A. R. Extreme Solar Sailing for Breakthrough Space Exploration. NASA Innovative Advanced Concepts Phase II Final Report, 2024, NASA NTRS 20250008150.
- [7] Janhunen, P. “Electric Sail for Spacecraft Propulsion.” Journal of Propulsion and Power 20, no. 4 (2004): 763-764. <https://doi.org/10.2514/1.8580>.
- [8] Janhunen, P. “Coulomb Drag Devices: Electric Solar Wind Sail Propulsion and Ionospheric Deorbiting.” Acta Astronautica 113 (2015): 10-16; arXiv:1404.7430.
- [9] Winglee, R. M., Slough, J., Ziemba, T., and Goodson, A. “Mini-Magnetospheric Plasma Propulsion: Tapping the Energy of the Solar Wind for Spacecraft Propulsion.” Journal of Geophysical Research: Space Physics 105, no. A9 (2000): 21067-21077. <https://doi.org/10.1029/1999JA000334>.
- [10] Zubrin, R. M., and Andrews, D. G. “Magnetic Sails and Interplanetary Travel.” Journal of Spacecraft and Rockets 28, no. 2 (1991): 197-203. <https://doi.org/10.2514/3.26230>.
- [11] Landis, G. A. “Interstellar Flight by Particle Beam.” In Space Technology and Applications International Forum, 2001. NASA NTRS 20020023956.

- [12] Davoyan, A. “Pellet-Beam Propulsion for Breakthrough Space Exploration.” NASA Innovative Advanced Concepts Phase I concept description, 2023.
- [13] Razin, Y. S., Pajer, G., Breton, M., Ham, E., Mueller, J., Paluszek, M., Glasser, A. H., and Cohen, S. A. “A Direct Fusion Drive for Rocket Propulsion.” *Acta Astronautica* 105, no. 1 (2014): 145-155. <https://doi.org/10.1016/j.actaastro.2014.08.008>.
- [14] Cohen, S. A., Swanson, C. P. S., McGreivy, N., et al. “Direct Fusion Drive for Interstellar Exploration.” *Journal of the British Interplanetary Society* 72, no. 2 (2019): 37-50.
- [15] Adams, R. B., et al. Pulsed Fission-Fusion (PuFF) - Phase I Report. NASA Innovative Advanced Concepts, 2018, NASA NTRS 20180008679.
- [16] Hoang, T., Lazarian, A., Burkhart, B., and Loeb, A. “The Interaction of Relativistic Spacecraft with the Interstellar Medium.” *Astrophysical Journal* 837, no. 1 (2017): 5. <https://doi.org/10.3847/1538-4357/aa5da6>.
- [17] Hoang, T., and Loeb, A. “Electromagnetic Forces on a Relativistic Spacecraft in the Interstellar Medium.” *Astrophysical Journal* 848 (2017): 31. arXiv:1706.07798.
- [18] Lubin, P., et al. “The Interstellar Environment and Its Implications for Radiation Damage on Relativistic Spacecraft.” *Applied Sciences* 12 (2022); arXiv:2201.02721.
- [19] Slough, J. Spacecraft-Scale Magnetospheric Protection from Galactic Cosmic Radiation. NASA Innovative Advanced Concepts Phase II Final Report, 2021, NASA NTRS 20250005979.
- [20] Westover, S. C., et al. Magnet Architectures and Active Radiation Shielding Study. NASA Technical Report, 2019, NASA NTRS 20190002579.
- [21] NASA Small Spacecraft Systems Virtual Institute. State of the Art: Thermal Systems. NASA, 2026.
- [22] NASA. Space Nuclear Propulsion. Space Technology Mission Directorate technical overview, accessed 12 July 2026.
- [23] NASA and DARPA. “NASA, DARPA Will Test Nuclear Engine for Future Mars Missions.” NASA news release, 24 January 2023.
- [24] Alcubierre, M. “The Warp Drive: Hyper-Fast Travel within General Relativity.” *Classical and Quantum Gravity* 11 (1994): L73-L77. <https://doi.org/10.1088/0264-9381/11/5/001>.
- [25] Bobrick, A., and Martire, G. “Introducing Physical Warp Drives.” *Classical and Quantum Gravity* 38 (2021): 105009. <https://doi.org/10.1088/1361-6382/abdf6e>.
- [26] Santiago, J., Schuster, S., and Visser, M. “Generic Warp Drives Violate the Null Energy Condition.” *Physical Review D* 105 (2022): 064038. <https://doi.org/10.1103/PhysRevD.105.064038>.
- [27] Fuchs, J., Helmerich, C., Bobrick, A., Sellers, L., Melcher, B., and Martire, G. “Constant Velocity Physical Warp Drive Solution.” *Classical and Quantum Gravity* 41, no. 9 (2024): 095013. <https://doi.org/10.1088/1361-6382/ad26aa>.

- [28] Morris, M. S., and Thorne, K. S. “Wormholes in Spacetime and Their Use for Interstellar Travel: A Tool for Teaching General Relativity.” *American Journal of Physics* 56, no. 5 (1988): 395-412. <https://doi.org/10.1119/1.15620>.
- [29] Ford, L. H., and Roman, T. A. “Quantum Field Theory Constrains Traversable Wormhole Geometries.” *Physical Review D* 53 (1996): 5496-5507. <https://doi.org/10.1103/PhysRevD.53.5496>.
- [30] National Research Council. *Recapturing a Future for Space Exploration: Life and Physical Sciences Research for a New Era*. National Academies Press, 2011.
- [31] ESA Advanced Concepts Team. “Electric Solar Wind Sail.” Technical seminar and programme overview, 2025.
- [32] ESA. “Touring Asteroids with Electric Sails.” Enabling and Support technology article, 29 October 2020.
- [33] Greason, J. K., et al. “Sunbeam: Near-Sun Statites as Beam Platforms for Beam-Driven Propulsion.” arXiv:2407.09414, 2024.

Appendix A. Author-Defined Design Requirements

Table 7. Proposed top-level requirements for a first integrated precursor.

ID	Requirement	Verification method
R1	Vehicle shall demonstrate at least two independently measurable momentum-coupling modes.	Orbit determination and calibrated force reconstruction.
R2	No propulsion claim shall depend on unmeasured reactionless thrust.	Closed momentum and uncertainty budget.
R3	The vehicle shall retain collision-avoidance and communication after loss of the primary advanced mode.	Fault-injection simulation and flight demonstration.
R4	Thermal control shall reject steady-state waste heat with 30% area and pump margin.	Thermal-vacuum balance test.
R5	All high-energy systems shall fail to a beam-off, coil-discharged, reactor-safe configuration.	Hardware-in-the-loop safety test.
R6	Forward shielding shall be modular and replaceable by robotic servicing.	Ground robotic maintenance demonstration.
R7	Braking shall be initiated with sufficient margin that one failed mode does not force an uncontrolled planetary encounter.	Monte Carlo trajectory and fault analysis.
R8	Speculative metric experiments shall be electrically,	Interface audit and

ID	Requirement	Verification method
	analytically, and programmatically isolated from flight-critical control.	independent review.