Rendering Elements

Elements are the smallest building blocks of React apps.

An element describes what you want to see on the screen:

```
const element = <h1>Hello, world</h1>;
```

Unlike browser DOM elements, React elements are plain objects, and are cheap to create. React DOM takes care of updating the DOM to match the React elements.

Note:

One might confuse elements with a more widely known concept of "components". We will introduce components in the <u>next section</u>. Elements are what components are "made of", and we encourage you to read this section before jumping ahead.

Rendering an Element into the DOM

Let's say there is a <div> somewhere in your HTML file:

```
<div id="root"></div>
```

We call this a "root" DOM node because everything inside it will be managed by React DOM.

Applications built with just React usually have a single root DOM node. If you are integrating React into an existing app, you may have as many isolated root DOM nodes as you like.

To render a React element into a root DOM node, pass both to ReactDOM.render():

```
const element = <h1>Hello, world</h1>;
ReactDOM.render(element, document.getElementById('root'));
```

Try it on CodePen

It displays "Hello, world" on the page.

Updating the Rendered Element

React elements are <u>immutable</u>. Once you create an element, you can't change its children or attributes. An element is like a single frame in a movie: it represents the UI at a certain point in time.

INSTALLATION ~

MAIN CONCEPTS ^

- 1. Hello World
- 2. Introducing JSX

3. Rendering Elements

- 4. Components and Props
- 5. State and Lifecycle
- 6. Handling Events
- 7. Conditional Rendering
- 8. Lists and Keys
- 9. Forms
- 10. Lifting State Up
- 11. Composition vs Inheritance
- 12. Thinking In React

ADVANCED GUIDES ~

API REFERENCE Y

ноокѕ ∨

TESTING ~

CONCURRENT MODE

(EXPERIMENTAL) V

CONTRIBUTING ~

FAQ ~

With our knowledge so far, the only way to update the UI is to create a new element, and pass it to ReactDOM.render().

Consider this ticking clock example:

Try it on CodePen

It calls ReactDOM.render() every second from a setInterval() callback.

Note:

In practice, most React apps only call ReactDOM.render() once. In the next sections we will learn how such code gets encapsulated into stateful components.

We recommend that you don't skip topics because they build on each other.

React Only Updates What's Necessary

React DOM compares the element and its children to the previous one, and only applies the DOM updates necessary to bring the DOM to the desired state.

You can verify by inspecting the last example with the browser tools:

Hello, world!

It is 12:26:46 PM.

INSTALLATION ~

MAIN CONCEPTS ^

- 1. Hello World
- 2. Introducing JSX

3. Rendering Elements

- 4. Components and Props
- 5. State and Lifecycle
- 6. Handling Events
- 7. Conditional Rendering
- 8. Lists and Keys
- 9. Forms
- 10. Lifting State Up
- 11. Composition vs Inheritance
- 12. Thinking In React

ADVANCED GUIDES ~

API REFERENCE ~

HOOKS V

TESTING ~

CONCURRENT MODE

(EXPERIMENTAL) ∨

CONTRIBUTING ✓

FAQ ~

Even though we create an element describing the whole UI tree on every tick, only the text node whose contents have changed gets updated by React DOM.

In our experience, thinking about how the UI should look at any given moment, rather than how to change it over time, eliminates a whole class of bugs.

Edit this page

Previous article
Introducing JSX

Next article

Components and Props

INSTALLATION ~

MAIN CONCEPTS ^

- 1. Hello World
- 2. Introducing JSX

3. Rendering Elements

- 4. Components and Props
- 5. State and Lifecycle
- 6. Handling Events
- 7. Conditional Rendering
- 8. Lists and Keys
- 9. Forms
- 10. Lifting State Up
- 11. Composition vs Inheritance
- 12. Thinking In React

ADVANCED GUIDES >

API REFERENCE Y

HOOKS ~

TESTING ✓

CONCURRENT MODE

(EXPERIMENTAL) ~

CONTRIBUTING ~

FAQ ~