




# RSA Explanation



Explain RSA

## RSA (Rivest–Shamir–Adleman)

RSA is an **asymmetric (public-key) cryptographic algorithm** used for:

-  Secure data transmission
-  Digital signatures
-  Secure key exchange

It was introduced in 1977 by **Ron Rivest**, **Adi Shamir**, and **Leonard Adleman**.

### ◆ 1. Basic Idea

RSA uses **two different keys**:

- **Public Key (e, n)** → Used for encryption
- **Private Key (d, n)** → Used for decryption

The security of RSA depends on the **difficulty of factoring large prime numbers**.

### ◆ 2. Key Generation (How RSA Keys Are Created)

#### Step 1: Choose Two Large Prime Numbers

p and q

#### Step 2: Compute

$$n = p \times q$$

#### Step 3: Compute Euler's Totient

$$\varphi(n) = (p - 1)(q - 1)$$

#### Step 4: Choose Public Exponent

e such that:

- $1 < e < \varphi(n)$

- $\gcd(e, \varphi(n)) = 1$

## Step 5: Compute Private Key

$d$  = modular inverse of  $e \bmod \varphi(n)$

So:

Public Key  $\rightarrow (e, n)$

Private Key  $\rightarrow (d, n)$

## ◆ 3. Encryption Process

If plaintext =  $M$

Ciphertext:

$$C = M^e \bmod n$$

Uses **receiver's public key**.

## ◆ 4. Decryption Process

$$M = C^d \bmod n$$

Uses **receiver's private key**.

## ◆ 5. Why RSA Works

RSA works because of:

- ✓ Modular arithmetic
- ✓ Euler's Theorem
- ✓ Difficulty of factoring  $n$  into  $p$  and  $q$

If an attacker finds  $p$  and  $q \rightarrow$  they can compute  $\varphi(n) \rightarrow$  they can compute private key  $d$ .

Factoring very large numbers (2048-bit or larger) is computationally infeasible.

## ◆ 6. Example (Small Numbers for Understanding)

Suppose:

$p = 3$

$q = 11$

$n = 33$

$\varphi(n) = 20$

Choose  $e = 3$

Compute  $d = 7$

Public Key = (3, 33)

Private Key = (7, 33)

Encrypt  $M = 4$

$C = 4^3 \bmod 33 = 31$

Decrypt:

$M = 31^7 \bmod 33 = 4$

## ♦ 7. Applications of RSA

### 1. Secure Web Communication

Used in **TLS** (HTTPS).

### 2. Digital Signatures

Used in:

- Bitcoin
- Software verification

### 3. Secure Key Exchange

Often used to encrypt symmetric keys like:

- AES

## ♦ 8. Attacks on RSA

### 1. Brute-force factoring attack

→ Try to factor  $n$

### 2. Chosen-ciphertext attack

→ If padding not used

### 3. Timing attack

→ Measures decryption time

### 4. Common modulus attack

→ Same  $n$  used improperly

## ♦ 9. How to Make RSA Secure

- ✓ Use large key sizes (2048+ bits)
- ✓ Use proper padding (e.g., OAEP)
- ✓ Never reuse keys improperly
- ✓ Use secure random prime generation

## ♦ 10. Advantages & Disadvantages

### ✓ Advantages

- No need to share secret key
- Widely supported
- Secure when implemented properly





### ✗ Disadvantages

- Slower than symmetric encryption
- Large key sizes
- Vulnerable to quantum computers

## ♦ In One Line

RSA is a **public-key cryptosystem based on prime factorization**, used to securely encrypt data and create digital signatures.

If you want, I can also explain:

-  RSA using mathematical proof
-  RSA attacks in detail (for exams)
-  How to implement RSA in C/Python
-  6-mark exam answer format

Just tell me what you need 🔥



what are the conditions for RSA to be secure (for example  $d \gg e$ , Selection of  $p, q$ ,  $e$  must be as large as  $p, q$  etc etc)

## Security Conditions for RSA

For RSA to be secure, certain mathematical and implementation conditions must be satisfied. These prevent known practical attacks.

### Strong Prime Selection ( $p$ and $q$ )

## ✓ Must be large primes

- Minimum **2048-bit modulus n**
- That means each prime  $\approx 1024$  bits (for 2048-bit RSA)

## ✓ p and q must be random and independent

- Not close in value (avoid  $p \approx q$ )
- Not predictable
- Not reused across systems

## ✓ $|p - q|$ must be large

If p and q are too close  $\rightarrow$  **Fermat factorization attack** becomes easy.

## ✓ $(p - 1)$ and $(q - 1)$ should not be smooth

Avoid small-factor structure  $\rightarrow$  prevents **Pollard p - 1 attack**

## 2 Modulus n Conditions

$$n = p \times q$$

### ✓ n must be sufficiently large

- 2048 bits  $\rightarrow$  standard
- 3072+ bits  $\rightarrow$  high security
- 4096 bits  $\rightarrow$  long-term security

If n is small  $\rightarrow$  factorization becomes feasible.

## 3 Public Exponent (e) Conditions

### ✓ e must satisfy:

- $1 < e < \varphi(n)$
- $\gcd(e, \varphi(n)) = 1$

### ✓ e should not be too small (with no padding)

Common safe value:

$$e = 65537$$

Why?

- Large enough to avoid certain attacks

- Small enough for fast encryption

### ✗ If $e$ is too small (like 3) and:

- Same message sent to multiple recipients
- No padding used

→ **Broadcast (Håstad's) attack possible**

So:

✓ Small  $e$  is acceptable

! Only when **proper padding (OAEP)** is used

## 4 Private Exponent ( $d$ ) Conditions

### ✓ $d$ must not be too small

If:

$$d < n^{0.25}$$

→ Vulnerable to **Wiener's attack**

So:

✓  $d$  must be sufficiently large

✓ Generated normally via modular inverse ensures this

There is **NO requirement that  $d \gg e$  mathematically**, but:

- $d$  should not be unusually small
- Random key generation typically ensures safety

## 5 Proper Padding is Mandatory

Raw RSA is insecure.

Must use:

- **OAEP** (for encryption)
- **PSS** (for signatures)

Without padding, RSA is:

- Deterministic
- Malleable
- Vulnerable to chosen ciphertext attacks

Used in:

- TLS
- Modern secure systems

## 6 Prime Reuse Must Never Happen

If two users share one prime:

$$n_1 = p \times q_1$$

$$n_2 = p \times q_2$$

Then:

$$\gcd(n_1, n_2) = p$$

→ Both keys break instantly.

## 7 Secure Random Number Generator

Primes must be generated using:

✓ Cryptographically secure RNG

Weak randomness → predictable primes → broken RSA.

## 8 Protection Against Side-Channel Attacks

Even mathematically secure RSA fails if:

- Timing leaks occur
- Power analysis attack possible
- Fault injection used

Mitigation:

✓ Constant-time implementation

✓ Blinding techniques

✓ Secure hardware

## 9 Avoid Using Same Modulus for Multiple Users

Common modulus attack possible if:

- Same  $n$
- Different public exponents

## 10 Protect Against Quantum Threat

RSA relies on difficulty of factorization.

Future risk:

- Quantum algorithms (like Shor's algorithm) can break RSA efficiently.

Currently:

- ✓ RSA is safe against classical computers
- ! Not quantum-safe in long term

## ✓ Final Summary (Exam-Oriented Points)

RSA is secure if:

1.  $p$  and  $q$  are large, random, and well-separated primes
2.  $n \geq 2048$  bits
3.  $\gcd(e, \phi(n)) = 1$
4.  $e$  is not dangerously small (without padding)
5.  $d$  is not too small (avoid Wiener's attack)
6. Proper padding (OAEP) is used
7. Strong randomness is used
8. No prime reuse
9. Side-channel protections implemented

If you want, I can now give:

- 📌 Attack mapping: which condition prevents which attack
- 📄 6-mark exam answer format
- 📊 Comparison of weak vs secure RSA
- 📖 Mathematical bounds explanation (like why  $d < n^{0.25}$  breaks RSA)



So strength of rsa depends on integer fact problem cannot be solved in polytime

Yes — **basically correct**, but let's state it precisely.

## 🔒 Strength of RSA

RSA's security depends on the **hardness of the Integer Factorization Problem (IFP)**:

Given a large number



$$n = p \times q$$

it should be computationally infeasible to recover  $p$  and  $q$ .

## ♦ Is Integer Factorization Polynomial-Time?

### 📌 Classical Computers

Currently:

- No known **polynomial-time algorithm** exists for factoring large integers on classical computers.
- The best known algorithm is the **General Number Field Sieve (GNFS)**.
- GNFS runs in **sub-exponential time**, not polynomial time.

That's why RSA with 2048-bit keys is considered secure today.

So yes —

✓ RSA's strength relies on factoring **not** being solvable in polynomial time (on classical machines).

## ♦ Important Clarification

RSA security is *not formally proven equivalent* to integer factorization.

It is:

**Believed** that breaking RSA is computationally equivalent to factoring  $n$ .

But mathematically, we only know:

Factoring  $n \rightarrow$  you can break RSA

However, we don't have a proof that breaking RSA always requires factoring  $n$ .

## ♦ What If Factoring Becomes Polynomial-Time?

Then RSA collapses.

This would happen if:

- A classical polynomial-time factoring algorithm is discovered, OR
- Large-scale quantum computers become practical.

## ♦ Quantum Threat

Using **Shor's algorithm**:

- Factoring *is* polynomial-time on a quantum computer.
- This would completely break RSA.

Currently:

- Large-scale fault-tolerant quantum computers do not yet exist.
- So RSA remains secure in practice (for now).

## ◆ Final Precise Statement (Exam-Ready)

The strength of RSA depends on the computational hardness of the integer factorization problem. Since no polynomial-time classical algorithm is known for factoring large integers, RSA is considered secure against classical adversaries.

If you want, I can also explain:

- Why GNFS is sub-exponential
- Exact time complexity expression
- Difference between NP-hard and factoring
- Why RSA isn't proven NP-hard

Tell me your depth requirement 🔥



Explain same all things for Diffie hellman

## Diffie-Hellman key exchange (DH)

Diffie-Hellman is a **key exchange algorithm**.

It allows two parties to agree on a shared secret over an insecure channel.

It was proposed in 1976 by **Whitfield Diffie** and **Martin Hellman**.

## ◆ 1 What Problem Does DH Solve?

DH solves:

How can two parties establish a shared secret over a public network without sending the secret directly?

It does **NOT** encrypt data directly.

It is used to generate a symmetric key (e.g., for AES).

## ◆ 2 Mathematical Setup

We choose:

- A large prime number **p**
- A generator **g** (primitive root mod p)

These values are public.

---

## ◆ **3 Key Exchange Process**

### **Step 1: Private Values**

- Alice picks secret **a**
- Bob picks secret **b**

### **Step 2: Compute Public Values**

- Alice sends:

$$A = g^a \mod p$$

- Bob sends:

$$B = g^b \mod p$$

### **Step 3: Compute Shared Secret**

Alice computes:

$$K = B^a \mod p$$

Bob computes:

$$K = A^b \mod p$$

Both get:

$$K = g^{ab} \mod p$$

Attacker sees:

p, g, A, B

But must compute  **$g^{ab} \mod p$**  without knowing a or b.

---

## ◆ **4 Security of Diffie-Hellman**

DH security depends on:

### **Discrete Logarithm Problem (DLP)**

Given:

$$A = g^a \mod p$$

It should be computationally infeasible to recover  $a$ .

---

## Computational Diffie–Hellman (CDH) Problem

Given:

$$g^a, g^b$$

It should be hard to compute:

$$g^{ab}$$


---

## Decisional Diffie–Hellman (DDH) Problem

Given:

$$g^a, g^b, g^c$$

Hard to decide whether:

$$c = ab$$


---

## ♦ 5 Is Discrete Log Polynomial-Time Solvable?

**On Classical Computers:**

- No known polynomial-time algorithm
- Best algorithms are sub-exponential:
  - Number Field Sieve for DLP (in finite fields)

Thus DH is secure **because discrete log is not known to be solvable in polynomial time.**

---

## ♦ 6 Quantum Threat

Using **Shor's algorithm**:

- Discrete logarithm becomes polynomial-time.
- Diffie–Hellman breaks completely.

So DH is not quantum-safe.

---

## ♦ 7 Security Conditions for Diffie–Hellman

To make DH secure:

## ✓ 1. Large Prime $p$

- At least 2048 bits
- Prevents discrete log attacks

## ✓ 2. Proper Generator $g$

- $g$  must be a primitive root mod  $p$
- Avoid small subgroup attacks

## ✓ 3. Safe Prime

Often choose:

$$p = 2q + 1$$

where  $q$  is prime.

Prevents small subgroup attacks.

## ✓ 4. Private Keys ( $a, b$ ) Must Be Large and Random

- Must be chosen with cryptographically secure RNG
- Never reuse private exponent

## ✓ 5. Authentication Required

**Basic DH is vulnerable to Man-in-the-Middle (MITM) attack.**

An attacker can:

- Intercept  $A$  and  $B$
- Replace them
- Establish two separate keys

Therefore, DH must be used with authentication.

Used securely in:

- TLS
- Digital signatures + DH

## ◆ 8 Types of Diffie-Hellman

## 1 Finite Field DH (Classical)

Uses integers mod  $p$ .

## 2 Elliptic Curve DH

### Elliptic-curve Diffie–Hellman (ECDH)

Uses elliptic curve discrete log problem.

Advantages:

- Smaller key size
- Faster
- Same security level

Example:

- 256-bit ECDH  $\approx$  3072-bit RSA security

## 9 Comparison: RSA vs DH Security Basis

Algorithm	Based On
RSA	Integer Factorization Problem
DH	Discrete Logarithm Problem

Both:

- Sub-exponential classical attacks
- Broken by quantum computers

## 10 Final Exam-Ready Statement

The security of Diffie–Hellman relies on the computational hardness of the discrete logarithm problem. Since no polynomial-time classical algorithm is known for solving discrete logarithms in large finite fields, Diffie–Hellman is considered secure against classical adversaries.

If you want, next I can explain:

- MITM attack on DH step-by-step
- Mathematical difference between CDH and DDH
- Why ECDH is stronger than classical DH

- Post-quantum key exchange alternatives

Tell me your level of depth 🔥



What is confusion and diffusion and explain DES

## Confusion and Diffusion

The terms **confusion** and **diffusion** were introduced by **Claude Shannon** to describe two fundamental principles of secure cipher design.

### ◆ 1 Confusion

#### **Definition:**

Confusion makes the relationship between the **key** and the **ciphertext** as complex as possible.

#### **Goal:**

An attacker should not be able to determine the key even if they know the plaintext-ciphertext pair.

#### **How It Is Achieved:**

- Substitution operations
- Non-linear functions (like S-boxes)

#### **Example:**

In block ciphers, substitution boxes (**S-boxes**) create confusion.

### ◆ 2 Diffusion

#### **Definition:**

Diffusion spreads the influence of one plaintext bit over many ciphertext bits.

#### **Goal:**

Change in one plaintext bit → many ciphertext bits change.

This is called the **avalanche effect**.

#### **How It Is Achieved:**

- Permutations

- Bit shuffling
- Mixing operations

## ✓ Simple Difference

Confusion	Diffusion
Hides key-plaintext relationship	Spreads plaintext influence
Done using substitution	Done using permutation
Non-linear	Mostly linear mixing

## Data Encryption Standard (DES)

DES is a **symmetric block cipher** developed by IBM and adopted in 1977.

- Block size: **64 bits**
- Key size: **56 bits**
- Structure: **Feistel Network**
- Rounds: **16**


Now considered insecure due to small key size.


## ◆ 1 Overall Structure





<https://www.researchgate.net/publication/220850878/figure/fig1/AS%3A394010326781952%401470950790085/Block-diagram-of-DES-algorithm.png>





## ◆ 2 Steps of DES Encryption

### Step 1: Initial Permutation (IP)

- Rearranges bits of the plaintext.
- No cryptographic strength — mainly hardware-oriented.

### Step 2: Split Into Two Halves

64-bit block →

- Left ( $L_0$ ) – 32 bits
- Right ( $R_0$ ) – 32 bits

### Step 3: 16 Rounds (Feistel Structure)

For each round:

$$L_i = R_{i-1}$$

$$R_i = L_{i-1} \oplus F(R_{i-1}, K_i)$$

## ◆ Round Function (F Function)

Each round does:

### 1. Expansion

- Expand 32 bits → 48 bits

### 2. XOR with round key

### 3. Substitution (S-boxes) ★ (Confusion here)

- 8 S-boxes
- Each maps 6 bits → 4 bits
- Non-linear step

### 4. Permutation (P-box) ★ (Diffusion here)

- Rearranges bits to spread influence

## ◆ Final Step

After 16 rounds:

- Swap halves
- Apply Final Permutation (Inverse IP)

Ciphertext produced.

## ◆ How DES Implements Confusion & Diffusion

### ✓ Confusion:

- Achieved using **S-boxes**
- Makes ciphertext non-linearly related to key

### ✓ Diffusion:

- Achieved via:
  - Expansion
  - P-box permutation
  - Multiple rounds

After 16 rounds → Strong avalanche effect.

## ◆ Why DES is Insecure Now

### ✗ Key Size Too Small

56-bit key →

Possible keys =  $2^{56}$

In 1998:

- EFF built a machine that broke DES in ~56 hours.

Now:

- Can be broken in hours or minutes using hardware.

## ◆ DES Attacks

- 1 Brute force
- 2 Differential cryptanalysis
- 3 Linear cryptanalysis

## ◆ Successor of DES

Due to weakness, DES replaced by:

- Triple DES (3DES)
- Advanced Encryption Standard (AES)

AES is currently standard.

## ◆ Final Exam-Ready Summary

**Confusion:** Makes key-ciphertext relationship complex using substitution.

**Diffusion:** Spreads plaintext bits across ciphertext using permutation.

**DES:**

- 64-bit block cipher
- 56-bit key
- 16-round Feistel structure
- Uses S-boxes (confusion) and permutation (diffusion)
- Insecure today due to small key size

If you want, I can next explain:

- DES key schedule
- Differential attack on DES
- Why Feistel allows same algorithm for encryption/decryption
- Comparison of DES vs AES

Tell me your depth level 🔥