AWS Scan Target Setup

This folder is only for customers who want CloudGuard to scan an AWS account. It is not required for hosting CloudGuard on DigitalOcean.

CloudFormation Template Upload

The template can be uploaded to any public HTTPS location. AWS S3 is one option, but for a DigitalOcean-hosted platform you can also store the template in DigitalOcean Spaces or serve it from the app/static hosting.

Recommended DigitalOcean Hosting

For a DigitalOcean deployment, place `enhanced-cloudformation-template.yaml` in a public DigitalOcean Space or serve it from the app/static hosting. The only requirement is a public HTTPS URL that AWS CloudFormation can fetch.

```
# Example with an S3-compatible CLI profile for DigitalOcean Spaces
aws --endpoint-url https://blr1.digitaloceanspaces.com s3 cp \
  infra/enhanced-cloudformation-template.yaml \
  s3://cloudguard-assets/cloudformation/aws-readonly-role.yaml \
  --content-type "text/yaml" \
  --acl public-read
```

The template URL will look like:

```
https://cloudguard-assets.blr1.digitaloceanspaces.com/cloudformation/aws-readonly-role.y
```

AWS S3 Alternative

If you already have an AWS bucket for scan-target setup assets, the old S3 flow still works. This is optional and is not part of CloudGuard hosting.

```
aws s3 cp infra/enhanced-cloudformation-template.yaml \
  s3://cloudguard-cfn-templates/cloudformation/aws-readonly-role.yaml \
  --region eu-north-1 \
  --content-type "text/yaml" \
  --acl public-read
```

Template URL

Use the public template URL in the AWS scanner onboarding flow when creating a read-only role in the customer's AWS account.

Validation

Validate the template before publishing:

```
aws cloudformation validate-template \
  --template-body file://infra/enhanced-cloudformation-template.yaml
```

CI/CD Integration

DigitalOcean Spaces can be used from GitHub Actions with S3-compatible credentials:

```
- name: Upload CloudFormation Template
  run: |
    aws --endpoint-url https://blr1.digitaloceanspaces.com s3 cp \
      infra/enhanced-cloudformation-template.yaml \
      s3://cloudguard-assets/cloudformation/aws-readonly-role.yaml \
      --content-type "text/yaml" \
      --acl public-read
  env:
    AWS_ACCESS_KEY_ID: ${{ secrets.DO_SPACES_KEY }}
    AWS_SECRET_ACCESS_KEY: ${{ secrets.DO_SPACES_SECRET }}
    AWS_DEFAULT_REGION: blr1
```

Troubleshooting

Permission denied

```
chmod +x scripts/upload-cfn-template.sh
```

Spaces credentials not configured

```
aws configure --profile digitalocean-spaces
```

AWS S3 bucket does not exist

```
aws s3 mb s3://cloudguard-cfn-templates --region eu-north-1
```

Public access blocked on an AWS S3 fallback bucket

```
aws s3api put-public-access-block \
  --bucket cloudguard-cfn-templates \
  --public-access-block-configuration \
    "BlockPublicAcls=false,IgnorePublicAcls=false,BlockPublicPolicy=false,RestrictPublic
```