This key is not known by any other names.

Are you sure you want to continue connecting (yes/no/[fingerprint])? yes

Warning: Permanently added '192.168.0.218' (ED25519) to the list of known hosts.

Sana@192.168.0.218's password:

Permission denied, please try again.

Sana@192.168.0.218's password:

Permission denied, please try again.

Sana@192.168.0.218's password:

Connection closed by 192.168.0.218 port 22

PS C:\Worthy\Linux Virtual Network> ssh root@192.168.0.218

root@192.168.0.218's password:

Permission denied, please try again.

root@192.168.0.218's password:

Permission denied, please try again.

root@192.168.0.218's password:

root@192.168.0.218: Permission denied (publickey,password).

PS C:\Worthy\Linux Virtual Network> ssh sana@192.168.0.218

sana@192.168.0.218's password:

Linux kali-Sana 6.18.9+kali-amd64 #1 SMP PREEMPT_DYNAMIC Kali 6.18.9-1kali1 (2026-02-10) x86_64

The programs included with the Kali GNU/Linux system are free software;

the exact distribution terms for each program are described in the

individual files in /usr/share/doc/*/copyright.

Kali GNU/Linux comes with ABSOLUTELY NO WARRANTY, to the extent

permitted by applicable law.

┌──(sana㉿kali-Sana)-[~]

└─$ hostname

kali-Sana

┌──(sana㉿kali-Sana)-[~]

└─$ whoami

sana

┌──(sana㉿kali-Sana)-[~]

└─$ pwd

/home/sana

┌──(sana㉿kali-Sana)-[~]

mand:

hint:

hint: git branch -m <name>

hint:

hint: Disable this message with "git config set advice.defaultBranchName false"

Initialized empty Git repository in /home/sana/projects/linux-virtual-network/.git/

┌──(sana㉿kali-Sana)-[~/projects/linux-virtual-network]

└─$ python3 -m venv .venv

┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]

└─$ source .venv/bin/activate

┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]

└─$ cd /home/Sana/projects/linux-virtual-network

cd: no such file or directory: /home/Sana/projects/linux-virtual-network

┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]

└─$ cd ~/home/Sana/projects/linux-virtual-network

cd: no such file or directory: /home/sana/home/Sana/projects/linux-virtual-network

ects/linux-virtual-network

┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]

└─$ cd ~/home/sana/projects/linux-virtual-network

cd: no such file or directory: /home/sana/home/sana/projects/linux-virtual-network

┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]

irtual-network

┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]

└─$ mkdir -p capture docs

┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]

└─$ touch README.md setup_network.py cleanup_network.py test_connectivity.py firewall.nft

┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]

└─$ cd ~/projects/linux-virtual-network

┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]

└─$ sudo python3 setup_network.py

[sudo] password for sana:

┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]

┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]

└─$ sudo ip netns list

┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]

└─$ cursor network_setup.py

cursor: command not found

┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]

└─$ nano network_setup.py

┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]

└─$ sudo python3 setup_network.py

┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]

└─$ sudo ip netns list

┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]

└─$ sudo ip netns exec lvc-client ping -c 3 10.10.1.1

Cannot open network namespace "lvc-client": No such file or directory

┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]

└─$ nano network_setup.py

┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]

└─$ ls -l

total 12

drwxrwxr-x 2 sana sana 4096 Oct 12 16:29 capture

-rw-rw-r-- 1 sana sana 0 Oct 12 16:31 cleanup_network.py

drwxrwxr-x 2 sana sana 4096 Oct 12 16:29 docs

-rw-rw-r-- 1 sana sana 0 Oct 12 16:31 firewall.nft

-rw-rw-r-- 1 sana sana 3940 Oct 12 16:51 network_setup.py

-rw-rw-r-- 1 sana sana 0 Oct 12 16:31 README.md

-rw-rw-r-- 1 sana sana 0 Oct 12 16:31 setup_network.py

-rw-rw-r-- 1 sana sana 0 Oct 12 16:31 test_connectivity.py

┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]

└─$ sudo python3 setup_network.py

```
┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]
└─$ sudo ip netns list

┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]
└─$ grep -n "netns\|namespace\|Namespace" setup_network.py

┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]
└─$ sudo python3 network_setup.py
+ ip netns delete lvc-client
Cannot remove namespace file "/run/netns/lvc-client": No such file or directory
+ ip netns delete lvc-router
Cannot remove namespace file "/run/netns/lvc-router": No such file or directory
+ ip netns delete lvc-server
Cannot remove namespace file "/run/netns/lvc-server": No such file or directory
+ ip link delete lvc-c-host
Cannot find device "lvc-c-host"
+ ip link delete lvc-r0-host
Cannot find device "lvc-r0-host"
+ ip link delete lvc-r1-host
Cannot find device "lvc-r1-host"
+ ip link delete lvc-s-host
Cannot find device "lvc-s-host"
+ ip link delete lvc-br0
Cannot find device "lvc-br0"
+ ip link delete lvc-br1
Cannot find device "lvc-br1"
+ ip netns add lvc-client
+ ip netns add lvc-router
+ ip netns add lvc-server
+ ip link add lvc-br0 type bridge
```

```
+ ip link set lvc-br0 up
+ ip link add lvc-br1 type bridge
+ ip link set lvc-br1 up
+ ip link add lvc-c-host type veth peer name lvc-c-ns
+ ip link set lvc-c-ns netns lvc-client
+ ip link set lvc-c-host master lvc-br0
+ ip link set lvc-c-host up
+ ip link add lvc-r0-host type veth peer name lvc-r0-ns
+ ip link set lvc-r0-ns netns lvc-router
+ ip link set lvc-r0-host master lvc-br0
+ ip link set lvc-r0-host up
+ ip link add lvc-r1-host type veth peer name lvc-r1-ns
+ ip link set lvc-r1-ns netns lvc-router
+ ip link set lvc-r1-host master lvc-br1
+ ip link set lvc-r1-host up
+ ip link add lvc-s-host type veth peer name lvc-s-ns
+ ip link set lvc-s-ns netns lvc-server
+ ip link set lvc-s-host master lvc-br1
+ ip link set lvc-s-host up
+ ip netns exec lvc-client ip link set lvc-c-ns name eth0
+ ip netns exec lvc-router ip link set lvc-r0-ns name eth0
+ ip netns exec lvc-router ip link set lvc-r1-ns name eth1
+ ip netns exec lvc-server ip link set lvc-s-ns name eth0
+ ip netns exec lvc-client ip link set lo up
+ ip netns exec lvc-client ip link set eth0 up
+ ip netns exec lvc-router ip link set lo up
+ ip netns exec lvc-router ip link set eth0 up
+ ip netns exec lvc-router ip link set eth1 up
+ ip netns exec lvc-server ip link set lo up
+ ip netns exec lvc-server ip link set eth0 up
+ ip netns exec lvc-client ip addr add 10.10.1.10/24 dev eth0
```

```
+ ip netns exec lvc-router ip addr add 10.10.1.1/24 dev eth0
+ ip netns exec lvc-router ip addr add 10.10.2.1/24 dev eth1
+ ip netns exec lvc-server ip addr add 10.10.2.10/24 dev eth0
+ ip netns exec lvc-client ip route add default via 10.10.1.1
+ ip netns exec lvc-server ip route add default via 10.10.2.1
+ ip netns exec lvc-router sysctl -w net.ipv4.ip_forward=1
net.ipv4.ip_forward = 1

Network created successfully.
Client: 10.10.1.10
Router: 10.10.1.1 and 10.10.2.1
Server: 10.10.2.10

┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]
└─$ sudo ip netns lis
lvc-server (id: 2)
lvc-router (id: 1)
lvc-client (id: 0)

┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]
└─$ sudo ip netns exec lvc-server ip addr
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue state UNKNOWN group default qlen 1000
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
    inet 127.0.0.1/8 scope host lo
       valid_lft forever preferred_lft forever
    inet6 ::1/128 scope host proto kernel_lo
       valid_lft forever preferred_lft forever
11: eth0@if12: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc noqueue state UP group default qlen 1000
    link/ether e6:94:18:c7:21:0c brd ff:ff:ff:ff:ff:ff link-netnsid 0
    inet 10.10.2.10/24 scope global eth0
       valid_lft forever preferred_lft forever
```

```
    inet6 fe80::e494:18ff:fec7:210c/64 scope link proto kernel_ll
       valid_lft forever preferred_lft forever

┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]
└─$ sudo ip netns exec lvc-router ip addr
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue state UNKNOWN group default qlen 1000
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
    inet 127.0.0.1/8 scope host lo
       valid_lft forever preferred_lft forever
    inet6 ::1/128 scope host proto kernel_lo
       valid_lft forever preferred_lft forever
7: eth0@if8: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc noqueue state UP group default qlen 1000
    link/ether d6:f4:e1:ff:a6:95 brd ff:ff:ff:ff:ff:ff link-netnsid 0
    inet 10.10.1.1/24 scope global eth0
       valid_lft forever preferred_lft forever
    inet6 fe80::d4f4:e1ff:feff:a695/64 scope link proto kernel_ll
       valid_lft forever preferred_lft forever
9: eth1@if10: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc noqueue state UP group default qlen 1000
    link/ether f6:e1:40:be:41:51 brd ff:ff:ff:ff:ff:ff link-netnsid 0
    inet 10.10.2.1/24 scope global eth1
       valid_lft forever preferred_lft forever
    inet6 fe80::f4e1:40ff:febe:4151/64 scope link proto kernel_ll
       valid_lft forever preferred_lft forever

┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]
└─$ sudo ip netns exec lvc-client ip addr
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue state UNKNOWN group default qlen 1000
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
    inet 127.0.0.1/8 scope host lo
       valid_lft forever preferred_lft forever
    inet6 ::1/128 scope host proto kernel_lo
```

```
    valid_lft forever preferred_lft forever
5: eth0@if6: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc noqueue state UP group default qlen 1000
  link/ether 9e:d5:ac:24:3d:4b brd ff:ff:ff:ff:ff:ff link-netnsid 0
  inet 10.10.1.10/24 scope global eth0
    valid_lft forever preferred_lft forever
  inet6 fe80::9cd5:acff:fe24:3d4b/64 scope link proto kernel_ll
    valid_lft forever preferred_lft forever


┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]
└─$ grep -nE "ip netns|ip addr|ip route|veth|bridge|nft" network_setup.py
29:    for bridge in BRIDGES:
30:        run("ip", "link", "delete", bridge, check=False)
43:    # Create bridges
44:    for bridge in BRIDGES:
45:        run("ip", "link", "add", bridge, "type", "bridge")
46:        run("ip", "link", "set", bridge, "up")
48:    # Create client-to-bridge veth pair
51:        "lvc-c-host", "type", "veth",
58:    # Create router-left-to-bridge veth pair
61:        "lvc-r0-host", "type", "veth",
68:    # Create router-right-to-bridge veth pair
71:        "lvc-r1-host", "type", "veth",
78:    # Create server-to-bridge veth pair
81:        "lvc-s-host", "type", "veth",


┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]
└─$ sudo ip netns exec lvc-client ping -c 10.10.2.10
ping: invalid argument: '10.10.2.10'


┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]
```

```
└─$ sudo ip netns exec lvc-client ping -c 3 10.10.2.10
PING 10.10.2.10 (10.10.2.10) 56(84) bytes of data.
64 bytes from 10.10.2.10: icmp_seq=1 ttl=63 time=0.102 ms
64 bytes from 10.10.2.10: icmp_seq=2 ttl=63 time=0.069 ms
64 bytes from 10.10.2.10: icmp_seq=3 ttl=63 time=0.075 ms

--- 10.10.2.10 ping statistics ---
3 packets transmitted, 3 received, 0% packet loss, time 2033ms
rtt min/avg/max/mdev = 0.069/0.082/0.102/0.014 ms

┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]
└─$ sudo ip netns exec lvc-client ip -br link
lo               UNKNOWN        00:00:00:00:00:00 <LOOPBACK,UP,LOWER_UP>
eth0@if6         UP             9e:d5:ac:24:3d:4b <BROADCAST,MULTICAST,UP,LOWER_UP>

┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]
└─$ ip -br link
lo               UNKNOWN        00:00:00:00:00:00 <LOOPBACK,UP,LOWER_UP>
wlan0            UP             b4:0e:de:25:2c:db <BROADCAST,MULTICAST,UP,LOWER_UP>
lvc-br0          UP             b6:44:b6:10:09:ee <BROADCAST,MULTICAST,UP,LOWER_UP>
lvc-br1          UP             46:23:7c:f1:aa:04 <BROADCAST,MULTICAST,UP,LOWER_UP>
lvc-c-host@if5   UP             b6:44:b6:10:09:ee <BROADCAST,MULTICAST,UP,LOWER_UP>
lvc-r0-host@if7  UP             de:7d:b7:3b:41:a3 <BROADCAST,MULTICAST,UP,LOWER_UP>
lvc-r1-host@if9  UP             e6:f4:41:ae:1b:82 <BROADCAST,MULTICAST,UP,LOWER_UP>
lvc-s-host@if11  UP             46:23:7c:f1:aa:04 <BROADCAST,MULTICAST,UP,LOWER_UP>

┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]
└─$ sudo ip netns exec lvc-client tcpdump -n -e -i eth0@if6 icmp
tcpdump: eth0@if6: No such device exists
(No such device exists)
```

┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]

└─$ sudo ip netns exec lvc-client tcpdump -n -e -i eth0 icmp

tcpdump: verbose output suppressed, use -v[v]... for full protocol decode

listening on eth0, link-type EN10MB (Ethernet), snapshot length 262144 bytes

^C17:36:32.481168 9e:d5:ac:24:3d:4b > d6:f4:e1:ff:a6:95, ethertype IPv4 (0x0800), length 98: 10.10.1.10 > 10.10.2.10: ICMP echo request, id 9909, seq 1, length 64

17:36:32.481197 d6:f4:e1:ff:a6:95 > 9e:d5:ac:24:3d:4b, ethertype IPv4 (0x0800), length 98: 10.10.2.10 > 10.10.1.10: ICMP echo reply, id 9909, seq 1, length 64

17:36:33.482473 9e:d5:ac:24:3d:4b > d6:f4:e1:ff:a6:95, ethertype IPv4 (0x0800), length 98: 10.10.1.10 > 10.10.2.10: ICMP echo request, id 9909, seq 2, length 64

17:36:33.482522 d6:f4:e1:ff:a6:95 > 9e:d5:ac:24:3d:4b, ethertype IPv4 (0x0800), length 98: 10.10.2.10 > 10.10.1.10: ICMP echo reply, id 9909, seq 2, length 64

17:36:34.506470 9e:d5:ac:24:3d:4b > d6:f4:e1:ff:a6:95, ethertype IPv4 (0x0800), length 98: 10.10.1.10 > 10.10.2.10: ICMP echo request, id 9909, seq 3, length 64

17:36:34.506518 d6:f4:e1:ff:a6:95 > 9e:d5:ac:24:3d:4b, ethertype IPv4 (0x0800), length 98: 10.10.2.10 > 10.10.1.10: ICMP echo reply, id 9909, seq 3, length 64

6 packets captured

6 packets received by filter

0 packets dropped by kernel

┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]

└─$ sudo ip netns exec lvc-client tcpdump -nn -i eth0 -w client-server.pcap

tcpdump: listening on eth0, link-type EN10MB (Ethernet), snapshot length 262144 bytes

^C14 packets captured

14 packets received by filter

0 packets dropped by kernel

┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]

└─$ sudo ip netns exec lvc-router tcpdump -nn -i any icmp

tcpdump: WARNING: any: That device doesn't support promiscuous mode

(Promiscuous mode not supported on the "any" device)

```
tcpdump: verbose output suppressed, use -v[v]... for full protocol decode
listening on any, link-type LINUX_SLL2 (Linux cooked v2), snapshot length 262144 bytes
^C17:41:07.226328 eth0  In  IP 10.10.1.10 > 10.10.2.10: ICMP echo request, id 9997, seq 1, length 64
17:41:07.226345 eth1  Out IP 10.10.1.10 > 10.10.2.10: ICMP echo request, id 9997, seq 1, length 64
17:41:07.226364 eth1  In  IP 10.10.2.10 > 10.10.1.10: ICMP echo reply, id 9997, seq 1, length 64
17:41:07.226367 eth0  Out IP 10.10.2.10 > 10.10.1.10: ICMP echo reply, id 9997, seq 1, length 64
17:41:08.234451 eth0  In  IP 10.10.1.10 > 10.10.2.10: ICMP echo request, id 9997, seq 2, length 64
17:41:08.234465 eth1  Out IP 10.10.1.10 > 10.10.2.10: ICMP echo request, id 9997, seq 2, length 64
17:41:08.234486 eth1  In  IP 10.10.2.10 > 10.10.1.10: ICMP echo reply, id 9997, seq 2, length 64
17:41:08.234489 eth0  Out IP 10.10.2.10 > 10.10.1.10: ICMP echo reply, id 9997, seq 2, length 64
17:41:09.258460 eth0  In  IP 10.10.1.10 > 10.10.2.10: ICMP echo request, id 9997, seq 3, length 64
17:41:09.258474 eth1  Out IP 10.10.1.10 > 10.10.2.10: ICMP echo request, id 9997, seq 3, length 64
17:41:09.258494 eth1  In  IP 10.10.2.10 > 10.10.1.10: ICMP echo reply, id 9997, seq 3, length 64
17:41:09.258497 eth0  Out IP 10.10.2.10 > 10.10.1.10: ICMP echo reply, id 9997, seq 3, length 64

12 packets captured
12 packets received by filter
0 packets dropped by kernel

┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]
└─$ sudo ip netns exec lvc-router sysctl net.ipv4.ip_forward
net.ipv4.ip_forward = 1

┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]
└─$ sudo ip netns exec lvc-client ip route
default via 10.10.1.1 dev eth0
10.10.1.0/24 dev eth0 proto kernel scope link src 10.10.1.10

┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]
└─$ sudo ip netns exec lvc-server ip route
```

default via 10.10.2.1 dev eth0

10.10.2.0/24 dev eth0 proto kernel scope link src 10.10.2.10

┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]

└─$ sudo ip netns exec lvc-router ip route

10.10.1.0/24 dev eth0 proto kernel scope link src 10.10.1.1

10.10.2.0/24 dev eth1 proto kernel scope link src 10.10.2.1

┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]

└─$ sudo nft list ruleset

┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]

└─$ sudo ip netns exec lvc-router nft list ruleset

┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]

└─$ wireshark client-server.pcap

** (wireshark:10287) 18:01:13.578596 [GUI WARNING] -- could not connect to display

** (wireshark:10287) 18:01:13.578623 [GUI WARNING] -- From 6.5.0, xcb-cursor0 or libxcb-cursor0 is needed to load the Qt xcb platform plugin.

** (wireshark:10287) 18:01:13.578636 [GUI ERROR] -- This application failed to start because no Qt platform plugin could be initialized. Reinstalling the application may fix this problem.

Available platform plugins are: wayland-brcm, wayland-egl, wayland, xcb, vkkhrdisplay, offscreen, minimal, vnc, eglfs, minimalegl, linuxfb.

** (wireshark:10287) Aborting on fatal log level exception

zsh: IOT instruction wireshark client-server.pcap

```
┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]
└─$ sudo ip netns exec lvc-router nft -f firewall.nft

┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]
└─$ sudo ip netns exec lvc-router nft list ruleset
table inet lvc_firewall {
    chain forward {
        ip saddr 10.10.1.0/24 ip daddr 10.10.2.0/24 icmp type echo-request counter packets 3 bytes 252 drop
    }
}

┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]
└─$ sudo ip netns exec lvc-router nft delete table inet lvc_firewall

        ip saddr 10.10.1.0/24 ip daddr 10.10.2.0/24 icmp type echo-request couirtual-network]
└─$ sudo ip netns exec lvc-router nft delete table inet lvc_firewall

┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]
└─$ sudo ip netns exec lvc-client ping -c 3 10.10.2.10
PING 10.10.2.10 (10.10.2.10) 56(84) bytes of data.
64 bytes from 10.10.2.10: icmp_seq=1 ttl=63 time=0.061 ms
64 bytes from 10.10.2.10: icmp_seq=2 ttl=63 time=0.072 ms
64 bytes from 10.10.2.10: icmp_seq=3 ttl=63 time=0.076 ms

--- 10.10.2.10 ping statistics ---
3 packets transmitted, 3 received, 0% packet loss, time 2053ms
rtt min/avg/max/mdev = 0.061/0.069/0.076/0.006 ms
irtual-network]
└─$ sudo ip netns exec lvc-router nft delete table inet lvc_firewall
```

┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-v┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]

└─$ sudo ip link add lvc-uplink-host type veth peer name lvc-uplink-router

Error: argument "lvc-uplink-router" is wrong: "name" not a valid ifname

┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]

└─$ sudo ip link add lvc-up-h type veth peer name lvc-up-r

┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]

└─$ sudo ip link set lvc-up-r netns lvc-router

┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]

└─$ sudo ip addr add 10.10.99.1/24 dev lvc-up-h

┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]

└─$ sudo ip link set lvc-up-h up

┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]

└─$ sudo ip netns exec lvc-router ip link set lvc-up-r name eth2

┌──(.venv)─(sana㉿kali-Sana)-[~/projects/linux-virtual-network]

└─$ client_loop: send disconnect: Connection reset

PS C:\Worthy\Linux Virtual Network> ssh sana@192.168.0.218

ssh: connect to host 192.168.0.218 port 22: Connection timed out

PS C:\Worthy\Linux Virtual Network> ssh sana@192.168.0.218

ssh: connect to host 192.168.0.218 port 22: Connection timed out

PS C:\Worthy\Linux Virtual Network> ping 192.168.0.218

Pinging 192.168.0.218 with 32 bytes of data:

Reply from 192.168.0.192: Destination host unreachable.

Reply from 192.168.0.192: Destination host unreachable.

Reply from 192.168.0.192: Destination host unreachable.

Reply from 192.168.0.192: Destination host unreachable.

Ping statistics for 192.168.0.218:

    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),

PS C:\Worthy\Linux Virtual Network> ssh sana@192.168.0.218

ssh: connect to host 192.168.0.218 port 22: Connection timed out