



**DEPARTMENT OF  
COMPUTER SCIENCE & ENGINEERING**

Discover. Learn. Empower.



**CHANDIGARH  
UNIVERSITY**

Discover. Learn. Empower.

## **Project Report:**

# **Maze Solver using A\* Algorithm**

**Subject Name – Design and Analysis of Algorithms**

**Subject Code – 23CSH-301**

<b>Submitted To:</b>	<b>Submitted By:</b>
<b>Er. Mohammad Shaqlain (E17211)</b>	<b>Name: Sanampreet Singh</b>
	<b>UID: 23BCS13053</b>
	<b>Section: KRG_2-B</b>

*An implementation of the Randomized Depth-First Search (DFS) algorithm to generate a maze, and the A\* algorithm to find the shortest path.*

## 1. Introduction / Constraints

The program generates a random 10 X 10 maze using the Depth-First Search (DFS) algorithm and subsequently finds the shortest path from the Start cell (top-left, index 0) to the Goal cell (bottom-right, index 99) using the A\* Search Algorithm.

### Constraints:

- **Grid:** N X N grid (where N=10).
- **Movement:** Only orthogonal movement is allowed (North, East, South, West).
- **Solution:** The path must exist only through broken walls (paths) and must be the shortest possible route between the start and goal.

## 2. Input / Apparatus Used

- **Programming Language:** C++
- **IDE Used:** [Code::Blocks / VS Code / Visual Studio]
- **Input:** 10 X 10 array representing the maze structure and walls (generated internally by DFS).

## 3. Procedure / Algorithm

### Algorithm: A\* Search Algorithm (Best-First Search)

The A\* algorithm finds the shortest path by evaluating a cost function  $f(n)$  for every node  $n$ :

$$f(n) = g(n) + h(n)$$

Term	Description
$g(n)$	The actual cost (distance/steps) from the <b>Start</b> node to the current node $n$ .
$h(n)$	The estimated cost (heuristic) from the current node $n$ to the <b>Goal</b> node.
$f(n)$	The total estimated cost of the path through node $n$ . The algorithm prioritizes the node with the lowest $f(n)$ value.

**Heuristic Used:** The program uses the **Manhattan Distance** as the heuristic  $h(n)$ , which calculates the sum of the absolute differences in the X and Y coordinates between the current cell and the goal cell. This is an admissible heuristic, guaranteeing the shortest path is found.

**Procedure Steps:**

1. Initialize the Start cell's  $g=0$  and calculate its initial  $f$  score.
2. Set the current cell to the Start cell and add it to the Closed List (or mark as visited in `mazeBlocks[n][3]`).
3. Identify all valid, unvisited neighbors of the current cell.
4. For each neighbor, calculate its new  $g$  (current  $g+1$ ),  $h$ , and  $f$  scores.
5. If the new  $f$  score is lower than the previously recorded  $f$  score, update the cell's scores and set the current cell as its Parent (`mazeBlocks[n][4]`).
6. Select the unvisited node with the lowest  $f$  score (breaking ties with the lowest  $h$  score) and make it the new current cell.
7. Repeat steps 3-6 until the Goal is reached.
8. Reconstruct the shortest path by backtracking from the Goal to the Start using the recorded Parent pointers.

**4. C++ Program:**

```
#include <iostream>
#include <cstdlib>
#include <ctime>
#include <cmath>
#include <vector>
#include <numeric>
#include <string>
#include <algorithm>

const int size = 10;

bool visited[size * size];
```

```
bool walls[size * size][2] = { 0 };
```

```
const int start = 0;  
const int goal = size * size - 1;
```

```
int path[size * size] = { 0 };
```

```
int mazeBlocks[size * size][5];
```

```
int pos = start;  
int rot = 0;  
int pathIndex = 0;
```

```
int emptyWalls[4] = { 0 };  
int emptyWallsCount = 0;
```

```
/**  
 * @brief Finds the delta to an unvisited neighbor for DFS maze generation.  
 * @param currentPos The index of the current cell.  
 * @param size The size of the maze grid (side length).  
 * @return The delta (+/- 1 or +/- size) to the next cell, or 0 if no unvisited neighbors exist.  
 */  
int nextCell(int currentPos, int size) {  
    std::vector<int> options;  
  
    if (currentPos >= size && !visited[currentPos - size]) { options.push_back(-size); }  
    if ((currentPos + 1) % size != 0 && !visited[currentPos + 1]) { options.push_back(1); }  
    if (currentPos < size * (size - 1) && !visited[currentPos + size]) { options.push_back(size); }  
    if (currentPos % size != 0 && !visited[currentPos - 1]) { options.push_back(-1); }  
  
    if (options.empty()) { return 0; }  
  
    return options[rand() % options.size()];  
}  
  
/**
```

```
* @brief Breaks the wall between two adjacent cells.
* @param pos1 Index of the first cell.
* @param pos2 Index of the second cell.
*/
void connect(int pos1, int pos2) {
    if (pos2 > pos1) {
        if (pos2 == pos1 + 1) {
            walls[pos2][0] = 1;
        } else {
            walls[pos2][1] = 1;
        }
    } else {
        if (pos1 == pos2 + 1) {
            walls[pos1][0] = 1;
        } else {
            walls[pos1][1] = 1;
        }
    }
}

/**
* @brief Generates the maze using Randomized Depth-First Search (DFS).
* @param currentPos The index of the current cell.
* @param size The size of the maze grid.
*/
void randomdfs(int currentPos, int size) {
    visited[currentPos] = true;
    int nextDelta;

    while ((nextDelta = nextCell(currentPos, size)) != 0) {
        int nextPos = currentPos + nextDelta;
        connect(currentPos, nextPos);
        randomdfs(nextPos, size);
    }
}
```



# DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

```
/**
 * @brief Initializes and runs the DFS maze generation.
 */
void createMazeDFS() {
    std::cout << "Starting DFS maze generation..." << std::endl;
    for (int i = 0; i < size * size; ++i) {
        visited[i] = false;
        walls[i][0] = 0;
        walls[i][1] = 0;
        path[i] = 0;
    }

    randomdfs(start, size);
    std::cout << "Maze generation complete." << std::endl;
}

/**
 * @brief Finds open walls from the current position. Used for A*.
 */
void getEmptyWalls() {
    emptyWallsCount = 0;

    if (pos >= size && walls[pos][1]) {
        emptyWalls[emptyWallsCount++] = -size;
    }
    if ((pos + 1) % size != 0 && walls[pos + 1][0]) {
        emptyWalls[emptyWallsCount++] = 1;
    }
    if (pos < size * (size - 1) && walls[pos + size][1]) {
        emptyWalls[emptyWallsCount++] = size;
    }
    if (pos % size != 0 && walls[pos][0]) {
        emptyWalls[emptyWallsCount++] = -1;
    }
}
```

```
/**
 * @brief Updates G, H, F, and Parent values for a neighbor in A* search.
 */
void aStarCalculate(int neighborPos) {
    int g = mazeBlocks[pos][0] + 1;

    int dx = std::abs(neighborPos % size - goal % size);
    int dy = std::abs((neighborPos / size) - (goal / size));
    int h = dx + dy;

    int f = g + h;

    if (mazeBlocks[neighborPos][2] == 0 || f < mazeBlocks[neighborPos][2]) {
        mazeBlocks[neighborPos][0] = g;
        mazeBlocks[neighborPos][1] = h;
        mazeBlocks[neighborPos][2] = f;
        mazeBlocks[neighborPos][4] = pos;
    }
}

/**
 * @brief Solves the maze using the A* search algorithm (guaranteed shortest path).
 * @return The length of the shortest path found.
 */
int solveMazeAstar() {
    for (int i = 0; i < size * size; i++) {
        for (int j = 0; j < 5; j++) {
            mazeBlocks[i][j] = 0;
        }
        path[i] = 0;
    }

    pos = start;
    mazeBlocks[pos][0] = 0;
    mazeBlocks[pos][1] = std::abs(pos % size - goal % size) + std::abs((pos / size) - (goal /
size));
}
```

```
mazeBlocks[pos][2] = mazeBlocks[pos][1];

while (pos != goal) {
    mazeBlocks[pos][3] = 1;

    getEmptyWalls();

    for (int i = 0; i < emptyWallsCount; i++) {
        int neighborPos = pos + emptyWalls[i];
        if (mazeBlocks[neighborPos][3] == 0) {
            aStarCalculate(neighborPos);
        }
    }
    int minf = size * size * 2;
    int minh = size * size;
    int nextCell = -1;

    for (int i = 0; i < size * size; i++) {
        if (mazeBlocks[i][3] == 0 && mazeBlocks[i][2] != 0) {
            if (mazeBlocks[i][2] < minf) {
                minf = mazeBlocks[i][2];
                minh = mazeBlocks[i][1];
                nextCell = i;
            } else if (mazeBlocks[i][2] == minf && mazeBlocks[i][1] < minh) {
                minh = mazeBlocks[i][1];
                nextCell = i;
            }
        }
    }

    if (nextCell == -1) {
        return -1;
    }

    pos = nextCell;
}
```



```
int currentCell = goal;
std::vector<int> shortestPathCells;

while (currentCell != -1) {
    shortestPathCells.push_back(currentCell);
    if (currentCell == start) break;
    currentCell = mazeBlocks[currentCell][4];
}
int pathLength = shortestPathCells.size() - 1;
for (size_t i = 0; i < shortestPathCells.size(); ++i) {
    int cellIndex = shortestPathCells[shortestPathCells.size() - 1 - i];
    path[cellIndex] = i + 1;
}
return pathLength;
}

/**
 * @brief Prints the maze representation with the corresponding solution path markers.
 * @param title The title for the maze output.
 */
void printMaze(const std::string& title) {
    std::cout << "\n===== " <<
std::endl;
    std::cout << "--- " << title << " (" << size << "x" << size << ") ---" << std::endl;
    std::cout << "===== " << std::endl;

    bool is_unsolved = title.find("Unsolved") != std::string::npos;
    bool is_astar_solved = title.find("A* Shortest Path") != std::string::npos;

    for (int j = 0; j < size; ++j) {
        for (int i = 0; i < size; ++i) {
            int currentPos = j * size + i;

            std::cout << "+";

            bool wallOpen = false;
```



# DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

```
if (j > 0) {
    wallOpen = walls[currentPos][1] == 1;
} else {
    if (currentPos == start) {
        wallOpen = true;
    }
}
if (wallOpen) {
    std::cout << " ";
} else {
    std::cout << "---";
}
}
std::cout << "+\n";

for (int i = 0; i < size; ++i) {
    int currentPos = j * size + i;

    bool wallOpen = false;
    if (i == 0) {
        if (currentPos == start) {
            wallOpen = true;
        } else {
            wallOpen = false;
        }
    } else {
        wallOpen = walls[currentPos][0] == 1;
    }
    if (wallOpen) {
        std::cout << " ";
    } else {
        std::cout << "|";
    }
}

if (is_unsolved) {
    if (currentPos == start) std::cout << " S ";
}
```

```
        else if (currentPos == goal) std::cout << " G ";
        else std::cout << " ";
    }
    else if (is_astar_solved && path[currentPos] > 0) {
        int step = path[currentPos];
        std::string s = std::to_string(step);

        if (s.length() == 1) std::cout << " " << s;
        else if (s.length() == 2) std::cout << " " << s;
        else if (s.length() >= 3) std::cout << s.substr(0, 3);
    }
    else {
        std::cout << " ";
    }
}

if (j == size - 1) {
    if (goal % size == size - 1) {
        bool pathExists = (is_astar_solved && path[goal] > 0);

        if (pathExists || is_unsolved) {
            std::cout << "\n";
        } else {
            std::cout << "| \n";
        }
    } else {
        std::cout << "| \n";
    }
} else {
    std::cout << " | \n";
}
}

for (int i = 0; i < size; ++i) {
    std::cout << "+";
    if (i == size - 1) {
        bool pathExists = (is_astar_solved && path[goal] > 0);

        if (pathExists || is_unsolved) {
            std::cout << " ";
        } else {

```



# DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

```
        std::cout << "---";
    }
} else {
    std::cout << "---";
}
}
std::cout << "+\n";

if (is_unsolved) {
    std::cout << "Legend: S=Start, G=Goal\n";
} else if (is_astar_solved) {
    std::cout << "Legend: 1,2,3...=A* Shortest Path Steps\n";
}
}

int main(){
    srand(time(NULL));
    createMazeDFS();

    for (int i = 0; i < size * size; i++)
        path[i] = 0;

    printMaze("Unsolved Maze");

    std::cout << "\nStarting A* search solution..." << std::endl;
    int aStarLength = solveMazeAstar();

    if (aStarLength != -1) {
        std::cout << "A* solution complete. Shortest path length: " << aStarLength << " steps." <<
std::endl;
        printMaze("A* Shortest Path");
    } else {
        std::cout << "A* FAILED: No path found." << std::endl;
    }

    std::cout << "\nExecution finished. Maze size reduced to " << size << "x" << size << " for console
visualization." << std::endl;

    return 0;
}
```



## 5. Sample Output:

```
Execution finished. Maze size reduced to 10x10 for console visualization.
PS C:\Users\HP\Desktop\DAA project>
```



# DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

```
cd "c:\Users\HP\Desktop\DAA project\" ; if ($?) { g++ main.cpp -o main } ; if ($?) { .\main }  
Starting DFS maze generation...  
Maze generation complete.
```

```
-----  
--- Unsolved Maze (10x10) ---  
-----
```

```
+ +---+---+---+---+---+---+---+---+  
S |           |           |  
+ + +---+---+---+ + +---+---+  
| | |           |           |  
+ +---+ + +---+---+---+---+ +  
| | |           |           |  
+---+ +---+ +---+ + +---+ + +  
| | |           | | |           |  
+ +---+ +---+ +---+ + +---+ +  
| | |           | | |           |  
+ + + +---+---+---+---+ + + +  
| | |           |           |  
+ + +---+---+ + +---+---+---+ +  
| | |           | | |           |  
+---+ + + + +---+ +---+ + + +  
| | |           | | |           |  
+ +---+---+---+---+---+ + + +  
| |           |           | | |  
+ +---+ + +---+---+ +---+ + +  
| |           |           | G  
+---+---+---+---+---+---+---+---+  
Legend: S=Start, G=Goal
```

```
Starting A* search solution...  
A* solution complete. Shortest path length: 20 steps.
```

```
-----  
--- A* Shortest Path (10x10) ---  
-----
```

```
+ +---+---+---+---+---+---+---+---+  
1 |           |           |  
+ + +---+---+---+ + +---+---+  
| 2 |           |           |  
+ +---+ + +---+---+---+---+ +  
| 3 4 |           |           |  
+---+ +---+ +---+ + +---+ + +  
| | 5 6 |           | | |           |  
+ +---+ +---+ +---+ + +---+ +  
| | | 7 |           | | |           |  
+ + + +---+---+---+ + + + +  
| | | 8 9 10 |           | |  
+ + +---+---+ + +---+---+---+ +  
| | |           | 11 | | 15 16 17 |  
+---+ + + + +---+ +---+ + + +  
| | |           | 12 13 14 | | 18 |  
+ +---+---+---+---+---+ + + +  
| |           |           | 19 |  
+ +---+ + +---+---+ +---+ + +  
| |           |           | 20 21  
+---+---+---+---+---+---+---+---+  
Legend: 1,2,3...=A* Shortest Path Steps
```

#### 4. Complexity Analysis:

Let  $N$  be the side length of the grid (10), and  $V$  be the total number of cells,  $V = N^2$  (100).

- **Worst Case Time:**  $O(V^2)$  or  $O((N^2)^2)$ 
  - The current implementation finds the next node with the minimum F score by iterating linearly through all  $V$  cells in every step. In the worst case, this leads to  $V$  iterations, repeated up to  $V$  times.
- **Space Complexity:**  $O(V)$  or  $O(N^2)$ 
  - Space is dominated by the storage for the maze grid (walls), the visited flags (visited), and the A\* data (mazeBlocks), all proportional to the total number of cells  $V$ .

#### 5. Result

The program successfully **generates a random maze and solves** the puzzle using the A\* Shortest Path Algorithm. The resulting path is guaranteed to be optimal (minimal number of steps) and is clearly visualized using sequential step numbers from 1 (Start) to L (Goal).

#### 6. Conclusion

1. **Project Success and Algorithm Validation:** The implementation successfully combined the **Randomized DFS** for robust maze generation and the **A\* Search Algorithm** to reliably find the path, demonstrating proficiency in graph traversal and informed search techniques.
2. **Optimality through Heuristic:** The use of the **admissible Manhattan Distance heuristic** ensures that the A\* algorithm is optimally guided and guarantees the discovery of the absolute shortest path, validating the core principle of the search strategy.



# DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

3. **Complexity Bottleneck:** The current A\* implementation exhibits a worst-case time complexity of  $O(V^2)$ . This is primarily due to the inefficient linear search used to select the next node with the minimum  $f(n)$  score in each iteration.
4. **Future Optimization:** To enhance performance for larger maze sizes, future work should focus on integrating a **Priority Queue** data structure. This optimization is expected to improve the worst-case time complexity to a more efficient  $O(V \log V)$ .