

Text file to create

We need to set red words

The blue part can be omitted

■ Neural network setting 「NET.txt」

CrossEntropy	Square or CrossEntropy
BATCH_SIZE 50	Mini batch size
EPOCH 10	Epoch number
LAMBDA 0.000000	Load decay (weight decay)
EPS 0.001000	Learning rate
OPTIMIZER Adam	Optimizer
VALIDATION_NUM 100	Number of Validation data
ERROR_PLOT_STEP 10	Graph data output interval(gnuplot format)
TEST_SAMPLE 10	Number of test data samples
ACCURACY_RATE_PLOT 1	Accuracy plotting
※optimizer solver is listed on the final page	

~~* Leave the setting of LAMBDA to 0 (there is a problem)~~

ERROR_PLOT_STEP

The loss value is output to 'error_loss.dat' at the interval specified at the time of learning. **gnuplot** can display graphs in real time.

Gnuplot script example



```
set border lc rgb "white"
set grid lc rgb "white" lt 2
set key opaque box
set object 1 rect behind from screen 0,0 to screen 1,1 fc rgb "#B8B2C3" fillstyle solid

# smooth [unique, csplines, acsplines, bezier, sbezier]

plot 'error_loss.dat' using 1:2 t "varidation" with lines linewidth 2 linecolor rgbcolor "red"
replot 'error_loss.dat' using 1:3 t "test sample" with lines linewidth 2 linecolor rgbcolor "blue"

#replot 'error_loss.dat' using 1:2 t "varidation" with lines linewidth 1 linecolor rgbcolor "red"
#replot 'error_loss.dat' using 1:3 t "test sample" with lines linewidth 1 linecolor rgbcolor "blue"

pause 10
reread
```

ACCURACY_RATE_PLOT

Accuracy is output to 'accuracy_rate.dat' at the interval specified at the time of learning. **gnuplot** can display graphs in real time.

Gnuplot script example



```
set border lc rgb "white"
set grid lc rgb "white" lt 2
set key opaque box
set object 1 rect behind from screen 0,0 to screen 1,1 fc rgb "#B8B2C3" fillstyle solid
set key right bottom

# smooth [unique, csplines, acsplines, bezier, sbezier]

plot 'accuracy_rate.dat' using 1:2 t "validation accuracy" with lines linewidth 2 linecolor
rgbcolor "red"
replot 'accuracy_rate.dat' using 1:3 t "test sample accuracy" with lines linewidth 2 linecolor
rgbcolor "blue"

pause 10
reread
```

■ Layer setting 「LAYER.txt」

LAYER 4 1 [28, 28] <i>Each layer setting</i> <i>See layer description</i> END	Number of layers Input feature map from left, input unit width, input unit height ※ Width and height are numbers when input units are regarded as a matrix
--	--

■ Describing layers Fully Connected layer

LAYER_TYPE_FullyConnected/layerName 1 [7, 7] -> [1, 10] Softmax	From the left, input of feature map, output unit width, output unit height, start function ※ The width and height are the numbers when looking at the input device as a matrix ※ Activation function described on final page
---	--

Convolutional layer

LAYER_TYPE_Convolutional/layerName 20 [28, 28] -> (5, 5) -> [28, 28] st 1 ReLU	From the left, input feature map, convolution width, convolution height, stride, activation function
---	--

Convolutional layer

LAYER_TYPE_Convolutional/layerName 20 [28, 28] -> (5, 5) -> [28, 28] st 1 pd 2 ReLU	From the left, input feature map, convolution width, convolution height, stride, padding activation function
--	--

maxPooling layer

LAYER_TYPE_maxPooling/layerName 20 [28, 28] -> (4, 4) -> [7, 7] st 4 Identity	From the left, input feature map, convolution width, convolution height, stride, activation function
--	--

maxPooling layer

LAYER_TYPE_maxPooling/layerName 20 [28, 28] -> (4, 4) -> [7, 7] st 4 pd 0 Identity	From the left, input feature map, convolution width, convolution height, stride, padding, activation function
---	---

AveragePooling layer

LAYER_TYPE_AveragePooling /layerName 20 [28, 28] -> (4, 4) -> [7, 7] st 4 Identity	From the left, input feature map, convolution width, convolution height, stride, activation function
---	--

maxPooling layer

LAYER_TYPE_AveragePooling /layerName 20 [28, 28] -> (4, 4) -> [7, 7] st 4 pd 0 Identity	From the left, input feature map, convolution width, convolution height, stride, padding, activation function
--	---


Dropout layer

LAYER_TYPE_Dropout/layerName 0.5 Identity	From the left, 0.5 is the dropout rate, activation function
--	---

■ Activation function can use


Identity

$$h(x) = x$$




ReLU

$$h(x) = \max(0, x)$$




Sigmoid

$$h(x) = \frac{1}{1 + e^{-x}} = \frac{\tanh(x/2) + 1}{2}$$




Tanh

$$h(x) = \tanh(x)$$




Abs

$$h(x) = |x|$$




Softsign

$$h(x) = \frac{x}{1 + |x|}$$




Softplus

$$h(x) = \log(1 + e^x)$$




LReLU

$$h(x) = \max(0.01x, x)$$



ELU

$$h(x) = \begin{cases} e^x - 1 & x < 0 \\ x & x \geq 0 \end{cases}$$



Softmax

$$h(x) = \frac{\exp(x)}{\sum_{j=1}^n \exp(x_j)}$$

Output UNIT

Activation function	Loss function	Differentiation of loss function
Identity $h(x) = x$	Square	$\frac{\partial E}{\partial w} = y - t$
Softmax $h(x) = \frac{\exp(x)}{\sum_{j=1}^n \exp(x_j)}$	CrossEntropy	$\frac{\partial E}{\partial w} = y - t$

■Optimizer solver

Adam

$$\begin{aligned}m_{t+1} &= \beta_1 m_t + (1 - \beta_1) \nabla E(\mathbf{w}^t) \\v_{t+1} &= \beta_2 v_t + (1 - \beta_2) \nabla E(\mathbf{w}^t)^2 \\ \hat{m} &= \frac{m_{t+1}}{1 - \beta_1^t} \\ \hat{v} &= \frac{v_{t+1}}{1 - \beta_2^t} \\ \mathbf{w}^{t+1} &= \mathbf{w}^t - \alpha \frac{\hat{m}}{\sqrt{\hat{v}} + \epsilon}\end{aligned}$$

$$\alpha=0.001, \beta_1=0.9, \beta_2=0.999, \epsilon=10E-8$$

AdaGrad

$$\begin{aligned}h_0 &= \epsilon \\ h_t &= h_{t-1} + \nabla E(\mathbf{w}^t)^2 \\ \eta_t &= \frac{\eta_0}{\sqrt{h_t}} \\ \mathbf{w}^{t+1} &= \mathbf{w}^t - \eta_t \nabla E(\mathbf{w}^t)\end{aligned}$$

$$\epsilon=10E-8, \eta_0=0.001$$

RMSprop

$$\begin{aligned}h_t &= \alpha h_{t-1} + (1 - \alpha) \nabla E(\mathbf{w}^t)^2 \\ \eta_t &= \frac{\eta_0}{\sqrt{h_t} + \epsilon} \\ \mathbf{w}^{t+1} &= \mathbf{w}^t - \eta_t \nabla E(\mathbf{w}^t)\end{aligned}$$

$$\alpha=0.99, \epsilon=10E-8, \eta_0=0.01$$

AdaDelta

$$\begin{aligned}h_t &= \rho h_{t-1} + (1 - \rho) \nabla E(\mathbf{w}^t)^2 \\ v_t &= \frac{\sqrt{s_t + \epsilon}}{\sqrt{h_t + \epsilon}} \nabla E(\mathbf{w}^t) \\ s_{t+1} &= \rho s_t + (1 - \rho) v_t^2 \\ \mathbf{w}^{t+1} &= \mathbf{w}^t - v_t\end{aligned}$$

$$\rho=0.95, \epsilon=10E-6$$

SGD

$$\mathbf{w}^{t+1} \leftarrow \mathbf{w}^t - \eta \frac{\partial E(\mathbf{w}^t)}{\partial \mathbf{w}^t}$$

$$\eta=0.01$$