

# Lecture 4 – Binary representation

Dr. Aftab M. Hussain,  
Assistant Professor, PATRIOT Lab, CVEST

## Chapter 2

# Signed magnitude representation

- In this notation, the number consists of a magnitude and a symbol ( + or - ) or a bit (0 or 1) indicating the sign
- This is similar to the representation of signed numbers used in ordinary arithmetic
- For example, the string of bits 01001 represents +9, and 11001 represents -9 in signed magnitude representation
- In signed-magnitude, -9 is obtained from +9 by changing only the sign bit in the leftmost position from 0 to 1
- Weird: +0 is represented as 0000 and minus 0 is represented as 1000. So, two representations for zero – inefficient and may cause errors

# Signed complement representation

- When arithmetic operations are implemented in a computer, it is more convenient to use a different system, referred to as the *signed complement* system, for representing negative numbers
- In this system, a negative number is indicated by its complement
- Whereas the signed-magnitude system negates a number by changing its sign, the signed-complement system negates a number by taking its complement
- Since positive numbers always start with 0 (plus) in the leftmost position (in all representations), it follows that the complement will always start with a 1, indicating a negative number
- In signed-1's-complement, -9 is obtained by taking the 1's complement of all the bits of +9, including the sign bit
- The signed-2's-complement representation of -9 is obtained by taking the 2's complement of the positive number, including the sign bit

# Reading and Writing signed complements

- Write into memory the following numbers in signed 2's complement representation in 4 bits:
  - +3
  - -7
  - 0
- We read these numbers from memory knowing its in signed 2's complement representation in 4 bits:
  - $(1100)_2$
  - $(1111)_2$
  - $(0000)_2$
  - $(1000)_2$

# Interpretations for 4 bit binary numbers

<b>Decimal</b>	<b>Signed-2's Complement</b>	<b>Signed-1's Complement</b>	<b>Signed Magnitude</b>
+7	0111	0111	0111
+6	0110	0110	0110
+5	0101	0101	0101
+4	0100	0100	0100
+3	0011	0011	0011
+2	0010	0010	0010
+1	0001	0001	0001
+0	0000	0000	0000
−0	—	1111	1000
−1	1111	1110	1001
−2	1110	1101	1010
−3	1101	1100	1011
−4	1100	1011	1100
−5	1011	1010	1101
−6	1010	1001	1110
−7	1001	1000	1111
−8	1000	—	—

# Signed addition

- Here is some magic: if the numbers are represented in memory in 2's complement form, we just need to add the two numbers, the sign takes care of itself!
- Bigger magic: the result is also in 2's complement representation
- The sign bit is to be included in the addition and if there is a carry, it is discarded
- Examples in 4-bit signed 2's complement representation:
  1.  $3+1$
  2.  $1+(-7)$
  3.  $(-8)+5$
  4.  $7+(-3)$
- In order to obtain a correct answer, we must ensure that the result has a sufficient number of bits to accommodate the sum
- If we start with two  $n$ -bit numbers and the sum occupies  $n + 1$  bits, we say that an overflow occurs

# Signed subtraction

- Subtraction of two signed binary numbers when negative numbers are in 2's-complement form is simple and can be stated as follows:
  - Take the 2's complement of the subtrahend (including the sign bit) and add it to the minuend (including the sign bit)
  - A carry out is discarded, if any
- This works because:  $M - N = M + (-N)$
- Examples in 4-bit signed 2's complement representation:
  1. 3-5
  2. 6-2
  3. 1-7