Date ___/___/_____

Assignment C4

* **Title:-** Sentiment Analysis

* **Objective:-** (i) Understand idea & concept of text preprocessing.
  (ii) Understand ML algorithms used for sentiment analysis.

* **Problem statement:-** Use Twitter data for sentiment analysis. Identify tweets which are hate tweets & which are not.

* **Outcome:-** (i) Understood Regex for text preprocessing.
  (ii) Understood concept of classification algorithms.

* **S/W & H/W Requirements:-**
  - Jupyter notebook, GPU (preferably).
  - Python libraries.

* **Theory:-**

1) **Sentiment Analysis:-**
   - Contextual mining of text.
   - Identifies & extracts subjecting meaning of text.
   - also called opinion mining.
   - basically refers to classification of given text, here tweet, as negative or positive based on words present in the tweet.



Date ___ / ___ / _____

supervised

↓ Decision tree ↓ Linear ↓ Rule-based ↓ Probabilistic.

Fig:- Sentiment Analysis Technique.

- Logistic Regression.
  - makes use of sigmoid fn to calculate probability of tweet belonging to a particular class.

$$P(t) = \sigma(t) = \frac{1}{1+e^{-t}}.$$



Fig:- Graph of sigmoid fn.

- idea is to minimize the cost fn

$$J(\theta) = \frac{1}{m}\left[\sum_{i=1}^{m} -y^{(i)} \log\left(y_p^{(i)}\right) + \left(1-y^{(i)}\right) \log\left(1-y_p^{(i)}\right)\right]$$

$y^{(i)}$: true label for i^{th} tweet.

$y_p^{(i)}$: predicted label for " "

m: total no. of samples.

2.) Text Preprocessing :-

- tweets contain characters & symbols which have no influence on sentiment of tweet.
- (i) Tokenization
  operation of splitting sentence into words.
  (ii) Removing stop words i.e. words which frequently occur but have no semantic value.
  (iii) Removing hastags, punctuations & other symbols.
  (iv) Stemming
  Reduction of words to root words by removal of suffixes & prefixes.

3.) Feature Extraction :-

- refers to transformation of tweets into vectors.
- (i) Bag-of-Words
  - builds vocabulary from a corpus & counts how many times a word occurs in a tweet. Poses Problem of high dimensionality.
  (ii) Term frequency - Inverse document frequency similar to BOW, but here the value of word decreases as the frequency of word increases.

* Algorithm :-

⇒ Import libraries such as NLTK, pandas, scikit-learn etc.
⇒ Load twitter dataset into dataframe
⇒ Preprocess tweets by
  (i) removing URLs.
  (ii) removing hastags.
  (iii) replacing all characters other than number or alphabets with " ".
  (iv) tokenize.

(v) Stemming.
(vi) Removing stop words.
(vii) Joining tokens to create processed tweets.

- Create corpus for positive & negative vocabulary.
- extract features by converting text to vector.
- Split dataset into train & test set.
- Train model and make predictions on test set.

* Conclusion:-
successfully implemented sentiment analysis for twitter dataset.