

Secure Discrete-Time Linear-Quadratic Mean-Field Games

Muhammad Aneeq uz Zaman, Sujay Bhatt & Tamer Başar

October 29, 2020



ILLINOIS

UNIVERSITY OF ILLINOIS AT URBANA-CHAMPAIGN

Agent Model & Objective

Agent Model & Objective

Secure n -agent Linear Quadratic (LQ) game

- Large population game, to solve a *consensus problem*, each agent aims to align with aggregate behavior.

Agent Model & Objective

Secure n -agent Linear Quadratic (LQ) game

- Large population game, to solve a *consensus problem*, each agent aims to align with aggregate behavior.
- An agent comprised of a sensor and a controller, connected through a noise-less channel.

Agent Model & Objective


Secure n -agent Linear Quadratic (LQ) game

- Large population game, to solve a *consensus problem*, each agent aims to align with aggregate behavior.
- An agent comprised of a sensor and a controller, connected through a noise-less channel.
- The channel is susceptible to eavesdropping by adversaries.

Agent Model & Objective

Secure n -agent Linear Quadratic (LQ) game


- Large population game, to solve a *consensus problem*, each agent aims to align with aggregate behavior.
- An agent comprised of a sensor and a controller, connected through a noise-less channel.
- The channel is susceptible to eavesdropping by adversaries.



Agent Model & Objective

Secure n -agent Linear Quadratic (LQ) game

- Large population game, to solve a *consensus problem*, each agent aims to align with aggregate behavior.
- An agent comprised of a sensor and a controller, connected through a noise-less channel.
- The channel is susceptible to eavesdropping by adversaries.




- State sketched using private key.

Agent Model & Objective

Secure n -agent Linear Quadratic (LQ) game

- Large population game, to solve a *consensus problem*, each agent aims to align with aggregate behavior.
- An agent comprised of a sensor and a controller, connected through a noise-less channel.
- The channel is susceptible to eavesdropping by adversaries.



- State sketched using private key.
- Adversary is non-strategic.

Main Results & Organization

Main Results & Organization

- We introduce the Secure n -agent Linear Quadratic (LQ) game and counterpart Secure LQ-MFG (SLQ-MFG).

Main Results & Organization

- We introduce the Secure n -agent Linear Quadratic (LQ) game and counterpart Secure LQ-MFG (SLQ-MFG).
- We propose a secure communication (Sketching & Reconstruction) mechanism.

Main Results & Organization

- We introduce the Secure n -agent Linear Quadratic (LQ) game and counterpart Secure LQ-MFG (SLQ-MFG).
- We propose a secure communication (Sketching & Reconstruction) mechanism.
- We prove that the MFE of the (vanilla) LQ-MFG is an ϵ -MFE of the SLQ-MFG (in linear controllers).

Main Results & Organization

- We introduce the Secure n -agent Linear Quadratic (LQ) game and counterpart Secure LQ-MFG (SLQ-MFG).
- We propose a secure communication (Sketching & Reconstruction) mechanism.
- We prove that the MFE of the (vanilla) LQ-MFG is an ϵ -MFE of the SLQ-MFG (in linear controllers).
- Furthermore, we show that the MFE of the LQ-MFG is an $(\epsilon + \varepsilon)$ -NE of the finite agent game.

Main Results & Organization

- We introduce the Secure n -agent Linear Quadratic (LQ) game and counterpart Secure LQ-MFG (SLQ-MFG).
- We propose a secure communication (Sketching & Reconstruction) mechanism.
- We prove that the MFE of the (vanilla) LQ-MFG is an ϵ -MFE of the SLQ-MFG (in linear controllers).
- Furthermore, we show that the MFE of the LQ-MFG is an $(\epsilon + \varepsilon)$ -NE of the finite agent game.
- Finally, we empirically investigate the performance of the $(\epsilon + \varepsilon)$ -NE.

Secure n -agent Linear Quadratic (LQ) game

Secure n -agent Linear Quadratic (LQ) game

- Consider an n -agent game, each agent $i \in \{1, 2, \dots, n\}$ has linear dynamics,

$$\begin{aligned}x_i(k\tau + (j+1)\Delta) &= Ax_i(k\tau + j\Delta) + Bu_i(k\tau) + \tilde{w}_i(k\tau + j\Delta), \\y_i(k\tau + j\Delta) &= \text{SKETCH}(x_i(k\tau + j\Delta)) = C_i x_i(k\tau + j\Delta),\end{aligned}$$

Secure n -agent Linear Quadratic (LQ) game

- Consider an n -agent game, each agent $i \in \{1, 2, \dots, n\}$ has linear dynamics,

$$\begin{aligned}x_i(k\tau + (j+1)\Delta) &= Ax_i(k\tau + j\Delta) + Bu_i(k\tau) + \tilde{w}_i(k\tau + j\Delta), \\y_i(k\tau + j\Delta) &= \text{SKETCH}(x_i(k\tau + j\Delta)) = C_i x_i(k\tau + j\Delta),\end{aligned}$$

- Observations generated at fast rate $1/\Delta$ and control at slow rate $1/\tau$, s.t. $\tau = N\Delta$.

Secure n -agent Linear Quadratic (LQ) game

- Consider an n -agent game, each agent $i \in \{1, 2, \dots, n\}$ has linear dynamics,

$$\begin{aligned}x_i(k\tau + (j+1)\Delta) &= Ax_i(k\tau + j\Delta) + Bu_i(k\tau) + \tilde{w}_i(k\tau + j\Delta), \\y_i(k\tau + j\Delta) &= \text{SKETCH}(x_i(k\tau + j\Delta)) = C_i x_i(k\tau + j\Delta),\end{aligned}$$

- Observations generated at fast rate $1/\Delta$ and control at slow rate $1/\tau$, s.t. $\tau = N\Delta$.
- $x_i(0)$ and \tilde{w}_i are generated i.i.d., second order distribution.

Secure n -agent Linear Quadratic (LQ) game

- Consider an n -agent game, each agent $i \in \{1, 2, \dots, n\}$ has linear dynamics,

$$\begin{aligned}x_i(k\tau + (j+1)\Delta) &= Ax_i(k\tau + j\Delta) + Bu_i(k\tau) + \tilde{w}_i(k\tau + j\Delta), \\y_i(k\tau + j\Delta) &= \text{SKETCH}(x_i(k\tau + j\Delta)) = C_i x_i(k\tau + j\Delta),\end{aligned}$$

- Observations generated at fast rate $1/\Delta$ and control at slow rate $1/\tau$, s.t. $\tau = N\Delta$.
- $x_i(0)$ and \tilde{w}_i are generated i.i.d., second order distribution.
- C_i (private key) chosen uniformly from set of private keys

$$\mathcal{C} = \{C_i | i \in \{1, 2, \dots, M\}, M < \infty, C_i \in \mathbb{R}^{q \times m}, N > \text{Obs}(A, C_i)\}.$$

Secure n -agent Linear Quadratic (LQ) game (contd.)

Secure n -agent Linear Quadratic (LQ) game (contd.)

- C_i is singular, multi-rate setup used to reconstruct state.

Secure n -agent Linear Quadratic (LQ) game (contd.)

- C_i is singular, multi-rate setup used to reconstruct state.
- Each agent aims to minimize its cost

$$J_i^n = \limsup_{T \rightarrow \infty} \frac{1}{T} \mathbb{E} \left\{ \sum_{k=0}^{T-1} \left\| x_i(k\tau) - \frac{1}{n-1} \sum_{j \neq i} x_j(k\tau) \right\|_Q^2 + \|u_i(k\tau)\|_R^2 \right\},$$

Secure n -agent Linear Quadratic (LQ) game (contd.)

- C_i is singular, multi-rate setup used to reconstruct state.
- Each agent aims to minimize its cost

$$J_i^n = \limsup_{T \rightarrow \infty} \frac{1}{T} \mathbb{E} \left\{ \sum_{k=0}^{T-1} \left\| x_i(k\tau) - \frac{1}{n-1} \sum_{j \neq i} x_j(k\tau) \right\|_Q^2 + \|u_i(k\tau)\|_R^2 \right\},$$

- The solution concept used is that of *Nash Equilibrium*.

Secure Linear Quadratic Mean-Field Game (SLQ-MFG)

Secure Linear Quadratic Mean-Field Game (SLQ-MFG)

- Consider the limiting case where $n \rightarrow \infty$.

Secure Linear Quadratic Mean-Field Game (SLQ-MFG)

- Consider the limiting case where $n \rightarrow \infty$.
- We focus on a generic agent whose dynamics are

$$\begin{aligned}x(k\tau + (j+1)\Delta) &= Ax(k\tau + j\Delta) + Bu(k\tau) + \tilde{w}(k\tau + j\Delta), \\y(k\tau + j\Delta) &= Cx(k\tau + j\Delta).\end{aligned}$$

Secure Linear Quadratic Mean-Field Game (SLQ-MFG)

- Consider the limiting case where $n \rightarrow \infty$.
- We focus on a generic agent whose dynamics are

$$\begin{aligned}x(k\tau + (j+1)\Delta) &= Ax(k\tau + j\Delta) + Bu(k\tau) + \tilde{w}(k\tau + j\Delta), \\y(k\tau + j\Delta) &= Cx(k\tau + j\Delta).\end{aligned}$$

- The cost function of the generic agent given the mean-field trajectory \bar{x} is

$$J(\mu, \bar{x}) = \limsup_{T \rightarrow \infty} \frac{1}{T} \mathbb{E} \left\{ \sum_{k=0}^{T-1} \|x(k\tau) - \bar{x}(k\tau)\|_Q^2 + \|u(k\tau)\|_R^2 \right\}.$$

Secure Linear Quadratic Mean-Field Game (SLQ-MFG) (contd.)

Secure Linear Quadratic Mean-Field Game (SLQ-MFG) (contd.)

- We use the solution concept of mean-field equilibrium (MFE).

Secure Linear Quadratic Mean-Field Game (SLQ-MFG) (contd.)

- We use the solution concept of mean-field equilibrium (MFE).
- First define operator $\Lambda : \mathcal{M} \rightarrow \ell^\infty$, generates a mean-field trajectory \bar{x} generated by a control law μ .

Secure Linear Quadratic Mean-Field Game (SLQ-MFG) (contd.)

- We use the solution concept of mean-field equilibrium (MFE).
- First define operator $\Lambda : \mathcal{M} \rightarrow \ell^\infty$, generates a mean-field trajectory \bar{x} generated by a control law μ .

Definition

The tuple $(\mu^*, \bar{x}^*) \in \mathcal{M} \times \ell^\infty$ is an MFE if $\bar{x}^* = \Lambda(\mu^*)$ and

$$J(\mu^*, \bar{x}^*) \leq J(\mu, \bar{x}^*), \quad \forall \mu \in \mathcal{M}$$

Secure Linear Quadratic Mean-Field Game (SLQ-MFG) (contd.)

- We use the solution concept of mean-field equilibrium (MFE).
- First define operator $\Lambda : \mathcal{M} \rightarrow \ell^\infty$, generates a mean-field trajectory \bar{x} generated by a control law μ .

Definition

The tuple $(\mu^*, \bar{x}^*) \in \mathcal{M} \times \ell^\infty$ is an MFE if $\bar{x}^* = \Lambda(\mu^*)$ and

$$J(\mu^*, \bar{x}^*) \leq J(\mu, \bar{x}^*), \quad \forall \mu \in \mathcal{M}$$

- MFE is analog to Nash Equilibrium.

State Reconstruction using Multi-Rate Output Sampling

State Reconstruction using Multi-Rate Output Sampling

- If we denote $y_{[k]} := [y^T((k-1)\tau), \dots, y^T((k-1)\tau + (N-1)\Delta)]^T$, then

$$y_{[k+1]} = C_0 x(k\tau) + D_0 u(k\tau) + C_d w_{[k]}$$

State Reconstruction using Multi-Rate Output Sampling

- If we denote $y_{[k]} := [y^T((k-1)\tau), \dots, y^T((k-1)\tau + (N-1)\Delta)]^T$, then

$$y_{[k+1]} = C_0 x(k\tau) + D_0 u(k\tau) + C_d w_{[k]}$$

- Thus the state $x(k\tau)$ can be expressed as,

$$x(k\tau) = L_y y_{[k]} + L_u u((k-1)\tau) + w(k\tau)$$

State Reconstruction using Multi-Rate Output Sampling

- If we denote $y_{[k]} := [y^T((k-1)\tau), \dots, y^T((k-1)\tau + (N-1)\Delta)]^T$, then

$$y_{[k+1]} = C_0 x(k\tau) + D_0 u(k\tau) + C_d w_{[k]}$$

- Thus the state $x(k\tau)$ can be expressed as,

$$x(k\tau) = L_y y_{[k]} + L_u u((k-1)\tau) + w(k\tau)$$

- The controller reconstructs the state as,

$$\hat{x}(k\tau) = L_y y_{[k]} + L_u u((k-1)\tau)$$

State Reconstruction using Multi-Rate Output Sampling

- If we denote $y_{[k]} := [y^T((k-1)\tau), \dots, y^T((k-1)\tau + (N-1)\Delta)]^T$, then

$$y_{[k+1]} = C_0 x(k\tau) + D_0 u(k\tau) + C_d w_{[k]}$$

- Thus the state $x(k\tau)$ can be expressed as,

$$x(k\tau) = L_y y_{[k]} + L_u u((k-1)\tau) + w(k\tau)$$

- The controller reconstructs the state as,

$$\hat{x}(k\tau) = L_y y_{[k]} + L_u u((k-1)\tau)$$

- Estimation error $w(k\tau)$ is a zero mean random vector with covariance matrix Σ_C . Define set $\mathcal{E}_C := \{\Sigma_C : C \in \mathcal{C}\}$.

MFE of the SLQ-MFG

MFE of the SLQ-MFG

- We show that the MFE of SLQ-MFG doesn't exist in class of linear controllers.

MFE of the SLQ-MFG

- We show that the MFE of SLQ-MFG doesn't exist in class of linear controllers.
- Define augmented state $z(k_T) = [x^T(k_T), \bar{x}^T(k_T)]^T$. MF trajectory \bar{x} is defined by matrix F .

MFE of the SLQ-MFG

- We show that the MFE of SLQ-MFG doesn't exist in class of linear controllers.
- Define augmented state $z(k\tau) = [x^T(k\tau), \bar{x}^T(k\tau)]^T$. MF trajectory \bar{x} is defined by matrix F .
- Dynamics of augmented state is

$$z((k+1)\tau) = \bar{A}z(k\tau) + \bar{B}u(k\tau) + \bar{w}(k\tau)$$

$$\bar{A} = \begin{bmatrix} A_0 & 0 \\ 0 & F \end{bmatrix}, \bar{B} = \begin{bmatrix} B_0 \\ 0 \end{bmatrix}, \bar{w}(k\tau) = \begin{bmatrix} w^0(k\tau) \\ 0 \end{bmatrix}$$

MFE of the SLQ-MFG

MFE of the SLQ-MFG

- Cost of generic agent under control law K ,
 $u(k\tau) = -K(\hat{x}^T(k\tau), \bar{x}^T(k\tau))$

$$J(K, F) = \limsup_{T \rightarrow \infty} \frac{1}{T} \mathbb{E} \left\{ \sum_{k=0}^{T-1} \|z(k\tau)\|_{\bar{Q}}^2 + \|u(k\tau)\|_R^2 \right\}.$$

MFE of the SLQ-MFG

- Cost of generic agent under control law K ,
 $u(k\tau) = -K(\hat{x}^T(k\tau), \bar{x}^T(k\tau))$

$$J(K, F) = \limsup_{T \rightarrow \infty} \frac{1}{T} \mathbb{E} \left\{ \sum_{k=0}^{T-1} \|z(k\tau)\|_{\bar{Q}}^2 + \|u(k\tau)\|_R^2 \right\}.$$

- The controller \hat{K}_F which minimizes $J(K, F)$ for any stable F is

$$\hat{K}_F = (\bar{B}^T \hat{P} \bar{B} + R)^{-1} \bar{B}^T \hat{P} \bar{A} (I - \hat{\Sigma}_C \Sigma_{\hat{K}_F}^{-1})$$

where \hat{P} is the solution to a Lyapunov equation.

MFE of the SLQ-MFG

- Cost of generic agent under control law K ,
 $u(k\tau) = -K(\hat{x}^T(k\tau), \bar{x}^T(k\tau))$

$$J(K, F) = \limsup_{T \rightarrow \infty} \frac{1}{T} \mathbb{E} \left\{ \sum_{k=0}^{T-1} \|z(k\tau)\|_{\bar{Q}}^2 + \|u(k\tau)\|_R^2 \right\}.$$

- The controller \hat{K}_F which minimizes $J(K, F)$ for any stable F is

$$\hat{K}_F = (\bar{B}^T \hat{P} \bar{B} + R)^{-1} \bar{B}^T \hat{P} \bar{A} (I - \hat{\Sigma}_C \Sigma_{\hat{K}_F}^{-1})$$

where \hat{P} is the solution to a Lyapunov equation.

- $\Sigma_{\hat{K}_F}$ is the covariance matrix of stationary distribution and is shown to be singular. Hence \hat{K}_F does not exist.

ϵ -MFE of the SLQ-MFG

ϵ -MFE of the SLQ-MFG

Definition

The tuple $(K', F') \in \mathbb{R}^{p \times 2m} \times \mathbb{R}^{m \times m}$ is an ϵ -MFE if $F' = \Lambda(K')$ and

$$J(K', F') \leq J(K, F') + \epsilon, \quad \forall K \in \mathbb{R}^{p \times 2m}, \epsilon > 0$$

ϵ -MFE of the SLQ-MFG

Definition

The tuple $(K', F') \in \mathbb{R}^{p \times 2m} \times \mathbb{R}^{m \times m}$ is an ϵ -MFE if $F' = \Lambda(K')$ and

$$J(K', F') \leq J(K, F') + \epsilon, \quad \forall K \in \mathbb{R}^{p \times 2m}, \epsilon > 0$$

Assumption

With P given as the unique positive definite solution to the DARE,

$$P = A_0^T P A_0 + Q - A_0^T P B_0 (R + B_0^T P B_0)^{-1} B_0^T P A_0$$

and furthermore that $G_P := -(R + B_0^T P B_0)^{-1} B_0^T$ and $H_P := A_0^T (I + P B_0 G_P)$, we have $\|H_P\|_2 + \frac{\|B_0 G_P\|_2 \|Q\|_2}{(1 - \|H_P\|_2)^2} < 1$

ϵ -MFE of the SLQ-MFG (contd.)

ϵ -MFE of the SLQ-MFG (contd.)

Theorem

Under above given Assumption, the MFE of LQ-MFG (K^, F^*) is also the ϵ -MFE of the SLQ-MFG where $\epsilon = \mathcal{O}(\text{tr}(\Sigma_C))$.*

ϵ -MFE of the SLQ-MFG (contd.)

Theorem

Under above given Assumption, the MFE of LQ-MFG (K^, F^*) is also the ϵ -MFE of the SLQ-MFG where $\epsilon = \mathcal{O}(\text{tr}(\Sigma_C))$.*

- ϵ is dependent on the estimation error

ϵ -MFE of the SLQ-MFG (contd.)

Theorem

Under above given Assumption, the MFE of LQ-MFG (K^, F^*) is also the ϵ -MFE of the SLQ-MFG where $\epsilon = \mathcal{O}(\text{tr}(\Sigma_C))$.*

- ϵ is dependent on the estimation error
- $\text{tr}(\Sigma_C) \rightarrow 0 \implies \epsilon \rightarrow 0$.

$(\epsilon + \varepsilon)$ -Nash Equilibrium of the secure n -agent LQ game

$(\epsilon + \varepsilon)$ -Nash Equilibrium of the secure n -agent LQ game

Theorem

Under above given Assumption, let the cost of secure n -agent LQ game under controller μ^ be $J_i^n(\mu^{*i}, \mu^{*-i})$, then*

$$J_i^n(\mu^{*i}, \mu^{*-i}) - \inf_{\pi^i \in \Pi_K^i} J_i^n(\pi^i, \mu^{*-i}) < \epsilon + \varepsilon$$

where $\epsilon = \mathcal{O}(\sigma_{\max})$ and $\sigma_{\max} := \max_{\Sigma_C \in \mathcal{E}_C} \text{tr}(\Sigma_C)$ and $\varepsilon = \mathcal{O}(\sigma_{\max}/\sqrt{n-1})$.

$(\epsilon + \varepsilon)$ -Nash Equilibrium of the secure n -agent LQ game

Theorem

Under above given Assumption, let the cost of secure n -agent LQ game under controller μ^ be $J_i^n(\mu^{*i}, \mu^{*-i})$, then*

$$J_i^n(\mu^{*i}, \mu^{*-i}) - \inf_{\pi^i \in \Pi_K^i} J_i^n(\pi^i, \mu^{*-i}) < \epsilon + \varepsilon$$

where $\epsilon = \mathcal{O}(\sigma_{\max})$ and $\sigma_{\max} := \max_{\Sigma_C \in \mathcal{E}_C} \text{tr}(\Sigma_C)$ and $\varepsilon = \mathcal{O}(\sigma_{\max}/\sqrt{n-1})$.

- If $\text{tr}(\sigma_{\max}) \rightarrow 0$ and $n \rightarrow \infty$ then $(\epsilon + \varepsilon) \rightarrow 0$.

Performance sensitivity w.r.t. sampling rate

Performance sensitivity w.r.t. sampling rate




Figure: Average accumulated cost w.r.t. change in sampling rate N .

Performance sensitivity w.r.t. model parameters

Performance sensitivity w.r.t. model parameters




Figure: Average accumulated cost w.r.t. perturbation of the A and B matrices.

Performance sensitivity w.r.t. private keys

Performance sensitivity w.r.t. private keys




Figure: Average accumulated cost w.r.t. perturbation of the set of keys \mathcal{C} .

Conclusion

Conclusion

- We proposed a multi-rate sensor output sampling mechanism to reconstruct the state with some estimation error.

Conclusion

- We proposed a multi-rate sensor output sampling mechanism to reconstruct the state with some estimation error.
- We showed that estimation error results in non-existence of the Mean-Field Equilibrium (MFE) of the SLQ-MFG for the class of linear controllers

Conclusion

- We proposed a multi-rate sensor output sampling mechanism to reconstruct the state with some estimation error.
- We showed that estimation error results in non-existence of the Mean-Field Equilibrium (MFE) of the SLQ-MFG for the class of linear controllers
- We established that MFE of (standard) LQ-MFG, corresponds to ϵ -MFE of the SLQ-MFG, and an $(\epsilon + \varepsilon)$ -Nash equilibrium for the secure n -agent dynamic game.

Conclusion

- We proposed a multi-rate sensor output sampling mechanism to reconstruct the state with some estimation error.
- We showed that estimation error results in non-existence of the Mean-Field Equilibrium (MFE) of the SLQ-MFG for the class of linear controllers
- We established that MFE of (standard) LQ-MFG, corresponds to ϵ -MFE of the SLQ-MFG, and an $(\epsilon + \varepsilon)$ -Nash equilibrium for the secure n -agent dynamic game.
- We empirically demonstrated that performance of the $(\epsilon + \varepsilon)$ -Nash equilibrium improves with increasing sampling rate N , deteriorates with variations in model parameters (A, B) , and is insensitive to small perturbations in the set of private keys \mathcal{C} .