

PLACEMENT REFRESHER PROGRAM

Session 1: Python I

Basics, Data Types, Control Structures

By
Ritesh Kumar Pandey

Agenda

- Basics
- Data Types
- Control Structures

Python

- High Level
- General Purpose
- Interpreted
- Dynamically Typed

Python

- High Level
- General Purpose
- Interpreted
- Dynamically Typed



Provides abstractions and simplifications making it Human Understandable language

Python

- High Level
- General Purpose
- Interpreted
- Dynamically Typed

Provides abstractions and simplifications making it Human Understandable language

Web Development, Data Science, Artificial Intelligence, Machine Learning, Application Development, Data Analytics

Python

- High Level
- General Purpose
- Interpreted
- Dynamically Typed

Provides abstractions and simplifications making it Human Understandable language

Web Development, Data Science, Artificial Intelligence, Machine Learning, Application Development, Data Analytics

Executed Line by Line

Python

- High Level
- General Purpose
- Interpreted
- Dynamically Typed

Provides abstractions and simplifications making it Human Understandable language

Web Development, Data Science, Artificial Intelligence, Machine Learning, Application Development, Data Analytics

Executed Line by Line

Variable types are determined at runtime
`int x = 10 # not required`
`x = 10`

Question 1

Which of the following is invalid ?

- a) `it = 100`
- b) `on = 200`
- c) `in = 'Hi'`
- d) `apple = mango`

Answer

Which of the following is invalid ?

- a) `it = 100`
- b) `on = 200`
- c) `in = 'Hi'`
- d) `apple = mango`

Answer

Which of the following is invalid ?

- a) `it = 100`
- b) `on = 200`
- c) `in = 'Hi'`
- d) `apple = mango`

in is a Keyword in Python, hence cannot be used as a variable name.

There are a total of **35** keywords in Python.

True, False, None are the only capitalized keywords, rest all are small case

Answer

Which of the following is invalid ?

- a) `it = 100`
- b) `on = 200`
- c) `in = 'Hi'`
- d) `apple = mango`

in is a Keyword in Python, hence cannot be used as a variable name.

There are a total of **35** keywords in Python.

True, False, None are the only capitalized keywords, rest all are small case

```
import keyword
```

```
keywords = keyword.kwlist
```

```
print(" The total number of keywords in Python is : ", len(keywords))
```

```
print("\n The list of keywords in Python is : ", keywords)
```

Answer

Which of the following is invalid ?

- a) `it = 100`
- b) `on = 200`
- c) `in = 'Hi'`
- d) `apple = mango`

mango is not defined

```
mango = 5
apple = mango
```

```
apple = 'mango'
```

in is a Keyword in Python, hence cannot be used as a variable name.

There are a total of **35** keywords in Python.


True, False, None are the only capitalized keywords, rest all are small case

```
import keyword
```

```
keywords = keyword.kwlist
```

```
print(" The total number of keywords in Python is : ", len(keywords))
```

```
print("\n The list of keywords in Python is : ", keywords)
```



Question 2

```
x = input('Enter Something : ')\nprint(type(x))
```

upGrad

32

32.5

True

Answer

```
x = input('Enter Something : ')\nprint(type(x))
```

Class <'str'>

upGrad

32

32.5

True

Question 3

```
var1 = ['Hi', 'Hello', 23]
print(type(var1))
var1[1] = 'Hey'
print(var1)
```

```
var2 = ('Hi', 'Hello', 23)
print(type(var2))
var2[1] = 'Hey'
print(var2)
```

```
var3 = {'Hi', 'Hello', 23}
print(type(var3))
var3[1] = 'Hey'
print(var3)
```


Answer

```
var1 = ['Hi', 'Hello', 23]
print(type(var1))
var1[1] = 'Hey'
print(var1)
```

```
var2 = ('Hi', 'Hello', 23)
print(type(var2))
var2[1] = 'Hey'
print(var2)
```

```
var3 = {'Hi', 'Hello', 23}
print(type(var3))
var3[1] = 'Hey'
print(var3)
```

```
class <'list'>
['Hi', 'Hey', 23]
```

Answer

```
var1 = ['Hi', 'Hello', 23]
print(type(var1))
var1[1] = 'Hey'
print(var1)
```

```
var2 = ('Hi', 'Hello', 23)
print(type(var2))
var2[1] = 'Hey'
print(var2)
```

```
var3 = {'Hi', 'Hello', 23}
print(type(var3))
var3[1] = 'Hey'
print(var3)
```

```
class <'list'>
['Hi', 'Hey', 23]
```

```
class <'tuple'>
ERROR !
```

Answer

```
var1 = ['Hi', 'Hello', 23]
print(type(var1))
var1[1] = 'Hey'
print(var1)
```

```
class <'list'>
['Hi', 'Hey', 23]
```

```
var2 = ('Hi', 'Hello', 23)
print(type(var2))
var2[1] = 'Hey'
print(var2)
```

```
class <'tuple'>
ERROR !
```

```
var3 = {'Hi', 'Hello', 23}
print(type(var3))
var3[1] = 'Hey'
print(var3)
```

```
class <'set'>
ERROR !
```

Question 4

```
var1 = ['Hi', 'Hello', 23]
var1.append('Hey')
var1.append('Hi')
print(var1)
```

```
var2 = {'Hi', 'Hello', 23}
var2.add('Hey')
var2.add('Hi')
print(var2)
```

Answer

```
var1 = ['Hi', 'Hello', 23]
var1.append('Hey')
var1.append('Hi')
print(var1)
```

```
var2 = {'Hi', 'Hello', 23}
var2.add('Hey')
var2.add('Hi')
print(var2)
```

```
['Hi', 'Hello', 23, 'Hey', 'Hi']
```

Answer

```
var1 = ['Hi', 'Hello', 23]
var1.append('Hey')
var1.append('Hi')
print(var1)
```

['Hi', 'Hello', 23, 'Hey', 'Hi']

```
var2 = {'Hi', 'Hello', 23}
var2.add('Hey')
var2.add('Hi')
print(var2)
```

['Hi', 23, 'Hey', 'Hello']

Aspect	List	Set	Tuple
Mutability	Mutable	Mutable	Immutable
Ordered	Ordered	Unordered	Ordered
Duplicates	Allowed	Not allowed	Allowed
Syntax	[]	{ }	()

Question 5

```
d = dict()  
k = (1, 2, 3, 4)  
d[k] = 'Hey'  
print(d)
```

```
d = dict()  
k = [1, 2, 3, 4]  
d[k] = 'Hey'  
print(d)
```


Answer

```
d = dict()
k = (1, 2, 3, 4)
d[k] = 'Hey'
print(d)
```

```
d = dict()
k = [1, 2, 3, 4]
d[k] = 'Hey'
print(d)
```

```
{ (1, 2, 3, 4): 'Hey' }
```

Answer

```
d = dict()  
k = (1, 2, 3, 4)  
d[k] = 'Hey'  
print(d)
```

```
{ (1, 2, 3, 4): 'Hey' }
```

```
d = dict()  
k = [1, 2, 3, 4]  
d[k] = 'Hey'  
print(d)
```

```
ERROR !
```

Question 6

```
d = dict()
k = (1, 2, 3, 4)
d[k] = 'Hey'
m = (5, 6)
d[m] = 'Hello'
print(d)
```

```
d = dict()
k = (1, 2, 3, 4)
d[k] = 'Hey'
m = (1, 2, 3, 4)
d[m] = 'Hello'
print(d)
```

```
d = dict()
k = (1, 2, 3, 4)
d[k] = 'Hey'
m = '1, 2, 3, 4'
d[m] = 'Hello'
print(d)
```

Answer

```
d = dict()
k = (1, 2, 3, 4)
d[k] = 'Hey'
m = (5, 6)
d[m] = 'Hello'
print(d)
```

```
d = dict()
k = (1, 2, 3, 4)
d[k] = 'Hey'
m = (1, 2, 3, 4)
d[m] = 'Hello'
print(d)
```

```
d = dict()
k = (1, 2, 3, 4)
d[k] = 'Hey'
m = '1, 2, 3, 4'
d[m] = 'Hello'
print(d)
```

```
{ (1, 2, 3, 4): 'Hey',
  (5, 6): 'Hello' }
```

Answer

```
d = dict()
k = (1, 2, 3, 4)
d[k] = 'Hey'
m = (5, 6)
d[m] = 'Hello'
print(d)
```

```
{ (1, 2, 3, 4): 'Hey',
  (5, 6): 'Hello' }
```

```
d = dict()
k = (1, 2, 3, 4)
d[k] = 'Hey'
m = (1, 2, 3, 4)
d[m] = 'Hello'
print(d)
```

```
{ (1, 2, 3, 4): 'Hello' }
```

```
d = dict()
k = (1, 2, 3, 4)
d[k] = 'Hey'
m = '1, 2, 3, 4'
d[m] = 'Hello'
print(d)
```

Answer

```
d = dict()
k = (1, 2, 3, 4)
d[k] = 'Hey'
m = (5, 6)
d[m] = 'Hello'
print(d)
```


```
{ (1, 2, 3, 4): 'Hey',
  (5, 6): 'Hello' }
```

```
d = dict()
k = (1, 2, 3, 4)
d[k] = 'Hey'
m = (1, 2, 3, 4)
d[m] = 'Hello'
print(d)
```

```
{ (1, 2, 3, 4): 'Hello' }
```

```
d = dict()
k = (1, 2, 3, 4)
d[k] = 'Hey'
m = '1, 2, 3, 4'
d[m] = 'Hello'
print(d)
```

```
{ (1, 2, 3, 4): 'Hey',
  '1, 2, 3, 4': 'Hello' }
```



Question 7

```
for i in range(0, 10):  
    if i % 2 == 0:  
        print(i)  
    elif i % 5 == 0:  
        continue  
        print('Divisible by 5')  
    elif i == 7:  
        break  
    else:  
        print('No')  
  
print('something \n')
```


Answer

```
for i in range(0, 10):  
    if i % 2 == 0:  
        print(i)  
    elif i % 5 == 0:  
        continue  
        print('Divisible by 5')  
    elif i == 7:  
        break  
    else:  
        print('No')  
  
print('something \n')
```

```
0  
something  
  
No  
something  
  
2  
something  
  
No  
something  
  
4  
something  
6  
something
```

Question 8

Given the following code, please rewrite it in Python after fixing all syntax errors. Please underline each correction you made.

```
30 = To
for k in (0, To):
    if k / 4 == 0:
        print(k is divisible by 4)
    else:
        print(k is not divisible by 4)
```

Answer

Given the following code, please rewrite it in Python after fixing all syntax errors. Please underline each correction you made.

```
30 = To
for k in (0, To):
    if k / 4 == 0:
        print(k is divisible by 4)
    else:
        print(k is not divisible by 4)
```

```
To = 30
for k in range(0, To):
    if k % 4 == 0:
        print(k + 'is divisible by 4')
    else:
        print(k + 'is not divisible by 4')
```

Question 9

Input: [1, 2, 3, 6, 4, 8]

Output: [8, 4, 6, 3, 2, 1]

Answer

Input: [1, 2, 3, 6, 4, 8]

Output: [8, 4, 6, 3, 2, 1]

```
list_name = list(reversed(list_name))
```

Answer

Input: [1, 2, 3, 6, 4, 8]

Output: [8, 4, 6, 3, 2, 1]

```
list_name = list(reversed(list_name))
```

```
left = 0
right = len(list_name) - 1
while left < right:
    list_name[left], list_name[right] = list_name[right], list_name[left]
    left += 1
    right -= 1
print(list_name)
```

Question 10


Input: 0100, 0011, 1010, 1001, 1100, 1011, 0101

Output : 1010, 0101

Answer

Input: 0100, 0011, 1010, 1001, 1100, 1011, 0101

Output : 1010, 0101




Answer

Input: 0100, 0011, 1010, 1001, 1100, 1011, 0101

Output : 1010, 0101


Binary Number divisible by 5



Answer

Input: 0100, 0011, 1010, 1001, 1100, 1011, 0101

Output : 1010, 0101



Binary Number divisible by 5

```
items = []  
  
for p in input_list:  
    x = int(p, 2)  
    if not x%5:  
        items.append(p)  
  
print(','.join(items))
```

THANK YOU