Notification Service Architecture

Document date: 2024-02-01 Classification: Internal

Table of Contents

1. Overview 2
2. Data Stores 3
3. Dependencies 4
4. Security and Authentication 5
5. Scaling 6
6. Open Questions 7

1. Overview

The Notification Service (notification-service) is owned by the Engagement team, with Arjun Mehta as technical lead. It is implemented in Python 3.11 with FastAPI and listens on port 8090. Feature work is paused during incident follow-up weeks until action items are closed. Database schema migrations must be backward compatible for at least one release. Database schema migrations must be backward compatible for at least one release.

Service-level objectives are reviewed quarterly with product owners. Postmortems are blameless and are published within five business days. Secrets must never be committed; the pre-commit hook scans for high-entropy strings. Postmortems are blameless and are published within five business days.

2. Data Stores

Primary data store: PostgreSQL notify-db for templates and delivery logs. Every service has a README that links to its dashboards and runbook. Container images are built once and promoted across environments by digest.

3. Dependencies

Notification Service depends on: SendGrid (email), Twilio (SMS), message broker. Feature work is paused during incident follow-up weeks until action items are closed. Capacity planning for the holiday peak starts in September every year.

4. Security and Authentication

Authentication mechanism: Notification Service uses internal-only; mTLS from callers. Tracing uses OpenTelemetry with a ten percent head-based sampling rate. Dependency upgrades are batched weekly by the platform bot.

5. Scaling

Remember to tag pull requests with the owning team so reviews get routed correctly. The dashboards were updated to show saturation alongside latency and errors. Flaky integration tests in CI are tracked on the quality board; please do not just re-run them. Capacity planning for the holiday peak starts in September every year. All services must expose Prometheus metrics on the /metrics path.

Secrets must never be committed; the pre-commit hook scans for high-entropy strings. On-call handover happens every Monday at 10:00 local time. Remember to tag pull requests with the owning team so reviews get routed correctly. Every service has a README that links to its dashboards and runbook.

6. Open Questions

Every service has a README that links to its dashboards and runbook. On-call handover happens every Monday at 10:00 local time. Load tests should be coordinated in the platform channel so they do not trip alerts.