Shipping Service Architecture

Document date: 2023-12-05 Classification: Internal

Table of Contents

1. Overview 2
2. Data Stores 3
3. Dependencies 4
4. Security and Authentication 5
5. Scaling 6
6. Open Questions 7

1. Overview

The Shipping Service (shipping-service) is owned by the Logistics team, with Chloe Dubois as technical lead. It is implemented in Python 3.10 with Django and listens on port 8500. Remember to tag pull requests with the owning team so reviews get routed correctly. The dashboards were updated to show saturation alongside latency and errors. Feature work is paused during incident follow-up weeks until action items are closed.

Remember to tag pull requests with the owning team so reviews get routed correctly. The dashboards were updated to show saturation alongside latency and errors. Staging mirrors production topology but runs at roughly one tenth of the capacity. Remember to tag pull requests with the owning team so reviews get routed correctly.

2. Data Stores

Primary data store: PostgreSQL shipping-db. Tracing uses OpenTelemetry with a ten percent head-based sampling rate. Feature work is paused during incident follow-up weeks until action items are closed.

3. Dependencies

Shipping Service depends on: order-service events, FedEx and DHL carrier APIs, labelgen. Service-level objectives are reviewed quarterly with product owners. Dependency upgrades are batched weekly by the platform bot.

4. Security and Authentication

Authentication mechanism: Shipping Service uses mTLS between services. Structured JSON logging is mandatory; free-text logs are dropped by the log pipeline. Database schema migrations must be backward compatible for at least one release.

5. Scaling

Capacity planning for the holiday peak starts in September every year. Postmortems are blameless and are published within five business days. Postmortems are blameless and are published within five business days. Dependency upgrades are batched weekly by the platform bot. Feature work is paused during incident follow-up weeks until action items are closed.

Dependency upgrades are batched weekly by the platform bot. Secrets must never be committed; the pre-commit hook scans for high-entropy strings. Structured JSON logging is mandatory; free-text logs are dropped by the log pipeline. Flaky integration tests in CI are tracked on the quality board; please do not just re-run them.

6. Open Questions

Flaky integration tests in CI are tracked on the quality board; please do not just re-run them. Secrets must never be committed; the pre-commit hook scans for high-entropy strings. Container images are built once and promoted across environments by digest.