

C Programming Questions

Weekly Assignments

Name- Sandeep Kumar

Section- AU-2

Roll No. - 52

Week 1

Q. 1 Write a program to accept height and base of triangle and calculate area of Triangle

Note: $\text{area} = (h*b)/2$

```
#include<stdio.h>
```

```
intmain()
```

```
{
```

```
inth,b,area;
```

```
printf("Enter the height:");
```

```
scanf("%d"
```

```
,&h);
```

```
printf("Enter the base:");
```

```
scanf("%d"
```

```
,&b);
```

```
area=(h*b)/2;
```

```
printf("Area of
```

```
triangle:%d"
```

```
,area);
```

```
return0;
```

```
}
```

Q. 2 Write a program to accept radius of circle and calculate area of

circle

Note: $\text{area} = \pi * r^2$

```
#include<stdio.h>
```

```
intmain()
```

```
{
```

```
intr,area;
```

```
printf("Enter the radius of
```

```
circle:");
```

```
scanf("%d"
```

```
,&r);
```

```
area=3.14*r*r;
```

```
printf("Area of circle:%d"
```

```
,area);
```

```
return0;
```

```
}
```

Q. 3 Write a program to find the lowest marks of three students using conditional operator.

```
#include<stdio.h>
```

```
voidmain() {
```

```
inta, b, c;
```

```
printf("Enter the marks of three
```

```
students: ");
```

```
scanf("%d%d%d"
```

```
, &a, &b, &c);
```

```
(a<b) ? ((a<c) ?printf("Lowest
```

```
marks: %d"
```

```
, a) :printf("Lowest marks:
```

```
%d"
```

```
, c)) : ((b<c) ?printf("Lowest
```

```
marks: %d"
```

```
, b) :printf("Lowest marks:
```

```
%d"
, c));
}
```

Q. 4 Write a program to Calculate Compound Interest.

```
# include<stdio.h>
# include<math.h>
intmain()
{
floatp,t,r,amt,ci;
printf("Enter the principal
amount:");
scanf("%f"
,&p);
printf("Enter the annual rate:");
scanf("%f"
,&r);
printf("Enter the annual time:");
scanf("%f"
,&t);
amt=p*pow((1+r/100),t);
printf("amount is %.2f"
,amt);
ci=amt-p;
printf("\ncompound interest is
%.2f"
,ci);
return0;
}
```

Q. 5 Write a program to Calculate Cube of a Number.

```
# include<stdio.h>
# include<math.h>
```

```

intmain()
{
    intn,cube;
    printf("enter the number:");
    scanf("%d"
    ,&n);
    cube=pow(n,3);
    printf("Cube of given number is
    %d"
    ,cube);
    return0;
}

```

Week - 2

Q. 1 Write a program to interchange two values by using Assignment Operator.

```

#include<stdio.h>

intmain()
{
    inta,b,temp=0;
    printf ("enter the value of a:");
    scanf("%d"
    ,&a);
    printf("enter the value of b:");
    scanf("%d"
    ,&b);
    temp=a;
    a=b;
    b=temp;
    printf("value of a after
    swaping:%d"

```

```
,a);
printf("\nvalue of b after
swaping:%d"
,b);
return0;
}
```

Q. 2 Write a program to interchange two values by using Arithmetic Operator.

```
# include<stdio.h>

intmain()
{
inta,b;
printf("enter the value for a:");
scanf("%d"
,&a);
printf("enter the value for b:");
scanf("%d"
,&b);
a=a+b;
b=a-b;
a=a-b;
printf("after swaping value of
a:%d"
,a);
printf("\nafterswaping value of
b:%d"
,b);
return0;
}
```

Q. 3 Write a program to interchange two values by using Bitwise Operator.

```

#include<stdio.h>

intmain()
{
inta,b;
printf ("enter the value of a:");
scanf("%d"
,&a);
printf("enter the value of b:");
scanf("%d"
,&b);
a=a^b;
b=a^b;
a=b^a;
printf("value of a after
swapping:%d"
,a);
printf("\nvalue of b after
swapping:%d"
,b);
return0;
}

```

Q. 4 Write a program to find the size of all data types (Int, Float, Char, Double, Long Double, Short Int etc.).

```

#include<stdio.h>

intmain()
{
printf("the size of
int:%lu"
,sizeof(int));
printf("\nthe size of
float:%lu"

```

```

, sizeof(float));
printf("\nthe size of
char: %lu"
, sizeof(char));
printf("\nthe size of
double: %lu"
, sizeof(double));
printf("\nthe size of long
double: %lu"
, sizeof(longdouble));
printf("\nthe size of short
int: %lu"
, sizeof(shortint));
return 0;
}

```

Q. 5 Write a program to find out whether input number is even or odd without using arithmetic operators.

```

#include <stdio.h>

int main() {
    int num;
    printf("Enter an integer: ");
    scanf("%d"
, &num);
    (num & 1) ? printf("%d is odd.",
num) : printf("%d is even.", num);
    return 0;
}

```

Week - 3

Q. 1 Write a C program to check whether a given number is even or odd.

```

#include<stdio.h>

intmain()
{
    intn;
    printf("enter the number:");
    scanf("%d"
    ,&n);
    if(n%2!=0)
    {
        printf("Odd!!!");
    }
    else
    {
        printf("Even!!!");
    }
}

```

Q. 2 Write a C program to check whether a given number is positive or negative.

```

#include<stdio.h>

intmain()
{
    intn;
    printf("enter the number:");
    scanf("%d"
    ,&n);
    if(n>0)
    {
        printf("positive!!!");
    }
    elseif(n<0)
    {

```



```

printf("negative!!!");
}
else{
printf("zero");
}
}

```

Q. 3 Write a C program to find whether a given year is a leap year or not.

```

#include<stdio.h>

intmain()
{
intn;
printf("enter the year:");
scanf("%d"
,&n);
if(n%4!=0)
{
printf("not a leap year!!!");
}
else
{
printf("leap year!!!");
}
return0;
}

```

Q. 4 Write a C program to find the largest of three numbers.

```

#include<stdio.h>

intmain()
{
intm1,m2,m3;
printf("enter the first

```

```

number:");
scanf("%d"
,&m1);
printf("enter the second
number:");
scanf("%d"
,&m2);
printf("enter the third
number:");
scanf("%d"
,&m3);
if(m1>m2&&m1>m3)
{
printf("first number is the
largest no.");
}
elseif(m2>m1&&m2>m3)
{
printf("second number is the
largest no.");
}
else
{
printf("third number is the
largest no.");
}
return0;
}

```

Q. 5 Write a C program to read temperature in centigrade and display a suitable message according to the temperature state below: a. Temp < 0 then Freezing weather b. Temp 0-10 then Very

Cold weather c. Temp 10-20 then Cold weather d. Temp 20-30 then

Normal in Temp e. Temp 30-40 then Its Hot f. Temp ≥ 40 then Its

Very Hot

```
# include<stdio.h>
```

```
intmain()
```

```
{
```

```
inttemp;
```

```
printf("enter the temperature in
```

```
centigrade:");
```

```
scanf("%d"
```

```
,&temp);
```

```
if(temp<=0)
```

```
{
```

```
printf("freezing weather");
```

```
}
```

```
elseif(temp<=10)
```

```
{
```

```
printf("very cold weather");
```

```
}
```

```
elseif(temp<=20)
```

```
{
```

```
printf("cold weather");
```

```
}
```

```
elseif(temp<=30)
```

```
{
```

```
printf("normal temperature");
```

```
}
```

```
elseif(temp<=40)
```

```
{
```

```
printf("its hot");
```

```
}
```

```
elseif(temp>40){  
printf("very hot");  
}  
return 0;  
}
```

Q. 6 Write a C program to read any digit and display it in the word.

```
#include<stdio.h>  
  
int main()  
{  
    int n;  
  
    printf("enter the digit to be  
displayed:");  
  
    scanf("%d",  
&n);  
  
    switch (n)  
    {  
        case 0: printf("Zero");  
        break;  
        case 1: printf("one");  
        break;  
        case 2: printf("Two");  
        break;  
        case 3: printf("Three");  
        break;  
        case 4: printf("Four");  
        break;  
        case 5: printf("Five");  
        break;  
        case 6: printf("Six");  
        break;  
        case 7: printf("Seven");
```

```

break;
case8:printf("Eight");
break;
case9:printf("nine");
break;
default:printf("nit a digit");
break;
}
}

```

Q. 7 Write a C program to create a Simple Calculator using a switch case.

```

#include<stdio.h>

intmain() {
charoperator;
doublefirst, second;
printf("Enter an operator (+, -,
*, /): ");
scanf("%c"
, &operator);
printf("Enter two operands: ");
scanf("%lf%lf"
, &first, &second);
switch (operator) {
case'+':
printf("%.1f + %.1f =
%.1f"
, first, second, first+second);
break;
case'-':
printf("%.1f - %.1f =
%.1f"

```

```

, first, second, first-second);

break;

case '*':

printf("%.1lf * %.1lf =

%.1lf"

, first, second, first*second);

break;

case '/':

printf("%.1lf / %.1lf =

%.1lf"

, first, second, first/second);

break;

default:

printf("Error! operator

is not correct");

}

return 0;

}

```

Q. 8 Write a C program using C Switch...Case to Calculate the Area of Rectangle/ Circle/ Triangle

```

#include<stdio.h>

int main() {

int choice;

float base, height, radius,

length, breadth, area;

printf("Switch Case in C Program

to Calculate Area of

Rectangle/Circle/Triangle\n");

printf("1. Calculate the area of

a circle\n");

printf("2. Calculate the area of

```

```
a rectangle\n");
printf("3. Calculate the area of
a triangle\n");
printf("Enter your choice (1, 2,
or 3): ");
scanf("%d"
, &choice);
switch (choice) {
case1:
printf("Enter the radius
of the circle: ");
scanf("%f"
, &radius);
area=3.14159*radius*radius;
printf("The area of the
circle is: %f\n"
, area);
break;
case2:
printf("Enter the length
and breadth of the rectangle: ");
scanf("%f%f"
, &length,
&breadth);
area=length*breadth;
printf("The area of the
rectangle is: %f\n"
, area);
break;
case3:
```

```

printf("Enter the base
and height of the triangle: ");
scanf("%f%f"
, &base,
&height);
area=0.5*base*height;
printf("The area of the
triangle is: %f\n"
, area);
break;
default:
printf("Invalid
choice\n");
break;
}
return 0;
}

```

H.O.T.S Questions

Q. 9 Write a C program to calculate the sum and average of positive numbers. If the user enters a negative number, the sum and average are displayed.

```

#include<stdio.h>

int main()
{
    int sum, avr, n, n1, n2;
    printf("enter the number:");
    scanf("%d"
, n);
    printf("enter the first
number:");
    scanf("%d"

```



```

,&n1);
printf("enter the second
number:");
scanf("%d"
,&n2);
if(n>0)
{
sum+=i;
avr=sum/i;
printf("sum is%d"
,sum);
printf("average is
%d"
,avr);
}
else
{
printf("sum is%d"
,sum);
printf("average is
%d"
,avr);
}
return 0;
}

```

Q. 10 Write a C program to design a digital clock.

```

#include<stdio.h>
#include<time.h>
int main() {
while (1) {
time_t currentTime=time(NULL);

```

```

struct tm*tm=localtime(&current
tTime);
printf("%02d:%02d:%02d\n"
,
tm->tm_hour, tm->tm_min, tm->tm_sec);
sleep(1);
}
return 0;
}

```

Q. 11 Write a C program to find the sum of digits of a number until a single digit is occurred

```

#include<stdio.h>
int main() {
int number, sum;
printf("Enter a number: ");
scanf("%d"
, &number);
while (number>9) {
sum=0;
while (number!=0) {
sum+=number%10;
number/=10;
}
number=sum;
}
printf("The sum of digits until a
single digit is occurred: %d\n"
,
number);
return 0;
}

```

Week - 4

Q. 1 Write a C program to print multiplication table of a number.

```
#include<stdio.h>

intmain()
{
    intn,mul;
    printf("enter the number:");
    scanf("%d"
    ,&n);
    for(inti=1;i<=10;++i)
    {
        mul=n*i;
        printf("%d*%d=%d\n"
        ,n,i,mul);
    }
    return0;
}
```

Q. 2 Write a C program to calculate factorial of a number

```
#include<stdio.h>

intmain()
{
    intn,i,fac=1;
    printf("enter the number:");
    scanf("%d"
    ,&n);
    for(i=1;i<=n;++i)
    {
        fac=fac*i;
    }
    printf("factorial of %d is
```

```
%d"
,n,fac);
return0;
}
```

Q. 3 Write a C program to check whether a number is palindrome or not.

```
#include<stdio.h>
intmain()
{
intn,i,r,rev=0;
printf("enter the number:");
scanf("%d"
,&n);
i=n;
while(i!=0)
{
r=i%10;
rev=rev*10+r;
i=i/10;
}
if(rev==n)
{
printf("palindrome");
}
else{
printf("not palindrome");
}
return0;
}
```

Q. 4 Write a C program to count frequency of digits in a given number.

```

#include<stdio.h>

intmain() {
    intnum, digit, count;
    printf("Enter a number: ");
    scanf("%d"
, &num);
    printf("Enter a digit to count:
");
    scanf("%d"
, &digit);
    count=0;
    while (num>0) {
        if (num%10==digit) {
            count++;
        }
        num/=10;
    }
    printf("Frequency of digit %d in
the given number is %d"
, digit,
count);
    return0;
}

```

Q. 5 Write a C program to find HCF(GCD) AND LCM of two numbers

```

#include<stdio.h>

intmain() {
    intnum1, num2, i, gcd, lcm;
    printf("Enter two numbers: ");
    scanf("%d%d"
, &num1, &num2);
    for (i=1; i<=num1&&i<=num2; ++i)

```

```

{
if (num1%i==0&&num2%i==0) {
gcd=i;
}
}

lcm= (num1*num2) /gcd;
printf("HCF(GCD) of %d and %d is
%d\n"
, num1, num2, gcd);
printf("LCM of %d and %d is %d"
,
num1, num2, lcm);
return0;
}

```

Q. 6 Write a C program to print all prime numbers between 1 to n.

```

#include<stdio.h>

intmain() {

inti, j, n, flag;

printf("Enter a number: ");

scanf("%d"

, &n);

printf("Prime numbers between 1

and %d are: ", n);

for (i=2; i<=n; ++i) {

flag=0;

for (j=2; j<=i/2; ++j) {

if (i%j==0) {

flag=1;

break;

}

}

}
}

```

```

if (flag==0)
printf("%d "
, i);
}
return0;
}

```

Q. 7 Write a C program to print Fibonacci series up to n terms.

```

#include<stdio.h>

intmain() {
inti, n, t1=0, t2=1, nextTerm;

printf("Enter the number of
terms: ");

scanf("%d"
, &n);

printf("Fibonacci Series: ");

for (i=1; i<=n; ++i) {
printf("%d, ", t1);
nextTerm=t1+t2;

t1=t2;
t2=nextTerm;
}

return0;
}

```

Q. 8 Write a C program to print Armstrong numbers from 1 to n AND check a given number is Armstrong numbers or not.

```

#include<stdio.h>

intmain()
{
intn,r,d,sum=0;

printf("enter the number:");

scanf("%d"

```

```
,&n);
d=n;
while(d!=0){
r=d%10;
sum+=r*r*r;
d=d/10;}
if(sum==n){
printf("armstrong number");
}
else{
printf("not armstrong number");
}
return0;
}
```

H.O.T.S Questions

Q. 9 Write a C program to print all Perfect numbers between 1 to n
AND Check a given number is Perfect numbers or not.

```
#include<stdio.h>

intmain() {
intnumber, sum;
printf("Enter a number: ");
scanf("%d", &number);
for (inti=1; i<=number; i++) {
sum=0;
for (intj=1; j<i; j++) {
if (i%j==0) {
sum+=j;
}
}
if (sum==i) {
printf("%d is a perfect number.\n", i);
```



```

}
}
printf("Perfect numbers between 1 and %d are: ", number);
for (inti=1; i<=number; i++) {
    sum=0;
    for (intj=1; j<i; j++) {
        if (i%j==0) {
            sum+=j;
        }
    }
    if (sum==i) {
        printf("%d ", i);
    }
}
printf("\n");
return 0;
}

```

Q. 10 Write a C program to print all Strong Numbers between 1 to n.

```

#include <stdio.h>

int main() {
    int n;

    printf("Enter the value of n: ");

    scanf("%d", &n);

    printf("Strong numbers between 1 and %d are:\n", n);

    for (int i = 1; i<= n; i++) {

        int originalNum = i;

        int sum = 0;

        int num = i;

        while (num> 0) {

            int digit = num % 10;

            int factorial = 1;

```

```

for (int j = 1; j <= digit; j++) {
    factorial *= j;
}
sum += factorial;
num /= 10;
}
if (sum == originalNum) {
    printf("%d\n", originalNum);
}
}
return 0;
}

```

Week 5

1.(a):

```

#include <stdio.h>

int main() {
    int rows = 4;
    for (int i = 1; i <= rows; i++) {
        for (int j = 1; j <= 5; j++) {
            printf("*");
        }
        printf("\n");
    }
    return 0;
}

```

(b):

```

#include <stdio.h>

int main() {
    int rows = 5;
    for (int i = 1; i <= rows; i++) {

```

```
    for (int j = 1; j <= rows; j++) {  
        printf("%d", j);  
    }  
    printf("\n");  
}  
return 0;  
}
```

(c):

```
#include <stdio.h>  
  
int main() {  
    int rows = 4;  
    for (int i = 1; i <= rows; i++) {  
        for (int j = 1; j <= i; j++) {  
            printf("%d", j);  
        }  
        printf("\n");  
    }  
    return 0;  
}
```

(d):

```
#include <stdio.h>  
  
int main() {  
    int rows = 4;  
    for (int i = 1; i <= rows; i++) {  
        for (int j = 1; j <= i; j++) {  
            printf("%d", i);  
        }  
        printf("\n");  
    }  
    return 0;  
}
```

(e):

```
#include <stdio.h>

int main() {
    int rows = 4;
    for (int i = 1; i <= rows; i++) {
        for (int j = 1; j <= i; j++) {
            printf("*");
        }
        printf("\n");
    }
    return 0;
}
```

(f):

```
#include <stdio.h>

int main() {
    int rows = 4;
    for (int i = 0; i < rows; i++) {
        for (int j = 0; j < rows - i - 1; j++) {
            printf(" ");
        }
        for (int k = 0; k <= i; k++) {
            printf("%c", 'A' + k);
        }
        printf("\n");
    }
    return 0;
}
```

(g):

```
#include <stdio.h>

int main() {
    int rows = 4;
```

```

int counter = 1;

for (int i = 1; i <= rows; i++) {

    for (int j = 1; j <= i; j++) {

        printf("%d", counter);

        counter++;

    }

    printf("\n");

}

return 0;

}

```

(h):

```

#include <stdio.h>

int main() {

    int rows = 5;

    for (int i = 1; i <= rows; i++) {

        for (int j = 1; j <= i; j++) {

            printf("%d", j % 2);

        }

        printf("\n");

    }

    return 0;

}

```

(i):

```

#include <stdio.h>

int main() {

    int rows = 5;

    for (int i = 5; i >= 1; i--) {

        for (int j = 5; j >= i; j--) {

            printf("%d", j);

        }

        printf("\n");

    }

}

```

```

}
return 0;
}
(j):
#include <stdio.h>
int main() {
    int rows = 5;
    for (int i = 1; i <= rows; i++) {
        for (int j = 5; j >= i; j--) {
            printf("%d", j);
        }
        printf("\n");
    }
    return 0;
}

```

```

(k):
#include <stdio.h>
int main() {
    int rows = 5;
    int cols = 5;
    for (int i = 1; i <= rows; i++) {
        for (int j = 1; j <= cols; j++) {
            if (i == 1 || i == rows || j == 1 || j == cols) {
                printf("*");
            } else {
                printf(" ");
            }
        }
        printf("\n");
    }
    return 0;
}

```

```
}
```

(L):

```
#include <stdio.h>
```

```
int main() {
```

```
    int rows = 4;
```

```
    for (int i = 1; i <= rows; i++) {
```

```
        for (int j = 1; j <= rows - i; j++) {
```

```
            printf(" ");
```

```
        }
```

```
        for (int k = 1; k <= 2 * i - 1; k++) {
```

```
            printf("*");
```

```
        }
```

```
        printf("\n");
```

```
    }
```

```
    return 0;
```

```
}
```

(m):

```
#include <stdio.h>
```

```
int main() {
```

```
    int rows = 4;
```

```
    for (int i = 1; i <= rows; i++) {
```

```
        for (int j = 1; j <= rows - i; j++) {
```

```
            printf(" ");
```

```
        }
```

```
        for (int k = 1; k <= 2 * i - 1; k++) {
```

```
            printf("*");
```

```
        }
```

```
        printf("\n");
```

```
    }
```

```
    for (int i = rows - 1; i >= 1; i--) {
```

```
        for (int j = 1; j <= rows - i; j++) {
```

```

printf(" ");
}
for (int k = 1; k <= 2 * i - 1; k++) {
printf("*");
}
printf("\n");
}
return 0;
}

```

(n):

```

#include <stdio.h>

int main() {
    int i, j, k;
    for (i = 3; i >= 0; i--) {
        for (k = 0; k < i; k++) {
            printf(" ");
        }
        for (j = 0; j <= 3 - i; j++) {
            printf("%d", 7 - (i * 2) + j);
        }
        printf("\n");
    }
    return 0;
}

```

Week 6

1. Write a menu driven program to insert and delete elements of kth position to an array of size N.

```

#include <stdio.h>

```

```

int main() {

```



```

int N, choice, k, i;

printf("Enter the size of the array: ");

scanf("%d", &N);

int arr[N];

for (i = 0; i < N; i++) {

printf("Enter element at position %d: ", i + 1);

scanf("%d", &arr[i]);

}

while (1) {

printf("\nMenu:\n");

printf("1. Insert element at kth position\n");

printf("2. Delete element at kth position\n");

printf("3. Display array\n");

printf("4. Exit\n");

printf("Enter your choice: ");

scanf("%d", &choice);

switch (choice) {

case 1:

printf("Enter the position (1 to %d) to insert element: ", N + 1);

scanf("%d", &k);

if (k < 1 || k > N + 1) {

printf("Invalid position. Position should be between 1 and

%d.\n", N + 1);

} else {

printf("Enter the element to insert: ");

int newElement;

scanf("%d", &newElement);

for (i = N - 1; i >= k - 1; i--) {

arr[i + 1] = arr[i];

}

arr[k - 1] = newElement;

```

```

    N++;
    printf("Element inserted successfully.\n");
}
break;
case 2:
    printf("Enter the position (1 to %d) to delete element: ", N);
    scanf("%d", &k);
    if (k < 1 || k > N) {
        printf("Invalid position. Position should be between 1 and
%d.\n", N);
    } else {
        for (i = k - 1; i < N - 1; i++) {
            arr[i] = arr[i + 1];
        }
        N--;
        printf("Element deleted successfully.\n");
    }
    break;
case 3:
    printf("Array elements: ");
    for (i = 0; i < N; i++) {
        printf("%d ", arr[i]);
    }
    printf("\n");
    break;
case 4:
    printf("Exiting the program.\n");
    return 0;
default:
    printf("Invalid choice. Please enter a valid option.\n");
}

```

```
}  
return 0;  
}
```

2. Write the program to print the biggest and smallest element in an array.

```
#include <stdio.h>  
  
int main() {  
    int N, i;  
  
    printf("Enter the size of the array: ");  
    scanf("%d", &N);  
  
    int arr[N];  
  
    for (i = 0; i < N; i++) {  
        printf("Enter element at position %d: ", i + 1);  
        scanf("%d", &arr[i]);  
    }  
  
    int largest = arr[0];  
    int smallest = arr[0];  
  
    for (i = 1; i < N; i++) {  
        if (arr[i] > largest) {  
            largest = arr[i];  
        }  
  
        if (arr[i] < smallest) {  
            smallest = arr[i];  
        }  
    }  
  
    printf("The largest element in the array is: %d\n", largest);  
    printf("The smallest element in the array is: %d\n", smallest);  
  
    return 0;  
}
```

3. Write the program to print the sum and average of an array.

```
#include <stdio.h>

int main() {
    int N, i;
    printf("Enter the size of the array: ");
    scanf("%d", &N);
    int arr[N];
    for (i = 0; i < N; i++) {
        printf("Enter element at position %d: ", i + 1);
        scanf("%d", &arr[i]);
    }
    int sum = 0;
    float average;
    for (i = 0; i < N; i++) {
        sum += arr[i];
    }
    average = (float)sum / N;
    printf("The sum of the elements in the array is: %d\n", sum);
    printf("The average of the elements in the array is: %.2f\n",
        average);
    return 0;
}
```

4. Write the program to sort an array using bubble sort.

```
#include <stdio.h>

int main() {
```

```

int N, i, j, temp;
printf("Enter the size of the array: ");
scanf("%d", &N);
int arr[N];
for (i = 0; i < N; i++) {
printf("Enter element at position %d: ", i + 1);
scanf("%d", &arr[i]);
}
for (i = 0; i < N - 1; i++) {
for (j = 0; j < N - i - 1; j++) {
if (arr[j] > arr[j + 1]) {
temp = arr[j];
arr[j] = arr[j + 1];
arr[j + 1] = temp;
}
}
}
printf("Sorted array: ");
for (i = 0; i < N; i++) {
printf("%d ", arr[i]);
}
printf("\n");
return 0;
}

```

5. Write the program to search an element using linear search as well as binary search.

```

#include <stdio.h>

int main() {
int N, i, element;

```

```
printf("Enter the size of the array: ");
scanf("%d", &N);

int arr[N];

printf("Enter the elements of the array:\n");

for (i = 0; i < N; i++) {
scanf("%d", &arr[i]);
}

printf("\nEnter the element to search using linear search: ");
scanf("%d", &element);

int linearIndex = -1;

for (i = 0; i < N; i++) {
if (arr[i] == element) {
linearIndex = i;
break;
}
}

if (linearIndex != -1) {
printf("Element %d found at position %d using linear search.\n",
element, linearIndex + 1);
} else {
printf("Element %d not found in the array using linear search.\n",
element);
}

printf("\nEnter the element to search using binary search: ");
scanf("%d", &element);

int low = 0, high = N - 1, mid, binaryIndex = -1;

while (low <= high) {
mid = (low + high) / 2;

if (arr[mid] == element) {
binaryIndex = mid;
break;
```

```

    } else if (arr[mid] < element) {
        low = mid + 1;
    } else {
        high = mid - 1;
    }
}

if (binaryIndex != -1) {
    printf("Element %d found at position %d using binary search.\n",
        element, binaryIndex + 1);
} else {
    printf("Element %d not found in the array using binary search.\n",
        element);
}

return 0;
}

```

6. Take an array of 20 integer inputs from user and

print the following:

- a. number of positive numbers
- b. number of negative numbers
- c. number of odd numbers
- d. number of even numbers e. number of 0.

```
#include <stdio.h>
```

```
int main() {
```

```
    int arr[20];
```

```
    int positiveCount = 0, negativeCount = 0, oddCount = 0, evenCount
    = 0, zeroCount = 0;
```

```
    printf("Enter 20 integers:\n");
```

```
    for (int i = 0; i < 20; i++) {
```

```
        scanf("%d", &arr[i]);
```

```

}
for (int i = 0; i < 20; i++) {
    if (arr[i] > 0) {
        positiveCount++;
    } else if (arr[i] < 0) {
        negativeCount++;
    } else {
        zeroCount++;
    }
    if (arr[i] % 2 == 0) {
        evenCount++;
    } else {
        oddCount++;
    }
}
printf("\na. Number of positive numbers: %d\n", positiveCount);
printf("b. Number of negative numbers: %d\n", negativeCount);
printf("c. Number of odd numbers: %d\n", oddCount);
printf("d. Number of even numbers: %d\n", evenCount);
printf("e. Number of zeros: %d\n", zeroCount);
return 0;
}

```

7. Take an array of 10 elements. Split it into middle and store the elements in two different arrays.

```

#include <stdio.h>

int main(){
    int initialArray[10];
    int firstHalf[5], secondHalf[5];
    printf("Enter 10 integers:\n");

```



```

for (int i = 0; i < 10; i++) {
scanf("%d", &initialArray[i]);
}

for (int i = 0; i < 5; i++) {
firstHalf[i] = initialArray[i];
secondHalf[i] = initialArray[i + 5];
}

printf("\nINITIAL array: ");
for (int i = 0; i < 10; i++) {
printf("%d, ", initialArray[i]);
}

printf("\n");
printf("After splitting:\n");
printf("First Half: ");
for (int i = 0; i < 5; i++) {
printf("%d, ", firstHalf[i]);
}

printf("\n");
printf("Second Half: ");
for (int i = 0; i < 5; i++) {
printf("%d, ", secondHalf[i]);
}

printf("\n");
return 0;
}

```

8. Write the program to count frequency of each element in an array.

```

#include <stdio.h>

int main() {

```

```

int N;

printf("Enter the size of the array: ");

scanf("%d", &N);

int arr[N];

printf("Enter %d integers:\n", N);

for (int i = 0; i < N; i++) {
scanf("%d", &arr[i]);
}

int frequency[N];

for (int i = 0; i < N; i++) {

frequency[i] = 0;

}

for (int i = 0; i < N; i++) {

if (frequency[i] == -1) {
continue;
}

for (int j = i + 1; j < N; j++) {

if (arr[i] == arr[j]) {
frequency[j] = -1;
frequency[i]++;
}

}

}

printf("\nFrequency of each element:\n");

for (int i = 0; i < N; i++) {

if (frequency[i] != -1) {

printf("%d occurs %d times.\n", arr[i], frequency[i] + 1);

}

}

return 0;

}

```

WEEK-7

Question 1

```
#include<stdio.h>

#defineMAX_ROWS3
#defineMAX_COLS3

voidprintRowMajor(int matrix[MAX_ROWS][MAX_COLS]) {
printf("Row Major Order:\n");
for (inti=0; i<MAX_ROWS; ++i) {
for (int j =0; j <MAX_COLS; ++j) {
printf("%d\t", matrix[i][j]);
}
printf("\n");
}
}

voidprintColumnMajor(int
matrix[MAX_ROWS][MAX_COLS]) {
printf("\nColumn Major Order:\n");
for (int j =0; j <MAX_COLS; ++j) {
for (inti=0; i<MAX_ROWS; ++i) {
printf("%d\t", matrix[i][j]);
}
printf("\n");
}
}

intmain() {
intmatrix[MAX_ROWS][MAX_COLS] = {{1, 2, 3},
{4, 5, 6},
```

```

{7, 8, 9}};

printRowMajor(matrix);

printColumnMajor(matrix);

return 0;

}

```

Question 2

```

#include<stdio.h>

#define MAX_ROWS 3

#define MAX_COLS 3

int calculateMatrixSum(int
matrix[MAX_ROWS][MAX_COLS]) {
    int sum = 0;
    for (int i = 0; i < MAX_ROWS; ++i) {
        for (int j = 0; j < MAX_COLS; ++j)
        {
            sum += matrix[i][j];
        }
    }
    return sum;
}

int main() {
    int matrix[MAX_ROWS][MAX_COLS] = {{1,
2, 3},
{4,
5, 6},
{7,
8, 9}};

    int sum = calculateMatrixSum(matrix);

    printf("Sum of the matrix: %d\n"

```

```
,  
sum);  
return0;  
}
```

Question 3

```
#include<stdio.h>  
  
#defineROWS3  
  
#defineCOLS3  
  
voidaddMatrices(intmat1[ROWS][COLS],  
intmat2[ROWS][COLS],  
intresult[ROWS][COLS]) {  
for (inti=0; i<ROWS; ++i) {  
for (int j =0; j <COLS; ++j) {  
result[i][j] =mat1[i][j]  
+mat2[i][j];  
}  
}  
}  
  
voidmultiplyMatrices(intmat1[ROWS][COLS],  
intmat2[ROWS][COLS],  
intresult[ROWS][COLS]) {  
for (inti=0; i<ROWS; ++i) {  
for (int j =0; j <COLS; ++j) {  
result[i][j] =0;  
for (int k =0; k <COLS; ++k)  
{  
result[i][j] +=mat1[i][k]  
*mat2[k][j];  
}  
}
```

```

}
}
}
void displayMatrix(int matrix[ROWS][COLS])
{
    for (int i=0; i<ROWS; ++i) {
        for (int j =0; j <COLS; ++j) {
            printf("%d\t"
, matrix[i][j]);
        }
        printf("\n");
    }
    printf("\n");
}

int main() {
    int matrix1[ROWS][COLS] = {{1, 2, 3},
{4, 5, 6},
{7, 8,
9}};
    int matrix2[ROWS][COLS] = {{9, 8, 7},
{6, 5, 4},
{3, 2,
1}};
    int sumMatrix[ROWS][COLS];
    int productMatrix[ROWS][COLS];
    addMatrices(matrix1, matrix2,
sumMatrix);
    multiplyMatrices(matrix1, matrix2,
productMatrix);
    printf("Matrix 1:\n");
    displayMatrix(matrix1);

```

```

printf("Matrix 2:\n");
displayMatrix(matrix2);
printf("Sum of Matrices:\n");
displayMatrix(sumMatrix);
printf("Product of Matrices:\n");
displayMatrix(productMatrix);
return 0;
}

```

Question 4

```

#include<stdio.h>

#define SIZE3

void printSumDiagonal(int matrix[SIZE][SIZE]) {
    int sum = 0;
    for (int i = 0; i < SIZE; ++i) {
        sum += matrix[i][i];
    }
    printf("Sum of diagonal elements: %d\n", sum);
}

void printUpperTriangular(int matrix[SIZE][SIZE]) {
    printf("Upper triangular matrix:\n");
    for (int i = 0; i < SIZE; ++i) {
        for (int j = 0; j < SIZE; ++j) {
            if (i <= j) {
                printf("%d\t", matrix[i][j]);
            } else {
                printf("0\t");
            }
        }
    }
    printf("\n");
}

```

```

}
}
void printLowerTriangular(int matrix[SIZE][SIZE]) {
    printf("Lower triangular matrix:\n");
    for (int i=0; i<SIZE; ++i) {
        for (int j =0; j <SIZE; ++j) {
            if (i>= j) {
                printf("%d\t", matrix[i][j]);
            } else {
                printf("0\t");
            }
        }
        printf("\n");
    }
}

int main() {
    int matrix[SIZE][SIZE] = {{1, 2, 3},
                               {4, 5, 6},
                               {7, 8, 9}};
    printSumDiagonal(matrix);
    printUpperTriangular(matrix);
    printLowerTriangular(matrix);
    return 0;
}

```

Question 5

```

#include<stdio.h>

#define ROWS3

#define COLS3

```



```

void findFrequency(int matrix[ROWS][COLS]) {
    int oddCount=0, evenCount=0;
    for (int i=0; i<ROWS; ++i) {
        for (int j =0; j <COLS; ++j) {
            if (matrix[i][j] %2==0) {
                evenCount++;
            } else {
                oddCount++;
            }
        }
    }
    printf("Frequency of odd elements: %d\n",
        oddCount);
    printf("Frequency of even elements: %d\n",
        evenCount);
}

int main() {
    int matrix[ROWS][COLS] = {{1, 2, 3},
        {4, 5, 6},
        {7, 8, 9}};
    findFrequency(matrix);
    return 0;
}

```

Question 6

```

#include<stdio.h>

#define ROWS3
#define COLS3

void findRowSum(int matrix[ROWS][COLS]) {
    printf("Sum of each row:\n");
}

```

```

for (inti=0; i<ROWS; ++i) {
    introwSum=0;
    for (int j =0; j <COLS; ++j) {
        rowSum+= matrix[i][j];
    }
    printf("Row %d: %d\n", i+1, rowSum);
}

void findColumnSum(int matrix[ROWS][COLS]) {
    printf("\nSum of each column:\n");
    for (int j =0; j <COLS; ++j) {
        intcolSum=0;
        for (inti=0; i<ROWS; ++i) {
            colSum+= matrix[i][j];
        }
        printf("Column %d: %d\n", j +1, colSum);
    }

    int main() {
        int matrix[ROWS][COLS] = {{1, 2, 3},
        {4, 5, 6},
        {7, 8, 9}};
        findRowSum(matrix);
        findColumnSum(matrix);
        return 0;
    }
}

```

Question 7

```
#include<stdio.h>
```

```

intmain() {
// Initialize a 3x3 matrix
intmatrix[3][3] = {
{1, 2, 3},
{4, 5, 6},
{7, 8, 9}
};
// Print the initialized matrix
printf("Initialized 3x3 Matrix:\n");
for (inti=0; i<3; ++i) {
for (int j =0; j <3; ++j) {
printf("%d\t", matrix[i][j]);
}
printf("\n");
}
return0;
}

```

Question 8

```

#include<stdio.h>

#defineSIZE3

voidcheckSpecialMatrix(int matrix[SIZE][SIZE]) {
intisDiagonal=1, isUpperTriangular=1,
isLowerTriangular=1;
for (inti=0; i<SIZE; ++i) {
for (int j =0; j <SIZE; ++j) {
if (i!= j && matrix[i][j] !=0) {
isDiagonal=0;
}
}
}
}

```

```

if (i > j && matrix[i][j] != 0) {
    isUpperTriangular=0;
}

if (i < j && matrix[i][j] != 0) {
    isLowerTriangular=0;
}

}

}

}

if (isDiagonal) {
    printf("The matrix is a diagonal
matrix.\n");
} elseif (isUpperTriangular) {
    printf("The matrix is an upper triangular
matrix.\n");
} elseif (isLowerTriangular) {
    printf("The matrix is a lower triangular
matrix.\n");
} else {
    printf("The matrix is not a special
matrix.\n");
}

}

int main() {
    int matrix[SIZE][SIZE];

    printf("Enter the elements of the %dx%d
matrix:\n", SIZE, SIZE);

    for (int i=0; i<SIZE; ++i) {
        for (int j =0; j <SIZE; ++j) {
            scanf("%d", &matrix[i][j]);
        }
    }
}

```

```
checkSpecialMatrix(matrix);  
return0;  
}
```

Question 9

```
#include<stdio.h>  
  
#defineROWS3  
  
#defineCOLS3  
  
intisSparseMatrix(intmatrix[ROWS][COLS]) {  
    intzeroCount=0, nonZeroCount=0;  
    for (inti=0; i<ROWS; ++i) {  
        for (int j =0; j <COLS; ++j) {  
            if (matrix[i][j] ==0) {  
                zeroCount++;  
            } else {  
                nonZeroCount++;  
            }  
        }  
    }  
  
    if (zeroCount> (ROWS*COLS) /2) {  
        return1;  
    } else {  
        return0;  
    }  
}  
  
voidmain() {  
    intmatrix[ROWS][COLS];  
  
    inti, j;  
  
    printf("Enter the elements of the %dx%d
```

```

matrix:\n", ROWS, COLS);
for (i=0; i<ROWS; ++i) {
for (j =0; j <COLS; ++j) {
scanf("%d", &matrix[i][j]);
}
}
if (isSparseMatrix(matrix)) {
printf("The matrix is a sparse matrix.\n");
} else {
printf("The matrix is not a sparse
matrix.\n");
}
}

```

Week-8

Question1

```

#include<stdio.h>

intmain() {

int number =10;

int*ptr=&number;

printf("Value of number: %d\n", number);

printf("Value pointed to by ptr: %d\n", *ptr);

*ptr=20;

printf("Updated value of number: %d\n", number);

doubledoubleNumber=3.14;

double*doublePtr=&doubleNumber;

printf("Value of doubleNumber: %lf\n", doubleNumber);

printf("Value pointed to by doublePtr: %lf\n", *doublePtr);

return0;

```

```
}
```

Question 2

```
#include<stdio.h>
```

```
void addNumbers(int*num1, int*num2, int*sum) {
```

```
    *sum = *num1 + *num2;
```

```
}
```

```
int main() {
```

```
    int number1, number2, result;
```

```
    printf("Enter first number: ");
```

```
    scanf("%d", &number1);
```

```
    printf("Enter second number: ");
```

```
    scanf("%d", &number2);
```

```
    addNumbers(&number1, &number2, &result);
```

```
    printf("Sum of %d and %d is: %d\n", number1, number2, result);
```

```
    return 0;
```

```
}
```

Question-3

```
#include<stdio.h>
```

```
void swapNumbers(int*num1, int*num2) {
```

```
    int temp = *num1;
```

```
    *num1 = *num2;
```

```
    *num2 = temp;
```

```
}
```

```
int main() {
```

```
    int number1, number2;
```

```
    printf("Enter first number: ");
```

```
    scanf("%d", &number1);
```

```
    printf("Enter second number: ");
```

```
    scanf("%d", &number2);
```

```
    printf("Before swapping: \n");
```

```
    printf("First number: %d\n", number1);
```

```

printf("Second number: %d\n", number2);
swapNumbers(&number1, &number2);
printf("After swapping: \n");
printf("First number: %d\n", number1);
printf("Second number: %d\n", number2);
return 0;
}

```

Question 4

```

#include<stdio.h>

void inputArray(int*arr, intsize) {
    printf("Enter %d elements:\n", size);
    for (inti=0; i< size; ++i) {
        scanf("%d", arr+i);}
    }

void printArray(int*arr, intsize) {
    printf("Array elements are:\n");
    for (inti=0; i< size; ++i) {
        printf("%d ", *(arr+i));
    }
    printf("\n");
}

int main() {
    intsize;
    printf("Enter the size of the array: ");
    scanf("%d", &size);
    int array[size];
    inputArray(array, size);
    printArray(array, size);
    return 0;
}

```

Question-5


```

#include<stdio.h>

voidcopyArray(int*source, int*destination, intsize) {
for (inti=0; i<size; ++i) {
*(destination+i) =*(source+i);
}
}

voidprintArray(int*arr, intsize) {
printf("Array elements are:\n");
for (inti=0; i<size; ++i) {
printf("%d ", *(arr+i));
}
printf("\n");
}

intmain() {
intsize;
printf("Enter the size of the array: ");
scanf("%d", &size);
intsourceArray[size];
intdestinationArray[size];
printf("Enter %d elements for the source array:\n", size);
for (inti=0; i< size; ++i) {
scanf("%d", &sourceArray[i]);
}
copyArray(sourceArray, destinationArray, size);
printf("\nSource Array:\n");
printArray(sourceArray, size);
printf("\nDestination Array (copied from source array):\n");
printArray(destinationArray, size);
return0;
}

```

Question-6

```

#include<stdio.h>

voidswapArrays(int*arr1, int*arr2, intsize) {
    int temp[size];
    for (inti=0; i< size; ++i) {
        temp[i] =*(arr1 +i);
    }
    for (inti=0; i< size; ++i) {
        *(arr1 +i) =*(arr2 +i);
    }
    for (inti=0; i< size; ++i) {
        *(arr2 +i) = temp[i];
    }
}

voidprintArray(int*arr, intsize) {
    printf("Array elements are:\n");
    for (inti=0; i< size; ++i) {
        printf("%d ", *(arr+i));
    }
    printf("\n");
}

intmain() {
    intsize;
    printf("Enter the size of the arrays: ");
    scanf("%d", &size);
    int array1[size];
    int array2[size];
    printf("Enter %d elements for the first array:\n", size);
    for (inti=0; i< size; ++i) {
        scanf("%d", &array1[i]);
    }
    printf("Enter %d elements for the second array:\n", size);

```

```

for (inti=0; i< size; ++i) {
scanf("%d", &array2[i]);
}

printf("\nArrays before swapping:\n");
printf("Array 1:\n");
printArray(array1, size);
printf("Array 2:\n");
printArray(array2, size);
swapArrays(array1, array2, size);
printf("\nArrays after swapping:\n");
printf("Array 1 (swapped):\n");
printArray(array1, size);
printf("Array 2 (swapped):\n");
printArray(array2, size);
return 0;}

```

Question-7

```

#include<stdio.h>

void reverseArray(int*arr, intsize) {
int*start =arr;
int*end =arr+ size -1;
while (start < end) {
int temp =*start;
*start =*end;
*end =temp;
start++;
end--;
}
}

void printArray(int*arr, intsize) {
printf("Array elements are:\n");
for (inti=0; i< size; ++i) {

```

```

printf("%d ", *(arr+i));
}
printf("\n");
}
intmain() {
intsize;
printf("Enter the size of the array: ");
scanf("%d", &size);
int array[size];
printf("Enter %d elements for the array:\n", size);
for (inti=0; i< size; ++i) {
scanf("%d", &array[i]);
}
printf("\nOriginal Array:\n");
printArray(array, size);s
reverseArray(array, size);
printf("\nArray after reversing:\n");
printArray(array, size);
return0;
}

```

Question 8

```

#include<stdio.h>

voidaddMatrices(int*mat1, int*mat2, int*result, introws, intcols) {
for (inti=0; i< rows; ++i) {
for (int j =0; j < cols; ++j) {
*(result +i* cols + j) =*(mat1 +i* cols + j) +*(mat2 +i* cols +
j);
}
}
}

voidprintMatrix(int*mat, introws, intcols) {

```

```

printf("Matrix elements are:\n");

for (inti=0; i< rows; ++i) {
for (int j =0; j < cols; ++j) {
printf("%d ", *(mat +i* cols + j));
}
printf("\n");
}
}

intmain() {
int rows, cols;

printf("Enter the number of rows: ");
scanf("%d", &rows);
printf("Enter the number of columns: ");
scanf("%d", &cols);
int matrix1[rows][cols];
int matrix2[rows][cols];
intresultMatrix[rows][cols];
printf("Enter elements for the first matrix:\n");
for (inti=0; i< rows; ++i) {
for (int j =0; j < cols; ++j) {
scanf("%d", &matrix1[i][j]);
}
}
printf("Enter elements for the second matrix:\n");
for (inti=0; i< rows; ++i) {
for (int j =0; j < cols; ++j) {
scanf("%d", &matrix2[i][j]);
}
}
addMatrices(&matrix1[0][0], &matrix2[0][0], &resultMatrix[0][0], rows,
cols);

```

```

printf("\nMatrix 1:\n");
printMatrix(&matrix1[0][0], rows, cols);
printf("\nMatrix 2:\n");
printMatrix(&matrix2[0][0], rows, cols);
printf("\nResult Matrix (Matrix 1 + Matrix 2):\n");
printMatrix(&resultMatrix[0][0], rows, cols);
return 0;
}

```

Question 9

```

#include<stdio.h>

void multiplyMatrices(int*mat1, int*mat2, int*result, introws1, intcols1,
intcols2) {
    for (inti=0; i< rows1; ++i) {
        for (int j =0; j < cols2; ++j) {
            *(result +i* cols2 + j) =0;
            for (int k =0; k < cols1; ++k) {
                *(result +i* cols2 + j) +=*(mat1 +i* cols1 + k) *(mat2 + k *
cols2 + j);
            }
        }
    }
}

void printMatrix(int*mat, introws, intcols) {
    printf("Matrix elements are:\n");
    for (inti=0; i< rows; ++i) {
        for (int j =0; j < cols; ++j) {
            printf("%d ", *(mat +i* cols + j));
        }
        printf("\n");
    }
}

```

```

intmain() {
int rows1, cols1, rows2, cols2;

printf("Enter the number of rows for matrix 1: ");
scanf("%d", &rows1);

printf("Enter the number of columns for matrix 1: ");
scanf("%d", &cols1);

printf("Enter the number of rows for matrix 2: ");
scanf("%d", &rows2);

printf("Enter the number of columns for matrix 2: ");
scanf("%d", &cols2);

if (cols1 != rows2) {
printf("Error: The number of columns in matrix 1 must be equal to the
number of rows in matrix 2 for multiplication.\n");
return1;
}

int matrix1[rows1][cols1];
int matrix2[rows2][cols2];
intresultMatrix[rows1][cols2];

printf("Enter elements for matrix 1:\n");
for (inti=0; i< rows1; ++i) {
for (int j =0; j < cols1; ++j) {
scanf("%d", &matrix1[i][j]);
}
}

printf("Enter elements for matrix 2:\n");
for (inti=0; i< rows2; ++i) {
for (int j =0; j < cols2; ++j) {
scanf("%d", &matrix2[i][j]);
}
}

multiplyMatrices(&matrix1[0][0], &matrix2[0][0], &resultMatrix[0][0],

```

```

rows1, cols1, cols2);

printf("\nMatrix 1:\n");

printMatrix(&matrix1[0][0], rows1, cols1);

printf("\nMatrix 2:\n");

printMatrix(&matrix2[0][0], rows2, cols2);

printf("\nResult Matrix (Matrix 1 * Matrix 2):\n");

printMatrix(&resultMatrix[0][0], rows1, cols2);

return 0;
}

```

Week 9

Question 1

```

#include<stdio.h>

int main() {
    char mainString[100], string[50];
    int i, j, found;
    printf("Enter the main string: ");
    gets(mainString);
    printf("Enter the substring to search: ");
    gets(string);
    for (i=0; mainString[i] != '\0'; ++i) {
        found = 1;
        for (j = 0; string[j] != '\0'; ++j) {
            if (mainString[i + j] != string[j]) {
                found = 0;
                break;
            }
        }
        if (found) {
            printf("string found at position %d.\n", i);
        }
    }
}

```



```

return0;
}
}
printf("string not found in the main string.\n");
return0;
}

```

Question 2

```

#include<stdio.h>
#include<string.h>
#defineMAX_SIZE100

voidreverseWords(char sentence[MAX_SIZE]);

intmain() {
    charsentence[MAX_SIZE];
    printf("Enter a sentence: ");
    gets(sentence);
    reverseWords(sentence);
    printf("Reversed sentence: %s\n", sentence);
    return0;
}

voidreverseWords(charsentence[MAX_SIZE]) {
    int start, end, length;
    length =strlen(sentence);
    for (start =0, end = length -1; start < end; ++start, --end) {
        char temp =sentence[start];
        sentence[start] =sentence[end];
        sentence[end] =temp;
    }
    start =0;
    for (end =0; end <= length; ++end) {
        if (sentence[end] == ' ' || sentence[end] =='\0') {
            intwordStart, wordEnd;

```

```

wordStart=start;
wordEnd= end -1;
while (wordStart<wordEnd) {
char temp =sentence[wordStart];
sentence[wordStart] =sentence[wordEnd];
sentence[wordEnd] =temp;
++wordStart;
--wordEnd;
}
start = end +1;
}
}
}

```

Question 3

```

#include<stdio.h>
intmain() {
charinputString[1000];
int vowels =0, consonants =0, digits =0, spaces =0, other =0;
printf("Enter a string: ");
gets(inputString);
for (inti=0; inputString[i] !='\0'; ++i) {
charcurentChar=inputString[i];
if ((currentChar>='a'&&currentChar<='z') ||
(currentChar>='A'&&currentChar<='Z')) {
if
(currentChar=='a' || currentChar=='e' || currentChar=='i' || currentChar=='o' || curre
ntChar=='u' ||
currentChar=='A' || currentChar=='E' || currentChar=='I' || currentC
har=='O' || currentChar=='U') {
++vowels;
} else {

```

```

++consonants;
}
} elseif (currentChar>='0'&&currentChar<='9') {
++digits;
} elseif (currentChar==' ' | currentChar=='\t' | currentChar=='\n') {
++spaces;
} else {
++other;
}
}

printf("Vowels: %d\n", vowels);
printf("Consonants: %d\n", consonants);
printf("Digits: %d\n", digits);
printf("Spaces: %d\n", spaces);
printf("Other characters: %d\n", other);
return0;
}

```

Question 4

```

#include<stdio.h>

intmain() {
charinputString[1000];
printf("Enter a string: ");
gets(inputString);
printf("Separated characters: ");
for (inti=0; inputString[i]!='\0'; ++i) {
printf("%c ", inputString[i]);
}
return0;
}

```

Question 5

```

#include<stdio.h>

```

```

#include<string.h>

#define MAX_SIZE 100

int main() {
    char firstString[MAX_SIZE], secondString[MAX_SIZE];

    printf("Enter the first string: ");
    gets(firstString);

    printf("Enter the second string: ");
    gets(secondString);

    strcat(firstString, " ");
    strcat(firstString, secondString);

    printf("Concatenated string: %s\n", firstString);

    return 0;
}

```

Question 6

```

#include<stdio.h>
#include<string.h>

#define MAX_SIZE 100

int main() {
    char inputString[MAX_SIZE];

    printf("Enter a string: ");
    gets(inputString);

    for (int i=0; i<strlen(inputString); ++i) {
        if (islower(inputString[i])) {
            inputString[i] = toupper(inputString[i]);
        } else if (isupper(inputString[i])) {
            inputString[i] = tolower(inputString[i]);
        }
    }

    printf("Toggled case string: %s\n", inputString);

    return 0;
}

```

Question 7

```
#include<stdio.h>

#define MAX_SIZE 100

int areIdentical(char str1[MAX_SIZE], char str2[MAX_SIZE]);

int main() {
    char firstString[MAX_SIZE], secondString[MAX_SIZE];
    printf("Enter the first string: ");
    gets(firstString);
    printf("Enter the second string: ");
    gets(secondString);
    if (areIdentical(firstString, secondString)) {
        printf("Identical\n");
    } else {
        printf("Not Identical\n");
    }
    return 0;
}

int areIdentical(char str1[MAX_SIZE], char str2[MAX_SIZE]) {
    int i=0;
    while (str1[i] != '\0' && str2[i] != '\0') {
        if (str1[i] != str2[i]) {
            return 0;
        }
        ++i;
    }
    if (str1[i] != str2[i]) {
        return 0;
    }
    return 1;
}
```

Question 8

```

#include<stdio.h>

#include<string.h>

#defineMAX_STUDENTS100

#defineMAX_NAME_LENGTH50

voidswap(chara[], charb[]) {
    chartemp[MAX_NAME_LENGTH];
    strcpy(temp, a);
    strcpy(a, b);
    strcpy(b, temp);
}

voidbubbleSort(charnames[][MAX_NAME_LENGTH], intn) {
    for (inti=0; i<n-1; ++i) {
        for (int j =0; j <n-i-1; ++j) {
            if (strcmp(names[j], names[j +1]) >0) {
                swap(names[j], names[j +1]);
            }
        }
    }
}

intmain() {
    intnumStudents;

    printf("Enter the number of students: ");
    scanf("%d", &numStudents);

    if (numStudents<=0 | numStudents>MAX_STUDENTS) {
        printf("Invalid number of students.
        Exiting.\n");
        return1;
    }

    charstudentNames[MAX_STUDENTS][MAX_NAME_LENGTH];

    for (inti=0; i<numStudents; ++i) {
        printf("Enter the name of student %d: ", i+1);
    }

```

```

scanf("%s", studentNames[i]);
}
bubbleSort(studentNames, numStudents);
printf("\nSorted List of Student Names:\n");
for (inti=0; i<numStudents; ++i) {
printf("%s\n", studentNames[i]);
}
return 0;
}

```

9. Write a C program to multiply two matrix using pointers.

```

#include <stdio.h>
#include <stdlib.h>
int main() {
    int n, m, p;
    printf("Enter the number of rows in the first matrix: ");
    scanf("%d", &n);
    printf("Enter the number of columns in the first matrix (and rows in the second
matrix): ");
    scanf("%d", &m);
    printf("Enter the number of columns in the second matrix: ");
    scanf("%d", &p);
    int *A = (int*)malloc(n * m * sizeof(int));
    int *B = (int*)malloc(m * p * sizeof(int));
    int *C = (int*)malloc(n * p * sizeof(int));
    if (!A || !B || !C) {
        printf("Error: Memory allocation failed.\n");
        exit(1);
    }
    printf("Enter elements of the first matrix:\n");
    for (int i = 0; i < n; ++i) {
        for (int j = 0; j < m; ++j) {

```

```

printf("Enter element [%d][%d]: ", i + 1, j + 1);
scanf("%d", A + i * m + j);
}
}

printf("Enter elements of the second matrix:\n");
for (int i = 0; i < m; ++i) {
    for (int j = 0; j < p; ++j) {
        printf("Enter element [%d][%d]: ", i + 1, j + 1);
        scanf("%d", B + i * p + j);
    }
}

for (int i = 0; i < n; ++i) {
    for (int j = 0; j < p; ++j) {
        int sum = 0;
        for (int k = 0; k < m; ++k) {
            sum += *(A + i * m + k) * *(B + k * p + j);
        }
        *(C + i * p + j) = sum;
    }
}

printf("Resultant matrix:\n");
for (int i = 0; i < n; ++i) {
    for (int j = 0; j < p; ++j) {
        printf("%d ", *(C + i * p + j));
    }
    printf("\n");
}

free(A);
free(B);
free(C);
return 0;

```



```
}
```

Week 10

1. Write a C program to find length of string using pointers.

```
#include <stdio.h>

int strlen(const char *str) {
    int l = 0;
    while (*str != '\0') {
        l++;
        str++;
    }
    return l;
}

int main(){
    char a[100];
    printf("Enter a string: ");
    scanf("%s",a);
    int l= strlen(a);
    printf("Length of the string: %d\n",l);
    return 0;
}
```

2. Write a C program to copy one string to another using pointer.

```
#include <stdio.h>

void copyString(char *dest, const char *src) {
    while ((*dest++ = *src++) != '\0');
}

int main() {
    char str[100],newstr[100];
    printf("Enter the source string: ");
    scanf("%s",str);
    copyString(newstr,str);
}
```

```
printf("Copied string: %s\n",newstr);  
return 0;  
}
```

3. Write a C program to concatenate two strings using pointers

```
#include <stdio.h>  
  
void concatenateStrings(char *dest, const char  
*src) {  
    while (*dest != '\0') {  
        dest++;  
    }  
    while ((*dest++ = *src++) != '\0');  
}  
  
int main() {  
    char firststr[100], secondstr[100];  
    printf("Enter the first string: ");  
    scanf("%s", firststr);  
    printf("Enter the second string: ");  
    scanf("%s", secondstr);  
    concatenateStrings(firststr, secondstr);  
    printf("Concatenated string: %s\n",firststr);  
    return 0;  
}
```

4. Write a C program to compare two strings using pointers.

```
#include <stdio.h>  
  
int cmpstr(const char *str1, const char *str2) {  
    while (*str1 != '\0' && *str2 != '\0') {  
        if (*str1 != *str2) {  
            return 0;  
        }  
        str1++;  
        str2++;  
    }
```

```

    }
    return (*str1 == '\0' && *str2 == '\0');
}

int main() {
    char firstStr[100], secondStr[100];
    printf("Enter the first string: ");
    scanf("%s", firstStr);
    printf("Enter the second string: ");
    scanf("%s", secondStr);
    if (cmpstr(firstStr, secondStr)) {
        printf("The strings are equal.\n");
    } else {
        printf("The strings are not equal.\n");
    }
    return 0;
}

```

5. WAP to find largest among three numbers using pointer.

```

#include <stdio.h>

int findLargest(int *n1, int *n2, int *n3) {
    int l = *n1;
    if (*n2 > l) {
        l = *n2;
    }
    if (*n3 > l) {
        l = *n3;
    }
    return l;
}

int main() {
    int n1, n2, n3;
    printf("Enter the first number: ");

```

```

scanf("%d", &n1);
printf("Enter the second number: ");
scanf("%d", &n2);
printf("Enter the third number: ");
scanf("%d", &n3);
int l = findLargest(&n1, &n2, &n3);
printf("The largest number is: %d\n", l);
return 0;
}

```

6. WAP to find largest among three numbers using pointer.

```

#include <stdio.h>

int findLargest(int *n1, int *n2, int *n3) {
    int l = *n1;
    if (*n2 > l) {
        l = *n2;
    }
    if (*n3 > l) {
        l = *n3;
    }
    return l;
}

int main() {
    int n1,n2,n3;
    printf("Enter the first number: ");
    scanf("%d", &n1);
    printf("Enter the second number: ");
    scanf("%d", &n2);
    printf("Enter the third number: ");
    scanf("%d", &n3);
    int l = findLargest(&n1, &n2, &n3);
    printf("The largest number is: %d\n", l);
}

```

```
return 0;
```

```
}
```

7. WAP to find factorial of a number using pointer.

```
#include <stdio.h>
```

```
long longFact(int *n) {
```

```
    long long f = 1;
```

```
    for (int i = 1; i <= *n; i++) {
```

```
        f *= i;
```

```
    }
```

```
    return f;
```

```
}
```

```
int main() {
```

```
    int n;
```

```
    printf("Enter a number: ");
```

```
    scanf("%d", &n);
```

```
    long long f = Fact(&n);
```

```
    printf("Factorial of %d is: %lld\n", n, f);
```

```
    return 0;
```

```
}
```

8. Write a program to print largest even number present in an array using pointer to an array.

```
#include <stdio.h>
```

```
int findLargestEven(int *a, int s) {
```

```
    int lEven = -1;
```

```
    for (int i = 0; i < s; i++) {
```

```
        if (a[i] % 2 == 0 && a[i] > lEven) {
```

```
            lEven = a[i];
```

```
        }
```

```
    }
```

```
    return lEven;
```

```
}
```

```

int main() {
    int s;
    printf("Enter the size of the array: ");
    scanf("%d", &s);
    int n[s];
    printf("Enter the array elements:\n");
    for (int i = 0; i < s; i++) {
        scanf("%d", &n[i]);
    }
    int lEven = findLargestEven(n, s);
    if (lEven != -1) {
        printf("The largest even number is: %d\n", lEven);
    } else {
        printf("No even numbers found in the array.\n");
    }
    return 0;
}

```

9.WAP to find sum of elements of an array using array of pointer.

```

#include <stdio.h>

int findArraySum(int *a[], int s) {
    int sum = 0;
    for (int i = 0; i < s; i++) {
        sum += *a[i];
    }
    return sum;
}

int main() {
    int s;
    printf("Enter the size of the array: ");
    scanf("%d", &s);
    int n[s];

```

```

printf("Enter the array elements:\n");

for (int i = 0; i < s; i++) {
scanf("%d", &n[i]);
}

int *ps[s];

for (int i = 0; i < s; i++) {
ps[i] = &n[i];
}

int sum = findArraySum(ps, s);

printf("Sum of elements in the array: %d\n", sum);

return 0;
}

```

10. WAP to compute simple interest using pointers.

```

#include <stdio.h>

float CSI(float *p, float *r, float *t) {
return (*p * *r * *t) / 100.0;
}

int main() {
float p, r, t;

printf("Enter principal amount: ");
scanf("%f", &p);

printf("Enter rate of interest: ");
scanf("%f", &r);

printf("Enter time in years: ");
scanf("%f", &t);

float i = CSI(&p, &r, &t);

printf("Simple Interest: %.2f\n", i);

return 0;
}

```

11. Write a program to print largest even number present in an array using pointer to an array.

```

#include <stdio.h>

int findLargestEven(int *a, int s) {
    int lEven = -1;
    for (int i = 0; i < s; i++) {
        if (a[i] % 2 == 0 && a[i] > lEven) {
            lEven = a[i];
        }
    }
    return lEven;
}

int main() {
    int s;
    printf("Enter the size of the array: ");
    scanf("%d", &s);
    int n[s];
    printf("Enter the array elements:\n");
    for (int i = 0; i < s; i++) {
        scanf("%d", &n[i]);
    }
    int lEven = findLargestEven(n, s);
    if (lEven != -1) {
        printf("The largest even number is: %d\n", lEven);
    } else {
        printf("No even numbers found in the array.\n");
    }
    return 0;
}

```

Week 11

1. Write a C function to return the maximum of three integers.


```

#include <stdio.h>

int findMaximum(int num1, int num2, int num3) {
    int max = num1;
    if (num2 > max) {
        max = num2;
    }
    if (num3 > max) {
        max = num3;
    }
    return max;
}

int main() {
    int num1, num2, num3;
    printf("Enter the first number: ");
    scanf("%d", &num1);
    printf("Enter the second number: ");
    scanf("%d", &num2);
    printf("Enter the third number: ");
    scanf("%d", &num3);
    int maximum = findMaximum(num1, num2, num3);
    printf("The maximum number is: %d\n", maximum);
    return 0;
}

```

2. Write a C function to check if a given number is prime or not.

```

#include <stdio.h>

int isPrime(int n) {
    if (n <= 1) {
        return 0;
    }
    for (int i = 2; i * i <= n; i++) {

```

```

if (n % i == 0) {
    return 0;
}
}

return 1;
}

int main() {
    int n;

    printf("Enter a number: ");
    scanf("%d", &n);

    if (isPrime(n)) {
        printf("%d is a prime number.\n", n);
    } else {
        printf("%d is not a prime number.\n", n);
    }

    return 0;
}

```

3. Write a C function to compute the factorial of a nonnegative integer.

```

#include <stdio.h>

unsigned long long factorial(int n) {
    if (n < 0) {
        return 0;
    }

    if (n == 0 || n == 1) {
        return 1;
    }

    unsigned long long r = 1;
    for (int i = 2; i <= n; i++) {
        r *= i;
    }

    return r;
}

```

```

}

int main() {

    int n;

    printf("Enter a non-negative integer: ");

    scanf("%d", &n);

    unsigned long long r = factorial(n);

    printf("The factorial of %d is: %llu\n", n, r);

    return 0;

}

```

4. Write a C function to swap the values of two integers in actual arguments.

```

#include <stdio.h>

void swapIntegers(int *a, int *b) {

    int temp = *a;

    *a = *b;

    *b = temp;

}

int main() {

    int num1, num2;

    printf("Enter the first integer: ");

    scanf("%d", &num1);

    printf("Enter the second integer: ");

    scanf("%d", &num2);

    swapIntegers(&num1, &num2);

    printf("After swapping:\n");

    printf("First integer: %d\n", num1);

    printf("Second integer: %d\n", num2);

    return 0;

}

```

5. Write a C function to compute the sum and average of an array of integers.

```

#include <stdio.h>

void computeSumAndAverage(int *arr, int size, int *sum, float *average) {
    *sum = 0;
    for (int i = 0; i < size; i++) {
        *sum += *(arr + i);
    }
    *average = (float)(*sum) / size;
}

int main() {
    int size;

    printf("Enter the size of the array: ");
    scanf("%d", &size);
    int numbers[size];
    printf("Enter the array elements:\n");
    for (int i = 0; i < size; i++) {
        scanf("%d", &numbers[i]);
    }
    int sum;
    float average;
    computeSumAndAverage(numbers, size, &sum, &average);
    printf("Sum of the array elements: %d\n", sum);
    printf("Average of the array elements: %.2f\n", average);
    return 0;
}

```

6. Write a C function to find the GCD (Greatest Common Divisor) of two nonnegative integers using Euclid's algorithm.

```

#include <stdio.h>

int findGCD(int a, int b) {
    while (b != 0) {
        int temp = b;
        b = a % b;

```

```

    a = temp;
}
return a;
}

int main() {
    int num1, num2;
    printf("Enter the first non-negative integer: ");
    scanf("%d", &num1);
    printf("Enter the second non-negative integer: ");
    scanf("%d", &num2);

    int gcd = findGCD(num1, num2);
    printf("The GCD of %d and %d is: %d\n", num1, num2, gcd);
    return 0;
}

```

7. Write a C function to check if a given string is a valid palindrome, considering only alphanumeric characters and ignoring cases.

```

#include <stdio.h>
#include <ctype.h>
#include <string.h>

int isPalindrome(const char *str) {
    int length = strlen(str);
    int start = 0;
    int end = length - 1;
    while (start < end) {
        while (!isalnum(str[start]) && start < end) {
            start++;
        }
        while (!isalnum(str[end]) && start < end) {
            end--;
        }
    }
}

```

```

char char1 = tolower(str[start]);
char char2 = tolower(str[end]);
if (char1 != char2) {
    return 0;
}
start++;
end--;
}
return 1;
}

int main() {
    char input[100];
    printf("Enter a string: ");
    fgets(input, sizeof(input), stdin);
    input[strcspn(input, "\n")] = '\0';
    if (isPalindrome(input)) {
        printf("The string is a valid palindrome.\n");
    } else {
        printf("The string is not a palindrome.\n");
    }
    return 0;
}

```

8. Write a C function to calculate the sum and difference of two complex numbers.

```

#include <stdio.h>

typedef struct {
    float real;
    float imaginary;
} ComplexNumber;

void addComplex(ComplexNumber num1, ComplexNumber num2,
ComplexNumber *result) {

```

```

result->real = num1.real + num2.real;
result->imaginary = num1.imaginary + num2.imaginary;
}
void subtractComplex(ComplexNumber num1, ComplexNumber num2,
ComplexNumber *result) {
    result->real = num1.real - num2.real;
    result->imaginary = num1.imaginary - num2.imaginary;
}
int main() {
    ComplexNumber complex1, complex2, sum, difference;
    printf("Enter the real part of the first complex number: ");
    scanf("%f", &complex1.real);
    printf("Enter the imaginary part of the first complex number: ");
    scanf("%f", &complex1.imaginary);
    printf("Enter the real part of the second complex number: ");
    scanf("%f", &complex2.real);
    printf("Enter the imaginary part of the second complex number: ");
    scanf("%f", &complex2.imaginary);
    addComplex(complex1, complex2, &sum);
    subtractComplex(complex1, complex2, &difference);
    printf("Sum: %.2f + %.2fi\n", sum.real, sum.imaginary);
    printf("Difference: %.2f + %.2fi\n", difference.real, difference.imaginary);
    return 0;
}

```

9. Write a C function to find the second largest and second smallest elements in an array of integers.

```

#include <stdio.h>

void findSecondLargestAndSmallest(int arr[], int size, int *secondLargest, int
*secondSmallest) {
    if (size < 2) {
        printf("Array should have at least two elements.\n");
    }
}

```

```

return;
}
*secondLargest = (arr[0] > arr[1]) ? arr[0] : arr[1];
*secondSmallest = (arr[0] < arr[1]) ? arr[0] : arr[1];
for (int i = 2; i < size; i++) {
    if (arr[i] > *secondLargest) {
        *secondLargest = arr[i];
    } else if (arr[i] < *secondSmallest) {
        *secondSmallest = arr[i];
    }
}
}

int main() {
    int size;
    printf("Enter the size of the array: ");
    scanf("%d", &size);
    if (size <= 0) {
        printf("Array size should be greater than 0.\n");
        return 1;
    }
    int numbers[size];
    printf("Enter the array elements:\n");
    for (int i = 0; i < size; i++) {
        scanf("%d", &numbers[i]);
    }
    int secondLargest, secondSmallest;
    findSecondLargestAndSmallest(numbers, size, &secondLargest,
    &secondSmallest);
    printf("Second Largest Element: %d\n", secondLargest);
    printf("Second Smallest Element: %d\n", secondSmallest);
    return 0;
}

```



```
}
```

10. Write a C function to find the number of occurrences of each unique element in an array.

```
#include <stdio.h>
```

```
void countOccurrences(int arr[], int size) {
```

```
    int frequency[size];
```

```
    for (int i = 0; i < size; i++) {
```

```
        frequency[i] = 0;
```

```
    }
```

```
    for (int i = 0; i < size; i++) {
```

```
        int currentElement = arr[i];
```

```
        int isEncountered = 0;
```

```
        for (int j = 0; j < i; j++) {
```

```
            if (arr[j] == currentElement) {
```

```
                isEncountered = 1;
```

```
                break;
```

```
            }
```

```
        }
```

```
        if (!isEncountered) {
```

```
            int count = 1;
```

```
            for (int j = i + 1; j < size; j++) {
```

```
                if (arr[j] == currentElement) {
```

```
                    count++;
```

```
                }
```

```
            }
```

```
            printf("Element %d occurs %d times\n", currentElement, count);
```

```
        }
```

```
    }
```

```
}
```

```
int main() {
```

```
    int size;
```

```
printf("Enter the size of the array: ");  
scanf("%d", &size);  
if (size <= 0) {  
printf("Array size should be greater than 0.\n");  
return 1;  
}  
int numbers[size];  
printf("Enter the array elements:\n");  
for (int i = 0; i < size; i++) {  
scanf("%d", &numbers[i]);  
}  
countOccurrences(numbers, size);  
return 0;
```