AVT Image Transform



AVT Image Transform Programmer's Manual

V1.3 2014-08-12





Legal Notice

Trademarks

Unless stated otherwise, all trademarks appearing in this document of Allied Vision Technologies are brands protected by law.

Warranty

The information provided by Allied Vision Technologies is supplied without any guarantees or warranty whatsoever, be it specific or implicit. Also excluded are all implicit warranties concerning the negotiability, the suitability for specific applications or the non-breaking of laws and patents. Even if we assume that the information supplied to us is accurate, errors and inaccuracy may still occur.

Copyright

All texts, pictures and graphics are protected by copyright and other laws protecting intellectual property. It is not permitted to copy or modify them for trade use or transfer, nor may they be used on websites.

Allied Vision Technologies GmbH 08/2014

All rights reserved.

Managing Director: Mr. Frank Grube

Tax ID: DE 184383113

Headquarters:

Taschenweg 2a

D-07646 Stadtroda, Germany

Tel.: +49 (0)36428 6770 Fax: +49 (0)36428 677-28

e-mail: info@alliedvisiontec.com



Contents

1	Contacting Attied vision recimologies	4
2	P.1 Document history	5 5 5 5
3	Technologies	6 6 7
4	General	8 8 8 9
5	Debayering into an Rgb8 image	l0 l0 l0 l1
6	5.1 Information 1 6.1.1 VmbGetVersion() 1 6.1.2 VmbGetErrorInfo() 1 6.1.3 VmbGetApiInfoString() 1 5.2 Transformation 1 6.3 VmbImageTransform() 1 6.4 Helper functions 1 6.4.1 VmbSetImageInfoFromPixelFormat() 1 6.4.2 VmbSetImageInfoFromString() 1 6.4.3 VmbSetDebayerMode() 1	13 13 13 14 14 14 15 15
7	7.1 VmbImage 1 7.2 VmbImageInfo 1 7.3 VmbPixelInfo 1	16 16 16 16



1 Contacting Allied Vision Technologies

Note



Technical Information

http://www.alliedvisiontec.com

Support

support@alliedvisiontec.com

Allied Vision Technologies GmbH (Headquarters)

Taschenweg 2a

07646 Stadtroda, Germany Tel.: +49 36428-677-0 Fax.: +49 36428-677-28

Email: info@alliedvisiontec.com

Allied Vision Technologies Canada Inc.

101-3750 North Fraser Way Burnaby, BC, V5J 5E9, Canada

Tel: +1 604-875-8855 Fax: +1 604-875-8856

Email: info@alliedvisiontec.com

Allied Vision Technologies Inc.

38 Washington Street Newburyport, MA 01950, USA Toll Free number +1 877-USA-1394

Tel.: +1 978-225-2030 Fax: +1 978-225-2029

Email: info@alliedvisiontec.com

Allied Vision Technologies Asia Pte. Ltd.

82 Playfair Road #07-02 D'Lithium Singapore 368001 Tel. +65 6634-9027

Fax:+65 6634-9029

Email: info@alliedvisiontec.com

Allied Vision Technologies (Shanghai) Co., Ltd.

2-2109 Hongwell International Plaza 1602# ZhongShanXi Road

Shanghai 200235, China Tel: +86 (21) 64861133 Fax: +86 (21) 54233670

Email: info@alliedvisiontec.com



2 Introduction

2.1 Document history

Version	Date	Changes	
1.0	2013-03-22	Initial version	
1.2	2013-06-18	Small corrections, layout changes	
1.3	2014-08-12	Rework of the whole document	

2.2 Conventions used in this manual

To give this manual an easily understood layout and to emphasize important information, the following typographical styles and symbols are used:

2.2.1 Styles

Style	Function	Example
Bold	old Programs, inputs or highlighting important things	
Courier	Code listings etc.	Input
Upper case	Constants	CONSTANT
Italics	Modes, fields, features	Mode
Blue and/or parentheses	Links	(Link)

2.2.2 Symbols

Note



This symbol highlights important information.

Caution



This symbol highlights important instructions. You have to follow these instructions to avoid malfunctions.

www



This symbol highlights URLs for further information. The URL itself is shown in blue.

Example: http://www.alliedvisiontec.com



3 General aspects of the Library

The purpose of the AVT Image Transform library is to transform images received via Vimba APIs into common image formats. It is part of Vimba and doesn't require a separate installation.

Applications using Vimba C or C++ APIs may need to integrate AVT Image Transform library as an additional library, whereas a subset of it is seamlessly integrated into the AVT Vimba .NET API via method Frame.Fill(). (See the Vimba.NET Programmer's Manual)

3.1 Technologies

The AVT Image Transform Library is available in two versions: The standard version executes a method call in a single thread. The OpenMP version is recommended for achieving a high performance with multi-core PCs, since the function calls are distributed over the cores of the processor. Although additional time is required to schedule the sub tasks, its performance roughly scales by the number of free cores.

Both libraries have the same interface and the same name, but are delivered in different folders in the Vimba installation, allowing you to use the library you want.

The OpenMP version of the library can be found in the subdirectory OpenMP beneath the standard library.

3.2 Supported image data formats

In contrast to image *file* formats, image *data* formats contain no embedded meta-data, but only pure images as rectangular arrays of pixels. These pixels have certain characteristics, e.g. a certain color or bit depth and the endianness for a bit depth of more than eight, and they may appear in a certain order. All this is described in a pixel format name.

Note



All implemented image transformations only accept multi-byte pixel formats in little-endian byte order.

For this library, pixel formats from the interface specifications IIDC and GigE Vision as well as common display formats on Windows and Linux platforms have been selected. The names of the pixel formats mainly match the list of values of the "PixelFormat" feature in the Standard Features Naming Convention of GenICam.

Since the following pixel formats span a few bytes or in some cases several lines, their width and height or size (in pixels) must be divisible by the following values:

Pixel format	Width	Height	Size
Mono12Packed	1	1	2
Bayer	2	2	1
Yuv411	4	1	1
Yuv422	2	1	1



3.3 Supported transformations

Source Target	Mono8	Mono16	Rgb8	Bgr8	Argb8	Bgra8	Yuv422
Mono8	~	-	✓	~	~	~	~
Mono10	~	✓	✓	~	~	~	-
Mono12	~	~	~	~	~	~	-
Mono12Packed	~	-	✓	~	✓	~	-
Mono14	~	~	~	~	~	~	-
Mono16	~	✓	~	~	~	~	-
BayerXX ¹ 8	~	✓	~	~	~	~	~
BayerXX ¹ 10	~	~	~	~	~	~	-
BayerXX ¹ 12	~	✓	~	~	~	~	-
BayerXX ¹ 12Packed	~	~	~	~	~	~	-
BayerXX ¹ 16	~	✓	✓	~	✓	~	-
Rgb8	~	-	~	~	~	~	-
Bgr8	~	-	~	~	~	~	-
Argb8	~	-	~	~	~	~	-
Bgra8	~	-	~	~	~	~	-
Yuv411	~	-	~	~	~	~	-
Yuv422	~	-	~	~	~	~	~
Yuv444	~	-	~	~	~	~	-

¹BayerXX is any of BayerGR, BayerRG, BayerGB or BayerBG



4 API usage

4.1 General

Every concrete image transformation must specify its three parameters:

- The fully-qualified input image (including complete format specification)
- The complete output format (plus a pointer to enough memory to hold the transformed image)
- The transformation itself (including transformation options if there is more than one possible way from the input format to the output format)

VmbImageTransform() is the main function, which covers all three transformation parameters. It uses two VmbImage pointers to specify the source and destination image and a list of VmbTransformInfo structs to specify the transformation.

To ease filling the structs that are needed for a successful call of VmbImageTransform(), several helper functions for initializing them are available:

- Methods for filling the necessary format information of either the input or the output image (described in chapter Filling Image Information).
- Methods for filling optional transformation parameters to invoke special and additional functionality, as can be seen in chapter Specifying Transformation Options.

4.2 Filling Image Information

There are three ways to fill VmbImage structs:

- Filling the fields explicitly one by one (not recommended)
- Using the function VmbSetImageInfoFromPixelFormat() by providing a VmbPixelFormat_t value and the size
- 3. Using the function VmbSetImageInfoFromString() by providing a string that describes the pixel format and the size

With the first approach, you have to specify many fields (that are important for the transformation process, but very possibly not for you), while the latter two approaches only require knowing either the name or the enumeration value of the image format.

4.3 Specifying Transformation Options

Depending on your application and the desired image characteristics, you can choose between several transformation options. A common way to transform color images is using a 3x3 matrix with method VmbSetColorCorrectionMatrix3x3(). The Matrix you have to specify is a 3x3 row order float matrix.



Every transformation of a Bayer image requires defining how to interpolate or combine the color pixels. This can done with the help of an additional transformation parameter to VmbImageTransform(), which can be filled with the help of function VmbSetDebayerMode() (using a VmbDebayerMode as input). VmbDebayerMode can be one of the following values:

Value	Description
VmbDebayerMode2x2	2x2 with green averaging
VmbDebayerMode3x3	3x3 with equal green weighting per line
VmbDebayerModeLCAA	Debayering with horizontal local color anti-aliasing
VmbDebayerModeLCAAV	Debayering with horizontal and vertical local color anti-aliasing
VmbDebayerModeYUV422	Debayering with YUV422-alike sub-sampling

4.4 Transforming images

When you've prepared all the parameters of a transformation, use the pre-filled structs and call VmbImageTransform().



5 Transformation examples

5.1 Debayering into an Rgb8 image

Example for a transformation of a BayerGR8 image with 640x480 pixels into an Rgb8 image of the same size:

```
VmbImage
                         sourceImage;
VmbImage
                         destinationImage;
VmbTransformInfo
                         info:
// set size member for verification inside API
sourceImage.Size = sizeof ( sourceImage );
destinationImage.Size = sizeof ( destinationImage );
// attach the data buffers
sourceImage.Data = pInBuffer;
destinationImage.Data = pOutBuffer;
// fill image info from pixel format
VmbSetImageInfoFromPixelFormat ( VmbPixelFormatBayerGR8,
                                   640,
                                   &sourceImage);
// fill image info from pixel format string
std::string name ( "RGB8" );
VmbSetImageInfoFromString ( name.c_str(),
                              static_cast < VmbUint32_t > ( name.size() ) ,
                              640,
                              480,
                              &destinationImage );
// set the debayering algorithm to simple 2 by 2
VmbSetDebayerMode ( VmbDebayerMode2x2, &info );
// perform the transformation
VmbImageTransform ( &sourceImage, &destinationImage, &info, 1 );
```

5.2 Debayering into a Mono8 image

Example for preparing a transformation of a BayerRG8 image with 640x480 pixels into a Mono8 image of the same size:

AVT Image Transform - Programmer's Manual



```
destinationImage.Data = pOutBuffer;
// fill image info from pixel format string % \left( 1\right) =\left( 1\right) +\left( 1\right)
std::string name ( "PixelFormatBayerRG8" );
VmbSetImageInfoFromString ( name.c_str(),
                                                                                                                                                                                                                                                              static_cast < VmbUint32_t > ( name.size() ),
                                                                                                                                                                                                                                                              640,
                                                                                                                                                                                                                                                              480,
                                                                                                                                                                                                                                                              &sourceImage );
 // fill image info from pixel format
{\tt VmbSetImageInfoFromPixelFormat} \ \ ( \ {\tt VmbPixelFormatMono8} \ ,
                                                                                                                                                                                                                                                                                                           640,
                                                                                                                                                                                                                                                                                                            480,
                                                                                                                                                                                                                                                                                                           &destinationImage );
// set the debayering algorithm to 3 by 3
VmbSetDebayerMode ( VmbDebayerMode3x3, &info );
// perform the transformation
VmbImageTransform ( &sourceImage, &destinationImage, &info, 1 );
```

5.3 Applying a color correction to an Rgb8 image

Example for applying a color correction to an Rgb8 image with 640x480 pixels:

```
VmbImage
                  sourceImage;
VmbImage
                  destinationImage;
VmbTransformInfo info;
const VmbFloat_t
                  mat[] = \{ 1.0f, 0.0f, 0.0f, 
                            0.0f, 1.0f, 0.0f,
                            0.0f, 0.0f, 1.0f };
// set size member for verification inside API
sourceImage.Size = sizeof ( sourceImage );
destinationImage.Size = sizeof ( destinationImage );
// attach the data buffers
sourceImage.Data = pInBuffer;
destinationImage.Data = pOutBuffer;
// fill image info from pixel format
VmbSetImageInfoFromPixelFormat ( VmbPixelFormatRgb8,
                                640,
                                480,
                                &sourceImage );
// fill image info from pixel format
VmbSetImageInfoFromPixelFormat ( VmbPixelFormatRgb8,
                                &destinationImage );
// set the transformation matrix
```



```
VmbSetColorCorrectionMatrix3x3 ( mat, &info );

// perform the transformation
VmbImageTransform ( &sourceImage, &destinationImage, &info, 1 );
```

5.4 Debayering a 12-bit image into a Mono16 image with additional color correction

Example for preparing a transformation of a BayerGR12 image with 640x480 pixels into a Mono16 image of the same size:

```
VmbImage
                   sourceImage;
                  destinationImage;
VmbImage
VmbTransformInfo
                 info[2];
const VmbFloat_t mat[] = { 1.0f, 0.0f, 0.0f,
                             0.0f, 1.0f, 0.0f,
                             0.0f, 0.0f, 1.0f };
// set size member for verification inside API
sourceImage.Size = sizeof ( sourceImage );
destinationImage.Size = sizeof ( destinationImage );
// attach the data buffers
sourceImage.Data = pInBuffer;
destinationImage.Data = pOutBuffer;
// fill image info from pixel format
{\tt VmbSetImageInfoFromPixelFormat}~(~{\tt VmbPixelFormatBayerGR12Packed}~,
                                 640,
                                 480,
                                 &sourceImage );
// fill image info from pixel format string
std::string name ( "MONO16" );
VmbSetImageInfoFromString ( name.c_str(),
                            static_cast < VmbUint32_t > ( name.size() ) ,
                            640,
                            &destinationImage );
// set the debayering algorithm to 2 by 2
VmbSetDebayerMode ( VmbDebayerMode2x2, &info[0] );
// set the transformation matrix
VmbSetColorCorrectionMatrix3x3 ( mat, &info[1] );
// perform the transformation
VmbImageTransform ( &sourceImage, &destinationImage, &info, 2 );
```



6 Function reference

6.1 Information

6.1.1 VmbGetVersion()

Inquire the library version.

	Туре	Name	Description	
out	VmbUint32Ptr_t	Value	Contains the library version (Major, Minor, Sub, Build)	

6.1.2 VmbGetErrorInfo()

Translate Vimba error codes into a human-readable string.

	Туре	Name	Description
in	VmbError_t	ErrorCode	The error code to get a readable string for
out	VmbANSIChar_t*	InfoString	Pointer to a zero terminated string that will contain the error information on return
in	VmbUint32_t	MaxInfoLength	The length of the InfoString buffer

6.1.3 VmbGetApiInfoString()

Get information about the currently loaded Vimba ImageTransform API.

	Туре	Name	Description
in	VmbAPIInfo_t	InfoType	Type of information to return
out	VmbANSIChar_t*	Info	Pointer to a zero terminated string that will contain the information on return
in	VmbUint32_t	MaxInfoLength	The length of the Info buffer

InfoType may be one of the following values:

Value	Description
VmbAPIInfoAll	Returns all information about the API
VmbAPIInfoPlatform	Returns information about the platform the API was built for (x86 or x64)
VmbAPIInfoBuild	Returns info about the API built (debug or release).
VmbApiInfoTechnology	Returns info about the supported technologies the API was built for (OpenMP or OpenCL).



6.2 Transformation

6.3 VmblmageTransform()

Images are transformed using the VmbImageTransform() function. The transformation is defined by the images used and the desired transformation. If a transformation is not supported, VmbErrorBadParameter is returned.

	Туре	Name	Description
in	VmbImage*	source	Image to transform
out	VmbImage*	destination	Destination image
in	VmbTransformInfo*	parameter	Optional transform parameters
in	VmbUint32_t	parameterCount	Number of transform parameters

6.4 Helper functions

6.4.1 VmbSetImageInfoFromPixeIFormat()

Set image info member values in VmbImage from pixel format or string.

	Туре	Name	Description
in	VmbPixelFormat_t	PixelFormat	PixelFormat describes the pixel format used by the image data member.
in	VmbUint32_t	width	Width of the image in pixels
in	VmbUint32_t	height	Height of the image in pixels
in/out	VmbImage*	image	Pointer to Vimba image to set the info to

Note



VmbPixelFormat_t can be obtained from Vimba C/C++ APIs frame or from the *PixelFormat* feature. For displaying images, it is suggested to use VmbSetImageInfoFromString() ortolookupa matching VmbPixelFormat

6.4.2 VmbSetImageInfoFromString()

Set image info member values in VmbImage from pixel format or string.

	Туре	Name	Description
in	VmbANSIChar_t*	imageFormat	Image format as a (const) case insensitive string that is either a PixelFormat (Vmb is optional) or a pixel struct name
in	VmbUint32_t	stringLength	The length of the pixel format string
in	VmbUint32_t	width	Width of the image in pixels
in	VmbUint32_t	height	Height of the image in pixels
in/out	VmbImage*	image	Pointer to Vimba image to set the info to

AVT Image Transform - Programmer's Manual



6.4.3 VmbSetDebayerMode()

Set transformation options to a predefined debayering mode.

	Туре	Name	Description
in	VmbDebayerMode_t	debayerMode	The mode used for debayering the source raw image, default mode is 2x2 debayering. Debayering modes only work for image widths and heights divisible by two.
in/out	VmbTransformInfo_t*	transformInfo	Parameter that contains information about special transform functionality.

Note



Debayering is only applicable to image formats with both an even width and an even height.

6.4.4 VmbSetColorCorrectionMatrix3x3()

Set transformation options to a 3x3 color matrix transformation.

	Туре	Name	Description
in	VmbFloat_t*	matrix	Color correction matrix
in/out	VmbTransformInfo_t*	transformInfo	Parameter that is filled with information about special transform functionality.



7 Structs

7.1 Vmblmage

VmbImage encapsulates image data for the transformation function.

Struct entry	Purpose
VmbUint32_t size	Size of the structure
void* data	Pointer to the payload received from AVT Vimba C/C++ API or to the display image data
VmbImageInfo imageInfo	Internal information data used for mapping the images to the correct transformation, imageInfo data can be set with VmbSetImageInfo() helper functions from VmbPixelFormat_t or format string

7.2 VmblmageInfo

VmbImageInfo contains image information needed for the transformation function.

Struct entry	Purpose
VmbUint32_t width	The width of the image in pixels. For macro pixel formats like YUV, it is the width in sub pixels
VmbUint32_t height	The height of the image in pixels
VmbInt32_t stride	The offset from the current line to the next line, a value not equal to width is currently not supported
VmbPixelInfo pixelInfo	Information about the pixel format

7.3 VmbPixelInfo

VmbPixelInfo describes the pixel format of an image.

Struct entry	Purpose
VmbUint32_t bitsPerPixel	Number of bits for one image pixel, or sub pixel in macro pixel formats
VmbUint32_t bitsUsed	Number of bits used per pixel, e.g. RGB12 has 48 bits per pixel and 36 bits used
VmbAlignment_t alignment	For image formats where bitsPerPixel is not equal to bitsUsed, the alignment specifies the bit layout of the pixel
VmbEndianness_t endianness	Specifies the endianness of pixels that are larger than one byte
VmbPixelLayout_t pixelLayout	Describes the layout of the pixel component, e.g., RGB or BGR layout
VmbBayerPattern_t bayerPattern	For raw image data, this field specifies the color filter array layout of the sensor



7.4 VmbTransformInfo

Transformation parameters given as a pointer to a VmbTransformInfo struct are used to invoke special and additional functionality, which is applied while interpreting the source image (debayering) or transforming the images (color correction).

Struct entry	Purpose
VmbTransformType_t transformType	Transform info type, may be VmbTransformTypeDebayer-Mode or VmbTransformTypeColorCorrectionMatrix
VmbTransformParameter parameter	Transform info variant, may be VmbTransformParameter- Debayer or VmbTransformParameterMatrix3x3