

Distributed Adversarial Attacks

Sander Prenen

Thesis voorgedragen tot het behalen
van de graad van Master of Science
in de ingenieurswetenschappen:
computerwetenschappen, hoofdoptie
Artificiële intelligentie

Promotoren:

Prof. dr. ir. W. Joosen
Dr. ir. D. Preuveneers

Assessoren:

Ir. W. Eetveel
W. Eetrest

Begeleiders:

V. Rimmer
I. Tsingenopoulos

© Copyright KU Leuven

Without written permission of the thesis supervisors and the author it is forbidden to reproduce or adapt in any form or by any means any part of this publication. Requests for obtaining the right to reproduce or utilize parts of this publication should be addressed to the Departement Computerwetenschappen, Celestijnenlaan 200A bus 2402, B-3001 Heverlee, +32-16-327700 or by email info@cs.kuleuven.be.

A written permission of the thesis supervisors is also required to use the methods, products, schematics and programmes described in this work for industrial or commercial use, and for submitting this publication in scientific contests.

Zonder voorafgaande schriftelijke toestemming van zowel de promotoren als de auteur is overnemen, kopiëren, gebruiken of realiseren van deze uitgave of gedeelten ervan verboden. Voor aanvragen tot of informatie i.v.m. het overnemen en/of gebruik en/of realisatie van gedeelten uit deze publicatie, wend u tot het Departement Computerwetenschappen, Celestijnenlaan 200A bus 2402, B-3001 Heverlee, +32-16-327700 of via e-mail info@cs.kuleuven.be.

Voorafgaande schriftelijke toestemming van de promotoren is eveneens vereist voor het aanwenden van de in deze masterproef beschreven (originele) methoden, producten, schakelingen en programma's voor industrieel of commercieel nut en voor de inzending van deze publicatie ter deelname aan wetenschappelijke prijzen of wedstrijden.

Preface

Sander Prenen

Contents

Preface	i
Contents	ii
List of Figures	ii
List of Tables	iii
1 Introduction	1
2 Background	3
2.1 Neural networks	3
2.2 Adversarial attacks	5
2.3 Particle swarm optimization	7
3 Related work	9
3.1 Boundary attack	9
Bibliography	11

List of Figures

2.1	Linear separability	4
2.2	Decision boundaries and decision regions	4
2.3	Activation functions	4
2.4	Difference targeted and untargeted attack	6
2.5	Particle swarm optimization	7
3.1	Intuition of the Boundary Attack	10

List of Tables

List of Abbreviations

- AI** Artificial Intelligence. 3
- ANN** Artificial Neural Network. 3, 5
- API** Application Programming Interface. 5
- BA** Boundary Attack. 9, 10
- BBA** Biased Boundary Attack. 10
- CNN** Convolutional Neural Network. 3
- DNN** Deep Neural Network. 3
- EA** Evolutionary Algorithm. 7
- FGSM** Fast Gradient Sign Method. 5
- PSO** Particle Swarm Optimization. 7
- ReLU** Rectified Linear Unit. 3, 4
- RNN** Recurrent Neural Network. 3

Chapter 1

Introduction

Chapter 2

Background

2.1 Neural networks

Ever since the invention of computer systems, it has always been a goal of scientists and engineers to create **Artificial Intelligence (AI)**. Current state of the art approaches are mimicking the human brain, more specifically the neurons inside the brain. Already in the fifties, Rosenblatt introduced his perceptron [1]. The perceptron is a single neuron able to learn linearly separable patterns. It does so by finding a hyperplane that separates the two classes. This hyperplane is called the decision surface or decision boundary and the perceptron itself is called a classifier. Geometric regions separated by a decision boundary are called decision regions. The concept of linear separability is explained in Figure 2.1 in two dimensions. In Figure 2.2, the decision boundaries and decision regions are explained visually.

Unfortunately not all patterns are linearly separable. To overcome this problem, the neurons can be layered, creating an **Artificial Neural Network (ANN)** in the process. Layering neurons sequentially is essentially a linear combination of neurons. This in itself does not create non-linear decision surfaces. Non-linear activation functions are added for the **ANN** to be able to learn more complex decision boundaries. Some commonly used activation functions are **Rectified Linear Unit (ReLU)** [2], Heaviside step function and softmax (or sigmoid when used on scalars). In Figure 2.3 the plots of the activation functions can be found.

The neurons can be combined in different ways to create different **ANN** architectures. Each architecture has its own strengths and weaknesses. **Convolutional Neural Networks (CNNs)** excel in classifying visual data [3, 4], whilst **Recurrent Neural Networks (RNNs)** are widely used when there exist dependencies inside the data, such as in speech recognition [5, 6] or time series prediction [7]. More recent research focuses on **Deep Neural Networks (DNNs)**, due to the ever increasing computational power available. **DNN** approaches are able to compare to and even surpass human performance [8, 9].




FIGURE 2.1: Linearly separable classes on the left and non-linearly separable classes on the right. Two classes are linearly separable if there exists a hyperplane for which all examples of one class are on the same side of this hyperplane, whilst all examples of the other class are on the other side of the hyperplane. In two dimensions, the hyperplane is a straight line.




FIGURE 2.2: Decision boundaries (blue lines) separate different decision regions (colored regions).




FIGURE 2.3: Plots of different activation functions. From left to right: **ReLU**, Heaviside step and sigmoid.

2.2 Adversarial attacks

The expressiveness of ANNs is a double-edged sword. It is the cause for the near-human performance on some tasks, but also for counter-intuitive properties. As studied by Szegedy et al [10], one of these properties is the presence of discontinuous decision boundaries. This might cause seemingly identical images to be classified differently. They first defined adversarial examples as *imperceptibly small perturbations to a correctly classified input image, so that it is no longer classified correctly* [10]. This property of ANNs might not seem important at first glance, but it can be quite worrisome from a security point-of-view. Malicious users could craft images to bypass face recognition software [11] or attack the camera of a self-driving car to misclassify traffic signs [12]. Other fields where adversarial examples are of interest include malware detection [13], natural language processing [14] and industrial control systems [15]. Adversarial attacks are algorithms used to craft such adversarial examples.

Most research on adversarial attacks is done using images. Researchers have the most freedom in this domain, since a slightly altered image is still an image with roughly the same contents. Slightly modifying an industrial control system however, might break the entire way the system works. Research in other domains is mostly conducted by altering existing image algorithms to the specific use case. For this reason this work only focuses on adversarial attacks on images.

TODO: Threat model!

2.2.1 Adversarial attacks terminology

Adversarial attacks are generally divided in two categories, white box attacks and black box attacks. In a white box attack, the attacker has complete knowledge of the classifier under attack. This knowledge consists of the architecture, parameters and thus their gradients and all output of the classifier. Examples of white box attacks are the Fast Gradient Sign Method (FGSM) [16] or the Carlini & Wagner attack [17].

In black box attacks, the only thing the attacker has access to is the output of the model. Depending on the literature, this output consists of class labels only (decision-based attack) or class labels and the corresponding confidence scores (score-based attacks). Black box attacks are more relevant in real-life scenarios, since most attacks are performed on a third-party Application Programming Interface (API). These APIs generally do not reveal the underlying model.

Both white box and black box attacks can be divided into targeted and untargeted attacks depending on their goal. In a targeted attack, the goal of the attacker is to create an adversarial example with a specific target class. In an untargeted attack the target class can be any class. Untargeted variants of attacks generally enjoy




FIGURE 2.4: Different decision regions are shown in different colors. An adversarial example is being created starting from the source image (black star). On the left an untargeted attack is performed. The adversarial example is the image closest to the source image, that is classified differently (black circle). On the right a targeted attack is performed with the red decision region being the target class. The adversarial example is the image closest to the source image that is in the red decision region.

much more freedom and are therefore able to craft adversarial examples that are closer to the original. Figure 2.4 visually explains the difference between the two types.

What does it mean for images to be close to each other? This is easy to visualize in two dimensions as in Figure 2.4, but in higher dimensions, this is more difficult. Images reside in d -dimensional space, where d is the amount of pixels of the image. Two commonly used distances in higher dimensions are the L_2 -distance and the L_∞ -distance. They are defined as follows:

$$L_2(X, Y) = \sqrt{\sum_{i=1}^d |x_i - y_i|^2}$$

$$L_\infty(X, Y) = \lim_{p \rightarrow \infty} \left(\sum_{i=1}^d |x_i - y_i|^p \right)^{1/p}$$

$$= \max(|x_1 - y_1|, |x_2 - y_2|, \dots, |x_d - y_d|)$$

In both distances X and Y represent the images and $(x_1, x_2, \dots, x_i, \dots, x_d)$ and $(y_1, y_2, \dots, y_i, \dots, y_d)$ are the pixel values of X and Y respectively. The L_2 -distance is also known as the Euclidean distance, which is a generalization of the Pythagorean theorem in more than two dimensions. It takes the pairwise distances between all pixels into account. The L_∞ -distance is also called the Chebyshev distance. This distance only depends on the maximal pairwise distance between the two images. By minimizing the L_∞ -distance, the maximal pixelwise difference is minimized [18].




FIGURE 2.5: Particles move based on a step towards their best known position, the swarm’s best known position and a step in the direction of the movement of the previous iteration. The different steps are combined to determine the new position of the particle.

2.2.2 Adversarial defenses

— Under Construction —

The existence of adversarial attacks naturally gave rise to adversarial defenses. The earliest defenses relied on

2.3 Particle swarm optimization

Particle Swarm Optimization (PSO) [19] is an optimization framework part of the **Evolutionary Algorithms (EAs)** family. In **EAs**, populations of candidate solutions evolve based on mechanisms inspired by the field of biology, such as ant colonies [20], mutation and recombination [21]. The mechanism that inspired **PSO** is the flocking of birds. The framework has been applied to numerous problems such as routing problems [22, 23], diagnosing diseases from imaging [24] and calculating heat transfer coefficients [25].

In **PSO**, different particles move through the search space based on a set of rules. Each position in the search space has a given fitness value. This value determines how ‘fit’ or good a certain position is with respect to the goal of the optimization problem. Every iteration, all particles take a step towards their personal best position, towards the group or swarm’s best position and a step in the current direction (inertia). The different step sizes can be weighted depending on the problem at hand. In Figure 2.5, the steps are graphically represented for a single particle.

Chapter 3

Related work

3.1 Boundary attack

Boundary Attack (BA) [26] is a decision-based adversarial attack. The basic intuition of **BA** differs from traditional adversarial attacks. Unlike these traditional adversarial attacks, where the original image is moved through search space in order to become adversarial, **BA** starts from an input that is already adversarial. This input is then moved closer to the original image, while staying adversarial.

The attack has to be initialized with an already adversarial input. Two different approaches can be taken depending on the attack setting. In the untargeted case, the input can be sampled from a maximum entropy distribution given the valid domain of this input. Samples that are not adversarial are rejected. In the case of a targeted attack, the input is a sample from the dataset that is classified as the target class by the model under attack.

BA iteratively updates the adversarial image by performing a step orthogonal to the original image and a step towards this image. In iteration k , a perturbation η_k is sampled from a Gaussian distribution. This perturbation is rescaled and added to the adversarial image. From this new position in search space, the step towards the original image is taken. This way the path of the attack follows the decision boundary, hence the name of the attack. The intuition of the **BA** is shown in Figure 3.1. The attack can only follow the boundary if the adversarial image is already near the boundary. The starting image is projected onto the boundary using binary search to ensure that the adversarial image is in the vicinity of the boundary.

The step sizes are adjusted according to local geometry of the boundary. The orthogonal step size δ is adjusted so that approximately half of the orthogonal perturbations is still adversarial. This approach is based on trust region methods [27]. The step size towards the original image ϵ is adjusted using the same principle, but here a user specified threshold is used. The decision boundary tends to become flatter, the closer to the original image the attack gets. Therefore the algorithm converges when




FIGURE 3.1: Intuition behind the Boundary Attack. On the left the path of the attack is shown. The first step is a projection onto the boundary, afterwards it follows the decision boundary of the class of the original image. Each arrow represents one iteration of the attack. On the right, the two different steps of each iteration can be seen. In the first step, a random direction is sampled and projected onto a sphere around the original image. A step towards the original image is taken from this new position. Image inspired by [26].

ϵ converges to zero.

Biased Boundary Attack (BBA) [28] improves the original **BA** in three different ways. The first improvement is a biased sampling technique. The key idea behind this is that most previous attacks yield adversarial examples with high frequencies in the image. By sampling the perturbations in the first step of the **BA** from a low frequency distribution, the frequency of the created adversarial example will be lowered as well. **BBA** does this by sampling from a Perlin noise [29] distribution.

Bibliography

- [1] F. Rosenblatt. The perceptron: A probabilistic model for information storage and organization in the brain. 65(6):386–408.
- [2] Vinod Nair and Geoffrey E. Hinton. Rectified linear units improve restricted boltzmann machines. In *Proceedings of the 27th International Conference on International Conference on Machine Learning*, ICML’10, page 807–814, Madison, WI, USA, 2010. Omnipress.
- [3] M.V. Valueva, N.N. Nagornov, P.A. Lyakhov, G.V. Valuev, and N.I. Chervyakov. Application of the residue number system to reduce hardware costs of the convolutional neural network implementation. *Mathematics and Computers in Simulation*, 177:232–243, 2020.
- [4] Steve Lawrence, C. Lee Giles, Ah Chung Tsoi, and Andrew D. Back. Face recognition: A convolutional neural network approach. *IEEE TRANSACTIONS ON NEURAL NETWORKS*, 8(1):98–113, 1997.
- [5] Xiangang Li and Xihong Wu. Constructing long short-term memory based deep recurrent neural networks for large vocabulary speech recognition. *CoRR*, abs/1410.4281, 2014.
- [6] Ilya Sutskever, Oriol Vinyals, and Quoc V. Le. Sequence to sequence learning with neural networks. *CoRR*, abs/1409.3215, 2014.
- [7] Hansika Hewamalage, Christoph Bergmeir, and Kasun Bandara. Recurrent neural networks for time series forecasting: Current status and future directions. *CoRR*, abs/1909.00590, 2019.
- [8] Jon Russell. Google’s alphago ai wins three-match series against the world’s best go player. <https://techcrunch.com/2017/05/24/alphago-beats-planets-best-human-go-player-ke-jie/amp/?guccounter=1>, 05 2017. Accessed: 2021-12-08.
- [9] Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. In F. Pereira, C. J. C. Burges, L. Bottou, and K. Q. Weinberger, editors, *Advances in Neural Information Processing Systems*, volume 25. Curran Associates, Inc., 2012.

- [10] Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian Goodfellow, and Rob Fergus. Intriguing properties of neural networks, 2014.
- [11] Fatemeh Vakhshiteh, Ahmad Nickabadi, and Raghavendra Ramachandra. Adversarial attacks against face recognition: A comprehensive study, 2021.
- [12] Abhiram Gnanasambandam, Alex M. Sherman, and Stanley H. Chan. Optical adversarial attack, 2021.
- [13] Octavian Suci, Scott E. Coull, and Jeffrey Johns. Exploring adversarial examples in malware detection, 2019.
- [14] Nicholas Carlini and David Wagner. Audio adversarial examples: Targeted attacks on speech-to-text, 2018.
- [15] Giulio Zizzo, Chris Hankin, Sergio Maffei, and Kevin Jones. Invited: Adversarial machine learning beyond the image domain. In *2019 56th ACM/IEEE Design Automation Conference (DAC)*, pages 1–4, 2019.
- [16] Ian J. Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples, 2015.
- [17] Nicholas Carlini and David Wagner. Towards evaluating the robustness of neural networks, 2017.
- [18] Distance. Distance. <https://en.wikipedia.org/wiki/Distance>, 11 2021. Accessed: 2021-12-09.
- [19] James Kennedy and Russell Eberhart. Particle swarm optimization. In *Proceedings of ICNN'95-international conference on neural networks*, volume 4, pages 1942–1948. IEEE, 1995.
- [20] Marco Dorigo, Vittorio Maniezzo, and Alberto Coloni. Ant system: Optimization by a colony of cooperating agents. *IEEE transactions on systems, man, and cybernetics - part b. IEEE transactions on systems, man, and cybernetics. Part B, Cybernetics : a publication of the IEEE Systems, Man, and Cybernetics Society*, 26:29–41, 02 1996.
- [21] John H. Holland. *Genetic Algorithms and Adaptation*, pages 317–333. Springer US, Boston, MA, 1984.
- [22] Rami Abouleiman and Osamah Rawashdeh. Electric vehicle modelling and energy-efficient routing using particle swarm optimisation. *IET Intelligent Transport Systems*, 10(2):65–72, 2016.
- [23] Tadashi Yamada and Zukhruf Febri. Freight transport network design using particle swarm optimisation in supply chain–transport supernetwork equilibrium. *Transportation Research Part E: Logistics and Transportation Review*, 75:164–187, 2015.

- [24] Bruno Almeida and Victor Coppo Leite. *Particle Swarm Optimization: A Powerful Technique for Solving Engineering Problems*. 12 2019.
- [25] Romeela Mohee and Ackmez Mudhoo. Analysis of the physical properties of an in-vessel composting matrix. *Powder Technology*, 155(1):92–99, 2005.
- [26] Wieland Brendel, Jonas Rauber, and Matthias Bethge. Decision-Based Adversarial Attacks: Reliable Attacks Against Black-Box Machine Learning Models. *arXiv:1712.04248 [cs, stat]*, February 2018. arXiv: 1712.04248.
- [27] Ye Wenhe. Trust-region methods. https://optimization.mccormick.northwestern.edu/index.php/Trust-region_methods, 06 2014. Accessed: 2021-12-09.
- [28] Thomas Brunner, Frederik Diehl, Michael Truong Le, and Alois Knoll. Guessing Smart: Biased Sampling for Efficient Black-Box Adversarial Attacks. *2019 IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 4957–4965, October 2019. arXiv: 1812.09803.
- [29] Ken Perlin. An image synthesizer. In *Proceedings of the 12th Annual Conference on Computer Graphics and Interactive Techniques*, SIGGRAPH '85, page 287–296, New York, NY, USA, 1985. Association for Computing Machinery.