

BSc (Hons) in **Computer Science****SE3062 : Intelligent Systems**

Year 3 · Semester 1 · 2026 Semester 2

Faculty of Computing**Practical 01**

Objective & Lecture Mapping: Recall that an intelligent agent acts within a continuous loop: Sensors generate percept sequences, and Actuators execute actions to maximize a Performance measure. Use this sheet to execute practical modifications and incrementally evaluate your design against Lecture 01 and 02 theory (from basic recall to analytical classification).

Part 1: Code Analysis & PEAS Evaluation**Task 0 : Setting up and getting the starter Code**

1. Go to the [Git Hub Repo](#). Create a Fork of this Git Repo to your Personal Github Profile. Open it using your favourite IDE and follow the below instruction to complete the practical. The base code is in the "master" brach of the repo.

Task 1.1: The Environment State (`_init_`)

1. (Remember) List the four components of the PEAS framework discussed in Lecture 01.

P – Performance Measure
E – Environment
A – Actuators
S – Sensors

2. (Understand) Look at the `VisualGridHuntGame.__init__` method. Which specific variables in this code represent the physical "Environment (E)" state?

self.width and self.height (grid size)
self.walls (obstacles)
self.food_positions (food locations)

These define the physical state of the environment.

3. (Analyze) Based on the variables initialized (specifically `self.opponents`), classify this baseline environment as "Single-Agent" or "Multi-Agent". Briefly justify your choice.

This is a Multi-Agent environment because it contains opponents that act independently of the main agent.

Task 1.2: The Perception Subsystem (`get_percept`)

4. (Remember) Define what a "percept sequence" is according to Lecture 01.

A percept sequence is the complete history of all percepts received by the agent from the beginning until the current time.

5. (Understand) Which component of the PEAS framework does the `get_percept()` method represent in our code?

The `get_percept()` method represents the Sensors component of the PEAS framework.

6. (Evaluate) Based on the exact dictionary returned by `get_percept()`, is this environment "Fully Observable" or "Partially Observable"? Explain why based on what the agent can and cannot see.

The environment is Partially Observable because the agent does not have access to the full environment state, such as hidden elements and complete future states.

Task 1.3: Action Execution (execute_action)

7. (Understand) When `execute_action()` deducts points for hitting a wall, which PEAS component is being actively updated?

It updates the Performance Measure because the score is reduced when the agent hits a wall.

8. (Evaluate) Why is it structurally important that this metric evaluates changes in the external environment state (hitting a wall) rather than the agent's internal processing effort?

It is important to measure changes in the external environment because agent performance is evaluated based on outcomes, not on internal computation or effort. The goal is to maximize success in the environment.

Part 2: Guided Modification & Deep Theory Mapping

Follow the implementation instructions to inject a new hazard, then answer the questions to map your code changes back to the theoretical nature of the environment.

Step 2.1: Extending the Environment Initialization (`__init__`)

1. **Implementation Instructions:** Declare a new trap collection attribute (e.g., `self.toxic_traps = set()`) inside `__init__`. Populate it with coordinate tuples safely avoiding position `(0, 0)`, walls, and food.

9. (Understand) If you successfully add `self.toxic_traps` to the environment but intentionally **hide** this data from the agent's sensors, how does this specifically alter

the environment's "Observability" classification?

If toxic traps are hidden from the agent's sensors, the environment becomes more Partially Observable because the agent cannot directly perceive all elements of the environment.

Step 2.2: Updating the Perception Subsystem (get_percept)

1. **Implementation Instructions:** Locate `get_percept(self)` and add a new boolean sensor key (e.g., `'smells_toxin': tuple(self.agent_pos) in self.toxic_traps`) to the dictionary returned to the agent loop.
10. (Analyze) By adding `'smells_toxin'`, you expand the agent's percept sequence. Explain how this specific sensor helps the agent act with "Rationality" (maximizing expected utility).

The 'smells_toxin' sensor helps the agent detect danger. This allows the agent to avoid harmful positions and make better decisions, thereby maximizing expected utility and acting more rationally.

Step 2.3: Modifying Action Execution & Visual Rendering (execute_action & draw_grid)

1. **Implementation Instructions:** In `execute_action`, check if the updated `self.agent_pos` intersects with `self.toxic_traps` to decrement `self.score` by 15 points. In `draw_grid`, iterate through traps to render custom purple shapes on the canvas.
11. (Remember) You programmed a severe score penalty for stepping on a trap to avoid metric exploitation. What was the classic "Vacuum World Exploit" example discussed in Lecture 01 that illustrated the danger of faulty metrics?

The classic vacuum world exploit is when the agent repeatedly cleans an already clean area to gain performance points, exploiting a poorly designed performance measure.

Finalize and Lock Lab 01 Analytical Evaluation



FACULTY OF COMPUTING