RELATIONSHIP AMONG CHARACTERASTICS	Anode Rod Sacrificial Rate (g/year)	Tank Coating Thickness (µm)	Scale Flush Valve Diameter (mm)	Anti-microbial Material Surface Area (%)	Max Pressure Resistance (MPa)	Voltage Surge Tolerance (V)	Thermal Expansion Coefficient (1/K)	First-Hour Delivery Rating (L/hr)	App/UI Thermal State-of-Charge Update Latency (ms)	Predictive Heating Algorithm Accuracy (%)	Thermostat Cut-off Accuracy (±°C)	Max Tap Outlet Temperature Limit (°C)	Thermal Mixing Valve Flow Rate (L/min)	Temperature Sensor Response Time (ms)	ELCB Trip Current (mA)	Leak Sensor Moisture Detection Threshold (mL)	Diagnostics Alert Latency (s)	Standing Heat Loss (kWh/24h)	Outlet Temperature Fluctuation (±°C/min)	Tank Stratification Efficiency (%)	Inlet Jetting Velocity (m/s)	Mean Time Between Failures (MTBF) (Hours)	App Health Diagnostics Coverage (%)	Predictive Maintenance Alert Lead Time (Days)	Warranty Supported Life (Years)
Anode Rod Sacrificial Rate (g/year)		++	++	++	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+
Tank Coating Thickness (µm)	++		++	++	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+
Scale Flush Valve Diameter (mm)	++	++		++	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+
Anti-microbial Material Surface Area (%)	++	++	++		+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+
Max Pressure Resistance (MPa)	+	+	+	+		++	++	+	+	+	+	+	+	+	+	++	+	+	+	+	+	+	+	+	+
Voltage Surge Tolerance (V)	+	+	+	+	++		++	+	–	+	+	+	+	+	+	++	–	+	+	+	+	+	+	+	+
Thermal Expansion Coefficient (1/K)	+	+	+	+	++	++		++	++	++	+	++	++	++	+	++	+	+	++	++	+	+	+	+	+
First-Hour Delivery Rating (L/hr)	+	+	+	+	+	+	++		++	++	+	++	++	++	+	+	+	+	++	++	+	+	+	+	+
App/UI Thermal State-of-Charge Update Latency (ms)	+	+	+	+	+	–	++	++		++	+	++	++	++	+	++	++	+	++	++	+	+	++	+	+
Predictive Heating Algorithm Accuracy (%)	+	+	+	+	+	+	++	++	++		+	++	++	++	+	++	++	+	++	++	+	+	++	+	+
Thermostat Cut-off Accuracy (±°C)	+	+	+	+	+	+	+	+	+	+		+	+	+	+	+	+	+	+	+	+	+	+	+	+
Max Tap Outlet Temperature Limit (°C)	+	+	+	+	+	+	++	++	++	++	+		++	++	+	+	+	+	++	++	+	+	+	+	+
Thermal Mixing Valve Flow Rate (L/min)	+	+	+	+	+	+	++	++	++	++	+	++		++	+	+	+	+	++	++	+	+	+	+	+
Temperature Sensor Response Time (ms)	+	+	+	+	+	+	++	++	++	++	+	++	++		+	++	++	+	++	++	+	+	++	+	+
ELCB Trip Current (mA)	+	+	+	+	+	+	+	+	+	+	+	+	+	+		+	+	+	+	+	+	+	+	+	+
Leak Sensor Moisture Detection Threshold (mL)	+	+	+	+	++	++	++	+	++	++	+	+	+	++	+		++	+	+	+	+	+	+	++	+	+
Diagnostics Alert Latency (s)	+	+	+	+	+	–	+	+	++	++	+	+	+	++	+	++		+	+	+	+	+	++	+	+
Standing Heat Loss (kWh/24h)	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+		+	+	+	+	+	+	+
Outlet Temperature Fluctuation (±°C/min)	+	+	+	+	+	+	++	++	++	++	+	++	++	++	+	+	+	+		++	+	+	+	+	+
Tank Stratification Efficiency (%)	+	+	+	+	+	+	++	++	++	++	+	++	++	++	+	+	+	+	++		+	+	+	+	+
Inlet Jetting Velocity (m/s)	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+		+	+	+	+
Mean Time Between Failures (MTBF) (Hours)	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+		+	+	+
App Health Diagnostics Coverage (%)	+	+	+	+	+	+	+	+	++	++	+	+	+	++	+	++	++	+	+	+	+	+		+	+
Predictive Maintenance Alert Lead Time (Days)	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+		++
Warranty Supported Life (Years)	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	